

Fire Marshal Division

February 15, 2019

Kevin Decilles BFPE International 115 Bestwood Drive Clayton, NC 27520

Re: Marcos Pizza

80 Amarillo Lane Sanford, NC 27332

Application Number BCOM1810-0002

Mr. Decilles,

Thank you for submitting the plans for the hood system. The plans have been carefully reviewed by a qualified code enforcement official to examine for compliance with the North Carolina Fire Prevention Code and all other fire protection regulatory documents. There are some items that were found during the plan review process that need to be addressed before a final inspection of the new facility can be given. These items are outlined and described below.

• Commercial cooking equipment.

O Portable fire extinguishers shall be provided within a 30-foot (9144 mm) travel distance of commercial-type cooking equipment. Cooking equipment involving vegetable or animal oils and fats shall be protected by a Class K rated portable extinguisher.

Acceptance Test

- An acceptance test will be conducted by the Fire Marshal's office once system has been installed and pre-tested.
- o Installation shall be per architectural and system submittals and compliant with NFPA-17A.

Manual system operation

O A manual actuation device shall be located at or near a means of egress from the cooking area, a minimum of 10 feet (3048 mm) and a maximum of 20 feet (6096 mm) from the kitchen exhaust system. The manual





www.harnett.oro

actuation device shall be located a minimum of 4.5 feet (1372 mm) and a maximum of 5 feet (1524 mm) above the floor. The manual actuation shall require a maximum force of 40 pounds (178 N) and a maximum movement of 14 inches (356 mm) to actuate the fire suppression system.

• System Interconnection

 The actuation of the fire suppression system shall automatically shut down the fuel or electrical power supply to the cooking equipment. The fuel and electrical supply reset shall be manual.

Notes

- o Please schedule all fire inspections through the Fire Marshal's Office.
- o Contact Number 910-893-0743.
- o Please provide system certification certificate from installing contractor.

Thank you again for submitting the plans for the hood system. Please review the plans and adhere to any notes and alterations that were made in addition to the original drawings. These remarks are for the plans that were submitted and its original intent. These remarks do not apply if the original intent changes or what was submitted on the above date changes. If you have any questions, please do not hesitate to call this office.

Again, thank you and we look forward to working with you during the construction period!

Sincerely,

Roger Sullivan Deputy Fire Marshal





Fire Marshal Division

P.O. Box 370 Lillington, NC 27546 910-893-7580

Application for Plan Review BCom 1810 - 0002

Application # _____-Received By: COUST Date Received: 2.13.19 MARCO'S PIZZA Physical Address of Project: St AMARIUS LAWE Plans Submitted By: (919)-350-2699 Project Phone: Contact Person/Address: KEVIN DECIUES (919₎₋350₋2699₍₎₋-Contact Phone: Contractor's Name/Info: BFPE INTERNATIONAL 115 BESTWOOD DR. CLAYTON, MC 27520 (919) 350 2699 Contractor's Phone: Plans that are submitted will be reviewed as quickly as possible with an average time of review between 7-10 working days. Status checks may be conducted on plan reviews by visiting the website http://hteweb.harnett.org/Click2GovBP/Index.jsp or by calling the Harnett County Central Permitting Office (910-893-4759), or the Harnett County Fire Marshal's Office (910-893-7580). Approved plans must be picked up from the Central Permitting Office and all fees paid before any required inspections can be conducted.

recuiled 2.13.19



BFPE International Kevin F. DeCilles

919-550-2699 FAX 919-550-0719

LETTER OF TRANSMITTAL	February 12, 2019
То:	RE:
Harnett County Building Inspections 108 E. Front Street Lillington, NC 27546	Marco's Pizza 80 Amarillo Lane Sanford, N.C. 27332
Attention: Plans Review and Permits	Re: Kitchen Fire Suppression
W	
We are sending you: X_Attached	Via: X UPSHand Delivered
X Drawings Prints	PlansX_Permit Application
Copies 3 1	<u>Description</u> Shop Drawing of Kitchen fire suppression system Application for Plan Review
_X_For ApprovalFor your use	eX_As requestedResubmitted for approval
COMMENTS: ************************************	
Copy to: File & Installation Dept.	Signed: Halle



Bulletin

by Tyco Fire Suppression & Building Products

One Stanton Street Marinette, WI 54143-2542 www.ansul.com

Bulletin No. 5653

DATE:

April 29, 2010

TO:

All Authorized ANSUL R-102 System Distributors and OEMS's

FROM:

Product Management - Restaurant Systems

SUBJECT:

Non-UL-Listed Fire Protection for Conveyor Pizza Ovens

The UL300 Standard: Fire Testing of Fire Extinguishing System for Protection of Commercial Cooking Equipment does not currently address a test protocol for conveyor pizza oven protection. However, in many jurisdictions, the Authority Having Jurisdiction has required fire protection for conveyor pizza ovens. In the past, appliances not addressed in the UL300 test standard have been protected by following listed protection options for other appliances with similar operating characteristics. Generally, these appliances presented a more severe hazard than the appliance in question. In the case of conveyor pizza ovens, chain broiler protection was utilized.

To confirm recommended protection, we recently conducted a conveyor pizza oven fire test following the chain broiler test protocol outlined in UL 300, substituting fatty hamburgers with a grease coated pizza crust, to emulate the cooking process used by conveyor pizza ovens.

Prior recommendations for conveyor pizza ovens larger than the <u>two</u> 1N horizontal nozzle limitations for a chain broiler, suggested using <u>four</u> 1N nozzles, each positioned at the end corners and aimed diagonally across the chain within the oven. Based on the actual fire testing, we now recommend <u>two</u> 245 nozzles per conveyor: one nozzle is positioned at the inlet and one nozzle is positioned at the outlet of the conveyor pizza oven on the same side of the oven and aimed at the opposite corners. Utilizing <u>two</u> 245 nozzles as recommended is suitable protection for conveyors larger than the limitations for a chain broiler but not exceeding 38 in.(96.5 cm) wide x 70 in (177.8 cm) long.


If you should have questions pertaining to this bulletin, please contact your U.S. District Manager or International Area Manager; or call Technical Services as noted below.

GAS APPLIANCE W/ SHUT-OFF DETECTOR TEMP FIELD DETERMINED MICRO SWITCH FOR ELECTRIC SHUT DOWN & ALARM IF NEEDED **PULL STATION IN AISLE OF EGRESS**



PLENUM

14" X 14"





14 FLOW POINTS 4.5 GALLON **ANSUL R102**

UL 300

80 AMARILLO LANE **SANFORD, N.C. 27332** MARCO'S PIZZA

BFPE INTERNATIONAL CLAYTON, NC 27520 115 BESTWOOD DRIVE PH: 919-550-2699 FAX: 919-550-0719 BY: KFD THE NOT TO SCALE






34" X 70" = COOKING CHAMBER **DOUBLE CHAIN OVEN**

MICRO SWITCH FOR ELECTRIC SHUT DOWN & ALARM IF NEEDED DETECTOR TEMP FIELD DETERMINED GAS APPLIANCE W/ SHUT-OFF PULL STATION IN AISLE OF EGRESS






14 FLOW POINTS 4.5 GALLON **UL** 300 **ANSUL R102**

45 1 Z ◀ PLENUM 28" DETECTOR 2W **EXHAUST DUCT DETECTORS** 14" × 14" 6'-2" 2W Conterior 18" X 7.3" OPENING 28" **▼** 1N

45"

SANFORD, N.C. 27332 80 AMARILLO LANE MARCO'S PIZZA

COPY



34" X 70" = COOKING CHAMBER DOUBLE CHAIN OVEN

115 BESTWOOD DRIVE CLAYTON, NC 27520 BFPE INTERNATIONAL


NOT TO SCALE

PH: 919-550-2699 BY: KFD - KFD

FAX: 919-550-0719

MICRO SWITCH FOR ELECTRIC SHUT DOWN & ALARM IF NEEDED **3AS APPLIANCE W/ SHUT-OFF PULL STATION IN AISLE OF EGRESS**







14 FLOW POINTS UL 300 4.5 GALLON **ANSUL R102**

COPY

EXHAUST HOOD (PLAN VIEW)





34" X 70" = COOKING CHAMBER DOUBLE CHAIN OVEN

SANFORD, N.C. 27332 80 AMARILLO LANE MARCO'S PIZZA

115 BESTWOOD DRIVE 2/5/19 CLAYTON, NC 27520 BY: KFD BFPE INTERNATIONAL

NOT TO SCALE

PH: 919-550-2699

FAX: 919-550-0719