


Abby & Bella's

24 E. Main Street
Coats, NC 27521



Exit Sign / Light;
Fire Extinguisher


OCCUPANT LOAD (MERCHANTILE - TABLE 1004.1.1)
 RETAIL AREA: 30 SQ.FT. GROSS / OCCUPANT = 1297 / 30 = 44 OCCUPANTS
 STORAGE AREA: 300 SQ.FT. GROSS / OCCUPANT = 438 / 300 = 2 OCCUPANTS
TOTAL = 46 OCCUPANTS

UNISEX FACILITY ALLOWED UNDER SECTION 2902.2 EXCEPTION #3
 (MERCHANTILE WITH OCCUPANCIES OF 100 OR LESS)

Existing
2.26.2019

Josh Parrish
9309 Sauls Rd.
Raleigh, NC 27603

phone: 919.820.1878
email: signsandrealstate@gmail.com




Reviewed For Code Compliance By:
D. Banks Wallace
 Chief Deputy Fire Marshal
 05/02/2019 8:11:30 AM

FLOOR PLAN

A100

Abby & Bella's

24 E. Main Street
Coats, NC 27521



Existing
2.26.2019

Josh Parrish

9309 Sauls Rd.
Raleigh, NC 27603

phone: 919.820.1878
email: signsandrealstate@gmail.com

OCCUPANT LOAD (MERCHANTILE - TABLE 1004.1.1)
 RETAIL AREA: 30 SQ.FT. GROSS / OCCUPANT = 1297 / 30 = 44 OCCUPANTS
 STORAGE AREA: 300 SQ.FT. GROSS / OCCUPANT = 438 / 300 = 2 OCCUPANTS
TOTAL = 46 OCCUPANTS

UNISEX FACILITY ALLOWED UNDER SECTION 2902.2 EXCEPTION #3
(MERCHANTILE WITH OCCUPANCIES OF 100 OR LESS)

1 LIFE SAFETY PLAN

Scale : 3/32" = 1'-0"



LIFE SAFETY PLAN

LS100

**2012 APPENDIX B
BUILDING CODE SUMMARY
FOR ALL COMMERCIAL PROJECTS
(EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)**
(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: Abby & Bella's
 Address: 24 E. Main St. Coats, NC Zip Code 27521
 Proposed Use: Consignment/Thrift Store
 Owner/Authorized Agent: Judy Parrish Phone # (919) 820-1892 E-Mail judypparrish@gmail.com
 Owned By: City/County Private State
 Code Enforcement Jurisdiction: City County Harnett State

LEAD DESIGN PROFESSIONAL: Jonas Parrish (919) 820-1940 jmphunter111@gmail.com

DESIGNER	FIRM	NAME	LICENSE #	TELEPHONE #	E-MAIL
Architectural				()	
Civil				()	
Electrical	<u>On Time Electric</u>	<u>James Collins</u>	<u>28249</u>	<u>(919) 616-7109</u>	
Fire Alarm				()	
Plumbing	<u>Gary Willis Plumbing</u>	<u>Gary Willis</u>	<u>18659</u>	<u>(919) 894-2987</u>	<u>contact@gwplumbinginc.com</u>
Mechanical	<u>Air Essentials</u>	<u>Jay Perry</u>	<u>21536</u>	<u>(919) 422-5991</u>	
Sprinkler-Standpipe				()	
Structural				()	
Retaining Walls >5' High				()	
Other				()	

2012 EDITION OF NC CODE FOR: New Construction Addition Upfit
 EXISTING: Reconstruction Alteration Repair Renovation
 CONSTRUCTED: (date) ? ORIGINAL USE(S) (Ch. 3): Merchandise
 RENOVATED: (date) ≈ 2011? CURRENT USE(S) (Ch. 3): Unoccupied
 PROPOSED USE(S) (Ch. 3): Merchandise

BASIC BUILDING DATA

Construction Type: I-A II-A III-A IV V-A
 (check all that apply) I-B II-B III-B V-B
 Sprinklers: No Partial Yes NFPA 13 NFPA 13R NFPA 13D
 Standpipes: No Yes Class I II III Wet Dry
 Fire District: No Yes (Primary) Flood Hazard Area: No Yes

Building Height: (feet) 33'-7"

Gross Building Area:

FLOOR	EXISTING (SQ FT)	NEW (SQ FT)	SUB-TOTAL
6 th Floor	—	—	—
5 th Floor	—	—	—
4 th Floor	—	—	—
3 rd Floor	—	—	—
2 nd Floor	<u>1920 sq ft</u>	—	<u>1920</u>
Mezzanine	—	—	—
1 st Floor	<u>1920 sq ft</u>	—	<u>1920</u>
Basement	—	—	—
TOTAL	<u>3840 sq. ft.</u>	—	—

ALLOWABLE AREA

Occupancy:

- Assembly [] A-1 [] A-2 [] A-3 [] A-4 [] A-5
Business []
Educational []
Factory [] F-1 Moderate [] F-2 Low
Hazardous [] H-1 Detonate [] H-2 Deflagrate [] H-3 Combust [] H-4 Health [] H-5 HPM
Institutional [] I-1 [] I-2 [] I-3 [] I-4
I-3 Condition [] 1 [] 2 [] 3 [] 4 [] 5
Mercantile [X]
Residential [] R-1 [] R-2 [] R-3 [] R-4
Storage [] S-1 Moderate [] S-2 Low [] High-piled
[] Parking Garage [] Open [] Enclosed [] Repair Garage
Utility and Miscellaneous []

Accessory Occupancies:

- Assembly [] A-1 [] A-2 [] A-3 [] A-4 [] A-5
Business []
Educational []
Factory [] F-1 Moderate [] F-2 Low
Hazardous [] H-1 Detonate [] H-2 Deflagrate [] H-3 Combust [] H-4 Health [] H-5 HPM
Institutional [] I-1 [] I-2 [] I-3 [] I-4
I-3 Condition [] 1 [] 2 [] 3 [] 4 [] 5
Mercantile []
Residential [] R-1 [] R-2 [] R-3 [] R-4
Storage [] S-1 Moderate [] S-2 Low [] High-piled
[] Parking Garage [] Open [] Enclosed [] Repair Garage
Utility and Miscellaneous []

Incidental Uses (Table 508.2.5):

- [] Furnace room where any piece of equipment is over 400,000 Btu per hour input
[] Rooms with boilers where the largest piece of equipment is over 15 psi and 10 horsepower
[] Refrigerant machine room
[] Hydrogen cutoff rooms, not classified as Group H
[] Incinerator rooms
[] Paint shops, not classified as Group H, located in occupancies other than Group F
[] Laboratories and vocational shops, not classified as Group H, located in a Group E or I-2 occupancy
[] Laundry rooms over 100 square feet
[] Group I-3 cells equipped with padded surfaces
[] Group I-2 waste and linen collection rooms
[] Waste and linen collection rooms over 100 square feet
[] Stationary storage battery systems having a liquid electrolyte capacity of more than 50 gallons, or a lithium-ion capacity of 1,000 pounds used for facility standby power, emergency power or uninterrupted power supplies
[] Rooms containing fire pumps
[] Group I-2 storage rooms over 100 square feet
[] Group I-2 commercial kitchens
[] Group I-2 laundries equal to or less than 100 square feet
[] Group I-2 rooms or spaces that contain fuel-fired heating equipment

- Special Uses: [] 402 [] 403 [] 404 [] 405 [] 406 [] 407 [] 408 [] 409 [] 410 [] 411 [] 412
[] 413 [] 414 [] 415 [] 416 [] 417 [] 418 [] 419 [] 420 [] 421 [] 422 [] 423 [] 424
[] 425 [] 426 [] 427

- Special Provisions: [] 509.2 [] 509.3 [] 509.4 [] 509.5 [] 509.6 [] 509.7 [] 509.8 [] 509.9

Mixed Occupancy: [X] No [] Yes Separation: _____ Hr. Exception: _____

[] Incidental Use Separation (508.2.5)

This separation is not exempt as a Non-Separated Use (see exceptions).

Non-Separated Use (508.3)

The required type of construction for the building shall be determined by applying the height and area limitations for each of the applicable occupancies to the entire building. The most restrictive type of construction, so determined, shall apply to the entire building.

Separated Use (508.4) - See below for area calculations

For each story, the area of the occupancy shall be such that the sum of the ratios of the actual floor area of each use divided by the allowable floor area for each use shall not exceed 1.

$$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} \leq 1$$

$$\underline{\hspace{2cm}} + \underline{\hspace{2cm}} + \dots = \underline{\hspace{2cm}} \leq 1.00$$

N/A

STORY NO.	DESCRIPTION AND USE	(A) BLDG AREA PER STORY (ACTUAL)	(B) TABLE 503 ⁵ AREA	(C) AREA FOR FRONTAGE INCREASE ¹	(D) AREA FOR SPRINKLER INCREASE ²	(E) ALLOWABLE AREA OR UNLIMITED ³	(F) MAXIMUM BUILDING AREA ⁴
1	Merchandise	1920	12,500	-	-	-	
2	Unoccupied	1920	12,500	-	-	-	

¹ Frontage area increases from Section 506.2 are computed thus:

- a. Perimeter which fronts a public way or open space having 20 feet minimum width = 128 (F)
- b. Total Building Perimeter = 208 (P)
- c. Ratio (F/P) = .61 (F/P)
- d. W = Minimum width of public way = 20 (W)
- e. Percent of frontage increase $I_f = 100 [F/P - 0.25] \times W/30 = \underline{\hspace{2cm}}$ (%)

² The sprinkler increase per Section 506.3 is as follows:

- a. Multi-story building $I_s = 200$ percent
- b. Single story building $I_s = 300$ percent

³ Unlimited area applicable under conditions of Section 507.

⁴ Maximum Building Area = total number of stories in the building x E (506.4).

⁵ The maximum area of open parking garages must comply with Table 406.3.5. The maximum area of air traffic control towers must comply with Table 412.1.2.

ALLOWABLE HEIGHT

	ALLOWABLE (TABLE 503)	INCREASE FOR SPRINKLERS	SHOWN ON PLANS	CODE REFERENCE
Type of Construction	Type <u>III B</u>		Type _____	
Building Height in Feet		Feet = H + 20' = _____		
Building Height in Stories	<u>2</u>	Stories + 1 = _____		

FIRE PROTECTION REQUIREMENTS

all elements are existing

BUILDING ELEMENT	FIRE SEPARATION DISTANCE (FEET)	RATING		DETAIL # AND SHEET #	DESIGN # FOR RATED ASSEMBLY	DESIGN # FOR RATED PENETRATION	DESIGN # FOR RATED JOINTS
		REQ'D	PROVIDED (w/ REDUCTION) *				
Structural Frame, including columns, girders, trusses							
Bearing Walls							
Exterior							
North							
East							
West							
South							
Interior							
Nonbearing Walls and Partitions							
Exterior walls							
North							
East							
West							
South							
Interior walls and partitions							
Floor Construction Including supporting beams and joists							
Roof Construction Including supporting beams and joists							
Shaft Enclosures - Exit							
Shaft Enclosures - Other							
Corridor Separation							
Occupancy Separation							
Party/Fire Wall Separation							
Smoke Barrier Separation							
Tenant Separation							
Incidental Use Separation							

* Indicate section number permitting reduction

LIFE SAFETY SYSTEM REQUIREMENTS

- Emergency Lighting: No Yes
Exit Signs: No Yes
Fire Alarm: No Yes
Smoke Detection Systems: No Yes Partial _____
Panic Hardware: No Yes

LIFE SAFETY PLAN REQUIREMENTS

Life Safety Plan Sheet #: LS 100

- Fire and/or smoke rated wall locations (Chapter 7)
 Assumed and real property line locations

- Exterior wall opening area with respect to distance to assumed property lines (705.8)
- Existing structures within 30' of the proposed building
- Occupancy types for each area as it relates to occupant load calculation (Table 1004.1.1)
- Occupant loads for each area
- Exit access travel distances (1016)
- Common path of travel distances (1014.3 & 1028.8)
- Dead end lengths (1018.4)
- Clear exit widths for each exit door
- Maximum calculated occupant load capacity each exit door can accommodate based on egress width (1005.1)
- Actual occupant load for each exit door
- A separate schematic plan indicating where fire rated floor/ceiling and/or roof structure is provided for purposes of occupancy separation
- Location of doors with panic hardware (1008.1.10)
- Location of doors with delayed egress locks and the amount of delay (1008.1.9.7)
- Location of doors with electromagnetic egress locks (1008.1.9.8)
- Location of doors equipped with hold-open devices
- Location of emergency escape windows (1029)
- The square footage of each fire area (902)
- The square footage of each smoke compartment (407.4)
- Note any code exceptions or table notes that may have been utilized regarding the items above

ACCESSIBLE DWELLING UNITS
(SECTION 1107)

N/A

TOTAL UNITS	ACCESSIBLE UNITS REQUIRED	ACCESSIBLE UNITS PROVIDED	TYPE A UNITS REQUIRED	TYPE A UNITS PROVIDED	TYPE B UNITS REQUIRED	TYPE B UNITS PROVIDED	TOTAL ACCESSIBLE UNITS PROVIDED

ACCESSIBLE PARKING
(SECTION 1106)

Street Parking

LOT OR PARKING AREA	TOTAL # OF PARKING SPACES		# OF ACCESSIBLE SPACES PROVIDED			TOTAL # ACCESSIBLE UNITS PROVIDED
	REQUIRED	PROVIDED	REGULAR WITH 5' ACCESS AISLE	VAN SPACES WITH 132" ACCESS AISLE	8' ACCESS AISLE	
TOTAL						

STRUCTURAL DESIGN

DESIGN LOADS:

N/A
All existing

Importance Factors: Wind (I_w) _____
 Snow (I_s) _____
 Seismic (I_E) _____

Live Loads: Roof _____ psf
 Mezzanine _____ psf
 Floor _____ psf

Ground Snow Load: _____ psf

Wind Load: Basic Wind Speed _____ mph (ASCE-7)
 Exposure Category _____
 Wind Base Shears (for MWFRS) $V_x =$ _____ $V_y =$ _____

SEISMIC DESIGN CATEGORY: A B C D

Provide the following Seismic Design Parameters:

Occupancy Category (Table 1604.5) I II III IV

Spectral Response Acceleration S_s _____ %g S_1 _____ %g

Site Classification (Table 1613.5.2) A B C D E F

Data Source: Field Test Presumptive Historical Data

Basic structural system (check one)

- Bearing Wall Dual w/Special Moment Frame
 Building Frame Dual w/Intermediate R/C or Special Steel
 Moment Frame Inverted Pendulum

Seismic base shear: $V_x =$ _____ $V_y =$ _____

Analysis Procedure: Simplified Equivalent Lateral Force Dynamic

Architectural, Mechanical, Components anchored? Yes No

LATERAL DESIGN CONTROL: Earthquake Wind

SOIL BEARING CAPACITIES:

Field Test (provide copy of test report) _____ psf

Presumptive Bearing capacity _____ psf

Pile size, type, and capacity _____

SPECIAL INSPECTIONS REQUIRED: Yes No

**PLUMBING FIXTURE REQUIREMENTS
(TABLE 2902.1)**

USE	WATERCLOSETS		URINALS	LAVATORIES		SHOWERS/ TUBS	DRINKING FOUNTAINS		
	MALE	FEMALE		MALE	FEMALE		REGULAR	ACCESSIBLE	
SPACE	EXISTING	0	0	-	0	0	-	0	0
	NEW	1	1	-	1	1	-	0	0
	REQUIRED	1	1	-	1	1	-	0	0

2902.2 Exception #3 Separate Facilities not Required.

SPECIAL APPROVALS

Special approval: (Local Jurisdiction, Department of Insurance, OSC, DPI, DHHS, ICC, etc., describe below)

ENERGY SUMMARY

ENERGY REQUIREMENTS:

The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portions of the project information for the plan data sheet. If performance method, state the annual energy cost for the standard reference design vs annual energy cost for the proposed design.

Climate Zone: 3 4 5

Method of Compliance:

- Prescriptive (Energy Code)
 Performance (Energy Code)
 Prescriptive (ASHRAE 90.1)
 Performance (ASHRAE 90.1)

THERMAL ENVELOPE

Roof/ceiling Assembly (each assembly)

Description of assembly: _____
U-Value of total assembly: _____
R-Value of insulation: _____
Skylights in each assembly: _____
U-Value of skylight: _____
total square footage of skylights in each assembly: _____

All existing

Exterior Walls (each assembly)

Description of assembly: _____
U-Value of total assembly: _____
R-Value of insulation: _____
Openings (windows or doors with glazing)
U-Value of assembly: _____
Solar heat gain coefficient: _____
projection factor: _____
Door R-Values: _____

Walls below grade (each assembly)

Description of assembly: _____
U-Value of total assembly: _____
R-Value of insulation: _____

Floors over unconditioned space (each assembly)

Description of assembly: _____
U-Value of total assembly: _____
R-Value of insulation: _____

Floors slab on grade

Description of assembly: _____
U-Value of total assembly: _____
R-Value of insulation: _____
Horizontal/vertical requirement: _____
slab heated: _____

MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Thermal Zone

winter dry bulb: _____
summer dry bulb: _____

Interior design conditions

winter dry bulb: _____
summer dry bulb: _____
relative humidity: _____

Building heating load: _____

Building cooling load: _____

Mechanical Spacing Conditioning System

Unitary
description of unit: _____
heating efficiency: _____
cooling efficiency: _____
size category of unit: _____

Boiler
Size category. If oversized, state reason.: _____
Chiller
Size category. If oversized, state reason.: _____

List equipment efficiencies: _____

ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance:

Energy Code: Prescriptive Performance
ASHRAE 90.1: Prescriptive Performance

Lighting schedule (each fixture type)

lamp type required in fixture LED
number of lamps in fixture 1
ballast type used in the fixture self ballast
number of ballasts in fixture
total wattage per fixture 13 watt
total interior wattage specified vs. allowed (whole building or space by space) 450w
total exterior wattage specified vs. allowed 39 watt

Existing electrical system we just have to install another meter base to separate power b/w this bldg and the adjacent building (they were wired to be easily seperated) Work was done prior to 2011 I think.

Additional Prescriptive Compliance

- 506.2.1 More Efficient Mechanical Equipment
- 506.2.2 Reduced Lighting Power Density
- 506.2.3 Energy Recovery Ventilation Systems
- 506.2.4 Higher Efficiency Service Water Heating
- 506.2.5 On-Site Supply of Renewable Energy
- 506.2.6 Automatic Daylighting Control Systems