

**EXIT REQUIREMENTS:
NUMBER AND ARRANGEMENTS OF EXITS**

FLOOR, ROOM OR SPACE DESIGNATION	MINIMUM NO. OF EXITS		TRAVEL DISTANCE		ARRANGEMENT MEANS OF EGRESS 1,3 (SECTION 1016-1021)	
	REQ'D.	SHOWN ON PLANS	ALLOWABLE TRAVEL DISTANCE (TABLE 1017.2)	ACTUAL TRAVEL DISTANCE SHOWN ON PLANS	REQUIRED DISTANCE BETWEEN EXIT DOORS	ACTUAL DISTANCE SHOWN ON PLANS
BUSINESS (TENANT 1)	2	2	200'	63'-10"	35'-8"	69'-0"
BUSINESS (TENANT 2)	2	2	200'	46'-2"	35'-8"	69'-0"
BUSINESS (TENANT 3)	2	2	200'	46'-0"	35'-8"	69'-0"
BUSINESS (TENANT 4)	2	2	200'	59'-1"	35'-8"	69'-0"

- CORRIDOR DEAD ENDS (SECTION 1020.4)
- BUILDINGS WITH SINGLE EXITS (TABLE 1006.3.2(2)), SPACES WITH ONE MEANS OF EGRESS (TABLE 1006.2.1)
- COMMON PATH OF TRAVEL (SECTION 1029.8)

EXIT WIDTH

USE GROUP OR SPACE DESCRIPTION	(a)		(b)		(c)				EXIT WIDTH (in)				
	AREA ¹ SQ. FT.	AREA ¹ PER OCCUPANT (TABLE 1004.1.2)	CALCULATED OCCUPANT LOAD (a/b)	EGRESS WIDTH PER OCCUPANT (TABLE 1005.1)	REQUIRED WIDTH (SECTION 1005.1) (a/b) x c		ACTUAL WIDTH SHOWN ON PLANS		STAIR		LEVEL		
					STAIR	LEVEL	STAIR	LEVEL	STAIR	LEVEL			
BUSINESS (TENANT 1)	1,750	100 GROSS	18	N/A	.2	N/A	3.6"	N/A	70"				
BUSINESS (TENANT 2)	1,750	100 GROSS	18	N/A	.2	N/A	3.6"	N/A	70"				
BUSINESS (TENANT 3)	1,750	100 GROSS	18	N/A	.2	N/A	3.6"	N/A	70"				
BUSINESS (TENANT 4)	1,750	100 GROSS	18	N/A	.2	N/A	3.6"	N/A	70"				


- SEE TABLE 1004.1.2 TO DETERMINE WHETHER NET OR GROSS AREA IS APPLICABLE. SEE DEFINITION "AREA, GROSS" AND "AREA, NET" (SECTION 1002, DEFINED IN CHAPTER 2)
- MINIMUM STAIRWAY WIDTH (SECTION 1011.2); MIN. CORRIDOR WIDTH (SECTION 1020.2); MIN. DOOR WIDTH (SECTION 1010.1.1)
- MINIMUM WIDTH OF EXIT PASSAGEWAY (SECTION 1024)
- SEE SECTION 1005.6 FOR CONVERGING EXITS.
- THE LOSS OF ONE MEANS OF EGRESS SHALL NOT REDUCE THE AVAILABLE CAPACITY TO LESS THAN 50% OF THE TOTAL REQUIRED (SECTION 1005.5)
- ASSEMBLY OCCUPANCIES (SECTION 1029)

LIFE SAFETY PLAN REQUIREMENTS:

- FIRE AND/OR SMOKE RATED WALL LOCATIONS (CHAPTER 7) - SEE NOTE 1
- ASSUMED AND REAL PROPERTY LINE LOCATIONS - SEE NOTE 2
- EXTERIOR WALL OPENING AREA WITH RESPECT TO DISTANCE TO ASSUMED PROPERTY LINES (705.8) - SEE NOTE 3
- OCCUPANCY TYPES FOR EACH AREA AS IT RELATES TO OCCUPANT LOAD CALCULATION (TABLE 1004.1.2)
- OCCUPANT LOADS FOR EACH AREA
- EXIT ACCESS TRAVEL DISTANCES (1017)
- COMMON PATH OF TRAVEL DISTANCES (1006.2.1 & 1006.3.2(1))
- DEAD END LENGTHS (1020.4) - SEE NOTE 4
- CLEAR EXIT WIDTHS FOR EACH EXIT DOOR
- MAXIMUM CALCULATED OCCUPANT LOAD CAPACITY EACH EXIT DOOR CAN ACCOMMODATE BASED ON EGRESS WIDTH (1005.3)
- ACTUAL OCCUPANT LOAD FOR EACH EXIT DOOR
- A SEPARATE SCHEMATIC PLAN INDICATING WHERE FIRE RATED FLOOR/CEILING AND/OR ROOF STRUCTURE IS PROVIDED FOR PURPOSES OF OCCUPANCY SEPARATION. SEE NOTE 5
- LOCATION OF DOORS WITH PANIC HARDWARE (1008.1.10) - SEE NOTE 6
- LOCATION OF DOORS WITH DELAYED EGRESS LOCKS AND THE AMOUNT OF DELAY (1008.1.9.7) - SEE NOTE 7
- LOCATION OF DOORS WITH ELECTROMAGNETIC EGRESS LOCKS (1008.1.9.8) - SEE NOTE 7
- LOCATION OF DOORS EQUIPPED WITH HOLD-OPEN DEVICES - SEE NOTE 7
- LOCATION OF EMERGENCY ESCAPE WINDOWS (1029) - SEE NOTE 7
- THE SQUARE FOOTAGE OF EACH FIRE AREA (902) - SEE NOTE 8
- THE SQUARE FOOTAGE OF EACH SMOKE COMPARTMENT (407.5) - SEE NOTE 9
- NOTE ANY CODE EXCEPTIONS OR TABLE NOTES THAT MAY HAVE BEEN UTILIZED REGARDING THE ITEMS ABOVE


LIFE SAFETY PLAN NOTES:

- NO RATED WALLS.
- ALL ASSUMED AND REAL PROPERTY LINES >30'.
- UNLIMITED (ALL 30' OR GREATER)
- NO DEAD ENDS; 20' ALLOWED.
- NO RATING REQUIRED THIS STRUCTURE.
- PANIC HARDWARE NOT REQUIRED.
- NO DELAYED EGRESS LOCKS, ELECTROMAGNETIC LOCKS, HOLD OPEN DEVICES, OR EMERGENCY ESCAPE WINDOWS
- FIRE AREAS DO NOT EXCEED CODE ALLOWANCE
- BUILDING MEETS CODE REQUIREMENTS WITHOUT SUBDIVISION INTO SMOKE COMPARTMENTS; NO SMOKE COMPARTMENTS



LIFE SAFETY PLAN
SCALE: 3/16" = 1'-0"

- 1. MAXIMUM CALCULATED OCCUPANT LOAD CAPACITY EACH EXIT DOOR CAN ACCOMMODATE BASED ON EGRESS WIDTH (1005.1)
- 2. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PEOPLE
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 3. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PEOPLE
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 4. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PEOPLE
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 5. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PERSON
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 6. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PEOPLE
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 7. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PERSON
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.
- 8. 35" CLEAR WIDTH DIVIDED BY .2" = 175 OCCUPANTS
CALCULATED OCCUPANCY PER EXIT = 9 PEOPLE
CALCULATED OCCUPANCY DOES NOT EXCEED MAXIMUM CAPACITY OF EXIT.



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	

414 E. Blount St.
Raleigh, NC 27601
TEL: (919) 882-4429
FAX: (919) 882-5162

Cruse And Associates, P.A.
LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22
DRAWN BY BAM
JOB NO. 22-60

SHEET NO.
LS-1 OF 1

THIS FACILITY HAS NO STORAGE ABOVE 12' A.F.F. AND IS NOT INTENDED FOR USE AS VEHICLE STORAGE, PARKING GARAGE OR OR REPAIR GARAGE.

NOTE:
AREA/ROOM/SPACE DESIGNATIONS USED ON LIFE SAFETY PLANS ARE EXCLUSIVE TO LIFE SAFETY PLAN ONLY, AND ARE NOT INDICATIVE OF ANY ACTUAL SPACE DESIGNATIONS USED ELSEWHERE.


PLUMBING FIXTURE SCHEDULE

MARK	MAKE	MODEL	DESCRIPTION	NOTES
P-1	AMERICAN STANDARD	CADET 2377.100	EL 1.6/PA 16.5" HC ELONGATED WATER CLOSET HC ACCESSIBLE, TANK TYPE	WHITE 5311.012 SEAT
P-2	AMERICAN STANDARD	REGALYN 4869.004	LAVATORY WALL-TYPE, CAST IRON	4" CENTERSET WALL MOUNT SINK, WHITE W/1340.227 METERING FAUCET PROVIDE PIPE WRAP AND BAFFLE UNDER LAVATORY
P-3	BOSCH	US7-2 PRO	7.2 KW POINT OF USE WATER HEATER	240V, 1φ
P-4	OASIS	PGBACSL	SPLIT LEVEL ELECTRIC WATER COOLER	BARRIER - FREE
P-5	AMERICAN STANDARD	AQUALYN 0476.028	SELF RIMMING DROP IN SINK	1340.227 FAUCET. PROVIDE W/BASKET DRAIN
P-6	FIAT	SERV-A-SINK L-1	23" SINGLE BASIN FREE STANDING MOP SINK	
P-7	JUST	SL-1921-A-GR	1 COMPARTMENT SINK	SELECTED BY OWNER
P-8	WOODFORD	MOD-65	HOSE BIB FREEZE PROOF	ANTI-SIPHONING WITH VACUUM BREAKER, SELF DRAINING.
P-9	STATE	PCE 50 20LSA	50 GAL 4.5 KW WATER HEATER	HEATER IS 32-1/4" TALL; ALLOW FOR MINIMUM CLEARANCES DURING INSTALLATION

* VERIFY ALL FIXTURES WITH OWNER BEFORE PURCHASE OR INSTALLATION

KEYNOTES:

- 1) INSTALL SUPPLY PIPE TIGHT TO WALL.
- 2) GANG WATER METERS



DETAIL-WATER SERVICE ENTRANCE AS REQUIRED
NOT TO SCALE

PLUMBING LEGEND	
DESCRIPTION	SYMBOL
COLD WATER	CW
HOT WATER	HW
COLD WATER (FILTERED)	
RECIRCULATED WATER	HWR
VENT PIPING	V
WASTE PIPING	NEW EXISTING W
CLEAN OUT IN GRADE	C.O.I.G.
FLOOR CLEAN OUT	F.C.O.
NON FREEZE HOSE BIBB	NFHB
FLOOR DRAIN	F.D.
CHECK VALVE	
BALL VALVE	
GATE VALVE	
SHUT-OFF VALVE	
DOUBLE CHECK VALVE	
FIXTURE DESIGNATION	P--
MOUNTING HEIGHT	MH
POINT OF CONNECTION NEW TO EXISTING	
FLOOR SINK	
SHOCK ABSORBER W/BALL VALVE SHUT-OFF	SA SIZE PER MANUF. RECOMMENDATIONS
CHANGE IN PIPE SIZE	

TENANT ONE

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	2	1.5	1.5	2	3.0	3.0	4.0	1/2
TOTAL					8.0	3.0	9.0	6.0

TOTAL
17.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 3/4"

TENANT TWO OR THREE

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	1	1.5	1.5	2	1.5	1.5	2.0	1/1
TOTAL					6.5	1.5	7.0	5.0


TOTAL
17.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 3/4"

TENANT FOUR

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	2	1.5	1.5	2	3.0	3.0	4.0	1/4
DRINKING FOUNTAIN	2	.25	-	.25	.50	-	.50	0.5/1.0
MOP SINK	1	2.25	2.25	3.0	2.25	2.25	3.0	2/2
TOTAL					10.75	5.25	12.5	11.0


TOTAL
25.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 1"



PLUMBING WASTE & VENT PIPING PLAN
SCALE: 3/16" = 1'-0"


PLUMBING CONNECTION SCHEDULE

FIXTURE	C.W.	H.W.	WASTE	VENT
FLUSH TANK WATER CLOSET	1/2"	-	3"	2"
LAVATORY	1/2"	1/2"	2"	1 1/2"
ELEC. WATER COOLER	1/2"	-	2"	1 1/2"
FLOOR DRAIN			3"	2"
MOP SINK	1/2"	1/2"	3"	2"



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	



Cruse
and
Associates, P.A.

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22
DRAWN BY BAM
JOB NO. 22-60

SHEET NO.
P-1 OF 3

PLUMBING FIXTURE SCHEDULE

MARK	MAKE	MODEL	DESCRIPTION	NOTES
P-1	AMERICAN STANDARD	CADET 2377.100	EL 1.6/PA 16.5"HC ELONGATED WATER CLOSET HC ACCESSIBLE, TANK TYPE	WHITE 5311.012 SEAT
P-2	AMERICAN STANDARD	REGALYN 4869.004	LAVATORY WALL-TYPE, CAST IRON	4" CENTERSET WALL MOUNT SINK, WHITE W/1340.227 METERING FAUCET PROVIDE PIPE WRAP AND BAFFLE UNDER LAVATORY
P-3	BOSCH	US7-2 PRO	7.2 KW POINT OF USE WATER HEATER	240V, 1Ø
P-4	OASIS	PGBACSL	SPLIT LEVEL ELECTRIC WATER COOLER	BARRIER - FREE
P-5	AMERICAN STANDARD	AQUALYN 0476.028	SELF RIMMING DROP IN SINK	1340.227 FAUCET. PROVIDE W/BASKET DRAIN
P-6	FIAT	SERV-A-SINK L-1	23" SINGLE BASIN FREE STANDING MOP SINK	
P-7	JUST	SL-1921-A-GR	1 COMPARTMENT SINK	SELECTED BY OWNER
P-8	WOODFORD	MOD-65	HOSE BIB FREEZE PROOF	ANTI-SIPHONING WITH VACUUM BREAKER, SELF DRAINING.
P-9	STATE	PCE 50 20LSA	50 GAL. 4.5 KW WATER HEATER	HEATER IS 32-1/4" TALL; ALLOW FOR MINIMUM CLEARANCES DURING INSTALLATION

* VERIFY ALL FIXTURES WITH OWNER BEFORE PURCHASE OR INSTALLATION

TENANT ONE

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	2	1.5	1.5	2	3.0	3.0	4.0	1/2
TOTAL					8.0	3.0	9.0	6.0

TOTAL 17.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 3/4"

TENANT TWO OR THREE

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	1	1.5	1.5	2	1.5	1.5	2.0	1/1
TOTAL					6.5	1.5	7.0	5.0

TOTAL 17.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 3/4"

TENANT FOUR

PLUMBING CALCULATIONS

ITEM	# OF	FIXTURE UNITS (EACH)			FIXTURE UNITS (TOTAL)			FIXTURE UNITS (WASTE)
		COLD	HOT	TOTAL	COLD	HOT	TOTAL	
FLUSH TANK WATER CLOSET	1	5.0	-	5.0	5.0	-	5.0	4/4
LAVATORY	2	1.5	1.5	2	3.0	3.0	4.0	1/4
DRINKING FOUNTAIN	2	.25	-	.25	.50	-	.50	0.5/1.0
MOP SINK	1	2.25	2.25	3.0	2.25	2.25	3.0	2/2
TOTAL					10.75	5.25	12.5	11.0


TOTAL 25.0 GPM
WATER SUPPLY PIPE SIZE: MINIMUM 1"

PLUMBING CONNECTION SCHEDULE


FIXTURE	C.W.	H.W.	WASTE	VENT
FLUSH TANK WATER CLOSET	1/2"	-	3"	2"
LAVATORY	1/2"	1/2"	2"	1 1/2"
ELEC. WATER COOLER	1/2"	-	2"	1 1/2"
FLOOR DRAIN			3"	2"
MOP SINK	1/2"	1/2"	3"	2"

NOTE:

DASHED LINES REPRESENT EXISTING WASTE PIPE AS INSTALLED IN SHELL BUILDING.




DETAIL-CLEAN OUT AT GRADE
NOT TO SCALE



PLUMBING WASTE & VENT PIPING PLAN
SCALE: 3/16" = 1'-0"

PLUMBING LEGEND


DESCRIPTION	SYMBOL
COLD WATER	— CW
HOT WATER	— HW
COLD WATER (FILTERED)	—
RECIRCULATED WATER	→ HWR
VENT PIPING	- - - V
WASTE PIPING	— NEW — EXISTING — W
CLEAN OUT IN GRADE	⊠ C.O.I.G.
FLOOR CLEAN OUT	○ F.C.O.
NON FREEZE HOSE BIBB	⊢ NFB
FLOOR DRAIN	○ F.D.
CHECK VALVE	⊢
BALL VALVE	⊢
GATE VALVE	⊢
SHUT-OFF VALVE	⊢
DOUBLE CHECK VALVE	⊢
FIXTURE DESIGNATION	P---
MOUNTING HEIGHT	MH
POINT OF CONNECTION NEW TO EXISTING	⊕
FLOOR SINK	⊠
SHOCK ABSORBER W/BALL VALVE SHUT-OFF	SA SIZE PER MANUF. RECOMMENDATIONS
CHANGE IN PIPE SIZE	↔



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS

NO.	DESCRIPTION



Cruse and Associates, P.A.
 414 E. Ziegler St., 28384
 Durham, NC 27701
 TEL: (919) 882-4429
 FAX: (919) 882-5162
 LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
 © COPY RIGHT


DATE 12-19-22
 DRAWN BY BAM
 JOB NO. 22-60

SHEET NO.
P-2 OF 3





PLUMBING FIXTURE SCHEDULE

MARK	MAKE	MODEL	DESCRIPTION	NOTES
P-1	AMERICAN STANDARD	CADET 2377.100	EL 1.6/PA 16.5"HC ELONGATED WATER CLOSET HC ACCESSIBLE, TANK TYPE	WHITE 5311.012 SEAT
P-2	AMERICAN STANDARD	REGALYN 4869.004	LAVATORY WALL-TYPE, CAST IRON	4" CENTERSET WALL MOUNT SINK, WHITE W/1340.227 METERING FAUCET PROVIDE PIPE WRAP AND BAFFLE UNDER LAVATORY
P-3	BOSCH	US7 2 PRO	7.2 KW POINT OF USE WATER HEATER	240V, 1Ø
P-4	OASIS	PGBACSL	SPLIT LEVEL ELECTRIC WATER COOLER	BARRIER - FREE
P-5	AMERICAN STANDARD	AQUALYN 0476.028	SELF RIMMING DROP IN SINK	1340.227 FAUCET. PROVIDE W/BASKET DRAIN
P-6	FIAT	SERV-A-SINK L-1	23" SINGLE BASIN FREE STANDING MOP SINK	
P-7	JUST	SL-1921-A-GR	1 COMPARTMENT SINK	SELECTED BY OWNER
P-8	WOODFORD	MOD-65	HOSE BIB FREEZE PROOF	ANTI-SIPHONING WITH VACUUM BREAKER, SELF DRAINING.
P-9	STATE	PCE 50 20LSA	50 GAL 4.5 KW WATER HEATER	HEATER IS 32-1/4" TALL; ALLOW FOR MINIMUM CLEARANCES DURING INSTALLATION


* VERIFY ALL FIXTURES WITH OWNER BEFORE PURCHASE OR INSTALLATION




(TENANT ONE)
PLUMBING WASTE & VENT PIPING PLAN
NOT TO SCALE



RESTROOM ACCESSIBILITY DETAILS
SCALE: 1/2" = 1'-0"




(TENANT TWO & THREE)
PLUMBING WASTE & VENT PIPING PLAN
NOT TO SCALE



(TENANT FOUR)
PLUMBING WASTE & VENT PIPING PLAN
NOT TO SCALE


PLUMBING LEGEND	
DESCRIPTION	SYMBOL
COLD WATER	— CW
HOT WATER	— HW
COLD WATER (FILTERED)	—
RECIRCULATED WATER	— HWR
VENT PIPING	- - - V
WASTE PIPING	— NEW — EXISTING — W
CLEAN OUT IN GRADE	□ C.O.I.G.
FLOOR CLEAN OUT	○ F.C.O.
NON FREEZE HOSE BIBB	— NFHB
FLOOR DRAIN	○ F.D.
CHECK VALVE	—
BALL VALVE	—
GATE VALVE	—
SHUT-OFF VALVE	—
DOUBLE CHECK VALVE	—
FIXTURE DESIGNATION	P--
MOUNTING HEIGHT	MH
POINT OF CONNECTION NEW TO EXISTING	—
FLOOR SINK	—
SHOCK ABSORBER W/BALL VALVE SHUT-OFF	— SA SIZE PER MANUF. RECOMMENDATIONS
CHANGE IN PIPE SIZE	—



DETAIL-WATER HEATER
NOT TO SCALE

GENERAL PLUMBING NOTES


- ALL WORK SHALL BE IN COMPLIANCE WITH APPLICABLE LOCAL, STATE, AND NATIONAL CODES.
- CONTRACTORS SHALL COORDINATE PIPING WITH ALL OTHER TRADES.
- CONTRACTOR SHALL REFER TO ARCHITECTURAL/STRUCTURAL DRAWINGS FOR DIMENSIONS.
- CONTRACTOR SHALL FURNISH AND INSTALL DIELECTRIC UNIONS AT ALL CONNECTIONS BETWEEN DISSIMILAR METALS.
- CONTRACTOR SHALL FURNISH AND INSTALL ESCUTCHEONS AND COVER PLATES AT ALL FINISHED WALLS, CEILINGS AND FLOOR OPENINGS.
- PIPING SHALL BE DISINFECTED IN ACCORDANCE WITH STATE AND LOCAL CODE. (REFER TO SPECIFICATIONS.)
- ALL PIPING SHALL BE TESTED FOR LEAKS. IF ANY LEAKS ARE DETECTED THE PIPING SHALL BE REPAIRED, RESOLDERED OR REPLACED AND RETESTED.
- ALL SOLDER SHALL BE OF THE LEAD FREE TYPE.
- WATER HEATER SHALL BE SUPPLIED WITH FACTORY INSTALLED T&P VALVES AND SHALL HAVE UNIONS AND ISOLATION VALVES.
- DOMESTIC WATER SUPPLY PIPING SHALL BE COPPER OR CPVC. PEX IS ALLOWED WHERE PERMITTED BY CODE.
- WASTE AND VENT PIPING SHALL BE SCH. 40 PVC OR HEAVY DUTY CAST IRON UNDER TRAFFIC AREAS.
- INSTALL THERMOSTATICALLY CONTROLLED MIXING VALVES AS NEEDED TO ENSURE HOT WATER TEMPERATURE TO ALL HAND WASHING LOCATIONS DOES NOT EXCEED 110°F.
- ALL FLOOR DRAINS & HUB DRAINS SHALL BE PROVIDED WITH TRAP PRIMER EXCEPT FLOOR DRAINS IN TOILETS WHERE HOSE BIBS ARE PROVIDED.
- HOT WATER PIPING SHALL BE INSULATED WITH 1" THICK FIBROUS GLASS INSULATION. COLD WATER PIPING SHALL BE INSULATED WITH 1/2" FIBROUS GLASS INSULATION. VAPOR BARRIER SHALL BE APPLIED TO EACH.



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS

NO.	



Cruse and Associates, P.A.
414 E. Washington St.
Raleigh, NC 27601
TEL: (919) 882-4429
FAX: (919) 882-5108

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22

DRAWN BY BAM

JOB NO. 22-60



SHEET NO.

P-3 OF 3

MECHANICAL SYMBOL LEGEND


SINGLE LINE	DOUBLE LINE	DESCRIPTION
		TAKE OFF TO SUPPLY AIR REGISTER WITH EXT. INSUL. DUCTWORK
		END CAP DUCT SMOKE DETECTOR
		ACCESS DOOR
		CEILING DIFFUSER FLEXIBLE DUCTWORK (14' MAX.)
		ONE SIDED REDUCING TRANSITION F.D.=FIRE DAMPER (1-1/2)=RATED FOR 1-1/2 HRS.
		RETURN AIR OR EXHAUST GRILLE SUPPLY AIR CEILING DIFFUSER, ARROW INDICATES DIRECTION OF BLOW & ACTIVE DIFFUSER SIDES
		(1)CUSHION HEAD @ BRANCH OR DIFFUSER RUNOUT (2)CUSHION HEAD IS EQUAL TO 1-1/2 WIDTH OF THE BRANCH DUCT OR DIFFUSER RUNOUT R.A. OR EXHAUST DUCT TURNS DOWN @ 90 DEGS.
		MANUAL VOLUME CONTROL DAMPER W/ QUADRANT LOCKING DEVICE TWO SIDED TRANSITION
		ELECT. DUCT INSERT HEATER WITH CONTROL PANEL AHU W/FLEXIBLE CONNECTION AT SUPPLY AND RETURN DUCT
		KEY NOTE MARK XXXX CFM-DIFFUSER, REGISTER OR GRILLE (SEE SCHEDULE)
		EXHAUST FAN

CONNECTION SCHEDULE



MECHANICAL HVAC PLAN
SCALE: 3/16" = 1'-0"

NOTE: MAINTAIN A MINIMUM SEPARATION OF 10' BETWEEN EXHAUST AND INTAKE GRILLES.



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	

414 E. Edgerton St.
Durham, North Carolina 27604
PHONE: (919) 882-5182
FAX: (919) 882-5182

Cruse And Associates, P.A.

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22
DRAWN BY BAM
JOB NO. 22-60

SHEET NO.
M-1 OF 2

EXHAUST FAN SCHEDULE										
MARK	MAKE	MODEL	TYPE	CFM	EXTERNAL S.P. IN (W.G.)	WATTS	ELECTRICAL			NOTES
							VOLT	PH	HZ	
EF-1	GREENHECK	SP-B90	CEILING FAN	75	.25	49.7	115	1φ	60	WALL CAP, INSECT SCREEN, W/BACK DRAFT DAMPER

LOUVER SCHEDULE										
MARK	DESCRIPTION	CFM	APPROXIMATE OUTSIDE DIMENSIONS (W X H)	FREE AREA(SF)	MAXIMUM VELOCITY OR S.P. DROP	MATERIAL	FINISH	MANUFACTURER	MODEL NO.	NOTES
L1	WALL LOUVER	177	12"W X 12"H	0.5	500 FPM	ALUMINUM		HART & COOLEY	1530ZF	

REGISTER, GRILLE, & DIFFUSER SCHEDULE*									
MARK	DESCRIPTION	MAX. NC	NECK	BORDER TYPE	MATERIAL	FINISH	MANUFACTURER	MODEL NUMBER	ACCESSORIES / NOTES
A	DIFFUSER-4-WAY	30	9"X9"	LAY-IN	STEEL	WHITE	TITUS	TDC 9X9 3 26 2	SQ-TO-RND
B	DIFFUSER-2-WAY	30	6"X6"	LAY-IN	STEEL	WHITE	TITUS	TDC 6X6 3 26 2	SQ-TO-RND
C	DIFFUSER-4-WAY	30	6"X6"	LAY-IN	STEEL	WHITE	TITUS	TDC 6X6 3 26 4	SQ-TO-RND
D	DIFFUSER-4-WAY	30	9"X9"	SURFACE	STEEL	WHITE	TITUS	TDC 6X6 3 26 4	SQ-TO-RND
R1	RETURN GRILLE	30	10"X10"	LAY-IN	STEEL	WHITE	TITUS	23RL 10X10 3 26	SQ-TO-RND
R2	RETURN GRILLE	30	10"X10"	SURFACE	STEEL	WHITE	TITUS	23RL 10X10 3 26	SQ-TO-RND

* VERIFY CEILING TYPE BEFORE ORDERING, NARROW TEE REQUIREMENTS, PLASTER FRAMES ETC. TO BE INCLUDED WITH DIFFUSERS AT NO ADDITIONAL COST TO OWNER

NOTE:
VERIFY THERMOSTAT LOCATION WITH OWNER PRIOR TO INSTALLING. FILTER ALL OUTSIDE AIR.

MECHANICAL NOTES (GENERAL)

- DUCTWORK LAYOUTS ARE SCHEMATIC. ALL RISES, DROPS, OFFSETS, AND TRANSITIONS REQUIRED BUT ARE NOT SHOWN SHALL BE PROVIDED AND INSTALLED BY THE CONTRACTOR AT NO ADDITIONAL EXPENSE TO THE OWNER.
- DUCTWORK SHALL BE GALVANIZED STEEL AND SHALL BE CONSTRUCTED IN COMPLIANCE WITH SMACNA STANDARDS FOR LOW VELOCITY DUCTWORK. DUCT SIZES SHOWN ARE INSIDE CLEAR DIMENSIONS. FLEXIBLE RUNOUTS SHALL NOT EXCEED 14' AND SHALL NOT BE USED TO FORM ELBOWS. CONNECTIONS FROM RECTANGULAR TO ROUND DUCT SHALL BE MADE WITH MANUFACTURED 45 DEG. LATERAL TAPS.
- SUPPLY AND RETURN DUCTWORK SHALL BE INSULATED WITH FIBERGLASS INSULATION WITH A MINIMUM THERMAL RESISTANCE OF R-8.0 (IN UNCONDITIONED AREAS) AND AN "FSK" VAPOR BARRIER. DIFFUSERS SHALL BE INSULATED WITH FIBERGLASS INSULATION WITH VAPOR BARRIER. ALL JOINTS SHALL BE TAPED WITH A FOIL BACKED TAPE TO PROVIDE A CONTINUOUS VAPOR BARRIER.
- THE ELECT. CONTRACTOR SHALL SUPPLY, AND MECH. CONTRACTOR SHALL INSTALL A SMOKE DETECTOR IN THE RETURN AIR DUCTWORK, THE EVAPORATOR FAN AND THE COMPRESSOR SHALL BE INTERLOCKED WITH THE SMOKE DETECTORS SO THAT THE COMPRESSOR AND THE EVAPORATOR FAN ARE DE-ENERGIZED WHEN SMOKE IS DETECTED. THE SMOKE DETECTORS SHALL HAVE A SUFFICIENT NUMBER OF CONTACTS TO INTERFACE WITH THE BUILDING FIRE ALARM SYSTEM.
- ALL DUCTWORK SHALL BE SEALED AIR TIGHT WITH SEALING COMPOUND.
- THIS CONTRACTOR SHALL COORDINATE HIS WORK WITH THAT OF OTHER TRADES PRIOR TO INSTALLATION OF ANY OF HIS PIPING, DUCTWORK, OR EQUIPMENT.
- THE MECHANICAL CONTRACTOR SHALL MAKE A COMPLETE REVIEW OF THE MECHANICAL PLANS, SCHEDULES, AND DETAILS PRIOR TO INSTALLATION OF THE MECHANICAL SYSTEMS AND REVIEW ANY CONFLICTS THAT ARE NOTED WITH THE ENGINEER.
- IT WILL BE THE RESPONSIBILITY OF THE MECHANICAL CONTRACTOR TO ENSURE THAT ITEMS TO BE FURNISHED UNDER HIS CONTRACT WILL FIT THE SPACE AVAILABLE. HE SHALL MAKE NECESSARY FIELD MEASUREMENTS TO ASCERTAIN SPACE REQUIREMENTS, INCLUDING THOSE FOR CONNECTIONS AND SHALL FURNISH AND INSTALL SUCH SIZES AND SHAPES OF EQUIPMENT THAT ARE THE TRUE AND INTENT MEANING OF THE PLANS AND SPECIFICATIONS. HE SHALL PROVIDE THE ENGINEER SCALED DRAWINGS OF ALL MECHANICAL DRAWINGS.
- ALL EQUIPMENT SHALL BE LOCATED AND INSTALLED TO PROVIDE MAXIMUM SPACE FOR MAINTENANCE AND SERVICE.
- ALL ELBOWS IN DUCTWORK SHALL BE RADIUS ELBOWS, UNLESS NOTED OTHERWISE. WHERE SQUARE ELBOWS ARE SHOWN, INSTALL TURNING VANES.
- MECHANICAL CONTRACTOR TO FIELD COORDINATE LOCATION OF MECHANICAL SYSTEMS WITH ELECTRICAL AND PLUMBING SYSTEMS. COORDINATE WITH ALL OTHER SYSTEMS AS NECESSARY.
- MECHANICAL WORK INCLUDES DEMOLITION, RELOCATION, IN EXISTING & NEW WORK AS APPLICABLE. MECHANICAL CONTRACTOR TO SUPPLY A COMPLETE SYSTEM IN EACH AREA.
- DUCT SIZES SHOWN ARE NET DIMENSIONS.

AIR HANDLER UNIT																		
AHU NO.	MANUFACTURER	MODEL	VOLTAGE	E.S.P.	OUTSIDE AIR (CFM)	CFM	UNIT FLA	REF LINES		SEER	HTR KW (240)	COOLING CAPACITY (MBH)		HEATING CAPACITY (MBH)		HSPF	MIN. CIRC. AMPACITY	M.O.C.P.
								GAS	LIQ.			TOTAL	SENS.	HIGH	LOW			
AHU-1,2,3,4	RHEEM	RH1T-4821STAN	240/1φ/60	.46	177	1600	40.0	3/8	7/8	15.0	9.6	47.0	34.1	44.5	28.8	9.0	56	60

SPLIT SYSTEM HEAT PUMP UNITS									
MARK	MANUF.	MODEL	VOLTAGE	# COMP.	MIN. CIRC. AMPACITY	M.O.C.P.	UNIT FLA.	ACCESSORIES	
HP-1,2,3,4	RHEEM	RP154BAJ1	240/1φ/60	1	26	40	21.3	EXCLUDE 8,18	

ACCESSORIES

- | | | |
|-------------------------------|----------------------------------------------------------|--------------------------------------------|
| 1 TIME-DELAY RELAY | 7 LIQUID SOLENOID VALVE | 13 DISCHARGE LINE MUFFLER |
| 2 CYCLE PROTECTOR | 8 LOW-AMBIENT CONTROLLER | 14 SUCTION AND LIQUID LINE SHUT OFF VALVES |
| 3 EVAPORATOR FREEZE PROTECTOR | 9 FILTER DRIER (LIQUID LINE) | 15 THERMOSTAT (SEE NOTE) |
| 4 ISOLATION RELAY | 10 OUTDOOR TSTAT TO LOCK OUT AUX. HT. (SET @ 40° F ADJ.) | 16 SUPPORT FEET |
| 5 TXV | 11 LOW PRESSURE CONTROL | 17 COIL GUARDS |
| 6 HIGH PRESSURE SWITCH | 12 CRANKCASE HEATER | 18 HUMIDISTAT |

COOLING CAPACITY @ 80 DEG. F DB/67 DEG WB AIR ENTERING INDOOR UNIT & 95 DEG. F DB AIR ENTERING OUTDOOR UNIT
HEATING CAPACITY: HIGH TEMP = 70 DEG F DB INDOOR EAT & 47 DEG F DB/43 DEG F WB AIR ENTERING OUTDOOR UNIT
LOW TEMP = 70 DEG F DB INDOOR EAT & 17 DEG F DB ENTERING OUTDOOR UNIT

T-STAT: THE NUMBER OF STAGES OF HEATING/COOLING SHALL MATCH THE NUMBER OF STAGES OF HEAT AVAILABLE IN THE HPIU OR THE NUMBER OF STAGES OF COOLING AVAILABLE IN THE HPOU. PROVIDE WITH T-STAT; 7 DAY PROGRAMMABLE, DIGITAL.

NOTE:
VERIFY THERMOSTAT LOCATION WITH OWNER PRIOR TO INSTALLING. FILTER ALL OUTSIDE AIR.

(TYPICAL OF EACH TENANT)
METHOD OF COMPLIANCE:
PRESCRIPTIVE ENERGY COST BUDGET
THERMAL ZONE 4A - HARNETT COUNTY, NC

EXTERIOR DESIGN CONDITIONS

WINTER DRY BULB 16 DEG. F.
SUMMER DRY BULB 92 DEG. F.

INTERIOR DESIGN CONDITIONS

WINTER DRY BULB 70 DEG. F.
SUMMER DRY BULB 74 DEG. F.
RELATIVE HUMIDITY 54%


BUILDING HEATING LOAD 31.6 MBH

BUILDING COOLING LOAD 3.8 TONS


MECHANICAL SPACE CONDITIONING SYSTEM

UNITARY DESCRIPTION OF UNIT - HEAT PUMP
HEATING EFFICIENCY - 9.0 HSPF
COOLING EFFICIENCY - 15.0 SEER
SIZE CATEGORY OF UNIT - <65K
BOILER - NOT APPLICABLE IN THIS PROJECT
CHILLER - NOT APPLICABLE IN THIS PROJECT

LIST EQUIPMENT EFFICIENCIES




PLAN VIEW
NOT TO SCALE




SECTION
NOT TO SCALE

LEAVE A 1/4" SPACE AT CONDUIT FACE & FILL WITH CLOSED CELL NEOPRENE FOAM INSULATION TO PROVIDE BACKING FOR SILICONE CAULKING




DETAIL-CEILING DIFFUSER CONNECTION
NOT TO SCALE



TYPICAL DETAIL AT AIR HANDLING UNITS
NOT TO SCALE

DETAIL-TYPICAL HEAT PUMP
OUTDOOR UNIT


NOT TO SCALE



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS

NO.	DESCRIPTION



Cruse
And
Associates, P.A.
144 E. Raleigh St.
Durham, NC 27601
PHONE: (919) 286-5188
FAX: (919) 286-5188
LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22

DRAWN BY BAM

JOB NO. 22-60

SHEET NO.

M-2 OF 2

LIGHT FIXTURE SCHEDULE

MARK	DESCRIPTION	MANUFACTURER	CATALOG NUMBER	LAMPS	BALLASTS	WATTAGE	REMARKS
A	8' LED STRIPLIGHT	LITHONIA	TZ1D L96 14000LM FST MVOLT 40K 80CRI WH	LED		121	INCLUDE HC36 HANGER CHAIN
B	2X4 LED FLAT PANEL LAY-IN	LITHONIA	CPANL 2X4 40/50/60LM 35K-40LM	LED		42.0	INCLUDE WSX D DIMMING OCCUPANCY WALL SWITCH
C	2X4 LED FLAT PANEL LAY-IN	LITHONIA	CPANL 2X4 40/50/60LM 35K-40LM	LED		32.0	INCLUDE WSX D DIMMING OCCUPANCY WALL SWITCH
D	LED WALLPACK	-		LED		28	SELECTED BY OWNER
F	GOOSENECK EXTERIOR LIGHT	-		LED		52	SELECTED BY OWNER
EM	EMERGENCY LIGHT WITH BATTERY BACKUP	MCPHILBEN	CAXR6L24W6				
EX	LED TYPE EXIT LIGHT WITH BATTERY BACKUP	MCPHILBEN	CXXL3RW				
EM2	EMERGENCY LIGHT REMOTE WEATHERHEAD(S)	MCPHILBEN	CR2CSWA				

* ALL FIXTURE SELECTIONS TO BE VERIFIED BY OWNER BEFORE PURCHASE. *
 ** SIGN LETTERING TO BE ON TIMECLOCK OR PHOTOCELL

LIGHTING DATA FOR N.C. ENERGY CODE (TENANT 1)

AREA USE	AREA FT ²	WATTS PER FT ² ALLOWED	TOTAL WATTS ALLOWED	TOTAL WATTS USED	TOTAL WATTS LEFT OVER
WAREHOUSE	500	1.2	600	484	116
OFFICE	1,250	1.3	1,625	704	921
TOTAL	1,750		2,225	1,188	1,037

LIGHTING DATA FOR N.C. ENERGY CODE (TENANT 2 & 3)


AREA USE	AREA FT ²	WATTS PER FT ² ALLOWED	TOTAL WATTS ALLOWED	TOTAL WATTS USED	TOTAL WATTS LEFT OVER
OFFICE (TENANT 2)	1,750	1.3	2,275	830	1,445
OFFICE (TENANT 3)	1,750	1.3	2,275	830	1,445
TOTAL	3,500		2,275	1,660	2,890

LIGHTING DATA FOR N.C. ENERGY CODE (TENANT 4)


AREA USE	AREA FT ²	WATTS PER FT ² ALLOWED	TOTAL WATTS ALLOWED	TOTAL WATTS USED	TOTAL WATTS LEFT OVER
WAREHOUSE	1,200	1.2	1,440	1,089	351
OFFICE	550	1.3	715	326	389
TOTAL	1,750		2,155	1,415	740

ELECTRICAL LEGEND

MARK	DESCRIPTION
⊕	QUAD RECEPTACLE
⊕	DUPLEX RECEPTACLE
⏏	TIMER WITH NO HOLD MECHANISM
⊕	CEILING MOUNTED DUPLEX RECEPTACLE
▭	FLUORESCENT FIXTURE
↪	SWITCHED BRANCH CIRCUIT
↪	UNSWITCHED BRANCH CIRCUIT
↪	120/208 VOLT CIRCUIT
Ⓜ	MOTION DETECTING SINGLE-POLE SWITCH ON TIMER
⊗	'EXIT' LIGHT FIXTURE, TYPE 'EX'
⊕	BATTERY OPERATED EMERG. LT. (2-HEAD, WALL MTD.)
Ⓜ	MOTION DETECTING 3-WAY SWITCH (4-WAY SWITCH) WITH TIMER
⊕	FUSED DISCONNECT SWITCH
⊕	CEILING MOUNTED FUSED DISCONNECT SWITCH
△	TELEPHONE
⊕	JUNCTION BOX
Ⓜ	SINGLE POLE SWITCH OR TIMER AS APPLICABLE
▭	UNSWITCHED FIXTURE
Ⓜ	OCCUPANCY SENSING SINGLE-POLE SWITCH NOT ON TIMER
⊕	DUPLEX RECEPTACLE
⊕	EMERGENCY LIGHT REMOTE WEATHERHEAD(S)




ELECTRICAL LIGHTING PLAN
 SCALE: 3/16" = 1'-0"



UP-FIT PLANS FOR:
 T&L COATS
 BUILDING #2
 COATS, NORTH CAROLINA

REVISIONS

NO.	




Cruse and Associates, P.A.
 414 E. Blount St., Raleigh, NC 27604
 TEL: (919) 882-4429
 FAX: (919) 882-5182
 LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
 © COPY RIGHT

DATE 12-19-22
 DRAWN BY BAM
 JOB NO. 22-60


SHEET NO.
E-1 OF 4

ELECTRICAL LEGEND	
MARK	DESCRIPTION
	QUAD RECEPTACLE
	DUPLEX RECEPTACLE
	TIMER WITH NO HOLD MECHANISM
	CEILING MOUNTED DUPLEX RECEPTACLE
	FLUORESCENT FIXTURE
	SWITCHED BRANCH CIRCUIT
	UNSWITCHED BRANCH CIRCUIT
	120/208 VOLT CIRCUIT
	MOTION DETECTING SINGLE-POLE SWITCH ON TIMER
	'EXIT' LIGHT FIXTURE, TYPE 'EX'
	BATTERY OPERATED EMERG. LT. (2-HEAD, WALL MTD.)
	MOTION DETECTING 3-WAY SWITCH (4-WAY SWITCH) WITH TIMER
	FUSED DISCONNECT SWITCH
	CEILING MOUNTED FUSED DISCONNECT SWITCH
	TELEPHONE
	JUNCTION BOX
	SINGLE POLE SWITCH OR TIMER AS APPLICABLE
	UNSWITCHED FIXTURE
	OCCUPANCY SENSING SINGLE-POLE SWITCH NOT ON TIMER
	DUPLEX RECEPTACLE
	EMERGENCY LIGHT REMOTE WEATHERHEAD(S)




ELECTRICAL POWER PLAN
SCALE: 3/16" = 1'-0"

CONNECTION SCHEDULE




NOTE:
1. VERIFY DATA/PHONE JACK LOCATIONS, QUANTITY, AND CONFIGURATIONS WITH OWNER BEFORE BEGINNING CONSTRUCTION.



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	




Cruse and Associates, P.A.
444 E. Salisbury St., Raleigh, NC 27604
PH: (919) 892-4429
FAX: (919) 892-5162
LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22
DRAWN BY BAM
JOB NO. 22-60

SHEET NO.
E-2 OF 4




HOUSE PANEL

PANEL: H SCHEDULE: _____ MANUFACTURER: SQ. D NO. OF SPACES 30
 VOLTS: 120/240 AMPS: 100 TYPE: NQOD MOUNTING: SURFACE
 ENCLOSURE: NEMA 3R ϕ : 1 SHORT CIRCUIT RATING: 22K
 MAIN M.L.O. TOP FEED BOTTOM FEED COPPER BUS GROUND BAR KIT NEUTRAL BAR KIT

L1	L2	CIRCUIT	POLES	TRIP	ASSIGNMENT	PHASE	ASSIGNMENT	TRIP	POLES	CIRCUIT	L1	L2
		1	1	20	FRONT & LEFT EXT. LIGHTING	o	SPARE	20	1	2	X	
	2.0	3	1	20	BUILDING SIGN	o	REAR & RIGHT EXT. LIGHTING	20	1	4		7.0
X		5	1	20	SPARE	o	SPARE	20	1	6	X	
	X	7	1	20	SPARE	o	SPARE	20	1	8		X
X		9	1	20	SPARE	o	SPARE	20	1	10	X	
	X	11	1	20	SPARE	o	SPARE	20	1	12		X
X		13	1	20	SPARE	o	SPARE	20	1	14	X	
	X	15	1	20	SPARE	o	SPARE	20	1	16		X
X		17	1	20	SPARE	o	SPARE	20	1	18	X	
	X	19	1	20	SPARE	o	SPARE	20	1	20		X
X		21	1	20	SPARE	o	SPARE	20	1	22	X	
	X	23	1	20	SPARE	o	SPARE	20	1	24		X
X		25	1	20	SPARE	o	SPARE	20	1	26	X	
	X	27	1	20	SPARE	o	SPARE	20	1	28		X
X		29	1	20	SPARE	o	SPARE	20	1	30	X	


L1 = 7.0 A
L2 = 9.0 A



ELECTRICAL RISER DIAGRAM
NOT TO SCALE

UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	



Cruse and Associates, P.A.
 LICENSE NO. C-1724
 115 E. Franklin St.
 Durham, North Carolina 27634
 P.O. Box 4459
 Durham, NC 27610
 TEL: (919) 286-3100
 FAX: (919) 286-3100

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
 © COPY RIGHT

DATE 12-19-22
 DRAWN BY BAM
 JOB NO. 22-60


SHEET NO.
E-4 OF 4

DOOR SCHEDULE

DOOR NO.	DOOR SIZE			REMARKS
	WIDE	HIGH	THICK.	
01	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD SLIDING DOOR
02	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
03	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
04	2'-6"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
05	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
06	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
07	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
08	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
09	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
10	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
11	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
12	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
13	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
14	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
15	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
16	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
17	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
18	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
19	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD DOOR: HM FRAME
20	3'-0"	7'-0"	1 3/4"	INTERIOR WOOD SLIDING DOOR

KEYNOTES:


- 1 FURROUT WALL & PROVIDE ACCESS PANEL FOR DOMESTIC WATER SUPPLY FOR WATER SERVICE ENTRANCE (SEE SHEET P-1)
- 2 2-1/2" 20 GA. METAL STUD @ 16" O.C.
- 3 6" 18 GA METAL STUDS @ 16" O.C. TO ROOF DECK
- 4 3-5/8" 20 GA. METAL STUD @ 16" O.C.
- 5 6" 20 GA METAL STUDS @ 16" O.C.




PROPOSED WALL DETAIL
SCALE: NOT TO SCALE

ROOM NO.	ROOM NAME	FLOOR				BASE				WALLS				CEL. HT.		CLG.		REMARKS
		CONCRETE	TILE	LVLT	VT	WOOD	CERAMIC TILE	RUBBER BASE	NONE	BRICK	1/2" DRYWALL	CERAMIC TILE	FRP	10'-0"+	11'-0"+	NONE	DRYWALL	
100	LOBBY			X				X	X	X	X	X	10'-0"+	X				
101	CONFERENCE ROOM			X				X	X	X	X	10'-0"+	X					
102	OFFICE			X				X	X	X	X	10'-0"+	X					
103	UNISEX RESTROOM			X				X	X	X	X	10'-0"+	X					
104	OFFICE 2			X				X	X	X	X	10'-0"+	X					
105	OFFICE 3			X				X	X	X	X	10'-0"+	X					
106	BREAKROOM			X				X	X	X	X	10'-0"+	X					
107	OFFICE 4			X				X	X	X	X	10'-0"+	X					
108	WAREHOUSE	X							X			NONE	X					
200	OPEN FLOOR AREA			X				X	X	X	X	11'-0"+	X					*
201	OFFICE 1			X				X	X	X	X	10'-0"+	X					
202	OFFICE 2			X				X	X	X	X	10'-0"+	X					
203	STORAGE			X				X	X	X	X	10'-0"+	X					
204	CORRIDOR			X				X	X	X	X	10'-0"+	X					
205	UNISEX RESTROOM			X				X	X	X	X	10'-0"+	X					
300	OPEN FLOOR AREA			X				X	X	X	X	11'-0"+	X					*
301	OFFICE 1			X				X	X	X	X	10'-0"+	X					
302	OFFICE 2			X				X	X	X	X	10'-0"+	X					
303	STORAGE			X				X	X	X	X	10'-0"+	X					
304	CORRIDOR			X				X	X	X	X	10'-0"+	X					
305	UNISEX RESTROOM			X				X	X	X	X	10'-0"+	X					
400	LOBBY			X				X	X	X	X	11'-0"+	X					*
401	UNISEX RESTROOM			X				X	X	X	X	10'-0"+	X					
402	OFFICE 1			X				X	X	X	X	10'-0"+	X					
403	WAREHOUSE			X					X			NONE	X					

OWNER TO VERIFY ALL COLORS, HEIGHTS, AND FINISHES BEFORE ORDERING MATERIALS
*COORDINATE CEILING HEIGHT WITH HEIGHT OF STOREFRONT GLASS.




PROPOSED FLOOR PLAN
SCALE: 3/16" = 1'-0"



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	



Cruse and Associates, P.A.
114 E. Robertson St.
Durham, North Carolina 28834
PHONE: (919) 282-5122
FAX: (919) 282-5122
LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISHED OR DUPLICATED DRAWINGS OR DESIGNS WITHOUT THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22
DRAWN BY BAM
JOB NO. 22-60

SHEET NO.
F-1 OF 2

FOUNDATION NOTES:


- FIELD VERIFY THE SIZE, LOCATIONS, ELEVATIONS, AND DETAILS OF ALL EXISTING CONSTRUCTION AND CONDITIONS THAT AFFECT THE WORK AND INFORM THE ENGINEER OF ANY DISCREPANCIES IN DIMENSION SIZES, LOCATIONS AND CONDITIONS BEFORE PROCEEDING WITH THE WORK.
- PROVIDE ALL SHORING, SHEETING, UNDERPINNING, AND OTHER MEANS REQUIRED TO PROTECT AND MAINTAIN THE SAFETY, INTEGRITY, AND STABILITY OF ALL EXISTING AND NEW CONSTRUCTION THAT MAY BE AFFECTED BY THE WORK.
- CONCRETE SHALL DEVELOP COMPRESSIVE STRENGTHS (F'C) AT 28 DAYS AS FOLLOWS: FOUNDATIONS, WALLS, FOOTING, ETC. $\frac{3000 \text{ PSI}}{3000 \text{ PSI}}$ SLABS ON GRADE $\frac{3000 \text{ PSI}}{3000 \text{ PSI}}$
- ALL BUILDING FOOTINGS AND FOUNDATIONS ARE DESIGNED BASED UPON A MINIMUM ALLOWABLE SOIL BEARING PRESSURE OF 2000 PSF. IF SUITABLE SOIL CAPABLE OF SUSTAINING THIS CAPACITY IS NOT FOUND AT THE ELEVATIONS INDICATED, THE ENGINEER SHALL BE NOTIFIED AND THE FOUNDATIONS SHALL BE CHANGED IN ELEVATION AND/OR SIZE AS DETERMINED BY THE ENGINEER.
- CONCRETE BAR REINFORCEMENT SHALL BE NEW BILLET STEEL CONFORMING TO THE STANDARD SPECIFICATION FOR DEFORMED BILLET STEEL BARS FOR CONCRETE REINFORCEMENT ASTM A-615, GRADE 60.
- ALL STRUCTURAL FILL INSIDE THE BUILDING SHALL BE SELECTED FILL COMPACTED TO 96% MAXIMUM DENSITY AT OPTIMUM MOISTURE CONTENT (ASTM D-698)
- ALL DETAILING, FABRICATION AND ERECTION OF REINFORCING STEEL SHALL CONFORM TO ACI "MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES" (ACI-315-80).
- PROVIDE CORNER BARS AT ALL FOOTING CORNERS AND STEPS UNLESS OTHERWISE NOTED. BARS SHALL BE A MINIMUM OF 4'-0" LONG AND HAVE THE SAME SIZE AND SPACING AS HORIZONTAL REINFORCING.
- WELDED WIRE FABRIC SHALL CONFORM TO ASTM A-185 AND A-82.
- CONTINUOUS REINFORCING BARS SHALL BE LAPPED 48 BAR DIAMETERS AT ALL SPLICES UNLESS OTHERWISE NOTED.
- STANDARD CONSTRUCTION JOINTS AND EXPANSION JOINTS SHALL BE LOCATED AS SHOWN ON THE PLANS.
- ALL CONCRETE SHALL BE PROTECTED AGAINST FREEZING FOR SEVEN DAYS AFTER POURING.
- FLOOR SLAB TO BE POURED ON 6 MIL POLYETHYLENE FILM OVER 4" THICK DRAINAGE FILL, COMPACTED FILL, OR OVER EXISTING CONCRETE SLAB.
- REFER TO MECHANICAL, ELECTRICAL, PLUMBING, AND ARCHITECTURAL DRAWINGS AND CONSULT ALL AFFECTED SUBCONTRACTORS FOR LOCATIONS AND SIZES OF REQUIRED OPENINGS AND CAST-IN-ITEMS IN CONCRETE WORK. ALL OPENINGS ON THE STRUCTURAL DRAWINGS SHALL BE SHOWN ON SHOP DRAWINGS FOR APPROVAL.

NOTES:

- ALLOWABLE SOIL BEARING CAPACITY OF 2000 PSF TO VERIFIED BY CONTRACTOR.
- CONCRETE TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI AT 28 DAYS.
- CONTROL JOINTS TO BE PLACED AS SHOWN ON PLAN.
- SEE METAL BUILDING DRAWINGS FOR ACTUAL COLUMN LOCATIONS.

NOTES:

- G.C. TO VERIFY ALL EQUIPMENT SIZES, ELECTRICAL, PLUMBING AND GAS REQUIREMENTS BEFORE BEGINNING CONSTRUCTION.




KEY NOTES:

- Ⓐ PERIMETER OF NEW CONCRETE SLAB. DOWEL INTO EXISTING SLAB.
- Ⓑ EXISTING CONCRETE SLAB & FOOTINGS.


FOUNDATION PLAN

SCALE: 3/16" = 1'-0"



UP-FIT PLANS FOR:
T&L COATS
BUILDING #2
COATS, NORTH CAROLINA

REVISIONS	
NO.	



Cruse and Associates, P.A.
Andy L. Cruse, P.E.
22834
Durham, North Carolina 27834
P.O. Box 22834
Durham, NC 27834
TEL: (919) 882-4489
FAX: (919) 882-3108
LICENSE NO.: C-1721

THESE DOCUMENTS ARE INSTRUMENTS OF SERVICE AND AS SUCH THESE DRAWINGS, DESIGNS, AND DESIGN CONCEPTS PRESENTED REMAIN THE PROPERTY OF THE ENGINEER. PUBLISH OR DUPLICATE THE DRAWINGS OR DESIGNS ONLY WITH THE WRITTEN PERMISSION OF THE ENGINEER.
© COPY RIGHT

DATE 12-19-22

DRAWN BY BAM

JOB NO. 22-60

SHEET NO.

F-2 OF 2