


1. **Concrete Blocks*** - Various designs. Classifications C-3 (3hr.)
See Concrete Blocks category for list of eligible manufacturers.
 2. **Mortar**- Blocks laid in full bed of mortar, nom. 3/8" thick, of not less than 2-1/4" and not more than 3-1/2" parts of clean sharp sand to one part Portland cement (proportioned by volume) and not more than 50 percent hydrated lime (by cement volume). Vertical joints staggered.
 3. **Portland cement stucco or gypsum plaster**-Add 1/2 hr. to classification if used. Attached to concrete blocks.
 4. **Loose Masonry Fill**- If all core spaces are filled with loose dry expanded slag, expanded clay or shale (Rotary Kilm Process), water repellent vermiculite masonry fill insulation, or silicone treated perlite loose fill insulation add 1 hr. to classification.
 5. **Foamed Plastic*** - (Optional-Not Shown) 1-1/2 in. thick max, 4 ft wide sheathing attached to concrete blocks (Item 1).
ATLAS ROOFING CORP.-EnergyShield Pro Wall Insulation, EnergyShield Pro 2 Wall Insulation, EnergyShield CGF Pro, EnergyShield Ply, EnergyShield
DUPONT DE NEMOURS, INC. - Type Thermax Sheathing, Thermax Light Duty Insulation, Thermax Heavy Duty Insulation, Thermax Metal Building Board, Thermax White Finish Insulation, Thermax G Exterior Insulation, Thermax XARMOR G Exterior Insulation, Thermax IH Insulation, Thermax Plus Liner Panel, Thermax Heavy Duty Plus (HDP), TUFF-RIM G Insulation, Thermax Butler Strywall Insulation Board and Thermax Morton Heavy Duty Insulation Board
FIRESTONE BUILDING PRODUCTS CO. L. C. - "Emergel™ G Foil Exterior Wall Insulation" and "Emergel™ G Glass Exterior Wall Insulation"
HUNTER PANELS, A DIVISION OF CARLISLE CONSTRUCTION MATERIALS, LLC - Type "Xci-Class A", "Xci 286", "Xci Foil (Class A)"
RMAX, A BUSINESS UNIT OF SIKA CORPORATION - Types "TSX-8500", "ECOMAX G FR", "TSX-8510", "ECOMAX X FR White", "ECOMAX G", "ECOMAX G FR Air Barrier", "Thermasheath-XP", "Thermasheath", "Durasheath"
JOHNS MANVILLE - Type "AP Foil-Faced Foam Sheathing"
- 5A. **Building Units*** - As an alternate to Item 5, min. 1-in thick polyisocyanurate composite foamed plastic insulation boards, nom. 48 by 48 or 96 in.
ATLAS ROOFING CORP. - EnergyShield
RMAX, A BUSINESS UNIT OF SIKA CORPORATION - Thermasheath-SI, "ECOBASECt", "ThermaBase-CI", "ECOMAX G FR Ply", "ECOMAX G Ply".
- * Indicates such products shall bear the UL or eUL Certification Mark for jurisdictions employing the UL or eUL Certification (such as Canada), respectively.




1. **Floor and Ceiling Runners** — (Not shown) — Channel shaped, fabricated from min 25 MSG (min 20 MSG when Item 4A is used) corrosion-protected steel, min width to accommodate stud size, with min 1 in. long legs, attached to floor and ceiling with fasteners 24 in. OC max.
 2. **Steel Studs** — Channel shaped, fabricated from min 25 MSG (min 20 MSG when Item 4A is used) corrosion-protected steel, min width as indicated under Item 4, min 1-1/4 in. flanges and 1/4 in. return, spaced a max of 24 in. OC. Studs to be cut 3/8 to 3/4 in. less than assembly height.
 3. **Batts and Blankets*** — (Required as indicated under Item 4) — Mineral wool batts, friction fitted between studs and runners. Min nom thickness as indicated under Item 4. See Batts and Blankets (BKNV or BZJZ) Categories for names of Classified companies.
 - 3A. **Batts and Blankets*** — (Optional) — Placed in stud cavities, any glass fiber or mineral wool insulation bearing the UL Classification Marking as to Surface Burning Characteristics and/or Fire Resistance. See Batts and Blankets (BKNV or BZJZ) Categories for names of Classified companies.
 4. **Gypsum Board*** — Gypsum panels with beveled, square or tapered edges, applied vertically or horizontally. Vertical joints centered over studs and staggered one stud cavity on opposite sides of studs. Vertical joints in adjacent layers (multilayer systems) staggered one stud cavity. Horizontal joints need not be backed by steel framing. Horizontal edge joints and horizontal butt joints on opposite sides of studs need not be staggered. Horizontal edge joints and horizontal butt joints in adjacent layers (multilayer systems) staggered a min of 12 in. The thickness and number of layers for the 1 hr, 2 hr, 3 hr and 4 hr ratings are as follows:
- | Wallboard Protection on Each Side of Wall | | | |
|---|----------------|--------------------------------|----------------------------------|
| Rating | Min Stud Depth | No. of Layers & Thkns of Panel | Min Thkns of Insulation (Item 3) |
| 1 | 3-1/2 | 1 layer, 5/8 in. thick | Optional |
| 1 | 2-1/2 | 1 layer, 1/2 in. thick | Optional |
| 1 | 1-5/8 | 1 layer, 3/4 in. thick | Optional |
| 2 | 1-5/8 | 2 layers, 1/2 in. thick | Optional |
| 2 | 1-5/8 | 2 layers, 5/8 in. thick | Optional |
| 2 | 3-1/2 | 1 layer, 3/4 in. thick | 3 in. |
| 3 | 1-5/8 | 3 layers, 1/2 in. thick | Optional |
| 3 | 1-5/8 | 2 layers, 3/4 in. thick | Optional |
| 3 | 1-5/8 | 3 layers, 5/8 in. thick | Optional |
| 4 | 1-5/8 | 4 layers, 5/8 in. thick | Optional |
| 4 | 1-5/8 | 4 layers, 1/2 in. thick | Optional |
| 4 | 2-1/2 | 2 layers, 3/4 in. thick | 2 in. |
- CANADIAN GYPSUM COMPANY — 1/2 in. thick Type C, IP-X2 or IPC-AR; WRC; 5/8 in. thick Type AR, C, IP-AR, IP-X1, IP-X2, IPC-AR, SCX, SHX, WRX or WRC; 3/4 in. thick Type IP-X3, ULTRACODE, ULTRACODE SHC or ULTRACODE WRC.
- UNITED STATES GYPSUM CO — 1/2 in. thick Type C, IP-X2, IPC-AR or WRC; 5/8 in. thick Type SCX, SHX, WRX, IP-X1, AR, C, WRC, FRX-G, IP-AR, IP-X2, IPC-AR; 3/4 in. thick Type IP-X3, ULTRACODE, ULTRACODE SHC or ULTRACODE WRC.
- USG MEXICO S A DE C V — 1/2 in. thick Type C, IP-X2, IPC-AR or WRC; 5/8 in. thick Type AR, C, IP-AR, IP-X1, IP-X2, IPC-AR, SCX, SHX, WRX, WRC or 3/4 in. thick Type IP-X3, ULTRACODE, ULTRACODE SHC or ULTRACODE WRC.


- 4A. **Gypsum Board*** — (As an alternate to Item 4) — 5/8 in. thick gypsum panels, installed as described in Item 4 with Type S-12 steel screws. The length and spacing of the screws as specified under Item 5.
- CANADIAN GYPSUM COMPANY — Type FRX
UNITED STATES GYPSUM CO — Type FRX
- 4B. **Gypsum Board*** — (As an alternate to Items 4 and 4A) — 5/8 in. thick, 2 ft. wide, tongue and groove edge, applied horizontally as the outer layer to one side of the assembly. Secured as described in Item 5. Joint covering (Item 7) not required.
- CANADIAN GYPSUM COMPANY — Type SHX.
UNITED STATES GYPSUM CO — Type SHX.
USG MEXICO S A DE C V — Type SHX.

5. **Fasteners** — (Not shown) — Type S or S-12 steel screws used to attach panels to studs (Item 2) or furring channels (Item 6). Single layer systems: 1 in. long for 1/2 and 5/8 in. thick panels or 1-1/4 in. long for 3/4 in. thick panels, spaced 8 in. OC when panels are applied horizontally, or 8 in. OC along vertical and bottom edges and 12 in. OC in the field when panels are applied vertically. Two layer systems: First layer- 1 in. long for 1/2 and 5/8 in. thick panels or 1-1/4 in. long for 3/4 in. thick panels, spaced 16 in. OC. Second layer- 1-5/8 in. long for 1/2 in., 5/8 in. thick panels or 2-1/4 in. long for 3/4 in. thick panels, spaced 16 in. OC with screws offset 6 in. from first layer. Three-layer systems: First layer- 1 in. long for 1/2 in., 5/8 in. thick panels, spaced 24 in. OC. Second layer- 1-5/8 in. long for 1/2 in., 5/8 in. thick panels, spaced 24 in. OC. Third layer- 2-1/4 in. long for 1/2 in., 5/8 in. thick panels or 2-5/8 in. long for 5/8 in. thick panels, spaced 12 in. OC. Screws offset min 6 in. from layer below. Four-layer systems: First layer- 1 in. long for 1/2 in., 5/8 in. thick panels, spaced 24 in. OC. Second layer- 1-5/8 in. long for 1/2 in., 5/8 in. thick panels, spaced 24 in. OC. Third layer- 2-1/4 in. long for 1/2 in. thick panels or 2-5/8 in. long for 5/8 in. thick panels, spaced 24 in. OC. Fourth layer- 2-5/8 in. long for 1/2 in. thick panels or 3 in. long for 5/8 in. thick panels, spaced 12 in. OC. Screws offset min 6 in. from layer below.
6. **Furring Channels** — (Optional, not shown, for single or double layer systems) — Resilient furring channels fabricated from min 25 MSG corrosion-protected steel, spaced vertically a max of 24 in. OC. Flange portion attached to each intersecting stud with 1/2 in. long Type S-12 steel screws. Not for use with Item 4A.
7. **Joint Tape and Compound** — Vinyl or casein, dry or premixed joint compound applied in two coats to joints and screw heads of outer layers. Paper tape, nom 2 in. wide, embedded in first layer of compound over all joints of outer layer panels. Paper tape and joint compound may be omitted when gypsum panels are supplied with a square edge.
8. **Siding, Brick or Stucco** — (Optional, not shown) — Aluminum, vinyl or steel siding, brick veneer or stucco, meeting the requirements of local code agencies, installed over gypsum panels. Brick veneer attached to studs with corrugated metal wall ties attached to each stud with steel screws, not more than each sixth course of brick.
9. **Caulking and Sealants*** — (Optional, not shown) — A bead of acoustical sealant applied around the partition perimeter for sound control.

UNITED STATES GYPSUM CO — Type AS
*Bearing the UL Classification Mark



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.773.9797
www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232b
DRAWING TITLE
UL'S

SHEET 2 OF 14

A0.2

PLOT DATE 10/25/23
REVISION ---

This original sheet is 24" x 36", other dimensions indicate it has been altered.

All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©

OCCUPANT LOAD				
	BUSINESS	10,518 sf	100 sf GROSS	106
	EXERCISE	1,276 sf	50 sf GROSS	26
	UNCONC. ASSEMBLY	373sf	15 sf NET	25
	STORAGE	4,759 sf	300sf GROSS	16
	F1	968 sf	100 sf GROSS	10
	REPAIR GARAGE (S1)	11,969 sf	500 sf GROSS	24
TOTAL OCCUPANTS				207

WALL LEGEND	
	BRICK VENEER EXT. WALL WITH METAL STUD BACK UP
	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM & FURRING W/ DRYWALL
	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM MTL. LINER PANELS AS SCHED.
	2 HOUR RATED FIRE BARRIER (PER U419)
	3 HOUR RATED FIRE BARRIER (SEE 8/A4.2)
	FULL HEIGHT MTL STUD WALL W/ SOUND BATT INSUL. (PER 3/A4.2)
	FULL HEIGHT WALL 6" MTL STUDS SIM TO 3/A4.2 WITH 8" METAL LINER PANELS
	PARTIAL HEIGHT WALL 3 5/8" MTL STUDS (PER 4/A4.2)

EGRESS REQ. & CODE REF.

COMMON PATH OF TRAVEL = 75' MAX.
MAX. TRAVEL DIST. = 200'


DOORS TO HAVE 32" MIN. CLR. PER 404.2.2 OF ANSI A117.1

THE CLEAR WIDTH OF INTERIOR ACCESSIBLE ROUTE IS 36" MIN. PER 403.5 OF ANSI A117.1


LEGEND

EGRESS PATH


FE
ABC FIRE EXTINGUISHER IN PARTIALLY RECESSED CABINET HANDLE OF EXT. 48" AFF MAX VERIFY LOC. W/ FIRE MARSHALL



1 LIFE SAFETY
SCALE: 3/32" = 1'-0"



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232b

DRAWING TITLE
LIFE SAFETY


SHEET 3 OF 14

A0.3


PLOT DATE 12/1/23
REVISION COUNTY COM. 11/10/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.

All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




2 FLOOR PLAN - WASH BAY
SCALE: 1/8" = 1'-0"




1 FLOOR PLAN - PARTIAL
SCALE: 1/8" = 1'-0"



WALL LEGEND	
1	BRICK VENEER EXT. WALL WITH METAL STUD BACK UP
2	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM & FURRING W/ DRYWALL
3	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM MTL. LINER PANELS AS SCHED.
4	2 HOUR RATED FIRE BARRIER (PER U419)
5	3 HOUR RATED FIRE BARRIER (SEE 8/A4.2)
6	FULL HEIGHT MTL. STUD WALL W/ SOUND BATT INSUL. (PER 3/A4.2)
7	FULL HEIGHT WALL 6" MTL STUDS SIM TO 3/A4.2 WITH 8" METAL LINER PANELS
	PARTIAL HEIGHT WALL 3 5/8" MTL STUDS (PER 4/A4.2)
	hyp. int. wall u.n.o.



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.773.9797
www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA


PROJECT NO.
2232b
DRAWING TITLE
REAR SECT-PLAN

SHEET 4 OF 14


A1.1

PLOT DATE 10/25/23
REVISION ---


This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com



WALL LEGEND	
1	BRICK VENEER EXT. WALL WITH METAL STUD BACK UP
2	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM & FURRING W/ DRYWALL
3	EXT. METAL WALL PANEL WITH LINER INSUL. SYSTEM MTL. LINER PANELS AS SCHED.
4	2 HOUR RATED FIRE BARRIER (PER U419) 2/A4.2
5	3 HOUR RATED FIRE BARRIER (SEE 8/A4.2)
6	FULL HEIGHT MTL STUD WALL W/ SOUND BATT INSUL. (PER 3/A4.2)
7	FULL HEIGHT WALL 6" MTL STUDS SIM TO 3/A4.2 WITH 8" METAL LINER PANELS
	typ. int. wall u.n.o.
	PARTIAL HEIGHT WALL 3/5/8" MTL STUDS (PER 4/A4.2)



1 FLOOR PLAN - PARTIAL
SCALE: 1/8" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA


PROJECT NO.
2232
DRAWING TITLE
FRONT PLAN

SHEET 5 OF 14


A1.2

PLOT DATE 11/10/23
REVISION COUNTY COM. 11/10/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.773.9797
 www.wsarchitectspa.com




ROOF DRAINAGE LEGEND	
	3.5" x 5" VERTICAL LEADER
	7" EAVE GUTTER @ 0.5% SLOPE
	8" EAVE GUTTER @ 0.5% SLOPE
ALL ROOF PENETRATIONS TO BE PAINTED TO MATCH ROOF.	

ROOF DRAINAGE CALCULATIONS PER 2018 NC PLUMBING CODE		
TABLE 1106.2 (2) RECTANGULAR VERTICAL LEADERS		
3-1/2 X 5	@ 4"/HR	5,320 SF MAX AREA
TABLE 1106.6 SIZE OF SEMI-CIRCULAR ROOF GUTTERS		
7" DIA. @ 4"/HR		1,380 SF MAX AREA
	@ 1/16: 12 (0.5%) SLOPE	
8" DIA. @ 4"/HR		1,990 SF MAX AREA
	@ 1/16: 12 (0.5%) SLOPE	



1 ROOF PLAN - MAIN BLDG.
 SCALE: 3/32" = 1'-0"



2 ROOF PLAN - WASH BAY AND SHED
 SCALE: 3/32" = 1'-0"

DS FROM UPPER ROOF TO GROUND LEVEL TYP. BOTH SIDES
 DS FROM LOWER ROOF TYP. BOTH SIDES
 DS FROM UPPER ROOF TO GROUND LEVEL TYP. BOTH SIDES
 DS FROM LOWER ROOF TYP. BOTH SIDES
 DS FROM UPPER ROOF TO LOWER ROOF-TYP x 4
 DS FROM LOWER ROOF TYP. BOTH SIDES

PROJECT TITLE
REVELS TURF & TRACTOR
 RAWLS CHURCH ROAD
 FUQUAY-VARINA, NORTH CAROLINA


PROJECT NO.
2232b
 DRAWING TITLE
ROOF PLAN

SHEET 6 OF 14

A1.3

PLOT DATE 10/25/23
 REVISION ...


This original sheet is 24" x 36", other dimensions indicate it has been altered.
 All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com




3 FRONT ELEVATION (SOUTH) - facing street
SCALE: 1/8" = 1'-0"




4 WASH BAY ELEVATION (NORTH)
SCALE: 1/8" = 1'-0"



2 SIDE ELEVATION (EAST) partial
SCALE: 1/8" = 1'-0"



5 WASH BAY ELEVATION (EAST)
SCALE: 1/8" = 1'-0"



1 SIDE ELEVATION (EAST) partial
SCALE: 1/8" = 1'-0"

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA


PROJECT NO.
2232b
DRAWING TITLE
ELEVATIONS

SHEET **7** OF **14**



A 2.1

PLOT DATE **10/25/23**
REVISION ---


This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W.S. Architects PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com




3 REAR ELEVATION (NORTH)
SCALE: 1/8" = 1'-0"




2 SIDE ELEVATION (WEST) partial
SCALE: 1/8" = 1'-0"



4 WASH BAY ELEVATION (SOUTH)
SCALE: 1/8" = 1'-0"



1 SIDE ELEVATION (WEST) partial
SCALE: 1/8" = 1'-0"



5 WASH BAY ELEVATION (WEST)
SCALE: 1/8" = 1'-0"

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232b




DRAWING TITLE
ELEVATIONS

SHEET 8 OF 114

A 2.2




PLOT DATE 10/25/23
REVISION ---

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




WINDOW SCHEDULE						
MARK	W	SIZE	H	MATERIAL	GLASS	REMARKS
A	4'-0"	x 4'-8"		ALUMINUM	1" INSUL. LOW E GLASS	FIXED
B	6'-0"	x 4'-8"		ALUMINUM	1" INSUL. LOW E GLASS	FIXED
C	3'-0"	x 4'-0"		ALUMINUM	90 MIN. RATED GLASS	FIXED
D	4'-4"	x 3'-8"		ALUMINUM	TEMPERED GLASS	SLIDER
E	5'-0"	x 3'-8"		ALUMINUM	TEMPERED GLASS	FIXED

NOTES:
 -SEE WINDOW TYPE ELEVATIONS AND DETAILS.
 -FIELD VERIFY ALL EXISTING OPENING SIZES. DIMENSIONS GIVEN FOR REFERENCE.
 -INCLUDE THERMAL BREAK PER MANUFACTURER'S STANDARDS WITH ALL FRAMES.
 -ALL WINDOWS TO MEET NCSBC SECTION 1609.1.2




SEE STRUCTURAL DRAWINGS FOR FOUNDATION AND FRAMING INFORMATION

SEE STRUCTURAL DRAWINGS FOR FOUNDATION AND FRAMING INFORMATION



W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.773.9797
 www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
 RAWLS CHURCH RD.
 FUQUAY-VARIN, NC


PROJECT NO.
2232b
 DRAWING TITLE
BLDG. SECTIONS

SHEET 9 OF 14



A3

PLOT DATE 10/25/23
 REVISION ...


This original sheet is 24" x 36", other dimensions indicate it has been altered.
 All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.773.9797
www.wsarchitectspa.com




4 DRYWALL BULKHEAD
SCALE: 3/4" = 1'-0"




SEE STRUCTURAL DRAWINGS FOR FOUNDATION AND FRAMING INFORMATION

1 WALL SECTION @ REAR
SCALE: 3/4" = 1'-0"



2 WALL SECTION @ FRONT
SCALE: 3/4" = 1'-0"



3 WALL SECTION @ SIDE
SCALE: 3/4" = 1'-0"

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA


PROJECT NO.
2232b
DRAWING TITLE
WALL SECTIONS

SHEET 10 OF 14

A4.1

PLOT DATE 10/25/23
REVISION ...

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




5 BOLLARD DETAIL
SCALE: 3/4" = 1'-0"


* MAXIMUM STUD HEIGHTS FOR INTERIOR TENANT SEPARATION WALLS

Size	Gauge	O.C. Spacing	Max. Height
2 1/2"	25 ga.	12"	13'-11"
		16"	12'-8"
		24"	11'-1"
3 5/8"	24 ga.	12"	18'-6"
		16"	16'-10"
		24"	14'-8"
3 1/2"	25 ga.	12"	18'-0"
		16"	16'-4"
		24"	14'-4"
6"	25 ga.	12"	27'-7"
		16"	26'-0"
		24"	21'-10"
8"	25 ga.	12"	34'-10"
		16"	31'-7"
		24"	27'-7"


Top track by Fire Trak Corp. or equal and of same gauge as stud
 * Based upon information furnished by Dietrich for CWN type steel studs. (alternate stud types and gauges shall be approved by the architect)




3 FULL HEIGHT WALL SECTION
SCALE: 1/2" = 1'-0"




6 TYP. MAS. EXP. JOINT
SCALE: 1 1/2" = 1'-0"




7 TYP. EXT. MAS. WALL
SCALE: 1 1/2" = 1'-0"




4 NON-RATED WALL SECTION
SCALE: NTS





2 2 HOUR SEPARATION WALL
SCALE: 1/2" = 1'-0"




1 WALL SECTION @ FRONT
SCALE: 3/4" = 1'-0"



8 3 HOUR SEPARATION WALL
SCALE: 1/2" = 1'-0"



W. S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.779.9797
 www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
 RAWLS CHURCH RD.
 FUQUAY-VARIN, NC

PROJECT NO.
2232b


DRAWING TITLE
WALL SECTIONS

SHEET 11 OF 14

A 4.2


PLOT DATE 10/25/23
 REVISION ---

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
 All information on this sheet is the property of W.S. Architects, PA and may not be duplicated in whole or in part without written authorization from W.S. Architects, PA, 2020 ©




W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.773.9797
www.wsarchitectspa.com


17 HC LAVATORY PLAN
SCALE: 1/2" = 1'-0"




16 ACCESSIBLE SINK
SCALE: 1/2" = 1'-0"




15 TYP. CABINET
SCALE: 1/2" = 1'-0"




14 HC LAV. SECTION
SCALE: 1/2" = 1'-0"




13 TYPICAL HEIGHTS




2 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"



11 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"




10 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"




TOILET ACCESSORY SCHEDULE		
MARK	ITEM	MOUNT
A	SURFACE-MOUNTED TOILET TISSUE DISPENSER (B-685)	RE: ELEV.
B	WELDED FRAME MIRROR (B-2908-1830)	RE: ELEV.
C	36" HORIZONTAL GRAB BAR (B-6806.99 X 36)	33"-36" A.F.S.
D	42" HORIZONTAL GRAB BAR (B-6806.99 X 42)	33"-36" A.F.S.
E	18" VERTICAL GRAB BAR (B-6806.99 X 18)	RE: ELEV.
F	24" HORIZONTAL GRAB BAR (B-6806.99 X 24)	33"-36" A.F.S.
G	TWO-WALL SHOWER GRAB BAR (B-6861.99)	33"-36" A.F.S.
H	48" HORIZONTAL GRAB BAR (B-6806.99 X 48)	33"-36" A.F.S.
J	FOLDING SHOWER SEAT (B-5191)	PER ANSI
K	REV. FOLDING SHOWER SEAT (B-5181)	PER ANSI
L	BREAK AWAY SHOWER CURTAIN ROD & FLANGES (1" DIA. SATIN STAINLESS) ELCOMA	---
M	SURFACE-MOUNTED TOWEL BAR (B-6737 X 24)	48" MAX. A.F.S.

MANUFACTURER: BOBRICK WASHROOM EQUIPMENT U.N.O. OR APPROVED EQUAL-SEE SPECIFICATION
FINISH: SATIN STAINLESS STEEL
NOTE: GC TO INSTALL BLOCKING FOR ALL TOILET ACCESSORIES AS REQ'D.


7 TYP. SIGNAGE
SCALE: 3" = 1'-0"




6 SIGNAGE PLACEMENT
SCALE: 1/4" = 1'-0"




5 ALUMINUM STOREFRONT DOOR W/ TRANSOM
SCALE: 1 1/2" = 1'-0"




9 ENLARGED RESTROOMS
SCALE: 1/2" = 1'-0"




4 HC EWC ELEVATION
SCALE: 1/2" = 1'-0"




3 HC EWC PLAN
SCALE: 1/2" = 1'-0"




2 INT. SOLID WOOD DOOR
SCALE: 1 1/2" = 1'-0"



1 HM DOOR @ MTL. PANEL
SCALE: 3/4" = 1'-0"



8 ENLARGED RESTROOMS
SCALE: 1/2" = 1'-0"



SHOWER NOTES

RECESS CONC. SLAB AS NEEDED FOR INSERT TO MEET ADA THRESHOLD REQUIREMENTS.

BOTH SHOWERS TO COMPLY WITH REQUIREMENTS OF ROLL-IN SHOWER COMPARTMENTS PER A117.1 SECTION 608.2.2

THE HAND SHOWER WILL HAVE A HOSE 59 IN. MIN. IN LENGTH THAT CAN BE USED ALSO AS A FIXED SHOWER HEAD. THE HAND SHOWER SHALL HAVE A CONTROL WITH A NONPOSITIVE SHUT-OFF FEATURE.

PROJECT TITLE
REVELS TURF & TRACTOR
RAWL'S CHURCH RD.
FUQUAY-VARINA, NC


PROJECT NO.
2232b
DRAWING TITLE
DETAILS


SHEET 13 OF 14

A5.2

PLOT DATE 10/25/23
REVISION ---


This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©






W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.773.9797
www.wsarchitectspa.com


17 HC LAVATORY PLAN
SCALE: 1/2" = 1'-0"




16 ACCESSIBLE SINK
SCALE: 1/2" = 1'-0"




15 TYP. CABINET
SCALE: 1/2" = 1'-0"




14 HC LAV. SECTION
SCALE: 1/2" = 1'-0"




13 TYPICAL HEIGHTS




2 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"



11 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"




10 HC SHOWER (ROLL-IN)
SCALE: 1/2" = 1'-0"




TOILET ACCESSORY SCHEDULE		
MARK	ITEM	MOUNT
A	SURFACE-MOUNTED TOILET TISSUE DISPENSER (B-685)	RE: ELEV.
B	WELDED FRAME MIRROR (B-2908-1830)	RE: ELEV.
C	36" HORIZONTAL GRAB BAR (B-6806.99 X 36)	33"-36" A.F.S.
D	42" HORIZONTAL GRAB BAR (B-6806.99 X 42)	33"-36" A.F.S.
E	18" VERTICAL GRAB BAR (B-6806.99 X 18)	RE: ELEV.
F	24" HORIZONTAL GRAB BAR (B-6806.99 X 24)	33"-36" A.F.S.
G	TWO-WALL SHOWER GRAB BAR (B-6861.99)	33"-36" A.F.S.
H	48" HORIZONTAL GRAB BAR (B-6806.99 X 48)	33"-36" A.F.S.
J	FOLDING SHOWER SEAT (B-5191)	PER ANSI
K	REV. FOLDING SHOWER SEAT (B-5181)	PER ANSI
L	BREAK AWAY SHOWER CURTAIN ROD & FLANGES (1" DIA. SATIN STAINLESS) ELCOMA	---
M	SURFACE-MOUNTED TOWEL BAR (B-6737 X 24)	48" MAX. A.F.S.

MANUFACTURER: BOBRICK WASHROOM EQUIPMENT U.N.O. OR APPROVED EQUAL-SEE SPECIFICATION
FINISH: SATIN STAINLESS STEEL
NOTE: GC TO INSTALL BLOCKING FOR ALL TOILET ACCESSORIES AS REQ'D.


7 TYP. SIGNAGE
SCALE: 3" = 1'-0"




6 SIGNAGE PLACEMENT
SCALE: 1/4" = 1'-0"




5 ALUMINUM STOREFRONT DOOR W/ TRANSOM
SCALE: 1 1/2" = 1'-0"




9 ENLARGED RESTROOMS
SCALE: 1/2" = 1'-0"




4 HC EWC ELEVATION
SCALE: 1/2" = 1'-0"



3 HC EWC PLAN
SCALE: 1/2" = 1'-0"



8 ENLARGED RESTROOMS
SCALE: 1/2" = 1'-0"




SHOWER NOTES

RECESS CONC. SLAB AS NEEDED FOR INSERT TO MEET ADA THRESHOLD REQUIREMENTS.


BOTH SHOWERS TO COMPLY WITH REQUIREMENTS OF ROLL-IN SHOWER COMPARTMENTS PER A117.1 SECTION 608.2.2

THE HAND SHOWER WILL HAVE A HOSE 59 IN. MIN. IN LENGTH THAT CAN BE USED ALSO AS A FIXED SHOWER HEAD. THE HAND SHOWER SHALL HAVE A CONTROL WITH A NONPOSITIVE SHUT-OFF FEATURE.

2 INT. SOLID WOOD DOOR
SCALE: 1 1/2" = 1'-0"



1 HM DOOR @ MTL. PANEL
SCALE: 3/4" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWL'S CHURCH RD.
FUQUAY-VARINA, NC


PROJECT NO.
2232b
DRAWING TITLE
DETAILS

SHEET 13 OF 14


A5.2

PLOT DATE 11/10/23
REVISION ---


This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©




6 BREAK ROOM 113 ELEVATION
SCALE: 1/2" = 1'-0"




5 BREAK ROOM 113 ELEVATION
SCALE: 1/2" = 1'-0"




4 BREAK ROOM 127 ELEVATION
SCALE: 1/2" = 1'-0"




3 BREAK ROOM-113
SCALE: 1/4" = 1'-0"



2 BREAK ROOM-127
SCALE: 1/4" = 1'-0"




8 SERVICE CTR.
SCALE: 1/2" = 1'-0"




7 STORAGE SHED
SCALE: 1/2" = 1'-0"


NOTES:
-4,000 PSI CONC @ 28 DAYS
-FLOOR SLOPES TO DRAIN
-SEE SITE PLAN FOR CONTINUATION OF DRAIN



1 24\" x 48\" CATCH BASIN
SCALE: nts



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NC


PROJECT NO.
2232b
DRAWING TITLE
DETAILS

SHEET 14 OF 14

A5.3

PLOT DATE 11/10/23
REVISION COUNTY COM. 11/10/23

This original sheet is 24" x 36", other dimensions indicate if has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2020 ©



SERVICE SHOP SLAB NOTES
 6" SLAB ON GRADE (3,500 PSI CONCRETE)
 REINFORCED WITH 6x6-W2.9xW2.9 WWF
 (1 1/2" CLR. FROM T/S LAB) ON 10 MIL
 POLYETHYLENE VAPOR BARRIER ON 4"
 COMPACTED ABC STONE.
 FINISHED FLOOR ELEVATION 0'-0"


MARK	SIZE			REINFORCEMENT	
	N-S	E-W	THK.	N-S	E-W
A	4'-0"	4'-0"	1'-4"	#5 AT 12"	#5 AT 12"
B	5'-0"	5'-0"	1'-4"	#5 AT 12"	#5 AT 12"
C	8'-0"	8'-0"	2'-0"	#6 AT 12"	#6 AT 12"
D	8'-6"	8'-6"	2'-0"	#6 AT 12"	#6 AT 12"
E	9'-0"	9'-0"	2'-0"	#6 AT 12"	#6 AT 12"

1 PARTIAL SLAB AND FOUNDATION PLAN
 S1.1 1/8" = 1'-0"



W.S. ARCHITECTS, PA
 3305-109 Durham Drive
 Raleigh, North Carolina 27603
 919.779.8727
 www.wsarchitectspa.com

ROSS LINDEN
 ENGINEERS P C
 709 W. JONES STREET RALEIGH, NC 27603
 TEL 919.832.5680 WWW.ROSSLINDEN.COM
 NC LICENSE NO. C-2364




PROJECT TITLE
REVELS TURF & TRACTOR
 RAWLIS CHURCH RD.
 FUQUAY-VARINA, NC

PROJECT NO.
C230405
 DRAWING TITLE
FOUNDATION PLAN

SHEET 0 OF 0

S1.1

PLOT DATE 10/20/2023
 REVISION 11/15/2023



FOOTING SCHEDULE					
MARK	SIZE		THK.	REINFORCEMENT	
	N-S	E-W		N-S	E-W
A	4'-0"	4'-0"	1'-4"	#5 AT 12"	#5 AT 12"
B	5'-0"	5'-0"	1'-4"	#5 AT 12"	#5 AT 12"
C	8'-0"	8'-0"	2'-0"	#6 AT 12"	#6 AT 12"
D	8'-6"	8'-6"	2'-0"	#6 AT 12"	#6 AT 12"
E	9'-0"	9'-0"	2'-0"	#6 AT 12"	#6 AT 12"

1 PARTIAL SLAB AND FOUNDATION PLAN
S1.2 1/8" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLIS CHURCH RD.
FUQUAY-VARINA, NC

PROJECT NO.
C230405
DRAWING TITLE
FOUNDATION PLAN

SHEET 0 OF 0

S1.2

PLOT DATE 10/20/2023
REVISION 11/15/2023

STRUCTURAL NOTES

I. GENERAL


- DESIGN CODES
 - NORTH CAROLINA BUILDING CODE, 2018 EDITION (AMENDED 2015 INTERNATIONAL BUILDING CODE)
 - ACI BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE (ACI 318-14)
 - AISC MANUAL OF STEEL CONSTRUCTION - ALLOWABLE STRESS DESIGN NINTH EDITION
 - ASCE 7-10 MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER STRUCTURES
- DESIGN LOADS
 - LIVE LOADS: FLOOR: 100 PSF
ROOF: 20 PSF
 - ULTIMATE DESIGN WIND SPEED: 116 MPH (RISK CATEGORY II)
 - GROUND SNOW LOAD: 15 PSF
 - SITE CLASS D
Ss = 0.172
S1 = 0.063
 - SEE PRE-ENGINEERING METAL BUILDING DRAWINGS BY OTHERS FOR FULL STRUCTURAL DESIGN LOAD SUMMARY USED FOR BUILDING DESIGN.
- ALL ELEVATIONS ARE REFERENCED FROM FINISHED FLOOR ELEVATION OF 0'-0".
- BUILDING DESIGN AND MAXIMUM FOUNDATION REACTIONS PROVIDED BY VP BUILDINGS, PRELIMINARY REACTION REPORT, DATED 4 OCTOBER 2023. FOUNDATION DESIGN IS BASED ON MAXIMUM AND MINIMUM LOADING CONDITIONS PROVIDED BY THE BUILDING DESIGNER. FINAL SEALED FOUNDATION REACTIONS SHALL BE PROVIDED OR REVIEW PRIOR TO CONSTRUCTION.
- SEE BUILDING DRAWINGS FOR COLUMN AND BASE PLATE SIZES AND LOCATIONS.
- ANCHOR BOLT DESIGN PROVIDED BY BUILDING DESIGNER. ANCHOR BOLT EMBEDMENT ONLY IS PROVIDED ON DRAWING S1.3.
- ENGINEER'S SEAL APPLIES TO STRUCTURAL COMPONENTS ONLY AND DOES NOT CERTIFY ARCHITECTURAL LAYOUT OR DIMENSIONAL ACCURACY.
- ROSS LINDEN ENGINEERS PC ASSUMES NO LIABILITY FOR CHANGES OR MODIFICATIONS MADE TO THESE DRAWINGS BY OTHERS, OR FOR CONSTRUCTION METHODS, OR FOR ANY DEVIATION FROM THESE DRAWINGS.

II. CONCRETE

- UNLESS OTHERWISE NOTED, ALL CONCRETE SHALL HAVE THE FOLLOWING STRENGTH AND SLUMP REQUIREMENTS: 3,500 PSI 28-DAY COMPRESSIVE STRENGTH, MAX. 5" SLUMP.
- ALL CONCRETE SHALL BE MOIST CURED PER ACI 301 OR CURED WITH AN APPROVED CURING COMPOUND. CONTRACTOR SHALL VERIFY THAT THE CURING COMPOUND IS COMPATIBLE WITH FLOOR COVERING ADHESIVES, COATINGS, OR TOPPING TO BE USED. CONCRETE SHALL BE CURED FOR A MINIMUM OF 7 DAYS.
- UNLESS OTHERWISE NOTED, ALL REINFORCING STEEL SHALL BE NEW BILLET STEEL, CONFORMING TO ASTM A-615, GRADE 60, DEFORMED.
- UNLESS OTHERWISE NOTED, ALL DETAILING, FABRICATION, AND PLACING OF REINFORCING STEEL SHALL CONFORM TO THE MANUAL OF STANDARD PRACTICE FOR DETAILING REINFORCED CONCRETE STRUCTURES, (ACI 315)
- ALL BAR SPLICES SHALL BE CLASS "B" TENSION SPLICES PER ACI 318-14, UNLESS OTHERWISE SHOWN.
- ANCHOR BOLTS TO BE ASTM A36 OR A307.
- CONTRACTOR SHALL REFER TO DRAWINGS OF OTHER TRADES AND VENDOR DRAWINGS FOR EMBEDDED ITEMS AND RECESSES NOT SHOWN ON THE STRUCTURAL DRAWINGS.
- ALL SPREAD FOOTINGS BEARING ON NATIVE SOIL OR STRUCTURAL FILL ARE DESIGNED FOR AN ALLOWABLE BEARING PRESSURE OF 2,500 PSF. A GEOTECHNICAL REPRESENTATIVE SHALL INSPECT ALL FOOTING EXCAVATIONS TO CONFIRM ALLOWABLE BEARING PRESSURES
- PROVIDE TWO (2) #5 x 4'-0" LONG DIAGONAL BARS IN TOP FACE OF ALL SLABS (1" CLEAR) AT ALL RE-ENTRANT CORNERS. SEE PLAN FOR LOCATIONS.
- CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING, PROTECTING, AND RELOCATING AS REQUIRED ALL SERVICE AND UTILITY LINES IN VICINITY OF THE WORK SITE.
- ALL DOWELS WHICH ARE TO BE DRILLED AND GROUTED INTO EXISTING CONCRETE SHALL BE DONE WITH AN EPOXY GROUT. DRILL HOLE WITH DIAMETER 1/8" LARGER THAN DOWEL OR AS RECOMMENDED BY GROUT SUPPLIER. USE HIT-RE 500 V3 BY HILTI OR APPROVED EQUAL.


III. LIGHT GAUGE STEEL FRAMING

- INSTALLATION OF LIGHT GAUGE STEEL FRAMING SHALL BE IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS.
- WALL STUDS SHALL HAVE THE FOLLOWING MINIMUM PROPERTIES:
 - 16" MAX. SPACING
 - STUD DEPTH = 3.58" (SEE ARCH. DWGS.)
 - FLANGE WIDTH = 1.5/8" MIN.
 - 18 GAUGE STEEL
 - SEE ARCH. DWGS. FOR WALL HEIGHT
- PROVIDE MIN. 18 GA. BOTTOM TRACK AND ANCHOR TO SLAB WITH POWDER ACTUATED FASTENERS AT 16" O.C. USE HILTI DS FASTENERS WITH 0.177" SHANK DIAMETER AND 1 7/16" EMBEDMENT. WELD STUDS TO TRACK EACH SIDE -OR- PROVIDE (2) NO. 10 SCREWS (ONE EACH SIDE OF TRACK).
- DETAILED SHOP DRAWINGS SHALL BE PROVIDED FOR REVIEW AND APPROVAL PRIOR TO CONSTRUCTION.




1 SLAB AND FOUNDATION PLAN
S1.3 1/4" = 1'-0"


MARK	SIZE			REINFORCEMENT	
	N-S	E-W	THK.	N-S	E-W
A	4'-0"	4'-0"	1'-4"	#5 AT 12"	#5 AT 12"




3 DETAIL - SLAB EDGE
S1.3 3/4" = 1'-0"




4 SECTION - COLUMN FOOTING
S1.3 3/4" = 1'-0"




2 STORAGE SHED FRAMING PLAN
S1.3 1/4" = 1'-0"



5 TYP. ANCHOR BOLT DETAIL
S1.3 NO SCALE



6 DETAIL - TYP. SLAB CONTROL JOINT
S1.3 1" = 1'-0"




7 SECTION - RETAINING WALL
S1.3 3/4" = 1'-0"



W.S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9777
www.wsarchitectspa.com

ROSS LINDEN
ENGINEERS PC
709 W. JONES STREET RALEIGH, NC 27603
TEL 919.832.5680 WWW.ROSSLINDEN.COM
NC LICENSE NO. C-2364



PROJECT TITLE
REVLS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NC

PROJECT NO.
C230405

DRAWING TITLE
WASH BAY PLAN AND DETAILS

SHEET 0 OF 0

S1.3

PLOT DATE 11/17/2023
REVISION

STRUCTURAL NOTES

I. GENERAL

1. DESIGN CODES

NORTH CAROLINA BUILDING CODE, 2018 EDITION
(AMENDED 2015 INTERNATIONAL BUILDING CODE)

ACI BUILDING CODE REQUIREMENTS FOR STRUCTURAL CONCRETE
(ACI 318-14)

AISC MANUAL OF STEEL CONSTRUCTION - ALLOWABLE STRESS DESIGN
NINTH EDITION

ASCE 7-10 MINIMUM DESIGN LOADS FOR BUILDINGS AND OTHER
STRUCTURES

2. DESIGN LOADS

LIVE LOADS: FLOOR: 100 PSF
ROOF: 20 PSF

ULTIMATE DESIGN WIND SPEED: 116 MPH (RISK CATEGORY II)

GROUND SNOW LOAD: 15 PSF

SITE CLASS D
S_s = 0.172
S₁ = 0.083

SEE PRE-ENGINEERING METAL BUILDING DRAWINGS BY OTHERS FOR FULL
STRUCTURAL DESIGN LOAD SUMMARY USED FOR BUILDING DESIGN.

3. ALL ELEVATIONS ARE REFERENCED FROM FINISHED FLOOR ELEVATION OF 0'-0".

4. BUILDING DESIGN AND MAXIMUM FOUNDATION REACTIONS PROVIDED BY VP
BUILDINGS, JOB NUMBER 23-018589-01, DATED 26 SEPTEMBER 2023. FOUNDATION
DESIGN IS BASED ON MAXIMUM AND MINIMUM LOADING CONDITIONS PROVIDED BY
THE BUILDING DESIGNER.

5. SEE BUILDING DRAWINGS FOR COLUMN AND BASE PLATE SIZES AND
LOCATIONS.

6. ANCHOR BOLT DESIGN PROVIDED BY BUILDING DESIGNER. ANCHOR BOLT
EMBEDMENT ONLY IS PROVIDED ON DRAWING S2.

7. ENGINEER'S SEAL APPLIES TO STRUCTURAL COMPONENTS ONLY AND DOES
NOT CERTIFY ARCHITECTURAL LAYOUT OR DIMENSIONAL ACCURACY.

8. ROSS LINDEN ENGINEERS PC ASSUMES NO LIABILITY FOR CHANGES OR
MODIFICATIONS MADE TO THESE DRAWINGS BY OTHERS, OR FOR CONSTRUCTION
METHODS, OR FOR ANY DEVIATION FROM THESE DRAWINGS.

II. CONCRETE

1. UNLESS OTHERWISE NOTED, ALL CONCRETE SHALL HAVE THE FOLLOWING
STRENGTH AND SLUMP REQUIREMENTS:
3,500 PSI 28-DAY COMPRESSIVE STRENGTH, MAX. 5" SLUMP.

2. ALL CONCRETE SHALL BE MOIST CURED PER ACI 301 OR CURED WITH AN
APPROVED CURING COMPOUND. CONTRACTOR SHALL VERIFY THAT THE CURING
COMPOUND IS COMPATIBLE WITH FLOOR COVERING ADHESIVES, COATINGS, OR
TOPPING TO BE USED. CONCRETE SHALL BE CURED FOR A MINIMUM OF 7 DAYS.

3. UNLESS OTHERWISE NOTED, ALL REINFORCING STEEL SHALL BE NEW BILLET
STEEL, CONFORMING TO ASTM A-615, GRADE 60, DEFORMED.

4. UNLESS OTHERWISE NOTED, ALL DETAILING, FABRICATION, AND PLACING OF
REINFORCING STEEL SHALL CONFORM TO THE MANUAL OF STANDARD PRACTICE
FOR DETAILING REINFORCED CONCRETE STRUCTURES. (ACI 315)

5. ALL BAR SPLICES SHALL BE CLASS "B" TENSION SPLICES PER ACI 318-14,
UNLESS OTHERWISE SHOWN.

6. ANCHOR BOLTS TO BE ASTM A36 OR A307.

7. CONTRACTOR SHALL REFER TO DRAWINGS OF OTHER TRADES AND VENDOR
DRAWINGS FOR EMBEDDED ITEMS AND RECESSES NOT SHOWN ON THE
STRUCTURAL DRAWINGS.

8. ALL SPREAD FOOTINGS BEARING ON NATIVE SOIL OR STRUCTURAL FILL ARE
DESIGNED FOR AN ALLOWABLE BEARING PRESSURE OF 2,500 PSF. A
GEOTECHNICAL REPRESENTATIVE SHALL INSPECT ALL FOOTING EXCAVATIONS
TO CONFIRM ALLOWABLE BEARING PRESSURES.

9. PROVIDE TWO (2) #5 x 4'-0" LONG DIAGONAL BARS IN TOP FACE OF ALL SLABS
(1' CLEAR) AT ALL RE-ENTRANT CORNERS. SEE PLAN FOR LOCATIONS.

10. CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING, PROTECTING, AND
RELOCATING AS REQUIRED ALL SERVICE AND UTILITY LINES IN VICINITY OF THE
WORK SITE.

11. CONTRACTOR SHALL VERIFY ALL SIZES AND LOCATIONS OF ALL MECHANICAL
AND ELECTRICAL OPENINGS AND EQUIPMENT PADS WITH THE MECHANICAL AND
ELECTRICAL DETAILS AND SHOP DRAWINGS BY OTHERS. IT SHALL BE THE
RESPONSIBILITY OF THE CONTRACTOR TO PROVIDE ALL OPENINGS AND SLEEVES
FOR PROPER DISTRIBUTION FOR ALL UTILITIES THROUGHOUT THE BUILDING.

12. ALL DOWELS WHICH ARE TO BE DRILLED AND GROUTED INTO EXISTING
CONCRETE SHALL BE DONE WITH AN EPOXY GROUT. DRILL HOLE WITH
DIAMETER 1/8" LARGER THAN DOWEL OR AS RECOMMENDED BY GROUT
SUPPLIER. USE HIT-RE 500 VS BY HILTI OR APPROVED EQUAL.

III. STRUCTURAL STEEL

1. ALL STRUCTURAL STEEL WIDE FLANGE BEAMS AND COLUMNS, UNLESS NOTED,
SHALL CONFORM TO THE REQUIREMENTS OF ASTM A992 OR ASTM A572, GRADE
50. ANGLES AND CHANNELS SHALL CONFORM TO ASTM A36. TUBES SHALL
CONFORM TO ASTM A500, GRADE B.

2. ALL DETAILING, FABRICATION, AND ERECTION OF STRUCTURAL STEEL, UNLESS
OTHERWISE NOTED, SHALL CONFORM TO THE REQUIREMENTS OF THE AISC
SPECIFICATIONS FOR BUILDINGS, LATEST EDITION.

3. UNLESS OTHERWISE NOTED, ALL SHOP CONNECTIONS SHALL BE MADE BY
WELDING OR HIGH STRENGTH BOLTING. (3/4" DIAMETER BOLTS, MINIMUM)

4. WELDS SHALL BE MADE WITH E-70XX ELECTRODES BY CERTIFIED WELDERS.

5. ALL COLUMN ANCHOR BOLT HOLES TO BE OVERSIZED IN ACCORDANCE WITH
RECOMMENDATIONS OF "AISC" MANUAL FOR "DETAILING FOR STEEL
CONSTRUCTION."

6. UNLESS OTHERWISE NOTED, ALL FIELD CONNECTIONS SHALL BE MADE WITH
3/4" DIAMETER HIGH STRENGTH BOLTS (ASTM A-325). CONNECTIONS SHALL BE
DESIGNED AS BEARING TYPE WITH THREADS IN SHEAR PLANE. BOLTS SHALL BE
TIGHTENED TO THE SNUG TIGHT CONDITION PER "AISC" UNLESS NOTED
OTHERWISE ON THE DRAWINGS.

7. UNLESS OTHERWISE SHOWN, ALL BEAM CONNECTIONS SHALL BE STANDARD
FRAMED OR SEATED CONNECTIONS AS SHOWN IN PART 4 OF THE AISC MANUAL
OF STEEL CONSTRUCTION.

8. GUSSET PLATES SHALL BE 3/8" THICK MINIMUM.

9. CONTRACTOR TO PROVIDE ADEQUATE BRACING FOR STRUCTURE SO THAT IT
WILL BE STABLE DURING ALL STAGES OF CONSTRUCTION. THE STRUCTURE IS
DESIGNED FOR A COMPLETED CONDITION ONLY AND THEREFORE MAY REQUIRE
ADDITIONAL SUPPORT TO MAINTAIN STABILITY BEFORE COMPLETION.

IV. LIGHT GAUGE STEEL FRAMING

1. INSTALLATION OF LIGHT GAUGE STEEL FRAMING SHALL BE IN ACCORDANCE
WITH THE MANUFACTURER'S RECOMMENDATIONS.

2. WALL STUDS SHALL HAVE THE FOLLOWING MINIMUM PROPERTIES:

18" MAX. SPACING
STUD DEPTH = 6" (SEE ARCH. DWGS.)
FLANGE WIDTH = 1 5/8" MIN.








18 GAUGE STEEL
L/600 MAX. DEFLECTION AT BRICK VENEER
SEE ARCH. DWGS. FOR GIRT HEIGHT

3. PROVIDE MIN. 18 GA. BOTTOM TRACK AND ANCHOR TO SLAB WITH POWDER
ACTUATED FASTENERS AT 16" O.C. USE HILTI DS FASTENERS WITH 0.177" SHANK
DIAMETER AND 1.7/16" EMBEDMENT. WELD STUDS TO TRACK EACH SIDE -OR-
PROVIDE (2) NO. 10 SCREWS (ONE EACH SIDE OF TRACK).

4. ATTACH STUDS TO BUILDING STRUCTURE WITH CLIP ANGLE AND SCREW
CONNECTION DETAILS PROVIDED BY SUPPLIER. CONNECTION OF EACH WALL
STUD TO BUILDING STRUCTURE SHALL CONSIST OF A MINIMUM OF (3) NO. 12
SCREWS.


5. PROVIDE MINIMUM (2) 8" x 18 GA. BOX HEADER AT ALL FRAMED WINDOW AND
DOOR OPENINGS UP TO A CLEAR SPAN OF 6'-4". PROVIDE A MINIMUM OF (2) KING
STUDS AT EACH END OF EACH HEADER. PROVIDE INSULATION PER
ARCHITECTURAL DRAWINGS.

6. DETAILED SHOP DRAWINGS SHALL BE PROVIDED FOR REVIEW AND APPROVAL
PRIOR TO CONSTRUCTION.



W.S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9777
www.wsarchitectspa.com

ROSS LINDEN
ENGINEERS PC
709 W. JONES STREET RALEIGH, NC 27603
TEL 919.832.5680 WWW.ROSSLINDEN.COM
NC LICENSE NO. C-2364




PROJECT TITLE
REVELS TURF & TRACTOR
RAWL'S CHURCH RD.
FUQUAY-VARINA, NC

PROJECT NO.
C230405
DRAWING TITLE
STRUCTURAL NOTES AND DETAILS

SHEET 0 OF 0

S2


PLOT DATE 10/20/2023
REVISION (REVIEW COMMENTS) 11/22/2023



1
S3
1/8" = 1'-0"


PORCH FRAMING PLAN

- LIGHT GA. STEEL TRUSS NOTES:
- TRUSS DESIGN LOADS:
20 PSF TOP CHORD LL
10 PSF TOP CHORD DL
10 PSF BOTTOM CHORD DL
115 MPH WIND
 - TRUSSES SHALL BE PLACED AT MAX. 24" o.c. SPACING WITH 3:12 PITCH. SEE ARCH. DRAWINGS.
 - PROVIDE DETAILED SHOP DRAWINGS FOR REVIEW AND APPROVAL PRIOR TO FABRICATION. TRUSS PROFILES SHALL BE ENGINEERED AND SEALED BY THE TRUSS MANUFACTURER.
 - SUPPORT TRUSSES AT BEARING LOCATIONS INDICATED ON PLAN. INSTALLATION SHALL BE IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS.



2
S3
3/4" = 1'-0"

SECTION AT STEEL POST
PORCH CONNECTION TO BUILDING




3
S3
1 1/2" = 1'-0"

POST BASE PLATE

LINTEL SCHEDULE			
WALL TYPE	CLEAR OPENING WIDTH	DESCRIPTION	LINTEL DEPTH
8" CMU	LESS THAN 4'-0"	8" BOND BEAM WITH (1) #5 BAR	8" (1 COURSE)
8" CMU	4'-0" TO 10'-4"	8" BOND BEAM WITH (2) #5 BAR	16" (2 COURSES)
4" BRICK	4'-0" MAX.	L 3 1/2 x 3 1/2 x 14	
4" BRICK	6'-4" MAX.	L 5 x 3 1/2 x 14 (LLV)	
4" BRICK	8'-4" MAX.	L 6 x 3 1/2 x 5/16 (LLV)	

- LINTEL NOTES:
- LINTEL SCHEDULE SHALL APPLY UNLESS NOTED OTHERWISE
 - PROVIDE MIN. 8" BEARING FOR ALL LINTEL ANGLES U.N.O.
 - PROVIDE MIN. 8" BEARING FOR CMU LINTELS U.N.O.
 - PLACE BARS IN BOTTOM OF BOND BEAM.
 - FOR LINTELS CONSISTING OF MULTIPLE COURSES OF CMU, PLACE BARS IN BOTTOM OF BOND BEAM AND GROUT THE ENTIRE LINTEL SOLID IN ONE LIFT.
 - SEE DETAIL 4/S3 FOR DEFINITION OF LINTEL DEPTH.




4
S3
3/4" = 1'-0"

LINTEL DETAIL



W.S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9707
www.wsarchitectspa.com

ROSS LINDEN
ENGINEERS P C
709 W. JONES STREET RALEIGH, NC 27603
TEL 919.832.5680 WWW.ROSSLINDEN.COM
NC LICENSE NO. C-2364



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NC




PROJECT NO.
C230405

DRAWING TITLE
PORCH PLAN AND DETAILS

SHEET 0 OF 0

S3

PLOT DATE 10/20/2023
REVISION (REVIEW COMMENTS) 11/22/2023




PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232


DRAWING TITLE
NORTH DWV PLAN

P2.1

PLOT DATE 12/01/23



NOTE:
VERIFY QUANTITY AND LOCATION OF ALL FLOOR DRAINS W/OWNER, ARCH.
PROVIDE TRAP PRIMERS (NOT SHOWN) FOR ALL FLOOR DRAINS IN AREAS NOT SERVED BY HOSE BIBBS.
(TYP)



1 SOUTH DWV PLAN
SCALE: 1/8" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
SOUTH DWV PLAN

P2.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



NOTE:
PROPERLY PROTECT/INSULATE ALL PIPING IN UNCONDITIONED AREAS.
VERIFY ROUTING OF WATER LINES W/ARCH. ALL LINES, VALVES, CP, ETC., SHOWN FOR CLARITY. VERIFY LOCATIONS OF ALL COMPONENTS. COORDINATE WITH ALL TRADES. COORDINATE W/DWY PLAN. PROVIDE TRAP PRIMERS (NOT SHOWN) FOR ANY FLOOR DRAINS IN AREAS NOT SERVED BY HOSE BIBBS. VERIFY QUANTITY/MOUNTING LOCATIONS OF ALL HB, FPHB, YH W/ARCH., OWNER. (TYP)

- KEY NOTES FOR SHEET P3.1
- 1 SEE SHEET P3.2 FOR CONTINUATION. VERIFY ROUTING IN SHOP AREA. COORDINATE WITH OWNER, ARCHITECT, G.C., STRUCTURE, ALL TRADES AND ANY OVERHEAD EQUIPMENT.
 - 2 DROP TO RUN 1" CW BELOW GRADE TO WASH BAY. VERIFY LOCATION. EXTEND 1" CW BELOW GRADE TO WASH BAY. VERIFY LOCATION/ROUTING. COORDINATE WITH OWNER, ARCHITECT, G.C., AND SITE.
 - 3 RISE TO MAIN SHUT-OFF VALVE A.F.F. VERIFY LOCATION. CONNECT TO RPZ-WB.
 - 4 DROP TO RUN BELOW GRADE TO YARD HYDRANT (YH). VERIFY LOCATION/ROUTING.

NOTE:
WASH BAY AREA SHOWN FOR CLARITY. VERIFY LOCATION. COORDINATE W/OWNER, ARCH., SITE.

2 WASH BAY DWV PLAN
SCALE: 1/8" = 1'-0"

1 NORTH WATER PLAN
SCALE: 1/8" = 1'-0"


PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
NORTH WATER PLAN

P3.1


PLOT DATE 12/01/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



NOTE:
PROPERLY PROTECT/INSULATE ALL PIPING IN UNCONDITIONED AREAS. VERIFY ROUTING OF WATER LINES W/ARCH. ALL LINES, VALVES, CP, ETC. SHOWN FOR CLARITY. VERIFY LOCATIONS OF ALL COMPONENTS. COORDINATE WITH ALL TRADES. COORDINATE W/DWV PLAN, PROVIDE TRAP PRIMERS (NOT SHOWN) FOR ANY FLOOR DRAINS IN AREAS NOT SERVED BY HOSE BIBBS. VERIFY QUANTITY/MOUNTING LOCATIONS OF ALL HB, FPFB W/ARCH. OWNER. PROVIDE PROPER ASSE 1070 TMV (NOT SHOWN) AT/FOR EACH LAVATORY FOR MTHW TO FAUCET. (TYP)

- KEY NOTES FOR SHEET P3.2
- 1-1/2" CW BELOW GRADE TO RPZ/METER/ SUPPLY MAIN. COORDINATE WITH SITE.
 - RISE CW FROM BELOW GRADE TO MAIN SHUT-OFF VALVE A.F.F., RISE TO RUN CW MAIN ABOVE CEILING. VERIFY LOCATION, RISE IN WALL W/ACCESS DOOR IF REQUIRED.
 - SEE SHEET P3.1 FOR CONTINUATION. VERIFY ROUTING IN SHOP AREA. COORDINATE WITH OWNER, ARCHITECT, G.C. STRUCTURE, ALL TRADES AND ANY OVERHEAD EQUIPMENT.



1 SOUTH WATER PLAN
SCALE: 1/8" = 1'-0"

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
SOUTH WATER PLAN


P3.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



11/30/23



NOTE:
VERIFY ALL GAS EQUIPMENT LOAD TOTALS.
VERIFY GAS METER LOCATION PRIOR TO
BID. VERIFY LINE SIZES, TOTAL DEVELOPED
LINE LENGTHS (TDL). NOTIFY ENGINEER OF
ANY DISCREPANCIES FOR POSSIBLE REVIEW
AND/OR RE-SIZING OF GAS LINES.

NOTE:
ANY SHUT-OFF VALVES, HOOD FIRE SUPPRESSION
VALVES, AND REGULATORS MUST BE ACCESSIBLE.
VENT REGULATORS TO EXTERIOR IF AS REQUIRED.
PAINT ANY INTERIOR OR EXTERIOR EXPOSED GAS
LINES PER CODE AND BUILDING STANDARD. PROVIDE
PROPER LABELING FOR ALL 2 PSI PIPING. PROVIDE
PROPER STAND-OFFS/SUPPORTS FOR GAS LINES
ON ROOF/EXTERIOR WALLS, BELOW ROOF, ETC.
PROPERLY SEAL ROOF/EXT. WALL PENETRATIONS
SO AS NOT TO VOID ANY EXISTING WARRANTIES.
VERIFY ROUTING OF ALL GAS LINES, COORDINATE
W/STRUCTURE, ALL TRADES, OWNER, ARCH., G.C.

KEY NOTES FOR SHEET P4.1

- 1 NATURAL GAS LINE BELOW ROOF STRUCTURE. SEE SHEET P4.2 FOR CONTINUATION. VERIFY ROUTING IN SERVICE SHOP AREA. COORDINATE WITH OWNER, ARCHITECT, G.C. STRUCTURE, ALL TRADES AND ANY OVERHEAD EQUIPMENT.
- 2 DROP TO RUN ABOVE GRADE TO EQUIPMENT. VERIFY LOCATION.
- 3 EXTEND BRANCH LINE ABOVE GRADE (ON WALL OR AS REQUIRED) TO EQUIPMENT. VERIFY ROUTING, COORDINATE W/OWNER, ARCH., G.C., ALL TRADES.
- 4 CONNECT TO HVAC GAS PACKAGE UNIT (GPU). VERIFY LOCATION. COORDINATE W/JUNIT, MECH. PLANS. PROVIDE PROPER REGULATOR.
- 5 DROP TO RUN GAS LINE BELOW GRADE TO WASH BAY PRESSURE WASHER. VERIFY LOCATION. EXTEND GAS LINE GRADE TO PRESSURE WASHER. VERIFY LOCATION/ROUTING, COORDINATE WITH OWNER, ARCHITECT, G.C., AND SITE.
- 6 RISE TO CONNECT TO PRESSURE WASHER (PW). VERIFY LOCATION. COORDINATE W/EQUIPMENT. PROVIDE PROPER REGULATOR.

UNDERGROUND STEEL GAS PIPING CORROSION PROTECTION:
PIPE SHALL HAVE A FACTORY-APPLIED, ELECTRICALLY-INSULATING COATING. FITTINGS AND JOINTS BETWEEN SECTIONS OF COATED PIPE SHALL BE COATED IN ACCORDANCE WITH THE COATING MFR SPECS. UNDERGROUND PIPING SYSTEMS SHALL BE INSTALLED A MIN. DEPTH OF 12 INCHES BELOW GRADE, AND SHALL BE REPUBLIC STEEL X-TRU-COAT (OR EQUAL), PLASTIC COATED SCHEDULE 40 ASTM A-53 STEEL PIPE W/WELDED JOINTS, USING X-TRU-TAPE AND PRIMER AT EACH JOINT. WRAP JOINTS SPIRALLY WITH A MINIMUM OVERLAP OF 1/2 TAPE WIDTH. EXTEND WRAP NOT LESS THAN 3" ABOVE GRADE. PROVIDE HIGH VOLTAGE HOLIDAY DETECTOR TEST OF COATING TO CHECK FOR HOLIDAYS. PROVIDE CATHODIC PROTECTION TO MEET REQUIREMENTS OF NACE STANDARD RP0169. ALL UNDERGROUND GAS PIPING PROTECTION SHALL COMPLY WITH NCSCB FUEL GAS SECT. 404.

NOTE:
WASH BAY AREA SHOWN FOR CLARITY. VERIFY LOCATION, COORDINATE W/OWNER, ARCH., SITE.

2 WASH BAY DWV PLAN
SCALE: 1/8" = 1'-0"

1 NORTH NATURAL GAS PLAN
SCALE: 1/8" = 1'-0"


PROJECT TITLE
REVELS TURF &
TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
NORTH NATURAL GAS PLAN

P4.1

PLOT DATE 12/01/23


This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



NOTE:
VERIFY ALL GAS EQUIPMENT LOAD TOTALS,
VERIFY GAS METER LOCATION PRIOR TO
BID. VERIFY LINE SIZES, TOTAL DEVELOPED
LINE LENGTHS (TDL), NOTIFY ENGINEER OF
ANY DISCREPANCIES FOR POSSIBLE REVIEW
AND/OR RE-SIZING OF GAS LINES.

NOTE:
ANY SHUT-OFF VALVES, HOOD FIRE SUPPRESSION
VALVES, AND REGULATORS MUST BE ACCESSIBLE.
VENT REGULATORS TO EXTERIOR IF/AS REQUIRED.
PAINT ANY INTERIOR OR EXTERIOR EXPOSED GAS
LINES PER CODE AND BUILDING STANDARD. PROVIDE
PROPER LABELING FOR ALL 2 PSI PIPING. PROVIDE
PROPER STAND-OFFS/SUPPORTS FOR GAS LINES
ON ROOF/EXTERIOR WALLS, BELOW ROOF, ETC.
PROPERLY SEAL ROOF/EXT. WALL PENETRATIONS
SO AS NOT TO VOID ANY EXISTING WARRANTIES.
VERIFY ROUTING OF ALL GAS LINES. COORDINATE
W/STRUCTURE, ALL TRADES, OWNER, ARCH., G.C.

- KEY NOTES FOR SHEET P4.2
- 1 PROVIDE MEDIUM PRESSURE (2 PSI) NATURAL GAS METER/SERVICE FOR BUILDING MAIN. VERIFY LOCATION, COORDINATE WITH GAS COMPANY.
 - 2 RISE TO RUN ABOVE CEILING/BELOW ROOF STRUCTURE. VERIFY LOCATION/ROUTING.
 - 3 EXTEND BRANCH LINE ABOVE GRADE (ON WALL OR AS REQUIRED) TO EQUIPMENT. VERIFY ROUTING, COORDINATE W/OWNER, ARCH., G.C., ALL TRADES.
 - 4 CONNECT TO HVAC GAS PACKAGE UNIT (GPU). VERIFY LOCATION, COORDINATE W/UNIT, MECH. PLANS. PROVIDE PROPER REGULATOR.
 - 5 DROP/CONNECT TO NATURAL GAS WATER HEATER (GWH). VERIFY LOCATION, PROVIDE REGULATOR.
 - 6 DROP TO RUN ABOVE GRADE TO EQUIPMENT. VERIFY LOCATION.
 - 7 SEE SHEET P4.1 FOR CONTINUATION. VERIFY ROUTING IN SERVICE SHOP AREA. COORDINATE WITH OWNER, ARCHITECT, G.C. STRUCTURE, ALL TRADES AND ANY OVERHEAD EQUIPMENT.



1 SOUTH NATURAL GAS PLAN
SCALE: 1/8" = 1'-0"


PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
SOUTH NATURAL GAS PLAN

P4.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023




(VERIFY ALL EQUIPMENT REQUIREMENTS PRIOR TO ROUGH-IN)

PIPE SIZING SCHEDULE		
FIXTURE TYPE	DRAIN	VENT
(DW) DISHWASHER	3/4"	-
(EWC) ELECTRIC WATER COOLER	1 1/4"	1 1/4"
(EW) EYEWASH	1 1/4"	1 1/4"
(FD) FLOOR DRAIN	3"	1 1/2"
(HD) HUB DRAIN	1 1/2"	1 1/4"
(L) LAVATORY	1 1/2"	1 1/4"
(MS) MOP SINK	3"	1 1/2"
(S) SINK	1 1/2"	1 1/4"
(SHR) SHOWER	2"	1 1/4"
(US) UTILITY SINK	1 1/2"	1 1/4"
(WC) FLUSH TANK WATER CLOSET	3"	1 1/2"

RISER NOTES:
REPRESENTATIVE SIZES ARE GIVEN FOR EACH TYPE OF FIXTURE. SEE PIPE SIZING SCHEDULE.
MINIMUM 2" DRAIN LINE SIZE UNDER SLAB.
MAINTAIN PIPE SIZES SHOWN UNTIL LARGER SIZE IS REACHED.
PIPE SIZES ARE MINIMUMS FOR INDIVIDUAL FIXTURES U.O.N.

NOTE:
PROVIDE PROPER VENT THRU ROOF (VTR).
RUN HORIZONTALLY AS REQUIRED TO MAINTAIN 10'-0" CLEARANCE FROM ANY INTAKES. PROPERLY FLASH ANY ROOF PENETRATION. (TYP)



1 DWV RISER
SCALE: NOT TO SCALE

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
DWV RISER

P5

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



(VERIFY ALL EQUIPMENT REQUIREMENTS PRIOR TO ROUGH-IN)

PIPE SIZING SCHEDULE		
FIXTURE TYPE	CW	HW
(DW) DISHWASHER	1/2" *	-
(EWC) ELECTRIC WATER COOLER	1/2" *	-
(EW) EYEWASH	1/2" *	1/2" *
(FPHB) FREEZE PROOF HOSE BIBB	3/4"	-
(HB) HOSE BIBB	3/4"	3/4"
(IM) ICE MACHINE	1/2" *	-
(L) LAVATORY	1/2"	1/2"
(MS) MOP SINK	1/2"	1/2"
(S) SINK	1/2"	1/2"
(SHR) SHOWER	1/2"	1/2"
(US) UTILITY SINK	1/2"	1/2"
(VB) VALVE BOX	1/2" *	-
(WC) FLUSH TANK WATER CLOSET	1/2"	-


RISER NOTES:
REPRESENTATIVE SIZES ARE GIVEN FOR EACH TYPE OF FIXTURE.
SEE PIPE SIZING SCHEDULE.
MAINTAIN PIPE SIZES SHOWN UNTIL LARGER SIZE IS REACHED.
PIPE SIZES ARE MINIMUMS FOR INDIVIDUAL FIXTURES U.O.N.

NOTE:
SEE PLAN FOR SHUT-OFF VALVE LOCATIONS.
COORDINATE LOCATION AND NUMBER
WITH LOCAL INSPECTIONS DEPARTMENT.
PROVIDE ACCESS DOORS IF REQUIRED.

KEY NOTES FOR SHEET P6

- 1-1/2" CW BELOW GRADE TO RPZ/METER/
SUPPLY MAIN. COORDINATE WITH SITE.
- DROP TO RUN 1" CW BELOW GRADE TO
WASH BAY. VERIFY LOCATION. EXTEND 1"
CW BELOW GRADE TO WASH BAY. VERIFY
LOCATION/ROUTING. COORDINATE WITH
OWNER, ARCHITECT, G.C., AND SITE.
- RISE TO MAIN SHUT-OFF VALVE A.F.F.,
VERIFY LOCATION. CONNECT TO RPZ-WB.
- DROP TO RUN BELOW GRADE TO YARD
HYDRANT (YH). VERIFY LOCATION/ROUTING.

* PROVIDE BACKFLOW PREVENTER PER NC8BC-PLUMBING SECT. 608.3,
EX: ASSE 1024 (WATTS SERIES 7 OR EQUAL) ASSE 1022 (WATTS
SERIES 50-3 EQUAL) ETC., WHERE REQUIRED IF NOT AN INTEGRAL
PART OF THE EQUIPMENT.



1 WATER RISER
SCALE: NOT TO SCALE



PROJECT TITLE
**REVELS TURF &
TRACTOR**
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
WATER RISER


P6

PLOT DATE 12/01/23

This original sheet is 24" x 36"; other dimensions
indicate it has been altered.
All information on this sheet is the property of
W. S. Architects, PA and may not be
duplicated in whole or in part without written
authorization from W. S. Architects, PA. 2023



2 EQUIPMENT CONNECTION DETAIL
SCALE: NOT TO SCALE



1 NATURAL GAS RISER
SCALE: NOT TO SCALE

NATURAL GAS PIPING LOAD SUMMARY

LINE SEGMENT (SEE GAS RISER)	CONNECTED GAS LOAD (BTUH)	MAX. DEVELOPED LENGTH (FT.)
A	230,000	60
B	1,020,000	400

PER 2018 NCSBG, FUEL GAS CODE, TABLE 402.4(5) - PIPE SIZES ARE BASED UPON A INITIAL PRESSURE OF 2 PSI AND A PRESSURE DROP OF 1 PSI. ALL GAS PIPE SIZES SHOWN ON RISER ARE NOMINAL INSIDE DIAMETER. TOTAL CONNECTED LOAD (OVERALL) = 1,250,000 BTUH

NOTE: VERIFY ALL GAS EQUIPMENT LOAD TOTALS. VERIFY GAS METER LOCATION PRIOR TO BID. VERIFY LINE SIZES, TOTAL DEVELOPED LINE LENGTHS (TDL). NOTIFY ENGINEER OF ANY DISCREPANCIES FOR POSSIBLE REVIEW AND/OR RE-SIZING OF GAS LINES.

NOTE: NAT. GAS PRESSURE FOR THE BUILDING MAIN IS TO BE AT 2 PSI. PROVIDE PROPER REGULATORS AT EACH PIECE OF GAS EQUIPMENT. VENT REGULATORS TO EXTERIOR IF REQUIRED. PROVIDE PROPER LABELING ON 2 PSI PIPING. PROVIDE REGULATOR/CONNECTION PER NCSBG- FUEL GAS SECT. 410.2 AND ALL OTHER APPLICABLE SECTIONS. EQUIPMENT CONNECTIONS/REGULATORS NOT SHOWN ON RISER- SEE CONNECTION DETAIL THIS SHEET.

NOTE: PROVIDE PROPER REGULATOR AT EACH PIECE OF EQUIPMENT. PROVIDE SHUT-OFF VALVE, DIRTLES, UNION, AND FLEXIBLE CONNECTION OR AS REQUIRED TO EACH PIECE OF EQUIPMENT. VERIFY CONNECTION TYPE/SIZE WITH EACH PIECE OF EQUIPMENT.

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH ROAD
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
NATURAL GAS RISER

P7

PLOT DATE 12/01/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023

GAS PACK SCHEDULE	
GAS PACK UNIT #1 (GPU-1)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 57,500 BTUH NET COOLING; 2000 CFM; 208 VOLT, 3 PHASE; COMP 15.9 RLA EA; OFM 1.4 FLA; IFM 6.9 FLA; 29 MCA, 40A MOCP; 5 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, "HUMIDIZER" HOT GAS REHEAT, ACCESS PANELS, FILTER RACK, AND COIL GUARDS. 115,000 BTUH INPUT NATURAL GAS. PROVIDE WITH MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.
GAS PACK UNIT #2 (GPU-2)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 57,500 BTUH NET COOLING; 2000 CFM; 208 VOLT, 3 PHASE; COMP 15.9 RLA EA; OFM 1.4 FLA; IFM 6.9 FLA; 29 MCA, 40A MOCP; 5 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, "HUMIDIZER" HOT GAS REHEAT, ACCESS PANELS, FILTER RACK, AND COIL GUARDS. 115,000 BTUH INPUT NATURAL GAS. PROVIDE WITH MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.
GAS PACK UNIT #3 (GPU-3)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 73,000 BTUH NET COOLING; 2400 CFM; 208 VOLT, 3 PHASE; COMP 19.6 RLA EA; OFM 2 @ 1.5 FLA EA; IFM 5.2 FLA; 33 MCA, 50A MOCP; 6 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, ENTHALPY BASED ECONOMIZER WITH BAROMETRIC RELIEF DAMPER, "HUMIDIZER" HOT GAS REHEAT, ACCESS PANELS, FILTER RACK, AND COIL GUARDS. 125,000 BTUH INPUT NATURAL GAS. PROVIDE MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.
GAS PACK UNIT #4 (GPU-4)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 57,500 BTUH NET COOLING; 2000 CFM; 208 VOLT, 3 PHASE; COMP 15.9 RLA EA; OFM 1.4 FLA; IFM 6.9 FLA; 29 MCA, 40A MOCP; 5 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, "HUMIDIZER" HOT GAS REHEAT, ACCESS PANELS, FILTER RACK, AND COIL GUARDS. 115,000 BTUH INPUT NATURAL GAS. PROVIDE WITH MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.
GAS PACK UNIT #5 (GPU-5)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 86,000 BTUH NET COOLING; 3000 CFM; 208 VOLT, 3 PHASE; COMP (2) @ 13.6 RLA EA; OFM (2) @ 1.5 FLA EA; IFM 5.8 FLA; 39 MCA, 50A MOCP; 7.5 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, ENTHALPY BASED ECONOMIZER WITH BAROMETRIC RELIEF DAMPER, "HUMIDIZER" HOT GAS REHEAT, 2-SPEED FAN, MEDIUM STATIC DRIVE, ACCESS PANELS, FILTER RACK, HAIL COIL GUARDS. 180,000 BTUH INPUT NATURAL GAS. PROVIDE MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.
GAS PACK UNIT #6 (GPU-6)	* CARRIER MODEL #48HCEA06A2A5-0A0A0 GAS HEAT ELECTRIC COOLING SINGLE PACKAGE UNIT; 12.5 EER; 86,000 BTUH NET COOLING; 3000 CFM; 208 VOLT, 3 PHASE; COMP (2) @ 13.6 RLA EA; OFM (2) @ 1.5 FLA EA; IFM 5.8 FLA; 39 MCA, 50A MOCP; 7.5 TONS. PROVIDE PROGRAMMABLE THERMOSTAT/HUMIDISTAT, ENTHALPY BASED ECONOMIZER WITH BAROMETRIC RELIEF DAMPER, "HUMIDIZER" HOT GAS REHEAT, 2-SPEED FAN, MEDIUM STATIC DRIVE, ACCESS PANELS, FILTER RACK, HAIL COIL GUARDS. 180,000 BTUH INPUT NATURAL GAS. PROVIDE MOTORIZED DAMPER TO CLOSE OUTSIDE AIR INTAKE WHEN UNIT IS NOT IN USE PER 2018 NC ENERGY CODE.

* OR APPROVED EQUAL

DUCTLESS SPLIT SYSTEM HEAT PUMP SCHEDULE	
DHP-1 OUTDOOR HEAT PUMP UNIT	* MITSUBISHI MODEL #MUZ-GL12NA, 1 TON OUTDOOR HEAT PUMP UNIT, 23.1 SEER, 208 VOLT, 1 PHASE, CONDENSING UNIT 9A MCA, 15A MOCP. FAN COIL UNIT IS POWERED VIA FIELD PROVIDED WIRING FROM OUTDOOR UNIT. SERVES (1) INDOOR FAN-COIL UNIT (DFC-1).
DFC-1 DIRECT EXPANSION FAN COIL UNIT	* MITSUBISHI MODEL #MSZ-GL12NA FAN COIL UNIT, NET COOLING CAPACITY = 12,000 BTUH, 145 CFM LD TO 399 CFM HI, 1 TON NOMINAL. PROVIDE WIRED PROGRAMMABLE THERMOSTAT, AND CONDENSATE PUMP. FAN MOTOR 0.76, FLA 208 VOLT, SINGLE PH.



EXHAUST FAN SCHEDULE	
EXHAUST FAN #1 (EF-1)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES. PROVIDE WALL MOUNTED THERMOSTAT TO CONTROL FAN.
EXHAUST FAN #2 (EF-2)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES. FAN IS FOR HEAT REMOVAL. PROVIDE WALL MOUNTED THERMOSTAT TO CONTROL FAN.
EXHAUST FAN #3 (EF-3)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.
EXHAUST FAN #4 (EF-4)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.
EXHAUST FAN #5 (EF-5)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.
EXHAUST FAN #6 (EF-6)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.
EXHAUST FAN #7 (EF-7)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.
EXHAUST FAN #8 (EF-8)	* CARNES MODEL# VDD0010C EXHAUST FAN, 93 CFM @ 1/4" SP, 640 RPM, 1.1 AMPS, 120V. THE ELECTRICAL CONTRACTOR SHALL PROVIDE THE SWITCH AND WIRE THE UNIT. THE HVAC CONTRACTOR SHALL PROVIDE UNIT, 6" RIGID DUCT TO ROOF CAP. LOCATE EXHAUST TERMINATION A MINIMUM OF 10'-0" FROM ANY INTAKES.

* OR APPROVED EQUAL
NOTE: RUN EXHAUST DUCTS HORIZONTALLY AS REQUIRED TO MAINTAIN 10'-0" MINIMUM SEPARATION FROM ANY INTAKES.

GENERAL NOTES -- MECHANICAL


- ALL WORK SHALL BE IN ACCORDANCE WITH THE LATEST EDITION OF THE STATE CODE AND ALL LOCAL AND OTHER APPLICABLE CODES.
- ANY PERMITS AND INSPECTION FEES SHALL BE SECURED AND PAID FOR BY THE MECHANICAL CONTRACTOR (MC).
- ALL WORK SHALL BE PERFORMED BY EXPERIENCED AND SKILLED CRAFTSMEN. THE MC SHALL COORDINATE ALL OF HIS WORK WITH THE GENERAL CONTRACTOR (GC) AND OTHER TRADES.
- THE LOCATION OF ALL DUCT, PIPING AND EQUIPMENT SHALL BE ADJUSTED TO ACCOMMODATE ANTIOPATED OR ENCOUNTERED INTERFERENCES.
- THESE PLANS ARE DIAGRAMMATIC AND MAY NOT SHOW MINOR DETAILS AND LOCATIONS. FOR DIMENSIONS REFER TO THE ARCHITECTURAL PLANS.
- THE MC SHALL BE RESPONSIBLE FOR ALL ELECTRICAL STARTERS INTERLOCKS, CONTROL WIRING CONDUIT AND POWER WIRING FROM DISCONNECTS TO HIS EQUIPMENT, USING A LICENSED ELECTRICIAN.
- THE MC SHALL USE FIRE DAMPERS FOR PROTECTION OF THE OPENING IN ACCORDANCE WITH STATE AND LOCAL CODES IN ALL LOCATIONS WHERE PENETRATIONS OF RATED WALLS AND FLOORS OCCUR. SEE ARCHITECTURAL PLANS FOR RATED WALL AND FLOOR LOCATIONS. PROVIDE ACCESS DOORS AT ALL DAMPER LOCATIONS. LOCATE DOORS FOR EASY ACCESS.
- INSTALL FLEXIBLE CONNECTORS ON SUPPLY AND RETURN DUCTWORK AHU. ALL MECHANICAL EQUIPMENT SHALL OPERATE FREE OF OBJECTIONAL NOISE AND VIBRATION.
- INSTALL TURNING VANES IN SUPPLY DUCTS AT ALL ELBOWS AND SPLITTER DAMPERS. PROVIDE BALANCING DAMPERS IN ALL DUCTS WHERE SHOWN OR REQUIRED FOR SYSTEM BALANCING.
- DUCT DIMENSIONS ARE SHOWN INSIDE CLEAR.
- THE MC SHALL KEEP THE PREMISES CLEAR OF DEBRIS FROM HIS WORK DURING CONSTRUCTION AND LEAVE THE AREA AND BUILDING CLEAN AT THE COMPLETION OF HIS WORK. HE SHALL ALSO LEAVE CLEAN ALL EXPOSED EQUIPMENT IN HIS CONTRACT.
- PROVIDE ALL REQUIRED ROOF PENETRATIONS FOR THE INSTALLATION OF THE NEW EQUIPMENT. ALL FLASHINGS ARE BY THE MECHANICAL CONTRACTOR. ALL ROOFING WORK SHALL BE DONE BY A LICENSED ROOFING CONTRACTOR SO AS TO MAINTAIN ORIGINAL WARRANTY.
- THE M.C. SHALL COORDINATE WITH AND PROVIDE EQUIPMENT SPEC. SHEETS TO THE GENERAL AND ELECTRICAL CONTRACTORS FOR REVIEW PRIOR TO ORDERING EQUIPMENT.
- PROPERLY SUPPORT ALL DUCT WORK, AND EQUIP FROM STRUCTURE. PROVIDE ALL STRUCTURAL SUPPORTS FOR THE LOADS AS REQUIRED AT NO ADDITIONAL COST TO THE OWNER.

LEGEND -- MECHANICAL



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com

ENGINEER
BURKE DESIGN GROUP, PA
CONSULTING ENGINEERS
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.771.1916 fax: 919.779.0828
email: benburke@nc.rr.com
Corp. License # C-2652



AIR DISTRIBUTION SCHEDULE							
MARK	* MANUFACTURER	MODEL NO.	NECK SIZE	FACE SIZE	MATERIAL	SERVICE	NOTES
A	CARNES	SPAB224	SEE FLEXIBLE DUCT SCHEDULE	24" X 24"	STEEL	SUPPLY	LAY-IN CEILING, WHITE 4-WAY BLOW
B	CARNES	RTDBH	12" X 4"	14" X 6"	STEEL	SUPPLY	DUCT MOUNTED, WHITE
C	CARNES	RTDBH	18" X 6"	20" X 8"	STEEL	SUPPLY	DUCT MOUNTED, WHITE
RA	CARNES	SPRB22	SEE FLEXIBLE DUCT SCHEDULE	24" X 24"	STEEL	RETURN	LAY-IN CEILING, WHITE
RB	CARNES	RSABH	8" X 6"	10" X 8"	STEEL	RETURN	WHITE, DUCT MOUNTED
RC	CARNES	RSHAH	24" X 36"	26" X 38"	STEEL	RETURN	WHITE, SIDEWALL MOUNTED HEAVY DUTY
RD	CARNES	RSABH	36" X 24"	38" X 26"	STEEL	RETURN	WHITE, DUCT MOUNTED,
RF	CARNES	RSABH	12" X 8"	14" X 10"	STEEL	RETURN	WHITE, DUCT MOUNTED,
RF	CARNES	RSABH	12" X 8"	14" X 10"	STEEL	RETURN	WHITE, SIDE WALL OR DUCT MOUNTED,
TA	CARNES	RSABH	24" X 12"	26" X 14"	STEEL	TRANSFER	WHITE, SIDE WALL MOUNTED

* OR APPROVED EQUAL

OUTDOOR AIR CALCULATIONS	
(SERVICE BAY AREA ONLY)	
OUTSIDE AIR PROVIDED BY NATURAL VENTILATION PER NCSCBC MECHANICAL CODE, SECTION 402. 1430 SQ.FT. TOTAL X 0.04 = 577 SQ.FT. REQUIRED FREE AREA. OPERABLE DOORS TO EXTERIOR PROVIDE 1728 SQ.FT. OF FREE AREA. FOR ADDITIONAL VENTILATION PROVIDE 450 CFM EACH IN GPU-5 & GPU-6	

APPENDIX B 2018 BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS

MECHANICAL DESIGN
(PROVIDE ON THE MECHANICAL SHEETS IF APPLICABLE)
MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEM AND EQUIPMENT

Thermal Zone 4A
winter dry bulb 18F
summer dry bulb 93F

Interior Design Conditions
winter dry bulb 72F
summer dry bulb 75F
relative humidity 50%

Building Heating Load 375,900 BTU/hr

Building Cooling Load 374,200 BTU/hr

Mechanical Spacing Conditioning System
Unitary - The tenant space is served the following systems:
(1) 8 Ton gas package units with dx cooling.
(2) 5 Ton gas package unit with dx cooling.
(3) 7.5 Ton gas package units with dx cooling.

Boiler - Not applicable to this project.
Chiller - Not applicable to this project.

Equipment efficiencies
Efficiencies and outputs are listed on equipment schedules - See drawings.

OA SCHEDULE OUTDOOR VENTILATION AIR PROVIDED PER TABLE 403.3 NCSCBC MECHANICAL CODE. (OFFICE AREA ONLY)								
APPLICATION	SQUARE FOOTAGE (SF)	OUTDOOR AIR FLOW RATE (CFM/SF)	PEOPLE DENSITY RATE (CFM/PERSON)	OCCUPANCY RATE (# PEOPLE/1000SF)	OCCUPANCY (# PEOPLE)	AREA OUTDOOR AIR FLOW (CFM)	PEOPLE OUTDOOR AIR FLOW (CFM)	TOTAL (CFM)
OFFICE	5877	0.08	5	5	29	145	353	498
CONFERENCE	408	0.08	5	50	20	25	100	125
CORRIDOR	3217	0.08	-	-	-	237	-	193
STORAGE	2116	0.12	-	-	-	266	-	254
WAREHOUSE	2540	0.08	-	-	-	192	-	192
WORKOUT ROOM	1243	0.08	20	10	13	77	260	337
TOTAL REQUIRED								1559

OUTDOOR AIR PROVIDED FROM EACH HVAC UNIT *	
HVAC UNIT	OUTDOOR AIR (CFM)
GPU-1	400
GPU-2	400
GPU-3	360
GPU-4	400
TOTAL PROVIDED	1560

APPLICATION	CFM
TOILETS	70 CFM/FLUSHING FIXTURE
8 FLUSHING FIXTURE X 70 CFM = 560 CFM	
EXHAUST PROVIDED BY FOUR EXHAUST FANS, MAKE UP AIR BY TRANSFER AIR	

* SET OUTDOOR AIR DAMPER CONTROLS TO PROVIDE OUTDOOR AIR AS INDICATED IN THIS SCHEDULE.

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
LIGHTING PLAN



M1

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA, 2023

ENGINEER

BD BURKE DESIGN GROUP, PA
CONSULTING ENGINEERS
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.771.1916 fax: 919.779.0826
email: benburke@nc.rr.com
Corp. License # C-2652



- KEY NOTES FOR M2.1
- ① GAS PACKAGE UNIT MOUNTED ON 4" THICK CONCRETE PAD. SEE DETAIL 1/M3. PROVIDE ALL MANUFACTURER'S REQUIRED CLEARANCES AROUND UNIT.
 - ② RUN DUCTWORK EXPOSED OVERHEAD IN THIS ROOM. SEE DETAIL 2/M3. ALL EXPOSED DUCTWORK SHALL HAVE INTERNAL DUCT LINER INSULATION AND HAVE "PAINT-GRIP" GALVANIZED FINISH. FINAL PAINTING BY GENERAL CONTRACTOR.
 - ③ DUCT MOUNTED SUPPLY AIR REGISTER. SEE DETAIL 2/M3. (TYPICAL).
 - ④ LOW SIDE WALL RETURN AIR GRILLE. MOUNT WITH BOTTOM AT 8" AFF.
 - ⑤ MOUNT THERMOSTAT AT 48" AFF.
 - ⑥ INSTALL DUCT TYPE SMOKE DETECTOR IN RETURN AIR DUCT FOR UNIT SHUTDOWN. PROVIDE ACCESS DOOR IN DUCT. SEE DETAIL 1/M3 AND SPECIFICATIONS CONCERNING THE SMOKE DETECTOR.
 - ⑦ RUN DUCTWORK UP EXPOSED, TIGHT AGAINST WALL ON EXTERIOR OF BUILDING TO HIGH OVERHEAD IN THE SPACE. ALL EXPOSED DUCTWORK SHALL HAVE INTERNAL DUCT LINER INSULATION, AND BE SEALED WATERTIGHT.
 - ⑧ HIGH SIDE WALL MOUNTED RETURN AIR TRANSFER GRILLE ON BOTH SIDES OF WALL. PROVIDE FIRE DAMPER IN WALL BETWEEN TRANSFER GRILLES.
 - ⑨ DUCT MOUNTED RETURN AIR GRILLE.

NOTE:
MOTOR VEHICLES IN THE SERVICE SHOP AREA WILL HAVE THEIR ENGINES RUNNING ONLY FOR THE DURATION REQUIRED TO MOVE THE MOTOR VEHICLE IN AND OUT OF THE BUILDING. THEREFORE MECHANICAL VENTILATION AND SOURCE CAPTURE EXHAUST ARE NOT REQUIRED PER NCSBC. MECHANICAL CODE SECTION 502.14, EXCEPTION NO. 3.

1 NORTH HVAC PLAN
SCALE: 1/8" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWL'S CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
NORTH HVAC PLAN

M2.1

PLOT DATE 12/01/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA, 2023



FLEXIBLE DUCTWORK SIZES		
MAXIMUM CFMS		
SIZES	SUPPLY	RETURN
4"	100	100
6"	175	175
10"	250	250
12"	400	350
14"	550	500
16"	NA	900

(CHANGE OUT EXISTING FLEX DUCTS AND COLLARS AS REQUIRED TO GET NEW CFMS SHOWN)

FLEXIBLE DUCTWORK NOTES

- INSTALL FLEXIBLE DUCTWORK RUNS AS STRAIGHT AS POSSIBLE.
- DO NOT ALLOW FLEXIBLE DUCT TO SAG BETWEEN SUPPORTS.
- DO NOT STRETCH A SHORT SECTION TO FIT A SLIGHTLY LONGER SECTION. THIS DISTORTS THE DUCT SHAPE AND IMPEDS AIR FLOW.
- DO NOT CRUSH DUCTWORK TO FIT IN A SPACE SMALLER THAN ITS ORIGINAL OUTSIDE DIAMETER. MAXIMUM ALLOWABLE DEFORMATION IS 15% OF ORIGINAL VOLUME.
- USE RIGID 90 DEGREE ELBOWS AT ANY LOCATION WHERE THE DUCTWORK BECOMES DISTORTED.
- EXTREME CARE SHALL BE TAKEN TO ELIMINATE ANY REDUCTION IN FLOW WITHIN THE FLEXIBLE DUCTS. THE MECH. CONTRACTOR WILL BE REQUIRED TO REPLACE THE FLEXIBLE DUCT WITH RIGID IF PROPER FLOW IS NOT OBTAINED.
- SIZE ALL FLEXIBLE DUCT SO AS NOT TO EXCEED MAXIMUM CFMS GIVEN IN TABLE.

1 SOUTH HVAC PLAN
SCALE: 1/8" = 1'-0"

KEY NOTES FOR M2.2

- GAS PACKAGE UNIT MOUNTED ON 4" THICK CONCRETE PAD. SEE DETAIL 1/M3. PROVIDE ALL MANUFACTURER'S REQUIRED CLEARANCES AROUND UNIT.
- RUN DUCTWORK EXPOSED OVERHEAD IN THIS ROOM. SEE DETAIL 2/M3. ALL EXPOSED DUCTWORK SHALL HAVE INTERNAL DUCT LINER INSULATION AND HAVE "PAINT-GRIP" GALVANIZED FINISH. FINAL PAINTING BY GENERAL CONTRACTOR.
- DUCT MOUNTED SUPPLY AIR REGISTER. SEE DETAIL 2/M3. (TYPICAL).
- DUCT MOUNTED RETURN AIR GRILLE.
- MOUNT THERMOSTAT AT 48" AFF.
- INSTALL DUCT TYPE SMOKE DETECTOR IN RETURN AIR DUCT FOR UNIT SHUTDOWN. PROVIDE ACCESS DOOR IN DUCT. SEE DETAIL 1/M3 AND SPECIFICATIONS CONCERNING THE SMOKE DETECTOR.
- NOT USED.
- RUN DUCTWORK UP EXPOSED, TIGHT AGAINST WALL ON EXTERIOR OF BUILDING TO HIGH OVERHEAD IN THE SPACE. ALL EXPOSED DUCTWORK SHALL HAVE INTERNAL DUCT LINER INSULATION, AND BE SEALED WATERTIGHT.
- 12" DIA. RIGID EXHAUST DUCT UP TO ROOF MOUNTED EXHAUST HOOD. EXHAUST DISCHARGE SHALL BE 10'-0" MIN. FROM ANY OUTSIDE AIR INTAKE.
- 8" DIA. RIGID EXHAUST DUCT UP TO ROOF MOUNTED EXHAUST HOOD. EXHAUST DISCHARGE SHALL BE 10'-0" MIN. FROM ANY OUTSIDE AIR INTAKE.
- NOT USED.
- DUCT MOUNTED RETURN AIR GRILLE.
- DUCTLESS SPLIT SYSTEM OUTDOOR HEAT PUMP UNIT MOUNTED ON 4" THICK CONCRETE PAD. PROVIDE ALL MANUFACTURER'S REQUIRED CLEARANCES AROUND UNIT.
- WALL MOUNTED DUCTLESS SPLIT SYSTEM FAN-COIL UNIT MOUNT WITH BOTTOM AT 7'-0" AFF. COORDINATE FINAL LOCATION WITH ARCHITECT AND OWNER TO ACCOMMODATE THE ARRANGEMENT OF THE CONFERENCE ROOM. RUN PUMPED CONDENSATE CONCEALED IN WALL AND ABOVE CEILING TO ROOF. RUN REFRIGERANT PIPING CONCEALED IN WALL AND ABOVE CEILING TO OUTDOOR HEAT PUMP UNIT.
- PRIMARY THERMOSTAT FOR GPU-4. MOUNT AT 48" AFF.
- SECONDARY (SLAVE) THERMOSTAT FOR GPU-4. MOUNT AT 48" AFF.
- HIGH SIDE WALL MOUNTED RETURN AIR GRILLE.
- EXHAUST FAN FOR HEAT REMOVAL. FAN SHALL DISCHARGE ABOVE CEILING. FAN SHALL BE CONTROLLED BY WALL MOUNTED THERMOSTAT.
- 6" DIA. RIGID EXHAUST DUCT UP TO ROOF MOUNTED EXHAUST HOOD. EXHAUST

PROJECT TITLE
REVELS TURF & TRACTOR
RAWL'S CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
SOUTH HVAC PLAN

M2.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023

DIVISION 15 B - HEATING, VENTILATING AND AIR CONDITIONING

1.1 DESCRIPTION OF THE WORK

- A. Work under this section includes, but is not necessarily limited to, furnishing and installing the following:
 1. Heating, ventilation, and air conditioning equipment.
 2. Ductwork.
 3. Grilles and diffusers.
 4. Controls and control wiring.
 5. Condensate piping.
- B. All work under this contract shall be installed in compliance with the latest edition of the following codes and standards insofar as they apply:
 1. ASHRAE Guide
 2. National Electric Code.
 3. 2018 NC State Building Code: Mech Code.
 4. The Electrical Specifications for this project.
 5. SMACNA HVAC Duct Construction Standards.
 6. All local codes and ordinances.
 7. ARI ratings.
 8. 2018 NC State Building Code: Energy Conservation Code.
- C. These codes are minimum standards. If codes require a more stringent method of construction than the specifications require, the codes shall govern.
- D. The HVAC Contractor shall be licensed in North Carolina and have all local licenses required for the work.

1.2 INTENT

- A. The intent of these specifications and the accompanying drawing is to convey as reasonably as possible the requirements for a complete job ready for the building to operate. The HVAC Contractor shall take this into consideration and include in his bid allowance for contingencies as will allow him to provide minor pieces of equipment and labor not specifically indicated but required for the job to operate properly, at no additional cost to the Owner.

1.3 COORDINATION

- A. Coordinate work with other contractors. Notify Owner of apparent conflicts early to expedite construction. If structural damage appears imminent, stop work and notify Owner for a decision before resuming operations.
- B. Locations shown are approximate. The HVAC Contractor shall verify with owner, the placement of equipment, fixtures, outlets, etc. The drawings do not give exact details as to elevations and locations of various pipes, fittings, ducts, conduit, etc., and do not show all offsets and other installation details which may be required.
- C. Changes in duct or piping design caused by obstructions shall be submitted to Engineer in sketch form for study and comment prior to execution. Additional cost will not be allowed for this type of work.

1.4 SHOP DRAWINGS

- A. Shop drawings shall be submitted for all major items of equipment. These may consist of the manufacturer's standard catalog or tear sheets and shall have the exact items being offered clearly identified. Shop drawings shall include but are not limited to the following:
 1. All equipment and accessories.
 2. Grilles and diffusers.
 3. Unit sizes and requirements.

PART 2 - PRODUCTS

2.1 EQUIPMENT

- A. All air handling devices must have the manufacturer's recommended filter rack, for 1" thick filters.

2.2 PIPING

- A. Condensate drain piping shall be PVC pipe. Provide tee and plug at changes in direction. Route pipe to proper termination point. All condensate piping shall be insulated with flexible elastomeric insulation. Provide copper piping in plenum areas.

2.3 DUCTWORK

- A. Ductwork shall be built in accordance with SMACNA HVAC Duct construction standards. Furnish and install all supply, return, and ventilation ductwork shown, together with splitters, deflectors, dampers, etc. This work shall be constructed of new galvanized prime grade steel sheets. The gages of metal to be used and the construction and bracing of joints shall be in accordance with the SMACNA recommendations.
- B. Seal all sheet metal joints with fiber impregnated mastic.
- C. Support from building structure on strap hangers not over 8 feet apart.
- D. Use manufactured turning vanes in each elbow where required or where indicated on drawings.
- E. Flexible connectors shall be 3 inches wide, of fireproof material and used to isolate noise between equipment and ductwork on supply and return side of all units.
- F. Round runouts, where used, shall be built in accordance with the above standards, and each runout shall also have manufactured side take off, adjustable quadrant damper at all accessible locations and shall be of Owens Corning INL-25 flexible duct with UL label. Flex duct lengths allowed up to 14 feet. Duct must be supported with sufficient hangers in order to prevent sags. Serpentine routing will not be permitted. Quadrant damper to be 22 gauge easily adjustable manually with exterior handle (similar to H&C Kwik-set) and is not to be mounted in side take-off.

2.4 DUCT INSULATION (LOW PRESSURE)

- A. All insulation, linings, coverings and adhesives shall have a flame spread classification of 25 or less and a smoke developed rating of not more than 50, exposed exterior piping.
- B. All duct insulation shall comply with Section 604, of the N. C. Building Code: Mechanical Code
- C. All supply and return ductwork shall be completely insulated, either internally or externally.
- D. Rectangular ductwork shall be lined with two-inch thick, 1.5 lb. per cubic foot density, duct liner, Armstrong, CSG Ultraliner, Johns Manville or approved equal.
- E. As an alternative to duct liner, rectangular duct may be wrapped with Class 1 - 2" 3/4 lb. density (R-6.5) thick reinforced foil back fiberglass insulation, Owens-Corning Series ED or equal. Tape shall be Kraft reinforced foil tape or equal.
- F. Exhaust air duct does not require insulation, unless otherwise noted on the plans.
- G. Insulation shall be held in place with adhesive and welding pins 16" on center.
- H. Duct dimensions shown on the drawings are Net Inside Dimensions

2.5 THERMOSTATS

- A. Provide programmable electronic thermostats.
- B. Submit proposed thermostats for approval.

2.6 ROOF PENETRATIONS

- A. Provide pre-manufactured roof flashings compatible with equipment served.
- B. Coordinate roof work with roof system used. Provide proper flashing as required.
- C. Provide 1 year warranty on all roof work performed.

2.7 DUCT SMOKE DETECTORS

- A. Install duct mounted smoke detectors in GPU-5, & GPU-6 only. The duct smoke detectors shall be supplied and wired by the Fire Alarm Contractor. Provide access doors and wire to unit for shut-down. Install per code.
- B. Duct detectors are not required in GPU-1, GPU-2, GPU-3, GPU-4 & GPU-7 since air flows are 2000 cfm or less per NCSCC: Mechanical Code, Section 608.2.

PART 3 - EXECUTION

3.1 PIPING

- A. The HVAC Contractor shall coordinate such routing with others, to line his work true to adjacent spaces and in a workmanlike manner and to use only short radius 90 degree elbows. Where required, piping to be sturdily supported and separated in a manner satisfactory to the Engineer.
- B. The HVAC Contractor shall paint all exterior refrigerant piping, with UV resistant paint as recommended by the closed cell insulation manufacturer.
- C. Insulate all condensate lines for their entire length with 1/2" closed cell insulation. Install insulation per the manufacturers recommendations.

3.2 ELECTRICAL WORK

- A. The electrical contractor shall provide all switches, starters, wire conduit for the air conditioning, heating and ventilation equipment. Control wiring shall be by the heating and air conditioning contractor.
- B. HVAC Contractor is responsible for verifying that power terminals have been properly grounded prior to operating equipment and must find connections to all equipment including control wiring.
- C. All materials and workmanship shall be in accordance with the electrical specifications for the project. All wiring shall be color coded, and as-built wiring diagram prepared showing all connections and colors of wiring and delivered to the Owner.
- D. Furnish certification for acceptance of control wiring from local electrical inspector prior to acceptance.

3.3 CLEAN UP


- A. During construction, keep the site clean of debris. Upon completion, and before final inspection, clean up the premises to remove all evidence of work. In addition upon completion of construction leave equipment clean.
- B. Furnish one box of clean filters, for each size required, at the time of final inspection to the owner.

3.4 OPERATOR'S MANUAL AND DIAGRAM

- A. The HVAC Contractor shall prepare in one copy a manual describing the proper maintenance and operation of the systems. This manual shall not consist of standard factory instructions (although these may be included) but shall be prepared to describe this particular job.
- B. The manual shall be bound, indexed, dated and signed by the HVAC Contractor.
- C. Qualified representative of the HVAC contractor shall meet with the designated representatives of the Owner and the Owner's representative shall be instructed in the proper operation and maintenance of the control system and other systems.

3.5 GUARANTEE

- A. Guarantee all materials and labor included in the HVAC work for a period of one year from date of final acceptance by the owner. In addition, motor compressors shall be a nonprorated five year warranty. Any part or parts of the work or equipment which prove to be defective during the guarantee period shall be replaced at no additional cost to the owner or tenant.
- B. All air flows must be measured and balanced to within 10% of design airflow. All equipment used must have a current certification. Provide two copies of the balance report to the owner at closeout. The HVAC contractor shall return and re-balance to occupant comfort after 90 days from close-out. Provide all balance dampers needed for satisfactory operation regardless if shown on the drawings or not, and shift location of thermostats if required for occupant comfort.




KEY NOTES FOR 3/M3

1. 2-HOUR OR 3-HOUR RATED GYPSUM BOARD WALL. SEE PLANS FOR WALL TYPES AND LOCATIONS.
2. 14 GALVANIZED STEEL SLEEVE. FASTEN TO FIRE DAMPER FRAME.
3. CURTAIN
4. ACCESS DOOR. TYPICAL AT ALL FIRE DAMPERS.
5. 1-1/2" X 1-1/2" X 1/8" STEEL ANGLE. FASTEN TO SLEEVE.
6. DUCTWORK SIZE VARIES.
7. DYNAMIC FIRE DAMPER.
8. PROVIDE BREAK-AWAY JOINTS AT DUCT CONNECTIONS TO FIRE DAMPER AND SLEEVE.

RATED GYPSUM WALL PENETRATION

NOTE: THIS DETAIL IS FOR GENERAL DESIGN INTENT ONLY. INSTALL FIRE DAMPER PER MANUFACTURERS INSTRUCTIONS.




NOTE:


ALL EXPOSED DUCT SHALL HAVE DUCT LINER INSULATION.

3 FIRE DAMPER DETAIL
SCALE: NOT TO SCALE

2 DUCT MOUNTED REGISTER DETAIL
SCALE: NOT TO SCALE




4 DUCT CONSTRUCTION DETAIL
SCALE: NOT TO SCALE



KEY NOTES FOR 1/M3

- 1 GAS PACKAGE UNIT MOUNTED AT GRADE.
- 2 4" THICK CONCRETE PAD.
- 3 FLEXIBLE CONNECTIONS (TYPICAL).
- 4 PROVIDE CONDENSATE DRAIN TRAP. SIZE PER MANUFACTURERS RECOMMENDATIONS.
- 5 CONDENSATE DRAIN. RUN TO GRADE.
- 6 OUTSIDE AIR DAMPER AND HOOD. SET UNIT CONTROLS TO PROVIDE FOR SCHEDULED OUTDOOR AIR AS THE MINIMUM.
- 7 SIDEWALL MOUNTED RETURN AIR GRILLE. MOUNT WITH BOTTOM AT 8" AFF
- 8 SUPPLY DUCT TO ABOVE
- 9 OUTDOOR DUCTWORK SHALL BE SEALED WATERTIGHT AND HAVE INTERNAL INSULATION.
- 10 GRADE.
- 11 EXTERIOR WALL.
- 12 GAS LINE TO UNIT PROVIDED BY PLUMBING CONTRACTOR. FINAL CONNECTION AND START UP BY MECH. CONTRACTOR.
- 13 GAS SHUT-OFF VALVE, UNION AND FLEXIBLE HOSE.
- 14 DUCT TYPE SMOKE DETECTOR IN RETURN AIR DUCT. SMOKE DETECTOR FURNISHED BY MC. PROVIDE RAIL. (REMOTE ALARM INITIATING DEVICE) LOCATE ADJACENT TO TSTAT. PROVIDE FOR FAN SHUT-DOWN. PROVIDE ACCESS DOOR IN DUCT. INSTALL PER CODE. SMOKE DETECTORS ONLY REQUIRED ON GPU-5 AND GPU-6.
- 15 RETURN DUCT.
- 16 SEE PLANS FOR UNITS THAT HAVE LOW SIDEWALL RETURNS AND ONES WHERE RETURN DUCTS GO ABOVE THE CEILING.


1 TYPICAL HORIZONTAL GAS PACKAGE UNIT DETAIL
SCALE: NOT TO SCALE



W. S. ARCHITECTS, PA
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.779.9797
www.wsarchitectspa.com

ENGINEER

BURKE DESIGN GROUP, PA
CONSULTING ENGINEERS
3305-109 Durham Drive
Raleigh, North Carolina 27603
919.771.1916 fax: 919.779.0826
email: benburke@nc.rr.com
Corp. License # C-2652



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA




PROJECT NO.
2232

DRAWING TITLE
HVAC SPECIFICATION & DETAILS

M3

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



NOTE: SWITCHES MAY BE STACKED
(D) DENOTES OPTIONAL DIMMING CAPABILITY

2 SWITCHBANK (SB) X2
SCALE: NTS

Revise E2.1

LIGHTING SCHEDULE *

MARK	MANUFACTURER	CATALOG NO.	VOLT.	LAMPS	BALLAST	W/	REMARKS
			NO.	NO.	TYPE	FIXTURE	
B	LITHONIA	CPX-2X4-4000LM-30K-M2	120	-	LED	-	LED 2X4 LAY-IN FIXTURE, DIMMING CAPABILITY *
C	PRESCOLITE	LFLEDD04-6MFLD60430K	120	-	LED	-	LED 6" RECESSED CAN LIGHT, DIMMING CAPABILITY *
CL	PRESCOLITE	LTC-6RD-(S/P)30L35K9MD	120	-	LED	-	LED 6" CYLINDER LIGHT, SURFACE OR PENDANT MOUNT, WET LOCATION *
F	BIG ASS FANS	HAKU	120	-	LED	-	52" INDOOR/OUTDOOR CEILING FAN, COLOR/FINISH BY OWNER/ARCH *
H	LITHONIA	HEBL-1BL-40K-80CRI	120	-	LED	-	LED HIGH BAY LIGHT FIXTURE, COLOR/FINISH BY OWNER/ARCH *
S	PRESCOLITE	LTC-6RD-W30L35K9MD	120	-	LED	-	LED 6" CYLINDER SCORCE, WET LOCATION, COLOR/FINISH BY OWNER/ARCH *
W	HUBBELL	S91-40-3K7-FT-UNV-BLT	120	-	LED	-	LED WALL PACK, WET LOCATION, COLOR/FINISH BY OWNER/ARCH *
X	COMPASS	CUSO	120	-	LED	-	LED EGRESS FIXTURE - DUAL MODE, NORMAL/EMERG. OPERATION *
EXIT	COMPASS	CEL	120	-	LED	-	LED EXIT SIGN W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAGNOSTICS *
EMERG	COMPASS	CU2	120	-	LED	-	LED EMERG. LIGHT W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAGNOSTICS *
EXIT	COMPASS	CCRG	120	-	LED	-	LED EXIT/EMERG. COMBO W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAG. *

* OR APPROVED EQUAL. PROVIDE CUT SHEETS FOR OWNER APPROVAL PRIOR TO ORDERING FIXTURES.
CATALOG NUMBERS ARE FOR REFERENCE ONLY, ACTUAL NUMBERS MAY VARY.
THE EMERGENCY LIGHTS AND EXIT SIGNS MUST HAVE INTEGRAL BATTERIES, CHARGERS AND TEST SWITCHES.

NOTE:
PROVIDE LABELING ON ALL SWITCHES AND DEVICES NOTING CIRCUIT SERVED.
AUTOMATIC LIGHTING SHUTOFF IS NOT SHOWN IN THE EGRESS PATH LIGHTING AS ALLOWED PER 905.2.2.2.1 EXCEPTION #3, WHERE AUTOMATIC SHUTOFF WOULD ENDANGER OCCUPANT SAFETY.
THE ALL EXIT AND EMERGENCY LIGHTS TO NEAREST AVAILABLE UNSWITCHED LIGHTING CIRCUIT IN THE AREA SERVED.
VERIFY HEIGHT/LOCATION OF ALL SWITCHES AND DEVICES PRIOR TO INSTALLATION.

PROVIDE LED PHOTOCELL (PC) CONTROLS FOR EXTERIOR LIGHTING CIRCUIT.
LOCATE "PC" AWAY FROM ARTIFICIAL LIGHT (ON ROOF, IF POSSIBLE).
PROVIDE SHIELDING AS REQUIRED. VERIFY LOCATION.

1 NORTH FLOOR PLAN
SCALE: 1/8" = 1'-0"



PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
LIGHTING PLAN

E2.1

PLOT DATE 12/01/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023



Revised E2.2

LIGHTING SCHEDULE *

MARK	MANUFACTURER	CATALOG NO.	VOLT.	LAMPS NO.	LAMP TYPE	BALLAST TYPE	W/ FIXTURE	REMARKS
B	LITHONIA	CPX-2X4-400LM-30K-M2	120	-	LED	-	40	LED 2X4 LAY-IN FIXTURE, DIMMING CAPABILITY *
C	PRESCOLITE	LFBLD64-8MFLD6430R	120	-	LED	-	20	LED 6" RECESSED CAN LIGHT, DIMMING CAPABILITY *
CL	PRESCOLITE	LTC-6RD-(S/P)30L35K8MD	120	-	LED	-	25	LED 6" CYLINDER LIGHT, SURFACE OR PENDANT MOUNT, WET LOCATION *
F	BIG ASS FANS	HAUKU	120	-	LED	-	50	52" INDOOR/OUTDOOR CEILING FAN, COLOR/FINISH BY OWNER/ARCH *
H	LITHONIA	HEBL-1BL-40K-80CRI	120	-	LED	-	136	LED HIGH BAY LIGHT FIXTURE, COLOR/FINISH BY OWNER/ARCH *
S	PRESCOLITE	LTC-6RD-W3QL35K8MD	120	-	LED	-	25	LED 6" CYLINDER SCIENCE, WET LOCATION, COLOR/FINISH BY OWNER/ARCH *
U	PHILLIPS	HUE LIGHTSTRIP PLUS	120	-	LED	-	3W/FT	LED FLEX STRIP (UNDERCOUNTER) LIGHTING, COLOR/FINISH BY ARCH *
W	HUBBELL	SG1-40-3K7-FT-UNV-BLT	120	-	LED	-	40	LED WALL PACK, WET LOCATION, COLOR/FINISH BY OWNER/ARCH *
X	COMPASS	OU50	120	-	LED	-	10	EMERG. EGRESS FIXTURE -- DUAL MODE, NORMAL/EMERG. OPERATION *
EXIT	COMPASS	CEL	120	-	LED	-	-	LED EXIT SIGN W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAGNOSTICS *
EM	COMPASS	OU2	120	-	LED	-	-	LED EMERG. LIGHT W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAGNOSTICS *
EXIT	COMPASS	CCRG	120	-	LED	-	-	LED EXIT/EMERG. COMBO W/ BATTERY, UNIVERSAL-MOUNT, SELF DIAG. *

* OR APPROVED EQUAL. PROVIDE CUT SHEETS FOR OWNER APPROVAL PRIOR TO ORDERING FIXTURES. CATALOG NUMBERS ARE FOR REFERENCE ONLY, ACTUAL NUMBERS MAY VARY. THE EMERGENCY LIGHTS AND EXIT SIGNS MUST HAVE INTEGRAL BATTERIES, CHARGERS AND TEST SWITCHES.

1 SOUTH FLOOR PLAN
SCALE: 1/8" = 1'-0"


PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
LIGHTING PLAN

E2.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36"; other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023




Revels E3.1


EQUIPMENT	MCA	MOCF	VOLTS	PH	WIRE SIZE
GRINDER	12.0A	20A	240V	1	3-#12, 1-#12 GND IN 1/2" CONDUIT
AIR COMP.	31.0A	50A	240V	1	3-#8, 1-#10 GND IN 3/4" CONDUIT
AIR COMP. (DRYER)	9.1A	20A	120V	1	2-#12, 1-#12 GND IN 1/2" CONDUIT
BRIDGE CRANE	10.0A	20A	120V	1	2-#12, 1-#12 GND IN 1/2" CONDUIT

NOTE:
THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL EQUIPMENT ELECTRICAL REQUIREMENTS PRIOR TO ROUGH-IN AND RELEASING GEAR. ADJUST BREAKER, WIRE SIZES, ETC. AS REQUIRED.

NOTE:
THE SHOP AREA IS CLASSIFIED AS A MINOR REPAIR GARAGE PER 2017 NEC 511.2. NATURAL GAS OR HYDROGEN FUELED VEHICLES WILL NOT BE REPAIRED IN THIS FACILITY. THE AREA 18" ABOVE THE FLOOR IS CLASSIFIED AS A CLASS 1, DIVISION 2 AREA. ALL ELECTRICAL OR MECHANICAL EQUIPMENT SHALL BE LOCATED OUTSIDE OF THIS AREA. THE OWNER SHALL PROVIDE STANDS FOR ALL EQUIPMENT, WITH OPEN MOTORS, ETC. TO LOCATE HIGHER THAN 18" A.F.F.




1 NORTH FLOOR PLAN
SCALE: 1/8" = 1'-0"



NOTE:
THE SHOP AREA IS CLASSIFIED AS A MINOR REPAIR GARAGE PER 2017 NEC 511.2. NATURAL GAS OR HYDROGEN FUELED VEHICLES WILL NOT BE REPAIRED IN THIS FACILITY. THE AREA 18" ABOVE THE FLOOR IS CLASSIFIED AS A CLASS 1, DIVISION 2 AREA. ALL ELECTRICAL OR MECHANICAL EQUIPMENT SHALL BE LOCATED OUTSIDE OF THIS AREA. THE OWNER SHALL PROVIDE STANDS FOR ALL EQUIPMENT, WITH OPEN MOTORS, ETC. TO LOCATE HIGHER THAN 18" A.F.F.

(SEE SHEET E3.1 FOR POWER IN THIS AREA)



1 SOUTH FLOOR PLAN
SCALE: 1/8" = 1'-0"

NOTE:
PROVIDE LABELING ON ALL DEVICES AND EQUIP NOTING CIRCUIT SERVED.
COORDINATE LOCATION AND MOUNTING OF ALL DISCONNECTS AND RECEPTACLES WITH EQUIPMENT SERVED. DO NOT BLOCK ANY ACCESS PANELS OR NAMEPLATE DATA. PROVIDE SEPARATE SUPPORTS IF REQUIRED.
VERIFY HEIGHT/LOCATION OF ALL EQUIP AND DEVICES PRIOR TO INSTALLATION.

WEATHER PROOF SWITCH SHALL BE LOCATED WITHIN SIGHT OF SIGN OR BE CAPABLE OF BEING LOCKED IN THE OPEN POSITION PER NEC 600.6. WIRE TO SPECIFIED MULTI-CIRCUIT TIMELOCK IN MAIN ELECTRICAL ROOM.
MONUMENTAL SIGN (SEE SITE PLAN FOR LOCATION)
PROVIDE 1" CONDUIT FROM BUILDING PANELS TO NEW SIGN LOCATION (COORDINATE W/ OWNER/EC).

PROJECT TITLE
REVELS TURF & TRACTOR
RAWLS CHURCH RD.
FUQUAY-VARINA, NORTH CAROLINA

PROJECT NO.
2232
DRAWING TITLE
POWER PLAN

E3.2

PLOT DATE 12/01/23
AHJ COMMENTS 11/30/23

This original sheet is 24" x 36", other dimensions indicate it has been altered.
All information on this sheet is the property of W. S. Architects, PA and may not be duplicated in whole or in part without written authorization from W. S. Architects, PA. 2023

