

#### **Egg Station** | ES



Eggs are the cornerstone of every successful breakfast menu. With the Egg Station from Antunes, any operation can easily serve a fresh, made-to-order egg sandwich or omelet. Using a combination of heat from the grill surface and steam, this unit cooks perfectly moist eggs in only a matter of minutes. No hassle, no guesswork.

The heated grill surface of the Egg Station cooks the eggs while the non-stick rings give the product its shape. Steam is created under the pivoting cover that is lowered over the rings. As water is poured into the trough on the cover, it drips down onto the platen, which produces steam to keep the eggs moist as they cook.

The small, compact footprint of the Egg Station makes it a great addition to any sized operation. Whether it's new menu items or extended hours, operations can continue to serve breakfast items without worrying about cross contamination or sacrificing space on the grill.

The Egg Station is available in models with 3" egg rings, 4" egg rings, or 8" omelets rings. Additional available features include a front grill for heating pre-cooked sliced meats.

Cooking time for all Egg Station models is approximately 120 seconds for room temperature eggs and 150 seconds for refrigerated eggs.

#### **FEATURES**

- Quickly cook eggs for breakfast items without taking up valuable grill space.
- Small footprint to easily fit into any operation.
- Cooks room temperature eggs in 120 seconds and refrigerated eggs in 150 seconds.
- Available with non-stick rings for 3" eggs, 4" eggs, and 8" omelets.
- Available with front grill for heating pre-cooked sliced
- Audio and visual signal for operation.
- Easy to clean with included scrap tray.





## **Egg Station** | ES

Model & Mfg. No.	Width	Depth	Height	Shipping Width	Shipping Depth	Shipping Height	Shipping Weight		Volts	Watts	Amps	Hertz	Plug Description
Capacity: S	ix 3" Eggs (	with front g	rill for Cana	adian bacon	)								
ES-600 9300530	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	45 lbs. (20 kg)	Back Side	208- 220- 240	2380- 2662- 3168	11.4- 12.1- 13.2	50/60	NEMA 6-20P 20 Amp., 250 Volt
ES-600 9300570	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	45 lbs. (20 kg)	Back Side	230	2900	12.6	50/60	IEC-309 16 Amp., 250 Volt Pin & Sleeve
ES-600 9300572	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	45 lbs. (20 kg)	Back Side	230	2900	12.6	50/60	CEE 7/7 16 Amp., 250 Volt
Capacity: T	wo 8" Omel	ets											NENGA
ES-602 9300577	18 1/4" (464 mm)	18 3/16" (462 mm)	8 1/4" (210 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	48 lbs. (22 kg)	Back Side	208	2400	11.5	50/60	NEMA 6-20P 20 Amp., 250 Volt
Capacity: S	ix 4" Eggs												
ES-604 9300574	19 3/4" (502 mm)	17 1/2" (445 mm)	7 3/4" (197 mm)	12" (305 mm)	21" (533 mm)	21" (533 mm)	50 lbs. (23 kg)	Back Side	208- 220- 240	2380- 2662- 3168	11.4- 12.1- 13.2	50/60	NEMA 6-20P 20 Amp., 250 Volt
ES-604 9300581	19 3/4" (502 mm)	17 1/2" (445 mm)	7 3/4" (197 mm)	12" (305 mm)	21" (533 mm)	21" (533 mm)	50 lbs. (23 kg)	Back Side	208- 220- 240	2400- 3150	11.5- 13.1	50/60	NEMA 5-15P 15 Amp., 250 Volt
Capacity: T	welve 3" Eg	gs											
ES-1200 9300532	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	48 lbs. (22 kg)	Back Side	208- 220- 240	2380- 2662- 3168	11.4- 12.1- 13.2	50/60	NEMA 6-20P 20 Amp., 250 Volt IEC-309
ES-1200 9300580	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	48 lbs. (22 kg)	Back Side	230	2900	12.6	50/60	16 Amp., 250 Volt Pin & Sleeve
ES-1200 9300582	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	48 lbs. (22 kg)	Back Side	230	2900	12.6	50/60	CEE 7/7 16 Amp., 250 Volt
ES-1200 9300584	17 1/4" (438 mm)	17 1/2" (445 mm)	9" (229 mm)	14" (356 mm)	22" (559 mm)	22" (559 mm)	48 lbs. (22 kg)	Back Side	230	2900	12.6	50/60	BS-1365 Fused, Permaplug 16 Amp., 250 Volt

P/N 1020222 08/17







### MercoEco™

Visual Heat-N-Hold Cabinet with Wi-Fi & Tray Tracking Technology

#### Item/Sku & Model/Description

- MHD32SST1T 3 shelf cabinet with touch screen only on front (Single Side)
- MHD32SST2T 3 shelf cabinet with touch screen on front & back (Pass Through)



MHD32SST1T (Single Side)



MHD32SST2T (Double Side)

#### Standard Features


- Available with single or double sided touch screen controls
- Industry-exclusive touch screen controls with Wi-Fi capability
- Industry-exclusive Tray Tracking Technology
- Independently programmable temperature controls for each shelf to optimize food quality
- Global timer and temperature buttons
- Removable back panel on single sided model provides dual-sided access to food items (pass-through feature)
- Stainless steel cabinet exterior
- Audible and visual end-of-hold time
- Hard anodized heating surfaces enhance performance and increase durability
- Stainless steel tray seals, one per shelf
- Includes (3) full size tray tracking pans
- 1 year Parts & Labor warranty on cabinet; 90 day warranty on the traytracking components of the pans

#### Options & Accessories

Additional custom tray tracking pan (full size)

#### Specifications

Merco's innovative design will hold multiple trays of hot prepared food in independently time-controlled slots.



The Merco Visual Holding Cabinet takes the worry out of maintaining food quality while holding a wide range of foods safely. Merco's exclusive Tray Tracking Technology allows for touch-free timer starts and tracking of trays as they are sequenced throughout the cabinet or your kitchen.

Merco's innovative technology gives you a holding cabinet with premier technology, versatility and reliability. Call Merco for more information.


Tel: 1.877.392.7770











Welbilt reserves the right to make changes to the design or specifications without prior notice.

8700 Line Avenue Shreveport, LA 71106-6800

(single side) MHD32SST2T

(double side)

Tel: 1.877.392.7770 www.MercoProducts.com www.MercoMax.com

20.8"

528mm

20.8"

528mm

22.5"

572mm

22.5"

572mm

208-240/60/1

208-240/60/1

12.8"

325mm

12.8"

325mm



8.3

8.3

1990

1990

6-20P

6-20P



87lb / 39kg

87lb / 39kg



#### **Ultra-Glo® Portable Foodwarmers**

Models: UGFF, UGFFL, UGFFB, UGFFBL

Hatco Ultra-Glo® Portable Foodwarmers keep food hot at kitchen work areas, waitress pickup stations or customer serving points. Available in models and sizes to meet every food warming need.

#### Standard features

- Ceramic heating elements provide more distance between the heat source and the holding pan
- The distance, combined with the compact element housing, makes it easier to access the product while maintaining proper food temperatures
- Models include heat above the food, with optional base heat
- Hatco can custom design portable foodwarmers to meet customer specifications or to fit an unusual situation
- UGFF and UGFFL include a pan skirt for 12" x 20" (305 x 508 mm) pans
- Factory pre-wired with a 6' (1829 mm) cord and plug

Project		
Item #	13	
Quantity		



#### **Options** (available at time of purchase only)

Designer Colors (One color per unit, heated base is not powdercoated) -						
Clear Anodized	Standard -	Non-sta	andard cold	ors are non-returnable		
☐ Warm Red	□Black	□Gra	ay Granite	☐ White Granite		
□ Navy Blue	□Hunter	Green	∆Antique (	Copper		

Gloss Finish	es (O	ne col	or per unit	, heated	base is	not p	oowderco	oated) – (	Clear
Anodized	Stan	dard -	Non-stan	dard cold	ors are	non-i	returnable	e /	
	_			_					


- ☐ Gleaming Gold ☐ Glossy Gray ☐ Bold Black □ Radiant Red □ Brilliant Blue
- ☐ Halogen Bulb

#### **Accessories**

- ☐ 5-Pleat Hardcoated French Fry Box Ribbon
- ☐8-Pleat Hardcoated French Fry Bag Ribbon
- ☐ Food Holding Pans
- ☐ Wire Trivets

Chef LED Bulb in lieu of Standard Display Light - bulb must be rotated down

- 2700K Similar to warm incandescent light
- ☐ 3000K Similar to warm halogen light
- 4000K Similar to cool fluorescent light
- 230V CE for input voltages above 200V
- 2700K Similar to warm incandescent light
- ☐ 3000K Similar to warm halogen light
- 4000K Similar to cool fluorescent light





For operation, location and safety information, please refer to the Installation and Operating Manual.







HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350




www.hatcocorp.com | support@hatcocorp.com | Find a Hatco Rep | Image Library | Document Library | Patents | Chat




#### **Ultra-Glo® Portable Foodwarmers**

Models: UGFF, UGFFL, UGFFB, UGFFBL

#### **UGFF and UGFFL**



#### **UGFFB** and **UGFFBL**



#### **SPECIFICATIONS Ultra-Glo® Portable Foodwarmers**

The shaded areas contain electrical information for International models only

Model	Dimensions (Width x Depth x Height)	Volts	Phase	Watts	Amps	Plug	Ship Weight*	
		100		625	6.3	NEMA 5-15P		
		120	1	750	6.3	NEMA 5-15P		
UGFF	10 20" x 20 25" x 10 27" (214 x 565 x 470 mm)	220	Single	630	2.8	CEE 7/7 Schuko	15 lbs. (7 kg)	
UGFF	12.38" x 22.25" x 18.87" (314 x 565 x 479 mm)	240	Sirigle	750	3.1	BS-1363	15 lbs. (7 kg)	
		220-230 (CE)	1	630-689	2.9-3.0	CEE 7/7 Schuko	1	
		230-240 (CE)		689-750	3.0-3.1	BS-1363		
		100		708	7.1	NEMA 5-15P		
		120	]	870	7.3	NEMA 5-15P	17 lbs. (9 kg)	
UGFFL	12.38" x 22.25" x 18.87" (314 x 565 x 479 mm)	220	Cinglo	730	3.3	CEE 7/7 Schuko		
UGFFL		240	Single	870	3.6	BS-1363		
		220-230 (CE)		730-799	3.3-3.5	CEE 7/7 Schuko		
		230-240 (CE)		799-870	3.5-3.6	BS-1363		
		100		875	8.8	NEMA 5-20P	25 lbs. (12 kg)	
	12.77" x 22.46" x 22" (324 x 570 x 559 mm)	120		1000	8.3	NEMA 5-15P		
UGFFB		220	Single	840	3.8	CEE 7/7 Schuko		
UGFFB		240	Sirigle	1000	4.2	BS-1363		
		220-230 (CE)	]	840-919	3.8-4.0	CEE 7/7 Schuko		
		230-240 (CE)		919-1000	4.0-4.2	BS-1363		
		100		959	9.6	NEMA 5-15P		
		120	]	1120	9.3	NEMA 5-15P	34 lbs. (16 kg)	
HOEEDI	10.77" v 00.46" v 00" (004 v 570 v 550 mm)	220	1	940	4.3	CEE 7/7 Schuko		
UGFFBL	12.77" x 22.46" x 22" (324 x 570 x 559 mm)	240	Single	1120	4.7	BS-1363		
		220-230 (CE)	]	940-1029	4.3-4.5	CEE 7/7 Schuko		
		230-240 (CE)	1	1029-1120	4.5-4.7	BS-1363		

<sup>\*</sup>Shipping weight includes packaging.


Note: Models with "L" contain two incandescent lights. The housing is 9" (229 mm) wide versus 6" (152 mm) without lights.


Note: Models with "B" include a thermostatically pre-set heated base.


#### CORD LOCATION

UGFF, UGFFL: Back, upper middle. UGFFB, UGFFBL: Back, lower middle.

#### **PLUG CONFIGURATIONS**







#### **PRODUCT SPECS Portable Foodwarmers**

The Portable Foodwarmer shall be an Ultra-Glo® manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A.

The Foodwarmer shall be rated at  $\dots$  watts,  $\dots$  volts, single phase and be ... inches (millimeters) in overall width.

The Ultra-Glo shall consist of an aluminum housing and include a ceramic heating

element and a 6' (1829 mm) cord with plug attached. Options: Designer Colors, Gloss Finishes, Halogen Bulb. Accessories: Food holding pans, trivets, fry ribbons, Chef LED bulbs.

Warranty consists of 24/7 parts and service assistance (U.S. and Canada only).

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350



www.hatcocorp.com | support@hatcocorp.com | Find a Hatco Rep | Image Library | Document Library | Patents | Chat

Form No. UGFF Spec Sheet Page 2 of 2 August 2022




#### Toast-Qwik® Electric **Conveyor Toaster**

Model: TQ3-10

Hatco's industry-leading Toast-Qwik® Conveyor Toasters have been completely redesigned to provide a great new look, and increased production capabilities. They continue to provide the best reliability, flexibility and value of any convevor toaster available!

#### Standard features

- Patented ColorGuard sensing system which monitors chamber temperature and adjusts conveyor speed to ensure consistent toast results - even in your busiest periods
- Power Save mode activates manually by pressing the Power Save Button above the leaf symbol
- Features an Air Intake Filter Screen which is removable for easy cleaning
- Crumb tray is removable
- 2" (51 mm) high opening
- DC stepper motor provides wide range of linear and precise speed control
- Available in Designer Black finish to blend with any decor
- 1780 watts in 120, 208 or 240 provides about 250 slices per hour
- Double-sided or single-sided toasting at the touch of a button









IFS anti-microbial coatings use naturally-occurring, environmentally sustainable, silver ions to help inhibit the growth of microbes on the powder coated surface. See www.hatcocorp.com/antimicrobial-paint for more information.



For operation, location and safety information, please refer to the Installation and Operating Manual.








#### Toast-Qwik® Electric Conveyor Toaster

Model: TQ3-10

#### **TQ3-10**



#### **SPECIFICATIONS** Toast-Qwik® Conveyor Toaster

Model	Opening Dimensions (W x H)	Dimensions (W x D x H)	<b>Volts</b> Single Phase	Hertz	Watts	Amps	Plug	Approx. Ship Weight
	10.00   0	44.40" 04.40" 40.47"	120	50/60	1780	14.8	NEMA 5-15P <b>◆</b>	
TQ3-10	TQ3-10 10.39" x 2" (264 x 51 mm)	14.49" x 21.18" x 16.17" (368 x 538 x 411 mm)	208	50/60	1780	8.6	NEMA 6-15P	54 lbs. (25 kg)
140 10			240	50/60	1780	7.4	NEMA 6-15P	

<sup>\*</sup> Canadian models use NEMA 5-20P.

#### **CORD LOCATION**

Lower right corner on back of unit.

#### **PLUG CONFIGURATIONS**



#### **PRODUCT SPECS Conveyor Toaster**

The electric Toast-Qwik® Conveyor Toaster with ColorGuard sensing system shall be a Hatco model ... as manufactured by the Hatco Corporation, Milwaukee, WI 53234

The Toaster shall have the capacity to toast up to ... pieces per hour and it shall be rated at ... kW, ... volts, single phase. The toaster shall be of Powdercoated steel

design and shall include double or single sided toasting capabilities, manual power save mode, a removable/cleanable air intake filter screen, variable speed control and power save mode. The toaster will have metal sheathed heating elements and factory attached UL listed cord and plug.

Warranty consists of 24/7 parts and service assistance (US and Canada only).

HATCO CORPORATION | P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. | (414) 671-6350



www.hatcocorp.com support@hatcocorp.com Find a Hatco Rep Image Library Document Library Patents Chat

Project:	Date:	Approval:	Qty:	Item #: 600DI1995

**15** 



## Regency 9" x 9" x 5" 18-Gauge Stainless Steel One Compartment Drop-In Sink

#600DI1995







#### **Technical Data**

Length	12 Inches
Width	14 Inches
Height	5 Inches
Cutout Length	11 1/4 Inches
Cutout Width	13 1/4 Inches
Bowl Depth	5 Inches
Basket Drain Size	3 1/2 Inches
Bowl Front to Back	9 Inches
Bowl Left to Right	9 Inches
Color	Silver

#### **Features**

- Durable, 18 gauge type 304 stainless steel construction
- 3 1/2" basket strainers collect food debris; includes 1 1/2" IPS drain connections
- Perfect for handwashing throughout the day
- Comes with installation hardware


#### **Certifications**



#### **Technical Data**

Drain Outlet Size	1 1/2 Inches
Edge Style	Flush
Faucet Centers	4 Inches
Features	Massachusetts Accepted Plumbing Product NSF Listed
Flow Rate	2 GPM
Gauge	18 Gauge
Installation Type	Drop-In
Material	Stainless Steel
Number of Compartments	1 Compartment
Stainless Steel Type	Type 304
Туре	Drop-In Sinks

#### **Plan View**



#### **Notes & Details**

Great for hand washing, this Regency  $9" \times 9" \times 5"$  stainless steel drop-in sink is a versatile addition to your food service operation. Featuring a durable 18 gauge, 304 series stainless steel top with a polished 18-gauge 304 series stainless steel bowl, this sink is built to last. Plus, it comes with a 3 1/2" drain basket to conveniently catch food debris to prevent clogging the drain.

It comes with 2 holes on 4" centers to accept a faucet (sold separately) and the hardware for installation is included. The compact compartment makes this sink ideal for small spaces like food trucks, concession stands, and snack bars. The raised marine edge helps prevent water from dripping onto the floor. With both hot and cold water capabilities, this drop-in sink is a practical solution in a variety of settings.

A WARNING: This product can expose you to chemicals including Lead and Nickel, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.


Project:	Date:	Approval:	Qty:	Item #: 600S3162018X

16



Regency 88" 16-Gauge Stainless Steel Three Compartment Commercial Sink with Stainless Steel Legs, Cross Bracing, and 2 Drainboards - 16" x 20" x 12" Bowls

#600S3162018X







#### **Technical Data**

Length	88 Inches
Width	25 1/2 Inches
Height	44 3/4 Inches
Drainboard Length	18 Inches
Bowl Depth	12 Inches
Backsplash Height	8 1/4 Inches
Work Surface Height	36 1/2 Inches
Basket Drain Size	3 1/2 Inches
Bowl Front to Back	20 Inches
Bowl Left to Right	16 Inches

#### **Features**

- Made of high-quality 16 gauge, type 304 stainless steel
- Designed with (3) 12" deep bowls and rounded corners for easy cleaning
- Stainless steel legs, sockets, bullet feet, and crossbracing for maximum strength and longevity
- Includes 1 1/2" IPS drain connection and 3 1/2" basket strainers
- Backsplash and rolled edges prevent splashes and overflow


#### **Certifications**



#### **Technical Data**

Drain Outlet Size	1 1/2 Inches
Faucet Centers	8 Inches
Features	NSF Listed
Gauge	16 Gauge
Leg Construction	Stainless Steel
Material	Stainless Steel
Number of Compartments	3 Compartments
Number of Drainboards	2 Drainboards
Stainless Steel Type	Type 304
Style	2 Drainboards
Туре	Straight / Line Sinks

#### **Plan View**



#### **Notes & Details**

Outfit your facility with a long-lasting sink with this Regency 88" stainless steel three compartment sink with 2 drainboards. It's constructed from high-quality, 16-gauge type 304 stainless steel, making it more corrosion-resistant and durable than other sinks made from thinner, 18-gauge material. This sink features 2 sturdy, 18" drainboards so you can easily wash and dry dishes and utensils in one convenient location. It's also dipped a minimum of 1/4" to facilitate better drainage, and the welded construction contributes to the long-lasting use and overall strength of this sink / drainboard combo.

The 12" deep bowls are die-stamped to a minimum of 1/4" to ensure proper drainage. Plus, each bowl includes a  $3\,1/2$ " basket strainer to catch food debris, which prevents the drain from clogging. For easy cleaning, each compartment has rounded corners so you can rinse and wipe down the sink.

A 8 1/4" tall backsplash is included and comes complete with (2) 1 1/8" diameter holes punched on 8" centers to accommodate 1 faucet (sold separately). This sink also includes a 1 1/2" raised rolled edge, which is 2" tall on the front and both sides to contain splashes and overflow. The legs are constructed of 1 5/8" diameter stainless steel with stainless steel cross-bracing and adjustable plastic feet for added stability. These features serve to prolong the life of your sink while adding exceptional strength to the unit.

⚠ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.

Project:	Date:	Approval:	Qty: 2	Item #: 60S1162018XL
----------	-------	-----------	--------	----------------------

19



Regency 36 1/2" 16 Gauge Stainless Steel One Compartment Commercial Sink with Stainless Steel Legs, Cross Bracing, and 1 Drainboard - 16" x 20" x 12" Bowl - Left Drainboard

#60S1162018XL







#### **Technical Data**

Length	36 1/2 Inches
Width	25 1/2 Inches
Height	43 3/4 Inches
Drainboard Length	18 Inches
Bowl Depth	12 Inches
Backsplash Height	9 Inches
Work Surface Height	34 3/4 Inches
Basket Drain Size	3 1/2 Inches
Bowl Front to Back	20 Inches
Bowl Left to Right	16 Inches

#### **Features**

- Features a durable 16-gauge type 304 stainless steel construction
- Designed with a 12" deep bowl and rounded corners for easy cleaning
- Stainless steel legs, sockets, bullet feet, and crossbracing for maximum strength and longevity
- Includes an 18" drainboard and 3 1/2" drain basket
- Backsplash and rolled edges prevent splashes and overflow


#### **Certifications**



#### **Technical Data**

8 Inches
NSF Listed
16 Gauge
Stainless Steel
Stainless Steel
1 Compartment
1 Drainboard
Type 304
1 Drainboard

#### **Plan View**



#### **Notes & Details**

Outfit your facility with a long-lasting sink with this Regency  $36\ 1/2$ " stainless steel one compartment sink with 1 drainboard. It's constructed from high-quality, 16-gauge type 304 stainless steel, making it more corrosion-resistant and durable than other sinks made from thinner, 18-gauge type 430 stainless steel. This sink features a sturdy, 18" drainboard so you can easily wash and dry dishes and utensils in one convenient location. It's dipped a minimum of 1/4" to facilitate better drainage, and the welded construction contributes to the long-lasting use and overall strength of this sink / drainboard combo.

The 12" deep bowl is die-stamped to a minimum of 1/4" to ensure proper drainage. Plus, it includes a  $3\ 1/2$ " basket strainer to catch food debris, which prevents the drain from clogging. For easy cleaning, the compartment has rounded corners so you can rinse and wipe down the sink.

A 9" tall backsplash is included and comes complete with (2) 1 1/8" diameter holes punched on 8" centers to accommodate 1 faucet (sold separately). This sink also includes a 1 1/2" raised rolled edge, which is 2" tall on the front and both sides to contain splashes and overflow. The legs are constructed of 1 5/8" diameter stainless steel with stainless steel cross-bracing and adjustable plastic feet for added stability. These features serve to prolong the life of your sink while adding exceptional strength to the unit.



## GR KLEENSCREEN PLUS® FILTRATION SYSTEM BUILT-IN FILTER SYSTEM FOR 2GRMF, 3GRMF & 4GRMF FRYERS



22







#### **SPECIFICATIONS**

Built-in filter system, Vulcan-Hart Model No. (# of fryers 2, 3, 4) GR (45, 65, 85) (control type M) F (add suffix-F to fryer battery model No., i.e. 2GR45DF). Filter system accommodates maximum of four cabinets for GR45F and maximum of three for GR65F and GR85F. Filter vessel constructed of 18 gauge series stainless steel. ½ H.P. motor/pump circulates hot frying compound at the rate of 8 gallons per minute, activated by a one touch push button switch. System provided standard with stainless steel mesh filter screen. Optional KleenScreen PLUS® envelopes filter out particulate down to .5 microns. Standard equipment comes on casters, has a tank brush, and clean-out rod. Hands free oil return line connection. Requires 120 volt, 60 Hz, 1 phase power supply.

CSA design certified. NSF listed.

#### SPECIFY TYPE OF GAS WHEN ORDERING

- □ Natural Gas
- ☐ Propane Gas

#### **SPECIFY ALTITUDE**

- ☐ Natural Gas for above 2,000 ft.
- ☐ Propane Gas for above 3,500 ft.

#### STANDARD FEATURES

- Filter system accommodates maximum of four fryer cabinets (GR45F), maximum of three (GR65F or GR85F).
- Boil Out ByPass<sup>™</sup> easily removes boil out solution from fry tank without contact of drain manifold, filter pan or motor/ pump.
- 6" Casters adjustable 2 locking, 2 non-locking.
- 18 gauge stainless steel filter pan. 70 lbs. frying compound capacity on GR45F, 110 lbs. capacity on GR65 & GR85F.
- Stainless steel filter mesh screen filters from 2 sides.
- 1/3 H.P. motor and pump circulates frying compound at a rate of 8.0 gallons per minute.
- Tank brush and clean-out rod.
- 120 volt, 60 Hz, 1 phase (NEMA 5-15P).
- One year limited parts and labor warranty.
- 10 year fry tank limited warranty.
- High Temperature Discard Hose.

#### ACCESSORIES (Packaged & Sold Separately)

- ☐ Stainless steel tank cover doubles as a work surface top.
- ☐ "Add-On" Frymate™ VX15 or VX21S.
- ☐ Rear oil reclamation discard connection (Factory Installed).
- ☐ GR45F Twin Basket Lifts (Factory Installed).
- ☐ GR65F & GR85F Single and Twin Basket Lifts (Factory Installed).
- ☐ Prison Security Package (Factory Installed).
- ☐ Flexible gas hose with quick disconnect.
- ☐ Micro-Filtration Fabric Conversion Kits hardware and 3 envelopes.
- ☐ Micro-Filtration Fabric Envelopes 6 filters/per package.

#### **OPTIONS**

☐ Second year extended limited parts and labor warranty.

#### REFERENCE MATERIALS

- See 1GR45M Spec Sheet F32630.
- See 1GR65M Spec Sheet F32631.
- See 1GR85M Spec Sheet F32632.
- See 1GRF Spec Sheet F32962 for single unit KleenScreen PLUS®.



a division of ITW Food Equipment Group LLC

P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

#### FRYERS



## **GR KLEENSCREEN PLUS® FILTRATION SYSTEM**BUILT-IN FILTER SYSTEM FOR 2GRMF, 3GRMF & 4GRMF FRYERS

#### **INSTALLATION INSTRUCTIONS**

- A combination valve with pressure regulator is provided with this unit.
  - Natural Gas
     Operating pressure 4.0" W.C.
     Recommended supply pressure 7-9" W.C.
     Not to exceed 14" W.C. (1/2 PSI)
  - Propane Gas
     Operating pressure 10.0" W.C.


     Recommended supply pressure 11-12" W.C.
     Not to exceed 14" W.C. (1/2 PSI)
- An adequate ventilation system is required for Commercial Cooking Equipment. Information may be obtained by writing to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269. When writing refer to NFPA No. 96.

- 3. All models require a 6" (152 mm) clearance at both sides and rear adjacent to combustible construction.
- 4. All models require a 16" (407 mm) minimum clearance to adjacent open top burner units.
- 5. This appliance is manufactured for commercial installation only and is not intended for home use.

#### **SERVICE CONNECTIONS:**

P1 11/4" (32 mm) NPT common rear gas connection.

**NOTE:** In line with its policy to continually improve its product, Vulcan reserves the right to change materials and specifications without notice.



Views Front, Side and Top 2GR45F, 2GR65F, 2GR85F,

		Filter Area /	Filter Area /				Battery Dimensions (Widths)		
Model	Filter Pan Capacity	Fabric Envelope	Motor	Pump	Electric Amps	Electric Power	2 Fryers	3 Fryers	4 Fryers
GR45MF	70 lbs.	270 sq. in 350 sq. in	1/3 HP 1750 RPM	8 Gal/Min	115V 6.0A	115V 60Hz 1Ph	31"	461/2"	62"
GR65MF	110 lb -	270 sq. in	¹/₃ HP	O Cal/Min	1151/ 0.04	115V COLL- 1Db	4011	601	
GR85MF	110 lbs.	350 sq. in	1750 RPM	8 Gal/Min	115V 6.0A	115V 60Hz 1Ph	42"	63"	_

This appliance is manufactured for commercial use only and is not intended for home use.



P.O. Box 696 ■ Louisville, KY 40201 ■ Toll-free: 1-800-814-2028 ■ Local: 502-778-2791 ■ Quote & Order Fax: 1-800-444-0602

## **VULCAN**

## MSA SERIES HEAVY DUTY GAS GRIDDLES



Model MSA48







#### **SPECIFICATIONS**

Low profile heavy duty gas griddle, Vulcan Model No.\_\_\_\_\_. Stainless steel front, sides and front top ledge. Fully welded stainless and aluminized steel body frame. 11" low profile cooking height on 4" legs. 1" thick polished steel griddle plate with 12 gage, 4" stainless steel back and tapered side splashes. Grease chute is fully welded to stop grease migration. One 27,000 BTU/hr. "U" shaped aluminized steel burner and mechanical snap action thermostat for each 12" of griddle width. Chrome thermostat knob guards. Temperature adjusts from 200° to 550°F. One pilot safety for every two burners. 3½" wide stainless steel grease trough. ¾" rear gas connection and gas pressure regulator.

#### **Exterior Dimensions:**

\_\_\_\_\_"w x 33" d x 15½" h on 4" legs.

CSA design certified. NSF listed.

SPECIFY TYPE OF GAS WHEN ORDERING. SPECIFY ALTITUDE WHEN ABOVE 3,999 FT.

☐ MSA	24	24" w x 24" d griddle plate
□ MSA	36	36" w x 24" d griddle plate
☐ MSA	48	48" w x 24" d griddle plate
☐ MSA	60	60" w x 24" d griddle plate
☐ MSA	72	72" w x 24" d griddle plate

#### **STANDARD FEATURES**

- Stainless steel front, sides and front top ledge with "Cool Bullnose" design.
- Fully welded stainless and aluminized steel chassis frame.
- 11" low profile cooking height on 4" adjustable legs.
- 1" thick polished steel griddle plate with 12 gauge, 4" stainless steel back and tapered side splashes.
- Spatula wide 3½" grease gutter and chute is fully welded for easier cleaning and to stop grease migration.
- One 27,000 BTU/hr. "U" shaped aluminized steel burner for every 12" of griddle width.
- One embedded snap action thermostat per burner with temperature adjust from 200°F to 550°F on Steel or Chrome plate. Temperature adjusts from 200°F to 450°F on Rapid Recovery™ plate.
- Large 6 quart stainless steel grease drawer (2 drawers on 60" and 72" models).
- Heavy duty chromed thermostat knob guards.
- One pilot safety valve for every two burners. Safety will completely shut off gas to pilot and burners if pilot extinguishes.
- Manual ignition.
- Bottom heat shields.
- ¾" rear gas connection and gas pressure regulator.
- One year limited parts and labor warranty.

#### **OPTIONAL FEATURES**

orily).
Rapid Recovery <sup>™</sup> griddle plate (200-450°F controls, 48" maximum length).
Hexavalent chrome plated cooking surface.
30" deep plate (steel plate only).
Stainless steel stand with marine edges and casters.
Cutting board, condiment rail, plate rail and banking strip accessories.

☐ Full or partially grooved griddle plate (steel or chrome plate



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602



### MSA SERIES HEAVY DUTY GAS GRIDDLES


#### **INSTALLATION INSTRUCTIONS**


- A gas pressure regulator supplied with the unit must be installed; Natural Gas 4.0" (102 mm) W.C. Propane Gas 10.0" (254 mm) W.C.
- All models require a 6" (152 mm) clearance at both sides and rear adjacent to combustible and 0" from non-combustible constructions. All models require a 4" (102mm) bottom clearance and must be installed with minimum 4" legs.
- 3. These units are manufactured for installation in accordance with ANSI/NFPA-70, National Electrical code.
  - An adequate ventilation system is required for Commercial Cooking Equipment (NFPA No. 96). Information may be obtained by writing to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02169.
- 4. These units are manufactured for installation in accordance with National Fuel Gas Code, ANSI-Z223.1/NFPA #54 (latest edition). Copies may be obtained from The American Gas Association, Accredited Standards Committee Z223 @ 400 N. Capital St. NW, Washington, DC 20001, or the Secretary Standards Council, NFPA, 1 Batterymarch Park, Quincy, MA 02169-7471.


#### NOTE: In The Commonwealth of Massachusetts

All gas appliances vented through ventilation hood or exhaust system equipped with a damper or with a power means of exhaust shall comply with 248 CMR.

5. This appliance is manufactured for commercial installation only and is not intended for home use.







MODEL	WIDTH	DEPTH	OVERALL HEIGHT*	WORKING HEIGHT*	NO. OF BURNERS	TOTAL BTU/HR.	NO. OF DRAWERS	APPROX. SHIP. WT.
MSA24	24"	311/2"	151/4"	111/8"	2	54,000	1	285 lbs./129 kg.
MSA36	36"	311/2"	151/4"	111/8"	3	81,000	1	400 lbs./181 kg.
MSA48	48"	311/2"	151/4"	111/8"	4	108,000	1	480 lbs./218 kg.
MSA60	60"	311/2"	151/4"	111/8"	5	135,000	2	650 lbs./295 kg.
MSA72	72"	311/2"	151/4"	111/8"	6	162,000	2	790 lbs./358 kg.

<sup>\*</sup>These are nominal dimensions and can vary by +1.75" with adjustable legs.



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

#### ICB Twin SH, Stainless

Height: 32.9" Width: 21.9" Depth: 23.0" (83.6cm) (55.6cm) (58.4cm)





- Sleek modernized design language, with rounded angles on the corners and trunk
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with six brew buttons and three batch sizes
- Energy-saver mode reduces tank temperature during idle periods
- The exclusive Peak Extraction® Sprayhead provides improved uniformity of extraction and greater resistance to limescale buildup.
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- USB programming capable
- Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.
- New Soft Heat® servers [sold separately] are ergonomic, lighter weight, energy
  efficient and now offer programmable recipe/batch based holding times and
  temperatures, alerting staff when freshness has expired or server is empty
- PROP 65 Warning Decal included in packaging with equipment

#### Agency:







Additional Features

#### **Specifications**

Product #: 51200.0102 Funnel: Black Plastic

Water Access: Plumbed Faucet: Side

Interface: Wireless Legs: 4" Stainless Steel Legs

Finish: Stainless

#### **Electrical & Capacity**

120/208	28	6000	Yes/		280	60°F (15.5°C)	1	3 3	<mark>60</mark>
Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H <sup>2</sup> O Temp.	Phase	# Wires plus Ground	Hertz

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

#### Plumbing Requirements


PSI kPa		kPa	Fitting Supplied	Water Flow Required (GPM)					
	20-90	138-621	3/8" Male Flare Fitting	1.00					

#### CAD Drawings

2D	Revit	KLC
•		

WARNING: This product can expose you to chemicals including Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov





Unit			Shipping					
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	32.9 in.	21.9 in.	23.0 in.	37.5 in.	26.1 in.	28.4 in.	78.400 lbs	16.087 ft <sup>3</sup>
Metric	83.6 cm	55.6 cm	58.4 cm	95.3 cm	66.4 cm	72.1 cm	35.562 kgs	0.456 m³



#### Related Products & Accessories: ICB Twin SH, Stainless (51200.0102)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000



1SH STAND, 120V INF **SERIES** 

Product #: 27825.0200



2SH STAND, 120V INF SERIES

Product #: 27875.0200



EQHP-10L

Product #: 39000.0001





KIT, DRIP TRAY INF TWIN SH

Product #: 53452.0000



KIT, DRIP TRAY SINGLE

Product #: 53452.0001



COFFEE BLK-CLEARED

Product #: 53463.0038



Product #: 56000.0001





Product #: 56000.0024



Product #: 56000.0027



CARTRIDGE, WQ-55(2)5L

Product #: 56000.0101



Product #: 56000.0104







#### Serving & Holding Options: ICB Twin SH, Stainless(51200.0102)





Project:	ch	ıam	p
roject:			•

n	nr	ον	<i>,</i> ~ I	
P	ИI	υv	'ai	

Qty:


Item#: 600HS17SP





## Regency 17" x 15" Wall-Mounted Hand Sink with Gooseneck Faucet and Side Splash

#600HS17SP







#### **Technical Data**

Length	17 Inches
Width	15 Inches
Height	13 1/2 Inches
Bowl Depth	5 1/2 Inches
Faucet Height	8 Inches
Bowl Front to Back	10 Inches
Bowl Left to Right	14 Inches
Faucet Centers	4 Inches
Flow Rate	2 GPM
Gauge	20 Gauge

#### **Features**

- 8" gooseneck faucet and 1 1/2" IPS drain baskets included
- 18 gauge type 304 stainless steel side splashes and a wall-mounted clip
- 20 gauge type 304 stainless steel
- Holes punched on 4" centers
- Single 14" x 10" x 5 1/2" bowl and 8" backsplash


#### **Certifications**



#### **Technical Data**

Features	Massachusetts Accepted Plumbing Product NSF Listed Side Splashes
Included	Faucet
Installation Type	Wall Mounted
Material	Stainless Steel
Number of Compartments	1 Compartment
Number of Faucets	1 Faucets
Spout Type	Gooseneck
Stainless Steel Type	Type 304
Туре	Hand Sinks

#### **Plan View**



#### **Notes & Details**

Keep your restaurant up to code without sacrificing space with this space saver hand sink with side splash. Suitable for wall or surface mounting, this sink comes standard with a single  $14" \times 10" \times 5 \times 1/2"$  bowl and 8" high back and side splashes. Additionally, this hand sink has two holes punched on 4" centers to accept its included Regency 8" gooseneck faucet.

This sink offers an economical, 20 gauge type 304 stainless steel construction along its top, bowl, and backspash, in addition to 18 gauge type 304 stainless steel side splashes and a wall-mounted clip. It comes standard with a  $1\,1/2$ " IPS drain basket.

MARNING: This product can expose you to chemicals including Lead and Nickel, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.

#### ULTRA NX, 120V BLK/SST

Height: 32.4" Width: 16.6" Depth: 26.4" (82.3cm) (42.2cm) (67.1cm)





3 unit

- Patented beverage monitoring technology and reversing auger design ensure consistent, great tasting frozen beverages
- Enhanced auger drive system and seal design for long-lasting, reliable performance
- New leak capture feature helps reduce service costs and clean-up time
- BUNNlink compatible
- Two large product hoppers hold 3 gallons (11.4L) each to maximize serving capacity
- User interface communicates need for cleaning and maintenance
- LED lighted merchandisers in hopper lids bring high visibility to front- of-house applications
- Low-product alert to minimize product outages
- Quick defrost feature to ensure beverage quality and maximize uptime
- Slide in hopper graphics allow quick and easy changes
- USB for easy software updates and downloads
- Optional faucet available for dispensing chilled (non-frozen) products
- Sanitation listings NSF 18 and NSF 6 (Dairy)
- R290 all-natural refrigerant provides a sustainable platform with extremely low Global Warming Potential

Additional Features

#### Agency:





#### Specifications

Product #: 58000.0015 Hoppers: Two
Autofill: None Refrigerant: R290

Flavors: 2 Flavors

Dispense: Pull & Hold

Finish: Stainless/Black

Handle: Extended Handle

#### **Electrical & Capacity**

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H <sup>2</sup> O Temp.	Phase	# Wires plus Ground	Hertz
120	12	1440	Yes	NEMA 5-15P	-	60°F (15.5°C)	1	2	60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

#### Plumbing Requirements


PSI	kPa	Fitting Supplied	Water Flow Required (GPM)
-	-	-	-


#### **CAD Drawings**


2D	Revit	KLC
•		


**M** WARNING:











		Unit				Shipping		
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	32.4 in.	16.6 in.	26.4 in.	43.9 in.	20.5 in.	25.9 in.	110.000 lbs	13.468 ft <sup>3</sup>
Metric	82.3 cm	42.2 cm	67.1 cm	111.4 cm	52.1 cm	65.7 cm	49.896 kgs	0.381 m³



#### Related Products & Accessories: ULTRA NX, 120V BLK/SST(58000.0015)

FILTER, AIR 13.562 X HANDLE, FAUCET KIT, FAUCET SEALS -KIT, LID LOCK ULTRA KIT, HDL LOCK ULTRA-2 11.062 MAGNETIC ULTRA BLK NYLON AM **ULTRA-2 SEALS** NX BLACK Product #: 28122.0002 Product #: 32265.0003 Product #: 32268.1000 Product #: 34996.0004 Product #: 34996.0010 HANDLE, EXTENDED DRIP TRAY ASSY, BASE KIT, LID & HDL LOCK KIT, LID LOCK ULTRA-2 KIT,LID & HDL LOCK ULTRA NX BLK NYLON **ULTRA NX BLK** SST CLR W/ NX LID ULTRA-2 SST CLR W/ NX **ULTRA NX - BLK** AM Product #: 57659.1001 Product #: 34996.0012 Product #: 34996.0013 Product #: 34996.0014 Product #: 44614.0004 DRIP TRAY COVER, VALVE, FAUCET LIQUID ULTRA NX - BLK **BLACK ULTRA NX** 



Product #: 57660.0001

Product #: 57793.0001

Serving & Holding	Options: ULTRA NX,	120V BLK/SST(58000.0015)
-------------------	--------------------	--------------------------

\*Serving and Holding selections are currently unavailable. Please contact your sales representative to find out more information.\*



# 

## Two-section Reach-in Refrigerator


Model #: MSD-2DR-BAL-X

## Product Details

- Eco-friendly R290 refrigerant
- Stainless steel exterior, aluminum interior and back
- Temperature range: 33-41°F
- Self-closing doors with 90 degree stay-open feature & locks
- Adjustable heavy-duty coated shelves
- Electronic control system makes it easy to adjust temperature set point and defrost frequency
- Condenser coil is easy to access for cleaning and maintenance
- Factory-installed 4" swivel casters
- · Safety-shielded incandescent interior lighting

Not suitable for installation in non-commercial or residential applications.

## Plan View



## Certifications



## Specifications

Model	Doors	Shelves	Cabinet Dims (in)			HP	Voltage	Amp	NEMA	Cord	Crated
		Sherves	Width	Depth	Height	HP	vollage	AIIIÞ	Plug	Length (ft)	Weight (lbs)
MSD-2DR-BAL-X	2	6	54"	32.25"	82.5"	1/4+	115/60/1	3.8	5-15P	10 ft.	513 lbs.

MOTAK reserves the right to make changes to the design or specifications without prior notice.



# 

## Two-section Reach-in Refrigerator


Model #: MSD-2DR-BAL-X

## Product Details

- Eco-friendly R290 refrigerant
- Stainless steel exterior, aluminum interior and back
- Temperature range: 33-41°F
- Self-closing doors with 90 degree stay-open feature & locks
- Adjustable heavy-duty coated shelves
- Electronic control system makes it easy to adjust temperature set point and defrost frequency
- Condenser coil is easy to access for cleaning and maintenance
- Factory-installed 4" swivel casters
- · Safety-shielded incandescent interior lighting

Not suitable for installation in non-commercial or residential applications.

## Plan View



## Certifications



## Specifications

Model	Doors	Shelves	Cabinet Dims (in)			HP	Voltage	Amp	NEMA	Cord	Crated
		Sherves	Width	Depth	Height	HP	vollage	AIIIÞ	Plug	Length (ft)	Weight (lbs)
MSD-2DR-BAL-X	2	6	54"	32.25"	82.5"	1/4+	115/60/1	3.8	5-15P	10 ft.	513 lbs.

MOTAK reserves the right to make changes to the design or specifications without prior notice.




## **ER1A-FS/ER2A-FS 29**

ER1A-FS/ER2A-FS 08/17/20 Item # 13563

One and Two Section Full Stainless Refrigerator

WxDxH 27" x 29.63" x 81.63" (including 4" casters)

WxDxH 54.38s" x 29.63" x 81.63" (including 4" casters)





















Dimensions / Capacity	One Section ER1A-FS	Two Section ER2A-FS
Interior Storage Capacity (CF) (AHAM)	17.8 ft <sup>3</sup>	38.61 ft <sup>3</sup>
Overall Width x Depth	27" x 29.63"	54.38" x 29.63"
Height (including 4" casters)	81.63"	81.63"
Door Opening (W x H)	22.25" x 52.1"	22.9" x 52.1"
Depth with Door Open at 90°	55.38"	55.38"
Adjustable Shelves	3	6
Shelf Dimensions (W x D)	21.5" x 23.1"	24.3" x 21.7"
Crated Shipping Weight	279 lbs	523 lbs
Crated Length x Depth x Height	31.5" x 28.75" x 84"	58" x 31.5" x 84"
Electrical / Refrigeration	One Section ER1A-FS	Two Section ER2A-FS
Voltage	115/60/1	115/60/1
HACR Breaker	15.0 Amps	15.0 Amps
Electrical Connection (NEMA)	5-15P 🚹	5-15P 🕦
Voltage Range	103-127	103-127
Ambient Temp. Range	45° to 100°F	45° to 100°F
Control Setpoint Range	33° to 39°F	33° to 39°F
Amperage	2	4.3
Energy Consumption (kWh/day) @ASHRAE	1.06	2.1
Appox. Nominal Compres. BTU/HR (HP)	1960(1/5HP)	4291(1/3HP)
Refrigerant / Charge Amount (oz.)	R290 / (2.3oz)	R290 / (3.7oz)

#### **Options**

Additional epoxy shelves

- ☐ HS-5511(1 section)
- ☐ HS-5512 (2 section)


#### Warranty


\* 2 Year - Parts and Labor on entire machine. 5 Year - Parts on Compressor Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

#### **Features**


- · Energy efficient interior LED light
- Environmentally friendly R290 hydrocarbon refrigerant
- Solid state digital controller with temperature alarms and LED display (Fahrenheit or Celsius)
- Self-closing door(s) is field reversible
- Stainless steel exterior door(s) come standard with lock(s)
- Stainless steel interior floor with aluminum sides, rear, and top
- · Time initiated automatic defrost
- Energy efficient heated condensate removal
- Heavy duty grey epoxy coated shelves are adjustable in 1/2" increments; 3 per section. 105 lbs. capacity
- Aluminum shelf supports
- Standard with 4" casters (two with brakes)
- 9 ft. cord and plug
- Container Qty:

ER1A-FS: 47 ER2A-FS: 28 FRONT VIEW SIDE VIEW





#### **PLAN VIEW**





## $KMD-705M_J(Z)$

0

#### MODULAR CRESCENT CUBER

WxDxH 30" x 24" x 26"



#### KMD-705MAJ

Air-Cooled model shown on optional bin B-500

> KMD-705MWJ Water-Cooled

KMD-705MRJZ Remote Air-Cooled

#### KM*Edge*™ Cube Dimensions\*



\* approximate size in inches, image not to scale















Project:

31

- Optimized for use with ice and beverage dispenser
- Simple one-hour cleaning CLEAN
- Factory-installed ultrasonic bin control can be adjusted on site
- Durable construction with fewer parts
- · Self-diagnostic programming automatically adjusts to changing conditions
- . Snap fit parts for easy cleaning
- · Stainless steel double-sided evaporator
- CycleSaver<sup>™</sup> design cruswer
- EverCheck™ alert system
- Removable air filters (air-cooled model only)
- R-404A Refrigerant

#### **Available on Bins:**

B-250SF B-700SF B-1150SS B-1650SS\* B-500SF B-800SF B-1300SS **DB-200H** BD-500SF B-900SF B-1500SS\*\* DM-200B

Top kit may be required. See Bin Spec Sheets. \*Two unit application only.

3 Year Parts & Labor on entire machine. 5 Year Parts & Labor on Evaporator. 5 Year Parts on Compressor; air-cooled condenser coil. Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Shipping: (LxWxH) 33.75" x 33.25" X 32" Volume: 20.78ft3

Mater   KMD-705MWJ   773   720   22.5   93   3.8   20A   13.0A   115V/60/1   3   9,500   1   b. 11.3 oz.   180 /			ICE PRODUCTION		WATER USAGE		ELECTRICAL							
Water         KMD-705MWJ         773         720         22.5         93         3.8         20A         13.0A         115V/60/1         3         9,500         1 lb. 11.3 oz.         180 /	Condense	r Model	Lbs. per	24 hours	Gal. per 100 lbs.	Gal. per 100 lbs.	per 100 lbs.	Max. Fuse		Voltage	Wires	Rejection		Net / Ship Weight (Ibs.)
	Air	KMD-705MAJ	721	620	22.0	N/A	4.75	20A	14.3A	115V/60/1	3	9,400	2 lb. 12.1 oz.	180 / 200
0.11, 40.0	Water	KMD-705MWJ	773	720	22.5	93	3.8	20A	13.0A	115V/60/1	3	9,500	1 lb. 11.3 oz.	180 / 200
Remote KMD-705MRJZ 727 670 21.0 N/A 4.40 20A 13.7A 115V/60/1 3 9,500 6 ID. 12.3 0Z. 180 /	Remote	KMD-705MRJZ	727	670	21.0	N/A	4.40	20A	13.7A	115V/60/1	3	9,500	6 lb. 12.3 oz. 10 lb. 11.1 oz.†	180 / 200

† (with condenser)

#### Operating Limits

- · Ambient Temp Range 45 - 100°F Water Temp Range 45 - 90°F
- Water Pressure 10 - 113 PSIG 104 - 127V Voltage Range
- If GFCI is required, a GFCI breaker MUST be used in lieu of GFCI receptacle

#### Service · Panels easily removed and all components

- accessible for service.
- · Removable/cleanable air filters. (Air-cooled model only)
- . Allow 6" (15 cm) clearance at rear, sides, and top for proper air circulation and ease of maintenance/service.

#### Plumbina


- Icemaker Water Supply Line: Min. 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Min. 3/4" Nominal ID Hard Pipe or Equivalent Water-Cooled Model (Lines Must Be Independent of Icemaker)
- Condenser Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Condenser Drain/Return Line: Minimum 1/4" Nominal ID Hard Pipe (open drain system) or Copper Water Tubing (closed loop system) or Equivalent

#### Accessories

- HS-2148, DB Top Kit
- HS-5562, Remote Monitoring System
- HS-5283, EcO Ice Filter
- . HS-5734, Side-Breathing Kit
- H9320-51, Single Water Filter Kit

Hoshizaki reserves the right to change specifications without notice.





SF Bins 03/19/21 Item # 13163

#### SF - Stainless Steel Finish













#### **Features**

- Protected by H-GUARD Plus
  Antimicrobial Agent H-GUARD.
- Polyethylene bin liner for sanitary storage
- Sturdy construction for side-by-side or stacked ice machine installation
- Ice storage capacity from 250 lbs. up to 900 lbs.
- Both surfaces are designed for easy cleaning
- · Long lasting attractive appearance
- Foamed-in-place polyurethane insulation, in all bin walls and bottom, provides dependable ice storage
- H-GUARD Plus Antimicrobial adds extra protection to the ice scoop (included)

#### SF - Stainless Steel Finish

#### **BD Bins**

 Fit 24" - 24 1/2" deep ice machine without top kit extension

#### Warranty

2 Year Parts & Labor (Production prior to January 2012) 3 Year Parts & Labor (Production January 2012 and after) Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Model Number	Exterior Dimensions W x D x H*	Interior Dimensions W x D x H	Application Storage Capacity	Cubic Volume	Shipping Dimensions L x W x H	Shipping Weight (lbs.)
B-250SF	30" x 32.3" x 33.4"	27" x 27.7" x 23.7"	250 lbs.	10.30 ft <sup>3</sup>	35" x 32" x 32"	_
B-300SF	22" x 32.3" x 46"	19" x 27.7" x 37.6"	300 lbs.	11.51 ft <sup>3</sup>	35" x 24" x 45"	125
BD-300SF	22" x 32.3" x 46"	19" x 27.7" x 37.6"	300 lbs.	11.51 ft³	35" x 24" x 45"	130
B-500SF	30" x 32.3" x 46"	27" x 27.7" x 37.6"	500 lbs.	16.33 ft <sup>3</sup>	35" x 32" x 45"	140
BD-500SF	30" x 32.3" x 46"	27" x 27.7" x 37.6"	500 lbs.	16.33 ft <sup>3</sup>	35" x 32" x 45"	140
B-700SF	44" x 32.3" x 46"	41" x 27.7" x 37.6"	700 lbs.	24.77 ft <sup>3</sup>	46" x 35" x 45"	175
B-800SF	48" x 32.3" x 46"	45" x 27.7" x 37.6"	800 lbs.	26.90 ft <sup>3</sup>	50.25" x 35" x 45"	185
B-900SF	52" x 32.3" x 46"	49" x 27.7" x 37.6"	900 lbs.	29.59 ft <sup>3</sup>	54.5" x 35" x 45"	195


<sup>\*</sup>Height includes 6" legs

<sup>†</sup> Capacity based on volume x 30 lb/ft3 average density of ice.

## **Ice Machine Model Application**

			-				
	22" Width KM-350M KM-520M KM-660M F-450M F-801M F-1002M	22" Width KMD-410M <sup>†</sup> KMS-822M FD-650M-C <sup>†</sup> FD-1002M-C	30" Width KM-901M KM-1340M KM-1601M KML Series F-1501M F-2001	30" Width KMD-460M‡ KMD-530M‡ KMD-860M‡ KMS-1402M* KMS-2000M*	44" Width 2 KM-350M 2 KM-520M 2 KM-660M IM-500S 2 F-450M 2 F-801M 2 F-1002M	<b>44" Width</b> 2 KMD-410M 2 FD-650M-C 2 FD-1002M-C	48" Width KM-1301S KM-1400S KM-1601S KM-1900S KM-2200S KM-2600S
Bins B-300SF DB-130H	 (DB-130H - KMD only)	NEED HS-5424 HS-2153 (KMD-410 on B-300 only)	N/A	N/A	N/A	N/A	N/A
Bins B-250SF B-500SF	NEED HS-2033	NEED HS-2033 & HS-2129	_	NEED HS-2129	N/A	N/A	N/A
Bins B-700SF	NEED HS-2035	NEED HS-2035 & HS-2130	NEED HS-2034	NEED HS-2130 & HS-2034	_	NEED HS-2130 (KMD-410 does not apply)	N/A
<b>Bins</b> B-800SF	NEED HS-2035 & HS-2032	NEED HS-2035, HS-2032 & HS-2131	NEED HS-2034 & HS-2032	NEED HS-2131, HS-2034 & 2032	NEED HS-2032	NEED HS-2032 & HS-2131	_
<b>Bins</b> B-900SF	NEED HS-2035 & HS-2033	NEED HS-2035, HS-2033 & HS-2132	NEED HS-2035	NEED HS-2132 & HS-2035	NEED HS-2033	NEED HS-2033 & HS-2132	NEED HS-2032
<b>Bins</b> DB-200H DM-200B	NEED HS-2036 (KM units only)	N/A	(KML only)	N/A	N/A	N/A	N/A





**Ice Drop Area** 

#### No top kit necesary N/A Combination of ice maker and bin is not possible

BD Bins fit 24" - 24 1/2" deep ice machine without Top Kit extension.

†BD-300SF: KMD-410M, KMS-822M, FD-650M-C, FD-1002M-C

**BD-500SF:** KMD-460M, KMD-530, KMD-860

\* Any KMS or FD on bin need Top Kit Extension:

- HS-2129 - for use with B-500 bins

- HS-2130 - for use with B-700 bins

- HS-2131 - for use with B-800 bins

- HS-2132 - for use with B-900 bins

HS-2032 - 4" ABS Top Kit

HS-2033 - 8" ABS Top Kit

HS-2034 - 14" ABS Top Kit

HS-2035 - 22" ABS Top Kit

HS-2036 - (2) 4" ABS Top Kits HS-2066 - Seismic Kit for SD 500 Stands

HS-2071 - Anchored Leg Kit SD 500 Stands

HS-2111 - 11.3" x 26.2" Stainless

Cover/Separator

HS-2148 - 30" x 3.1" Stainless Cover

HS-2153 - KMD-410 on B-300 bin

HS-2160 - 2 KM-901M

# 281/2









B-250SF, B/BD-500SF B-700SF, B-800SF B-900SF

SF Bins 03/19/21 Item # 13163













# **Features**

Item #: \_ Project: Qty:\_\_\_\_

ΔΙΔ#-

32

bd-500sf

- Protected by H-GUARD Plus
  Antimicrobial Agent H-GUARD
- Polyethylene bin liner for sanitary storage
- Sturdy construction for side-by-side or stacked ice machine installation
- Ice storage capacity from 250 lbs. up to 900 lbs.
- Both surfaces are designed for easy cleaning
- · Long lasting attractive appearance
- Foamed-in-place polyurethane insulation, in all bin walls and bottom, provides dependable ice storage
- H-GUARD Plus Antimicrobial adds extra protection to the ice scoop (included)

## SF - Stainless Steel Finish

## **BD Bins**

 Fit 24" - 24 1/2" deep ice machine without top kit extension

#### Warranty

2 Year Parts & Labor (Production prior to January 2012) 3 Year Parts & Labor (Production January 2012 and after) Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

Model Number	Exterior Dimensions W x D x H*	Interior Dimensions W x D x H	Application Storage Capacity	Cubic Volume	Shipping Dimensions L x W x H	Shipping Weight (lbs.)
B-250SF	30" x 32.3" x 33.4"	27" x 27.7" x 23.7"	250 lbs.	10.30 ft <sup>3</sup>	35" x 32" x 32"	_
B-300SF	22" x 32.3" x 46"	19" x 27.7" x 37.6"	300 lbs.	11.51 ft <sup>3</sup>	35" x 24" x 45"	125
BD-300SF	22" x 32.3" x 46"	19" x 27.7" x 37.6"	300 lbs.	11.51 ft³	35" x 24" x 45"	130
B-500SF	30" x 32.3" x 46"	27" x 27.7" x 37.6"	500 lbs.	16.33 ft <sup>3</sup>	35" x 32" x 45"	140
BD-500SF	30" x 32.3" x 46"	27" x 27.7" x 37.6"	500 lbs.	16.33 ft <sup>3</sup>	35" x 32" x 45"	140
B-700SF	44" x 32.3" x 46"	41" x 27.7" x 37.6"	700 lbs.	24.77 ft <sup>3</sup>	46" x 35" x 45"	175
B-800SF	48" x 32.3" x 46"	45" x 27.7" x 37.6"	800 lbs.	26.90 ft <sup>3</sup>	50.25" x 35" x 45"	185
B-900SF	52" x 32.3" x 46"	49" x 27.7" x 37.6"	900 lbs.	29.59 ft <sup>3</sup>	54.5" x 35" x 45"	195


<sup>\*</sup>Height includes 6" legs

<sup>†</sup> Capacity based on volume x 30 lb/ft3 average density of ice.

## **Ice Machine Model Application**

			-				
	22" Width KM-350M KM-520M KM-660M F-450M F-801M F-1002M	22" Width KMD-410M <sup>†</sup> KMS-822M FD-650M-C <sup>†</sup> FD-1002M-C	30" Width KM-901M KM-1340M KM-1601M KML Series F-1501M F-2001	30" Width KMD-460M‡ KMD-530M‡ KMD-860M‡ KMS-1402M* KMS-2000M*	44" Width 2 KM-350M 2 KM-520M 2 KM-660M IM-500S 2 F-450M 2 F-801M 2 F-1002M	<b>44" Width</b> 2 KMD-410M 2 FD-650M-C 2 FD-1002M-C	48" Width KM-1301S KM-1400S KM-1601S KM-1900S KM-2200S KM-2600S
Bins B-300SF DB-130H	 (DB-130H - KMD only)	NEED HS-5424 HS-2153 (KMD-410 on B-300 only)	N/A	N/A	N/A	N/A	N/A
Bins B-250SF B-500SF	NEED HS-2033	NEED HS-2033 & HS-2129	_	NEED HS-2129	N/A	N/A	N/A
Bins B-700SF	NEED HS-2035	NEED HS-2035 & HS-2130	NEED HS-2034	NEED HS-2130 & HS-2034	_	NEED HS-2130 (KMD-410 does not apply)	N/A
<b>Bins</b> B-800SF	NEED HS-2035 & HS-2032	NEED HS-2035, HS-2032 & HS-2131	NEED HS-2034 & HS-2032	NEED HS-2131, HS-2034 & 2032	NEED HS-2032	NEED HS-2032 & HS-2131	_
<b>Bins</b> B-900SF	NEED HS-2035 & HS-2033	NEED HS-2035, HS-2033 & HS-2132	NEED HS-2035	NEED HS-2132 & HS-2035	NEED HS-2033	NEED HS-2033 & HS-2132	NEED HS-2032
<b>Bins</b> DB-200H DM-200B	NEED HS-2036 (KM units only)	N/A	(KML only)	N/A	N/A	N/A	N/A





**Ice Drop Area** 

#### No top kit necesary N/A Combination of ice maker and bin is not possible

BD Bins fit 24" - 24 1/2" deep ice machine without Top Kit extension.

†BD-300SF: KMD-410M, KMS-822M, FD-650M-C, FD-1002M-C

**BD-500SF:** KMD-460M, KMD-530, KMD-860

\* Any KMS or FD on bin need Top Kit Extension:

- HS-2129 - for use with B-500 bins

- HS-2130 - for use with B-700 bins

- HS-2131 - for use with B-800 bins

- HS-2132 - for use with B-900 bins

HS-2032 - 4" ABS Top Kit

HS-2033 - 8" ABS Top Kit

HS-2034 - 14" ABS Top Kit

HS-2035 - 22" ABS Top Kit

HS-2036 - (2) 4" ABS Top Kits HS-2066 - Seismic Kit for SD 500 Stands

HS-2071 - Anchored Leg Kit SD 500 Stands

HS-2111 - 11.3" x 26.2" Stainless

Cover/Separator

HS-2148 - 30" x 3.1" Stainless Cover

HS-2153 - KMD-410 on B-300 bin

HS-2160 - 2 KM-901M

# 281/2









B-250SF, B/BD-500SF B-700SF, B-800SF B-900SF

# 750-S

## Low-Temperature Hot-Food Holding Cabinet

Keeping food that has been cooked to perfection hot and fresh until the moment it is served demands the gentle precision of Alto-Shaam's exclusive Halo Heat® technology. With controlled temperatures and a closed environment free from forced air, harsh heating elements, and added humidity, food is kept warm and flavorful, just as intended.

## **Standard features**

- Simple and intuitive pushbutton control that commands all appliance functions with easily identifiable icons
- Halo Heat—a controlled, uniform heat source that gently surrounds food for better appearance, taste, and longer holding life
- Stainless steel interior resists corrosion
- Digital control senses temperature drops faster, providing quick heat recovery time
- Close temperature tolerance and even heat application maintain ideal serving temperature throughout the cabinet
- Antimicrobial handle retards the growth of illness-causing pathogens
- Door venting holds crispy food better

## Deluxe control option (select one)

Deluxe control features SureTemp™ heat recovery system. SureTemp™ reacts immediately to compensate for any loss of heat whenever the door is opened.

- ☐ Deluxe control (A)
- ☐ Deluxe control with probe (A)
- ☐ Deluxe control with six (6) independent shelf timers (B)
- ☐ Deluxe control with probe and shelf timers (B)











Ten full-size or GN 1/1 pans 2-1/2" (65mm) deep Six full-size or GN 1/1 pans 4" (100mm) deep

Four full-size or GN 1/1 pans 6" [150mm] deep

Six full-size sheet pans (on wire shelves only)

Two side racks with eleven pan positions spaced on 1-3/8" (35mm) centers

120 lb (54 kg) product maximum

100 qt (95 L) volume maximum

Includes three shelves. Additional shelves required for maximum capacity. See pan capacities guide















## Configurations (select one)

#### **Door choices**

- ☐ Solid door, standard
- ☐ Window door, optional

#### **Door swing**

- ☐ Right hinged, standard
- ☐ Left hinged, optional

## Cabinet choices

- ☐ Reach-in, standard
- ☐ Pass-through, optional—note: pass-through cabinets cannot have doors hinged on the same side

## **Electrical**

- □ 120V, 1 ph
- □ 230V, 1 ph
- □ 208-240V, 1 ph

## Accessories (select all that apply)

- ☐ Bumper, full perimeter (5010371)—not available with 2-1/2" casters
- ☐ Handle, push/pull [55662]
- □ Door lock with key (LK-22567)
- ☐ Security panel with lock—requires door lock (LK-22567)[5013936]
- ☐ Drip tray—external (5010391)
- ☐ Pan grid, wire—18" x 16" (457mm x 406mm) pan insert (PN-2115)
- ☐ Legs, 6" (152mm), flanged—set of four (5011149)
- ☐ Carving holder, prime rib (HL-2635)
- ☐ Carving holder, steamship (cafeteria) round (4459)
- ☐ Drip pan with drain, 1-11/16" (43mm) deep (14831)
- ☐ Drip pan without drain, 1-5/8" (41mm) deep (1014684)

## Casters, stem-2 rigid, 2 swivel w/ brake

- □ 5" [127mm] [5004862]
- □ 3-1/2" (89mm) (5008017)
- □ 2-1/2" [64mm][5008022]—standard

## **Shelves**

- ☐ Chrome wire, reach-in [SH-2105]
- ☐ Chrome wire, pass-through (SH-2327)
- ☐ Stainless steel, flat wire, reach-in [SH-2324]
- ☐ Stainless steel, rib rack (SH-2743)


## Stacking hardware

- ☐ Over or under 750-TH, 767-SK, 750-S-Series [5004864]
- ☐ Under CTX4-10 Combitherm®

# 750-S

## **DIMENSIONS**







## Model 750-S

Exterior (H x W x D)

31-7/8" x 26-5/8" x 31-3/8" [809mm x 676mm x 797mm]

#### **Pass-Through Exterior**

31-7/8" x 26-3/4" x 33-13/16" [809mm x 679mm x 858mm]

## Ship Dimensions (L x W x H)\*

750-S 35" x 35" x 41" (889mm x 889mm x 1041mm)

\*Domestic ground shipping information. Contact factory for export weight and dimensions.

## Interior (H x W x D)

20" x 21-15/16" x 26-1/2" (507mm x 556mm x 673mm)

## **Net Weight**

157 lb (71 kg)

## Ship Weight\*

228 lb (103 kg)



• Appliance must be installed level.

- Appliance must not be installed in any area where it may be affected by steam, grease, dripping water, extreme temperatures, or any other severely adverse conditions.
- Appliances with casters and no cord or plug must be secured to the building structure with a flexible connector. Not factory supplied.



Тор: 2" (51mm) Left: 1" (25mm) 1" (25mm) Right:

CLEARANCE

Back: 3" (76mm)



**CONTACT US** 

	750-S	V	Ph	Hz	Α	kW	Cord & Plug	
	120V	120	1	50/60	9.0	1.1	NEMA 5-15p 15A-125V plug	
,	208-240V	208	1	50/60	3.9	.81	NEMA 6-15p	
		240	1	50/60	4.5	1.1	15A-250V plug (U.S.A. only)	· /
	230V	230	1	50/60	4.3	1.0	Plugs rated 250V CEE 7/7	
							CH2-16p	
							BS 1363 (U.K. only)	
							AS/NZS 3112	('\ <u>\</u>



11	Heat of	f rejection	
1 72	750-S	Heat Gain	Heat Gain
		qs, BTU/hr	qs, kW
HEAT		БТО/П	KVV
		223	0.07

W164 N9221 Water Street | Menomonee Falls, Wisconsin 53051 | U.S.A. Phone: 262.251.3800 | 800.558.8744 U.S.A./Canada | Fax: 262.251.7067 | alto-shaam.com

UL

ALTO-SHAAM.

Drive foodservice profits with display cases from Alto-Shaam. LED lighting and mirrored back doors enhance food appearance and boost impulse sales. To not only look but taste great, food is held at optimal, precise temperatures with Halo Heat® technology and top ceramic heaters. Multiple access points and a removable back work shelf makes unloading and loading food effortless for employees. Reduce labor and cleaning time with removable back doors and side panels, and a lifting glass front.

# ED3-72 with Legs

# ED3-72 w



ED3(SYS)-72 With Stationary Base

## Standard features

- Fanless, waterless Halo Heat technology
- Overhead LED lighting
- Adjustable thermostats 1-10 per heat zone for top and bottom heat
- Ceramic top heaters
- Operator-side work shelf and cutting board
- Sliding back doors with mirrored glass
- Tempered glass front with self-supported lifting mechanism
- Removable back doors and side glass panels
- One set of 4" (102mm) legs with rubber feet
- Five (5) pan zones to hold standard pan sizes (GN)
- Two (2) heat zones
- Two (2) heat-on indicator lights
- Four (4) long pan dividers (1002584)
- Five (5) short pan dividers (1002621)
- Fifteen [15] short pan dividers [11318]

Pan* Capacity										
Pan Size	Pan Dimensions	Qty.								
Full-Size & One-Third**:	12" x 20" x 2-1/2" [GN 1/1] 12" x 6" x 2-1/2" [GN 1/3]	5 5								
Half-Size & One-Third**:	12" × 10" × 2-1/2" [GN 1/2] 12" × 6" × 2-1/2" [GN 1/3]	10 5								
Full-Size Sheet Pans:	18" x 26" x 1"	3								
Max. Capacity/Volume:	80 lbs (36 kg) 50 qts (6	60 L)								

<sup>\*</sup> Pans are not included with display case.
\*\* Will also accept 4" [100mm] deep pans.

## Configuration

## □ ED3-72 with 4-inch legs and rubber feet (standard)

 $\hfill\square$  ED3-72 with mobile base, standard height

 $\square$  ED3-72 with mobile base, short

☐ ED3(SYS)-72 with stationary base

#### **Electrical**

## □ 208V, 50/60 Hz, 1PH

□ 240V, 50/60 Hz, 1PH

## **Options and Accessories**

## Panel Color (select one)

- ☐ Black, standard
- ☐ Stainless steel, optional

## End Glass (select one)

- ☐ Clear glass, standard
- ☐ Solar bronze glass, optional (5011353)

## Additional

- ☐ Temperature gauge [GU-48153]
- ☐ Right-mounted scale platform (5001307)
- ☐ Left-mounted scale platform [5001308]
- ☐ Work shelf with gravy lane (5005639)
- ☐ Pan insert [4" deep] [1001990]
- ☐ 1/3 Pan cover-up bar [1008014]
- ☐ Sheet pan divider bar package [5002803]

## **Extended warranty**

☐ One-year warranty extension













## **DIMENSIONS**

## ED3-72 with Legs





Model ED3-72 Legs Exterior (H x W x D)

30-3/16" x 72-5/16" x 43-13/16" [767mm x 1836mm x 1113mm]

Ship Dimensions (H x W x D)\*

45" x 85" x 55" (1143mm x 2159mm x 1397mm)

Well (W x L x D)

27-1/4" x 69-5/16" x 4-1/2" (692mm x 1761mm x 114mm)

**Net Weight** 419 lb [190 kg]

Ship Weight\*


465 lb (210 kg)

\*Domestic ground shipping information. Contact factory for export weight and dimensions.



## **DIMENSIONS**

## ED3(SYS)-72 with Stationary Base



Model ED3-72 SYS Exterior (H x W x D)

48-5/16" x 72-5/16" x 47-7/16" [1227mm x 1836mm x 1205mm]

Ship Dimensions (H x W x D)\*

65" x 85" x 55" (1651mm x 2159mm x 1397mm)

Well (W x L x D)

27-1/4" x 69-5/16" x 4-1/2" (692mm x 1761mm x 114mm)

Net Weight

621 lb (282 kg)

Ship Weight\*


700 lb (317 kg)

\*Domestic ground shipping information. Contact factory for export weight and dimensions.



## **DIMENSIONS**

## **ED3-72 Standard Mobile Base**



Model ED3-72 Mobile Exterior (H x W x D)

63-3/8" x 72-5/16" x 43-13/16" [1609mm x 1836mm x 1113mm]

Ship Dimensions (H  $\times$  W  $\times$  D)\*

45" x 85" x 75" (1143mm x 2159mm x 1905mm)

Well (W x L x D)

27-1/4" x 69-5/16" x 4-1/2" [692mm x 1761mm x 114mm]

Net Weight

549 lb (249 kg)

Ship Weight\*


595 lb (270 kg)

 $\hbox{*Domestic ground shipping information. Contact factory for export weight and dimensions.}$ 



## **DIMENSIONS**

## **ED3-72 Short Mobile Base**



Model ED3-72 Mobile Short Exterior (H x W x D)

57-5/16" x 72-5/16" x 43-13/16" (1456mm x 1836mm x 1113mm)

Ship Dimensions (H  $\times$  W  $\times$  D)\*

45" x 85" x 75" (1143mm x 2159mm x 1905mm)

Well (W x L x D)

27-1/4" x 69-5/16" x 4-1/2" (692mm x 1761mm x 114mm)

Net Weight

549 lb (249 kg)


Ship Weight\*

595 lb (270 kg)

\*Domestic ground shipping information. Contact factory for export weight and dimensions.



## **ED3 Pan Configurations**





## **Installation Requirements**

- The display case must be installed level.
- The display case must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.
- Do not install a heated display case near a cold air source such as a freezer, air conditioning vents, or in any area where outside air fluctuation can affect performance.



ED3-72 With feet	V	Ph	Hz	AWG* minimum	Α	Breaker minimum	kW	Connection
	208	1	50/60	14	15.0	19A	3.11	6ft; NEMA 6-30 🔘
	240	1	50/60	14	17.2	22A	4.14	6ft; NEMA 6-30 🕒

\*Recommended minimum conductor sized at 90°C and ambient 30°C. Electrical connections must meet all applicable federal, state, and local codes.

ED3-72 With base	V	Ph	Hz	AWG*	Α	Breaker minimum	kW	Connection
	208	1	50/60	14	15.0	19A	3.11	Cord, no plug
	240	1	50/60	14	17.2	22A	4.14	Cord, no plug

<sup>\*</sup>Recommended minimum conductor sized at 90°C and ambient 30°C. Electrical connections must meet all applicable federal, state, and local codes.



roject Name:
ocation:
em #:
Σty:

## **MoTak 2 Swing Glass Door Merchandiser Freezer**

MFM-2D



**ELECTRIC** 

115 / 60Hz / 1Ph

Cord Length (Inches): 98.40

Plug Type: NEMA 5-15P

Cord set included

**NEMA 5-15P** 



**3RD PARTY APPROVALS** 





Intertek

Intertek

## **WARRANTY (USA / CANADA)**

2 Year Warranty on Parts & Labor, 5 Years on Compressor



Elevate your commercial frozen storage solutions with the MoTak Glass Door Merchandiser Freezer, ideal for showcasing frozen drinks, food, and treats in high-traffic areas. Constructed with durable aluminum doors, this freezer ensures longevity and performance. With a spacious 35.8 cubic feet capacity, it accommodates a variety of products. The temperature range of -8° to 0°F keeps items perfectly frozen, while the fully automatic controller and R290 refrigerant enhance efficiency. Self-closing doors and manual cleaning features make maintenance simple and convenient.

## **FEATURES AND CONSTRUCTION -**

- 35.8 cu ft capacity provides ample frozen storage for various items
- Equipped with a compressor cooling system for optimal performance
- Constructed with durable aluminum for longevity and reliability
- Maintains a temperature range of -8° to 0°F for optimal frozen storage
- Utilizes R290 refrigerant for eco-friendly cooling
- Operates on 115V with a NEMA-5-15P plug for convenience
- Features eight adjustable shelves for versatile storage options
- Includes casters for easy mobility and positioning
- Perfect for showcasing frozen treats in various commercial settings
- Features self-closing doors to conserve energy and maintain temperature

## **NOMINAL STORAGE CAPACITY -**

Cubic Feet: 35.8 cu. f.t

## **TEMPERATURE -**


Holding Temperature (Fahrenheit): -8 - 0

These models are designed to operate in an environment where temperature and humidity do not exceed 75°F (24°C) and 55% relative humidity



# MoTak 2 Swing Glass Door Merchandiser Freezer

**FRONT** SIDE



# **TOP**

## Merchandiser

Doors	Shelves	Amps	НР	Capacity	Refrigerant Type / Ounces	Assembled Dimensions	ltem Weight lbs	Shipping Weight lbs
2	8	10.6	1	35.8 cu. f.t	R290 / 4.942	31.90" x 53.20" x 83.90"	440.9	507



## INDIG® NXT

# iT0420 Ice Cube Machine

## Models

IDT0420A IYT0420A

IDT0420W IYT0420W





## Ice Machine Electric

115/60/1 standard (208-230/60/1also available)

## Minimum circuit ampacity:

11.3, 115v, 5.5 208-230v Air-cooled: Water-cooled: 10.6,-115v, 5.2 -208-230v

## Maximum fuse size:

Air-cooled: 15 *1ph* Water-cooled: 15 1ph

## Specifications

## **BTU Per Hour:**

3,800 (average), and 6,000 (peak)

## Refrigerant:

R410A CFS - Free Lowers global warming by 48%

## **Operating Limits:**

- Ambient Temperature Range: 40° to 110°F (4.4° to 43.3°C) Water Temperature Range: 40° to 90°F (4.4° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- New levels of Performance Showcasing an average of 41% lower energy consumption, 21% reduction in in potable water usage and a 34% reduction in condenser water usage. This translates into lower cost of ownership over the life of your
- easyTouch® Display New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume.
- Easy to Clean Foodzone Hinge front door swing out for easy access. Removable water-trough, distribution tube, curtain, water probe and water pump for fast and efficient cleaning. Selected components are made with AlphaSan® antimicrobial.
- Intelligent Diagnostics Provides 24 hour preventative maintenance and diagnostic feedback for trouble free
- Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions and environments
- DuraTech® Exterior Provides superior corrosion resistant above stainless steel. Innovative clear-coat resists fingerprints and dirt making it easier to keep clean.
- Available LuminIce® II Growth Inhibitor Controls the growth of bacteria and yeast within the Food zone keeping the machine cleaner longer. A new indicator in the display keeps you abreast of the operational status.



## Ice Shape



**Half Dice** 3%" x 11%" x 7%" (.95 x 2.86 x 2.22 cm)



Dice %" x %" x %" (2.22 x 2.22 x 2.22 cm)














COMPANY WITH **QUALITY SYSTEM** 



Tel: 1.920.682.0161 Fax: 1.920.683.7589

www.manitowocice.com








## iT0420 on D-320 Storage Bin

- B 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- (vater-cooled units)



11.00" (27.94 cm)

## Space-Saving Design





	iT0420 D-320	iT0420 D-420
Height	59.50" 151.13 cm	71.50" 181.61 cm
Width	22.00" 55.88 cm	22.00" 55.88 cm
Depth	34.00" 86.30 cm	34.00" 86.30 cm
Bin Storage	264 lbs. 118 kgs.	383 lbs. 174 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). Bin capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

## Specifications

		lce	lce Producti	Power Usage kWh/100 lbs. @90°Air/70°F	Potable Water Usage/100 lbs.	
	Model	Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	45.4 kgs. of Ice
	IDT04204	dice	470 lbs.	375 lbs.	4	19 Gal.
AIR COOLED	IDT0420A		213 kgs	170 kgs	5.6 ★	72 L
88	IYT0420A	half-dice	460 lbs.	375 lbs.	<b>-</b>	19 Gal.
	1110420A	100	209 kgs	170 kgs	5.4 ★	72 L
	IDT0420W	dice	454 lbs.	400 lbs.	4.28	19 Gal.
<b>a</b>	101042000		206 kgs	181 kgs	4.28	72 L
COOLED	IYT0420W	half-dice	490 lbs.	425 lbs.	4.24	19 Gal.
	111042000		222 kgs.	193 kgs	4.24	72 L
ER C	111042000		222 kgs.	193 kgs	4.24	72 L

\* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 140 gal/ 530 L. \*Water-cooled models are excluded from ENERGY STAR qualification.

Order separately: Ice storage bin for all units ★ENERGY STAR® 3.0

## Accessories

## LuminIce® II **Growth Inhibitor**

reduces yeast and bacteria growth for a cleaner ice machine.



## **External** Scoop holder

Protect the ice scoop with the NSF approved versatile scoop holder.



## **Arctic Pure® Water Filters**

Reduces sediment and chlorine odors for better tasting ice.



## iAuCS®

schedules and performs routine ice machine cleaning automatically.



Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220

Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 6468 01/18





# High Capacity Hot Food Displays Impulse Series





# Serving Looks


Not only is the HFDHC line capable of holding high volume, it is also fully customizable to suit your needs. Two adjustable shelves can be arranged to fit full, half, or bun size pans. Fit three wide or two full size pans lengthwise across all selling surfaces. Six heating zones can be individually adjusted to each product for optimal heating and freshness.


The HFDHC features swing open front and sliding back doors, making the case perfect for rear or front load self serve applications. The HFDHC Combo-Serve can be purchased with the controller mounted in the front or rear. This display is designed for holding wrapped or boxed food.

Model		HFDHC
Overall Unit	Height	35.1 inches (891.54 mm)
	Width	42.7 inches (1084.58 mm)
	Depth	29.8 inches at base (756.92 mm)
Approx. Internal Volume		14 ft <sup>3</sup>
Weight		276 lbs. (125 kg)
Temp. Controlled Hot Plates		(4) 200W (2) 300W
Lamps (Illumination)		(3) LED lighting
Controller (Adjus	stable	Six temperature controls, 100°F-270°F
Temp.)	, table	Front or Rear Mount
Timers		12 Timers, programmable for 30 min-4 hr increments
Power		115VAC 60Hz
Amp Rating		14.7 Amps
Standard Access	orios	(6) Removable Wire or stainless steel Racks
Standard Access	ories	Removable Lexan Spaced Shelf Guards
Optional Accesso	ories	4" Leg Kit

 ${\it NOTE:}\ The\ manufacturer\ reserves\ the\ right\ to\ make\ product\ improvements\ and\ change\ specifications\ without\ notice.$ 









## **FEDERAL INDUSTRIES**

A Standex Company

215 Federal Avenue Belleville, Wisconsin 53508-9201

**Phone:** 800-356-4206 **Fax:** 608-424-3234

Email: Geninfo@Federalind.com Website: Federalind.com

Project Name:	AIA#
Item #:	
Model #: Qty:	SIS#
Approval:	

## **ELEMENTS™ REFRIGERATED SELF-SERVE ISLAND MERCHANDISER**

Designed with impulse sales in mind. Get maximum return and increased profits with shop-around merchandising.



Model EIMSS84SC-3 Shown \*Black Exterior Finish Only

OPTION	AL ACCE	ECCUDI	EC
OFIIUN	AL AUUI	-SOUKI	<b>E</b> 3

- High Capacity Condensate Evaporator Assembly (Field Installed)
  - Requires the removal of the standard Evaporator Assembly shipped with unit, and a separate 208-240V / 20 amp circuit.

							•				•			
1														
	-	-	 	-	•	 	 •	-	 •	-			 -	

MODEL	DIMENSIONS (Includes End Panels)
□ EIMSS60SC-3	60 x 40 x 60 (in) 1524 x 1016 x 1524 (mm)
□ EIMSS84SC-3	84 x 40 x 60 (in) 2134 x 1016 x 1524 (mm)

## **STANDARD FEATURES**

## **Model Features**

- Black metal base, interior and canopy.
- Air Deflector
- Easily accessible light switch and temperature control
- Insulated with high-density foam
- Adjustable leg levelers
- Wired for either top or bottom mount electrical connections

## Refrigeration

- Condensate evaporator provided for a totally self-contained system
- Easy clean, rust-proof insulated evaporator coil compartment
- Refrigeration controls maintain 38°-40°F. Note: Case temperature will vary if the air curtain is disrupted
- R449a Refrigerant
- Thermometer

## **Shelving**

• Adjustable black metal shelves, three tiers

## Lighting

- LED top and undershelf lighting
- UL Safety and UL Sanitation Listed to NSF Standard
- DOE 2017 Compliant













Note: Information is subject to change at any time. Visit www.federalind.com for the most current specs. AIA#

## **ELEMENTS™ REFRIGERATED SELF-SERVE ISLAND MERCHANDISER**

SIS#


**Product Specifications** 

Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Avg prod temp °F / °C
All	Packaged Refrigerated Products	38°F/(3.3°C)

DIMENSION: xx"/(mm)

**DIMENSION TOLERANCE+/-0.25(6.4)** 



MODEL	DIMENSIONS			S	DISPLAY AREA	SHIPPING WEIGHT		SELF CONTAINED WIT	H.P.		
MODEL	L	D	Н1	UNITS	(SQ. FT.)	LBS	KILO	VOLTAGE	AMPS	n.r.	
EIMSS60SC-3	60	40	60	in	3 TIERS - 31.3	910	413	208-240/60/1	30 AMPS	1-1/2 HP	
EIM33003C-3	1524	1016	1524	mm	3 HER5 - 31.3			200-240/00/1			
EIMSS84SC-3	84	40	60	in	3 TIERS - 41.4	1375	624	208-240/60/1	30 AMPS	1 2// 110	
EIM55845U-3	2134	1016	1524	mm	3 HER3 - 41.4	13/3	024	200-240/60/1	SU AMPS	1-3/4 HP	

- Case temperature will vary if the air curtain disrupted
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.









**Phone:** 800-356-4206 **Fax:** 608-424-3234

**Email:** Geninfo@Federalind.com **Website:** Federalind.com



Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project: 55	
Model #:	
Item #:	
Available W/H:	Qty:
Approval:	
AIA#:	SIS#:
CSI Section 11400	

## Sandwich / Salad Unit

Food Prep Tables M3 Series

Model: MST-60-N

## **Patented Self-Cleaning Condenser**



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



## *=== FEATURES & BENEFITS ===*

## Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

## Digital temperature control & monitor system

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

## ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

## Cold Bunker system

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

## ■ Insulated pan cover

## Stainless steel exterior

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is AL interior with stainless steel floor and ABS door liner. It guarantees the utmost in cleanliness and long product life. The M3 model adds a touch of style to the most refined setting.

## High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- 9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves

## LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

## ■ Refrigerator holds 33°F ~ 39°F for the best in food preservation

## NATURAL Refrigerant







Model	Swing Doors	CU./FT.	#of Shelves	#of Pans	#of Hood	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
MST-60-N	2	16	2	16	1	1/3	4.4	330	601/4 x 30 x 37

(unit: inch)

## Model: MST-60-N

ELECTRICAL DATA	
Voltage	115/60/1
Plug Type	(i) NEMA 5-15P
Full Load Amperes	4.4
Compressor HP	1/3
Cord Length (ft.)	9
Refrigerant	R-290
DIMENSIONAL DATA	
Ext. Length Overall (in.)	60 <sub>1/4</sub> (1530mm)
Ext. Depth Overall (in.)*	30 (762mm)
Ext. Height Overall (in.)†	37 (940mm)
# of Doors	2
# of Shelves	2
# of Pans	16
Net Capacity (cu. ft.)	16
Shelf Size (L x D) (in.)	27 x 17
Net Weight (lbs.)	308
Gross Weight (lbs.)	330

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- \* Depth does not include 1" for rear spacers.
- † Height does not include 5" for caster height.

# ■ WARRANTY: 5 Year Parts and Labor Warranty 7 Year Compressor Warranty

## STANDARD FEATURES


- · Anti-corrosion coated evaporator
- · Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included
- # Accommodates 1/6 size, 6" deep condiment pans


## OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster,  $\frac{1}{2}$ " diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake): ADA compliant unit under 34" work surface height
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Removable food cover: RCT-60
- Single overshelf, stainless steel, 60-3/8" W: TSOS-5S
- Double overshelf, stainless steel, 60-3/8" W: TSOS-5R-T
- · Clear lid: CL-60
- Door lock: lead time applies. Please contact your sales representative for more details to order.

Ver.20230815

## **PLAN VIEW**





SIDE VIEW













■ Turbo Air : 800-627-0032 ■ GK : 800-500-3519 ■ Warranty : 800-381-7770 ■ AC : 888-900-1002









## **Features**

- Durable stainless steel exterior and interior
- 0.9 cu. ft. capacity accommodates (1) 1/2 size 6" deep food pan with cover
- 10 programmable memories, including defrost
- 1000W of power with 4 settings provide a variety of cooking
- See-through door and lighted interior to monitor cooking

## Certifications







# **Solwave Stainless Steel Commercial** Microwave with Push Button Controls - 120V, 1000W

#180MW1000SS

Item #:	180MW1000SS	Qty:	
Project:	56	_	
Approva	l:	Date:	





Technical Data	
Width	20 Inches
Depth	18 1/2 Inches
Height	12 Inches
Interior Width	13 Inches
Interior Depth	13 1/4 Inches
Interior Height	8 Inches
Amps	8.3 Amps
Hertz	60 Hz
Phase	1 Phase
Voltage	120 Volts

Technical Data	
Wattage	1000 Watts
Capacity	0.9 cu. ft.
Control Type	Push-Button
Features	Digital Display ETL Sanitation Fits Half Size Pans Programmable UL Listed
Microwave Usage Level	Light Duty
Microwave Wattage	Less Than 1200 Watts
Number of Power Levels	4
Plug Type	NEMA 5-15P
Power Type	Electric
Туре	Microwaves
Usage Per Day	Less Than 50 Times

## **Notes & Details**

This Solwave commercial microwave with push button control is a perfect way to save time and provide quick heating capabilities at your concession stand, lunch room, snack bar, coffee shop, or other quick-serve establishment. This easy-to-use, light duty unit boasts 1000 watts of microwave power that is ideal for warming soups, sandwiches, prepackaged lunches, beverages, and more.

Designed with operator convenience in mind, this unit features 10 programmable memories, including defrost, and a sturdy door handle that is easy to quickly grab during busy times in your establishment. The durable stainless steel exterior and interior will withstand repeated use in busy kitchens, and the spacious 0.9 cu. ft. cavity provides ample room to handle an array of items. 4 power settings provide a variety of unique cooking options. Plus, the automatic cool down feature operates the fan for 60 seconds after each use to ensure continued peak performance without overheating!

It sits on four, 1 3/4" legs and requires a 120V electrical connection for operation.

▲ WARNING: This product can expose you to chemicals including lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to <a href="https://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>.

## **UL-Listed**

Providing an unmatched volume and variety of food, Vector H Series countertop models are specifically designed for foodservice operations where space is at a premium but food demand is high.

Featuring up to four independent oven chambers, operators can control the temperature, fan speed and cook time in each individual chamber for maximum flexibility – simultaneously cooking a variety of menu items with no flavor transfer.

Exclusive Structured Air Technology® delivers focused heat for faster, more even cooking and consistent, high-quality results.

Reduce labor by eliminating extra steps in food production and the need to watch and rotate pans.

Place anywhere with a small, 21" (533mm) footprint and ventless, waterless operation.

Custom colors available for enhanced branding and a front-of-house experience for customers.

An advanced control - designed intentionally simple - features an intuitive, user-friendly interface and programmable recipes to ensure consistency with each cook

ChefLinc™, cloud-based remote oven management software, streamlines processes and maximizes profits with data-driven insights (deluxe control only). ISO 9001:2015-certified

#### **Standard Features**

- Programmable, touchscreen control
- Easy recipe upload/download via USB port
- UL-listed ventless catalytic converter
- Double-pane glass door
- One (1) wire stainless steel rack and two (2) jet plates per cooking chamber
- 4" (102mm) adjustable legs
- Cord and plug on 208-240V models (except Canada)



- VMC-H2: 2 shelf, 2 half-size sheet pans—18" x 13" x 1" [2 GN 2/3 pans—354mm x 325mm x 25mm)
- VMC-H3: 3 shelf, 3 half-size sheet pans—18" x 13" x 1" [3 GN 2/3 pans—354mm x 325mm x 25mm)
- VMC-H4: 4 shelf, 4 half-size sheet pans—18" x 13" x 1" [4 GN 2/3 pans—354mm x 325mm x 25mm)
- VMC-H2H: 2 shelf, 2 full-size hotel pans—20-3/4" x 12-3/4" x 4" [2 GN 1/1 pans - 530mm x 325mm x 65mm] or 2 half-size sheet pans—18" x 13" x 1" (2 GN 2/3 pans—354mm x 325mm x 25mm)
- VMC-H3H: 3 shelf, 3 full-size hotel pans—20-3/4" x 12-3/4" x 4" [3 GN 1/1 pans—530mm x 325mm x 65mm] or 3 half-size sheet pans—18" x 13" x 1" (3 GN 2/3 pans—354mm x 325mm x 25mm)
- VMC-H4H: 4 shelf, 4 full-size hotel pans—20-3/4" x 12-3/4" x 4" [4 GN 1/1 pans—530mm x 325mm x 65mm] or 4 half-size sheet pans—18" x 13" x 1" [4 GN 2/3 pans—354mm x 325mm x 25mm]





## Configurations (select one)

#### **Models**

These models accommodate a half-size sheet pan

□ VMC-H2 □ VMC-H4 □ VMC-H3

These models accommodate a full-size hotel pan

□ VMC-H2H □ VMC-H4H

□ VMC-H3H

## Control

Deluxe

☐ Simple

☐ Ethernet Cable [5030518] for Deluxe only

## **Door swing**

☐ Right hinged

☐ Left hinged

## **Electrical**

## VMC-H2/H2H

□ 208-240V. 1PH, with cord and plug

☐ 208-240V, IPH, no cord, no plug [Canada] ☐ 220-240V, IPH, no cord, no plug ☐ 380-415V, 3PH, no cord, no plug

## VMC-H3/H3H

## □ 208-240V, 1PH, with cord and pluce

□ 208-240V, 1PH, no cord, no plug [Canada] □ 208-240V, 3PH, with cord and plug

□ 208-240V, 3PH, no cord, no plug (Canada)

☐ 220-240V, 1PH, no cord, no plug

☐ 380-415V, 3PH, no cord, no plug

#### VMC-H4/H4H

□ 208-240V, 3PH, with cord and plug

☐ 208-240V, 3PH, no cord, no plug (Canada)

☐ 380-415V, 3PH, no cord, no plug

## **Accessories**

☐ See accessories brochure for all available accessories

## Casters and legs

☐ 3" (76mm) casters, set of four (4) (5027946)

#### Cookware

☐ Jet plate assembly, half-size sheet pan (5025235)

☐ Jet plate assembly, hotel pan [5025236]

☐ Wire shelf, half-size sheet pan (SH-37662)

☐ Wire shelf, hotel pan (SH-39077)


#### Cleaning

☐ Alto-Shaam® non-caustic cleaner, one [1] bottle [CE-46828] ☐ Alto-Shaam® non-caustic cleaner, case of six (6) bottles (CE-468291

☐ Internal chamber filters—order one [1] kit per chamber [5027119]

Specification







#### Model Exterior (H x W x D)

VMC-H2 29-5/8" x 21-1/2" x 37-1/2" [752mm x 546mm x 953mm] VMC-H2H 29-5/8" x 21-1/2" x 39-1/2" (752mm x 546mm x 1003mm) VMC-H3 36-5/8" x 21-1/2" x 37-1/2" (929mm x 546mm x 953mm) VMC-H3H 36-5/8" x 21-1/2" x 39-1/2" [929mm x 546mm x 1003mm] VMC-H4 43-5/8" x 21-1/2" x 37-1/2" (1108mm x 546mm x 953mm) VMC-H4H

## Interior (H x W x D)

Ship Weight\*

**Net Weight** 14-3/8" x 14-11/16" x 19" [366mm x 373mm x 483mm] 209 lb (95 kg) 14-3/8" x 14-11/16" x 21-1/2" [366mm x 373mm x 546mm] 213 lb [97 kg] 21-3/8" x 14-11/16" x 19" [544mm x 373mm x 483mm] 272 lb [123 kg] 21-3/8" x 14-11/16" x 21-1/2" [544mm x 373mm x 546mm] 278 lb [126 kg] 28-3/8" x 14-11/16" x 19" [721mm x 373mm x 483mm] 341 lb (155 kg) 43-5/8" x 21-1/2" x 39-1/2" [1108mm x 546mm x 1003mm] 28-3/8" x 14-11/16" x 21-1/2" [721mm x 373mm x 546mm] 348 lb [158 kg]

#### Ship Dimensions (L x W x H)\* Model

VMC-H2/H 48" x 29" x 56" [1219mm x 737mm x 1422mm] 291 lb [132 kg] VMC-H3/H 48" x 29" x 56" [1219mm x 737mm x 1422mm] 375 lb (170 kg) VMC-H4/H 48" x 29" x 56" [1219mm x 737mm x 1422mm] 425 lb (193 kg)

<sup>\*</sup>Domestic ground shipping information. Contact factory for export weight and dimensions.





2" [51mm]\* Тор: Left: 2" (51mm) Right: 2" (51mm) 20" (508mm) Front: Back: 2" [51mm]



- The oven must be installed level.
- The oven must not be installed in any area where it may be affected by steam, grease, dripping water, high temperatures, or any other severely adverse conditions.
- Oven not intended for built-in installation.



## Heat of rejection

VMC-H	Heat Gain	Heat Gain		
	qs, BTU/hr	qs, kW		
	1,898	0.56		



Maximum temperature: 525°F (274°C)



VMC-H2/VMC-H2H	V	Ph	Hz	Awg	IEC	Α	Breaker (A)	kW	Plug Configuration**	Certification
208-240V	208	1	60	8	_	25	30*	5.2	NEMA 6-30	cUL us VIL
	240	1	60	8	_	28	30*	6.7	NEMA 6-30	CUL US USTED
220-240V	220	1	50/60	_	4	25	32*	5.4	No cord, no plug	EH[ <€
	240	1	50/60	_	4	28	32*	6.4	No cord, no plug	IP X4 🙆
380-415V	380	3	50/60	_	1.5	8	16	5.4	No cord, no plug	FRE C€
	415	3	50/60	_	1.5	9	16	6.4	No cord, no plug	IP X4 🔕
VMC-H3/VMC-H3H										
208-240V	208	1	60	6	_	38	50*	7.9	NEMA 6-50	CUL US US EPH
	240	1	60	6	_	43	50*	10.3	NEMA 6-50	COORDO APP. MINIC COORDO APP. MINIC MITH RETORNAL STITUS FOR LIMITUS THE CHESSES OF BREED LIMITUS OF BREED L
208-240V	208	3	60	10	_	22	30	7.9	NEMA 15-30P	CUL US US EPH
	240	3	60	10	_	25	30	10.3	NEMA 15-30P	COUNTY INFO BY
220-240V	220	1	50/60	6	10	37	63	8.1	No cord, no plug	EH[ <€
	240	1	50/60	6	10	41	63	9.6	No cord, no plug	IP X4 🔕
380-415V	380	3	50/60	_	1.5	13	16	8.1	No cord, no plug	FRE C€
	415	3	50/60	_	1.5	14	16	9.6	No cord, no plug	IP X4 💩
VMC-H4/VMC-H4H										
208-240V	208	3	60	6	_	32	40	10.6	NEMA 15-50P	CUL US US EPH
	240	3	60	6	_	36	40	13.9	NEMA 15-50P	USTED EPH COORDINATE MACE APPLICATION OF THE PHOTO PROPERTY OF THE PHOTO OF THE PHO
380-415V	380	3	50/60	_	4	17	32	10.8	No cord, no plug	FAI C€
	415	3	50/60	_	4	18	32	12.7	No cord, no plug	IP X4 🙆

Electrical connections must meet all applicable federal, state, and local codes.










<sup>\*</sup> For use on individual branch circuit only.

<sup>\* \*</sup>No cord, no plug, in Canada.





## **Stacked Configurations and Stands**

## VMC-H on stand 5034115




Dimensions shown are with adjustable feet at minimum height.







## VMC-H on stand 5034118




Dimensions shown are with casters at minimum height.







## VMC-H on stand 5034294



Dimensions shown are with adjustable feet at minimum height.









## **Stacked Configurations and Stands**

## VMC-H on stand 5033311 over VMC-H3 or VMC-H3H with casters




Dimensions shown are with adjustable feet at minimum height.




## Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-1DN, 500-2DN, 500-3DN, VMC-H2/H2H

# VMC-H on stand 5033314 over VMC-H4 or VMC-H4H with casters



Dimensions shown are with adjustable feet at minimum height.




## Other Bottom Unit Options

300-TH; 500-S; 500-TH; 500-IDN; 500-2DN; 500-3DN; VMC-H2/H2H; VMC-H3/H3H



## **Alternative Stacked Configurations and Stands**

## VMC-H on stand 5033317 over VMC-H3 or VMC-H3H




Dimensions shown are with adjustable feet at minimum height.

## Other Bottom Unit Options

300-TH, 500-S, 500-TH, 750-TH, 750-S, 500-1D, 500-2D, 500-3D, 500-2DI, 500-1DN, 500-2DN, 500-3DN, VMC-H2/H2H, VMC-H2HW

## VMC-H on stand 5033384 over VMC-H2, VMC-H2H, or VMC-H2HW



Dimensions shown are with casters at minimum height.

\*Smoker models must be under a hood.

## Other Bottom Unit Options

300-TH, 500-S\*, 500-TH, 750-TH, 750-S\*, 500-1D, 500-2D, 500-3D, 500-2DI, 500-1DN, 500-2DN, 500-3DN


\*exluding ovens with 5" (127mm) casters

<sup>\*</sup>Smoker models must be under a hood.



## **Alternative Stacked Configurations and Stands**

## VMC-H on stand 5027834 over 500-TH




Dimensions shown are with adjustable feet at minimum height.

Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-1DN, 500-2DN, 500-3DN

## CTX4-10 on stand 5033312 over VMC-H3 or VMC-H3H



Dimensions shown are with adjustable feet at minimum height.

Other Bottom Unit Options

300-TH, 500-S, 500-TH, 500-1DN, 500-2DN, 500-3DN, VMC-H2/H2H