## 2018 APPENDIX B BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS

### (EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)

(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: Harnett County Jetport Hanger						
Address: 497 Airport Rd., Erwin, NC			Zip Co	de		
Owner/Authorized Agent:	Phone # (		-			
	cy/County		Sta			
<u> </u>	y	<u> </u>	<del>_</del>			
	<i>J</i>					
CONTACT:						
DESIGNER FIRM	NAME	LICENSE #	TELEPHONE #	E-MAIL		
Architectural Jenkins Consulting	Kelly Dodson	42009	<u>(910</u> ) 822-1724	KellyD@jenkinsce.pro		
Civil 4d site solutions	Scott Brown Kelly Dodson	027452 42009	$\frac{(910)}{(910)} \frac{426-6777}{822-1724}$	sbrown@4dsitesolutions.com KellyD@jenkinsce.pro		
Electrical Jenkins Consulting  Fire Alarm  N/A	Tony Bodson	<del></del>	( )			
Plumbing MLS Plumbing Co. LLC	Michael Smith	NC 28833P1	910 ) 484-1124	mlsplumbing@hotmail.com		
Mechanical N/A			( )			
Sprinkler-Standpipe N/A			()			
Structural Wayne Brad Baker	Steve Pinto	33446	<u>941</u> ) 993-0722	Steve@steelcor.com		
Retaining Walls >5' High N/A			()			
Other N/A ("Other" should include firms and individu	ala ayah aa tuyaa		()	amous etc.)		
Other should include fifths and individu	als such as truss,	precast, pre-engin	eered, interior desi	gners, etc.)		
2018 NC BUILDING CODE:  New Building Addition Renovation  1st Time Interior Completion  Shell/Core - Contact the local inspection jurisdiction for possible additional procedures and requirements  Phased Construction - Shell/Core- Contact the local inspection jurisdiction for possible additional procedures and requirements						
2018 NC EXISTING BUILDING CODE		☐ Prescriptive☐ Level I	-	Chapter 14   Level III		
		☐ Historic Prope		Change of Use		
CONSTRUCTED: (date)	CURRE	=	•			
RENOVATED: (date)						
RISK CATEGORY (Table 1604.5):	Current:	] I 🗆 II 🗆 I	II 🗆 IV			
Proposed: I II III IV						
BASIC BUILDING DATA						
Construction Type:	☐ II-A	☐ III-A	□IV	□ V-A		
(check all that apply)	☐ II-B	☐ III-B		☐ V-B		
Sprinklers:	=			PA 13D		
Standpipes:						
Fire District: No Yes	Flood Hazard	Area: 🔽 No	Yes Yes			
<b>Special Inspections Required:</b> Mo		he local inspection es and requiremen	n jurisdiction for acts.)	<u>dditional</u>		

		<b>Gross Building Area Table</b>	
FLOOR	EXISTING (SQ FT)	NEW (SQ FT)	SUB-TOTAL
3 <sup>rd</sup> Floor			
2 <sup>nd</sup> Floor			
Mezzanine			
1st Floor		9000	
Basement			
TOTAL			
		ALLOWABLE AREA	
Drimany Occurs	ancy Classification(s):		
-	•	A 2	
Assembly	☐ A-1 ☐ A-2 ☐ .	A-3	
Business			
Educational			
Factory		-2 Low	_
Hazardous		I-2 Deflagrate  H-3 Combus	t H-4 Health H-5 HPM
Institutional	I-1 Condition I	☐ 2	
	☐ I-2 Condition ☐ 1	$\square$ 2	
	☐ I-3 Condition ☐ 1	$\square$ 2 $\square$ 3 $\square$ 4 $\square$	<b>5</b>
	☐ I-4		
Mercantile			
Residential	$\square$ R-1 $\square$ R-2 $\square$ 1	R-3	
Storage	S-1 Moderate	S-2 Low High-piled	
Ü		Open    Enclosed    Repair	Garage
Utility and N	Aiscellaneous	r i i i i i i i i i i i i i i i i i i i	
•			
Incidental Uses			
	` '	etions):	
-	ns: (Chapter 5 – List Co		
Mixed Occupan	cy: No Y	es Separation: Hr.	Exception:
☐ Non	-Separated Use (508.3) -		on for the building shall be determined by
			mitations for each of the applicable
			ing. The most restrictive type of
		construction, so determined, sh	nall apply to the entire building.
☐ Sepa	arated Use (508.4) - See b	pelow for area calculations for e	each story, the area of the occupancy shall
	be su	ich that the sum of the ratios of	the actual floor area of each use divided by
	the a	llowable floor area for each use	shall not exceed 1.
Actua	al Area of Occupancy A	+ <u>Actual Area of Occup</u>	$ancy B \leq 1$
	ole Area of Occupancy A	Allowable Area of Occu	
	·		. 4.00
		+	+ = <u>≤</u> 1.00

STORY	DESCRIPTION AND	(A)	(B)	(C)	(D)
NO.	USE	BLDG AREA PER	TABLE $506.2^{4}$	AREA FOR FRONTAGE	ALLOWABLE AREA PER
		STORY (ACTUAL)	AREA	INCREASE <sup>1,5</sup>	STORY OR UNLIMITED <sup>2,3</sup>

<sup>&</sup>lt;sup>1</sup> Frontage area increases from Section 506.3 are computed thus:

- a. Perimeter which fronts a public way or open space having 20 feet minimum width = \_\_\_\_\_ (F)
- b. Total Building Perimeter = \_\_\_\_\_(P)
- c. Ratio (F/P) = \_\_\_\_\_ (F/P)
- d. W = Minimum width of public way = \_\_\_\_\_(W)
- e. Percent of frontage increase  $I_f = 100[F/P 0.25] \times W/30 =$  \_\_\_\_\_(%)
- <sup>2</sup> Unlimited area applicable under conditions of Section 507.
- <sup>3</sup> Maximum Building Area = total number of stories in the building x D (maximum3 stories) (506.2).
- <sup>4</sup> The maximum area of open parking garages must comply with Table 406.5.4.

#### ALLOWABLE HEIGHT

	ALLOWABLE	SHOWN ON PLANS	CODE REFERENCE 1
Building Height in Feet (Table 504.3) <sup>2</sup>		26-32	
Building Height in Stories (Table 504.4) <sup>3</sup>			

<sup>&</sup>lt;sup>1</sup> Provide code reference if the "Shown on Plans" quantity is not based on Table 504.3 or 504.4.

<sup>&</sup>lt;sup>5</sup> Frontage increase is based on the unsprinklered area value in Table 506.2.

<sup>&</sup>lt;sup>2</sup> The maximum height of air traffic control towers must comply with Table 412.3.1.

<sup>&</sup>lt;sup>3</sup> The maximum height of open parking garages must comply with Table 406.5.4.

### FIRE PROTECTION REQUIREMENTS

BUILDING ELEMENT	FIRE SEPARATION DISTANCE (FEET)	REQ'D	PROVIDED (W/* REDUCTION)	DETAIL # AND SHEET #	DESIGN# FOR RATED ASSEMBLY	SHEET # FOR RATED PENETRATION	SHEET # FOR RATED JOINTS
Structural Frame, including columns, girders, trusses	(FEET)				AGGEMBET		JOHAIS
Bearing Walls							
Exterior							
North							
East							
West							
South							
Interior							
Nonbearing Walls and Partitions Exterior walls							
North							
East							
West							
South							
Interior walls and partitions							
Floor Construction Including supporting beams and joists Floor Ceiling Assembly							
Columns Supporting Floors							
Roof Construction, including supporting beams and joists							
Roof Ceiling Assembly							
Columns Supporting Roof							
Shaft Enclosures - Exit							
Shaft Enclosures - Other							
Corridor Separation	_						
Occupancy/Fire Barrier Separat	ion						
Party/Fire Wall Separation							
Smoke Barrier Separation							
Smoke Partition							
Tenant/Dwelling Unit/ Sleeping Unit Separation							
Incidental Use Separation							

st Indicate section number permitting reduction

### PERCENTAGE OF WALL OPENING CALCULATIONS

FIRE SEPARATION DISTANCE (FEET) FROM PROPERTY LINES	Degree of openings Protection (Table 705.8)	Allowable area (%)	ACTUAL SHOWN ON PLANS (%)
	(TABLE 705.0)		

LIFE SAFETY SYSTEM REQUIREMENTS  Emergency Lighting: No Yes  Exit Signs: No Yes  Fire Alarm: No Yes  Smoke Detection Systems: No Yes Partial  Carbon Monoxide Detection: No Yes
LIFE SAFETY PLAN REQUIREMENTS
Life Safety Plan Sheet #:
Fire and/or smoke rated wall locations (Chapter 7)  Assumed and real property line locations (if not on the site plan)  Exterior wall opening area with respect to distance to assumed property lines (705.8)  Occupancy Use for each area as it relates to occupant load calculation (Table 1004.1.2)  Occupant loads for each area  Exit sign locations (1013)  Exit access travel distances (1017)  Common path of travel distances (Tables 1006.2.1 & 1006.3.2(1))  Dead end lengths (1020.4)  Clear exit widths for each exit door  Maximum calculated occupant load capacity each exit door can accommodate based on egress width (1005.3)  Actual occupant load for each exit door  A separate schematic plan indicating where fire rated floor/ceiling and/or roof structure is provided for purposes of occupancy separation
Location of doors with panic hardware (1010.1.10)  Location of doors with delayed egress locks and the amount of delay (1010.1.9.7)  Location of doors with electromagnetic egress locks (1010.1.9.9)  Location of doors equipped with hold-open devices  Location of emergency escape windows (1030)  The square footage of each fire area (202)  The square footage of each smoke compartment for Occupancy Classification I-2 (407.5)
Note any code exceptions or table notes that may have been utilized regarding the items above

### ACCESSIBLE DWELLING UNITS

(SECTION 1107)

UNIT CLASSIFICATION	TOTAL UNITS	ACCESSIBLE UNITS REQUIRED	ACCESSIBLE UNITS PROVIDED	TYPE A UNITS REQUIRED	TYPE A UNITS PROVIDED	TYPE B UNITS REQUIRED	TYPE B Units Provided	TOTAL ACCESSIBLE UNITS
								PROVIDED

#### ACCESSIBLE PARKING

(SECTION 1106)

LOT OR PARKING AREA	TOTAL # OF PARKING SPACES		# OF ACCESSIBLE S	PACES PROVIDED	TOTAL # ACCESSIBLE
	REQUIRED	PROVIDED	96" SPACES	132" SPACES	PROVIDED
TOTAL					

# PLUMBING FIXTURE REQUIREMENTS (TABLE 2902.1)

U	ISE	WATER CLOSETS		URINALS		LAVATORIES		SHOWERS	DRINKING	FOUNTAINS	
		MALE	FEMALE	UNISEX		MALE	FEMALE	UNISEX	/TUBS	REGULAR	ACCESSIBLE
SPACE	EXIST'G										
	NEW										
	REQ'D										

#### **SPECIAL APPROVALS**

Special approval: (Local Jurisdiction, Department of Insurance, OSC, DPI, DHHS, etc., describe below)	

#### **ENERGY SUMMARY**

### **ENERGY REQUIREMENTS:**

The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portions of the project information for the plan data sheet. If performance method, state the annual energy cost for the standard reference design vs annual energy cost for the proposed design.

Existing building envelope complies with code:	☐ No ☐ Yes (The remainder of this section is not applicable)
Exempt Building: No Yes (Provide cod	le or statutory reference):
Climate Zone: 3A 4A 5A	A
ASHRAE 90.1	Performance Prescriptive Performance Prescriptive pecify source here)
THERMAL ENVELOPE (Prescriptive method o	only)
R-Value of insulation:	
Exterior Walls (each assembly)  Description of assembly: U-Value of total assembly: R-Value of insulation: Openings (windows or doors wit U-Value of assembly: Solar heat gain coefficient projection factor: Door R-Values:	
Walls below grade (each assembly)  Description of assembly: U-Value of total assembly: R-Value of insulation:  Floors over unconditioned space (each a Description of assembly: U-Value of total assembly: U-Value of total assembly:	assembly)
U-Value of total assembly: R-Value of insulation:  Floors slab on grade  Description of assembly:	
U-Value of total assembly: R-Value of insulation: Horizontal/vertical requirement: slab heated:	

### 2018 APPENDIX B

# **BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS**

### STRUCTURAL DESIGN

### $(PROVIDE\ ON\ THE\ STRUCTURAL\ SHEETS\ IF\ APPLICABLE)$

### **DESIGN LOADS:**

	Importance Factors:	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
	Live Loads:	Roof psf Mezzanine psf Floor psf
	Ground Snow Load:	psf
		imate Wind Speed mph (ASCE-7) posure Category
SEISMI	C DESIGN CATEGORY	7: □A □B □C □D
Provide	the following Seismic Des Risk Category (Table 16 Spectral Response Accel	04.5)
	Site Classification (ASCI	
	Basic structural system	rce:
	Analysis Procedure:	☐ Simplified ☐ Equivalent Lateral Force ☐ Dynamic  al, Components anchored? ☐ Yes ☐ No
	,	<u> </u>
LATER	AL DESIGN CONTROI	: Earthquake  Wind
SOIL B		of test report) psf city psf

# 2018 APPENDIX B BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS

MECHANICAL DESIGN (PROVIDE ON THE MECHANICAL SHEETS IF APPLICABLE)

### MECHANICAL SUMMARY

### MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Thermal Zone				
winter dry bulb:				
summer dry bulb:				
Interior design conditions				
winter dry bulb:				
summer dry bulb:				
relative humidity:				
Building heating load:				
Building cooling load:				
Mechanical Spacing Conditioning System				
Unitary				
description of unit:				
heating efficiency:				
cooling efficiency:				
size esta com: of units				
size category of unit:				
Boiler				
· · · · · · · · · · · · · · · · · · ·				
Boiler				
Boiler Size category. If oversized, state reason.:				

### 2018 APPENDIX B

# **BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS**

ELECTRICAL DESIGN

(PROVIDE ON THE ELECTRICAL SHEETS IF APPLICABLE)

### **ELECTRICAL SUMMARY**

ELECTRICAL SYSTEM AND EQUIPMENT				
Method of Compliance: Energy Code ☐ Perform ASHRAE 90.1 ☐ Perform	rmance Prescriptive rmance Prescriptive			
Lighting schedule (each fixture type)				
lamp type required in fixture number of lamps in fixture ballast type used in the fixture number of ballasts in fixture total wattage per fixture total interior wattage specified vs. allowed total exterior wattage specified vs. allowed				
Additional Efficiency Package Options				
(When using the 2018 NCECC; not required for ASHRAE 90.1)				
☐ C406.2 More Efficient HVAC Equipm ☐ C406.3 Reduced Lighting Power Dens ☐ C406.4 Enhanced Digital Lighting Con ☐ C406.5 On-Site Renewable Energy ☐ C406.6 Dedicated Outdoor Air System	ity ntrols			
C406.7 Reduced Energy Use in Service Water Heating				