


ABBREVIATIONS

A	AMPERE(S)	KAIC	1000 AMPERE INTERRUPTING CAPACITY
AC	ALTERNATING CURRENT		
ADA	AMERICANS WITH DISABILITIES ACT	KCMIL	1000 CIRCULAR MIL(S)
AFCI	ARC-FAULT CIRCUIT INTERRUPTER	KVA	KILOVOLT AMPERE(S)
AFF	ABOVE FINISHED FLOOR	K/W	KILOWATT(S)
AFG	ABOVE FINISHED GRADE	LTG	LIGHTING
AHJ	AUTHORITY HAVING JURISDICTION	MC	MECHANICAL CONTRACTOR
ANSI	AMERICAN NATIONAL STANDARDS INSTITUTE	MCA	MINIMUM CIRCUIT AMPACITY
		MCB	MAIN CIRCUIT BREAKER
ATS	AUTOMATIC TRANSFER SWITCH	MIC	MICROWAVE
AWG	AMERICAN WIRE GAUGE	MISC	MISCELLANEOUS
BLDG	BUILDING	MIN	MINIMUM
C	CONDUIT	MFR	MANUFACTURER
CB/CKT BKR	CIRCUIT BREAKER	MH	MOUNTING HEIGHT
CL	CLOSET	MTD	MOUNTED
CLG	CEILING	N	NEUTRAL
CKT	CIRCUIT	NC	NORMALLY CLOSED
CO	CONDUIT ONLY	NEC	NATIONAL ELECTRIC CODE
CONC	CONCRETE	NFPA	NATIONAL FIRE PROTECTION ASSOCIATION
COND	CONDUCTOR		
CONST	CONSTRUCTION	NL	NIGHT LIGHT
CONT	CONTRACT	NO	NORMALLY OPEN
CP	CONTROL PANEL	NTS	NOT TO SCALE
CT	CURRENT TRANSFORMER	P	POLE
CU	COPPER	PB	PULL BOX
DED	DEDICATED	PC	PLUMBING CONTRACTOR
DISC	DISCONNECT	PH/Ø	PHASE
DISH	DISHWASHER	PL	PLUG LOAD
DISP	DISPOSAL	PNL	PANEL
DIV	DIVISION	PRI	PRIMARY
DT	DUAL TECHNOLOGY (IR/US)	PWR	POWER
DWG	DRAWING	QTY	QUANTITY
EA	EACH	REC/RECEPT	RECEPTACLE
EC	ELECTRICAL CONTRACTOR	REF	REFRIGERATOR
ELEC	ELECTRIC	SEC	SECONDARY
EM/EMER	EMERGENCY	SPEC	SPECIFICATION
EX/EXIST	EXISTING	SW	SWITCH
F	FUSE	TEL	TELEPHONE
FA	FIRE ALARM	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION
FBO	FURNISHED BY OTHERS		
FDR	FEEDER	TYP	TYPICAL
FL	FLOOR	UG	UNDERGROUND
FLA	FULL LOAD AMPS	UL	UNDERWRITER'S LABORATORIES
FLUOR	FLUORESCENT	UNO	UNLESS NOTED OTHERWISE
FT	FEET	UON	UNLESS OTHERWISE NOTED
G/GND	GROUND	UPS	UNINTERRUPTIBLE POWER SUPPLY
GC	GENERAL CONTRACTOR	US	ULTRASONIC
GFI	GROUND FAULT INTERRUPTER	UV	ULTRAVIOLET
HC	HUNG CEILING	V	VOLT(S)
HOA	HAND-OFF-AUTO SELECTOR SWITCH	VA	VOLTAMPERE(S)
HP	HORSEPOWER	VFD	VARIABLE FREQUENCY DRIVE
IR	INFRARED	W	WATT(S)
JB	JUNCTION BOX	WP	WEATHERPROOF

SHEET NO.

E0.1



1 ELECTRICAL DEMOLITION PLAN
Scale: 1/4"=1'

DEMO KEYED NOTES

- 1 ALL DEVICES IN THE DEMOLISHED WALLS AND REMOVED EQUIPMENT DEVICES/CONNECTIONS SHALL BE DISCONNECTED AND REMOVED BACK TO SOURCE. UNLESS OTHERWISE NOTED, ALL DEVICES ON WALLS NOT TO BE DEMOLISHED SHALL BE REUSED WHEN POSSIBLE. "EX" DENOTES EXISTING TO REMAIN.
- 2 ALL EXISTING COOLER AND FREEZER EQUIPMENT ARE TO REMAIN, INCLUDING ROOF MOUNTED EQUIPMENT.
- 3 ELECTRICAL DEVICES IN ROOM ARE EXISTING TO REMAIN.
- 4 EXISTING ELECTRICAL PANELS TO REMAIN. REFER TO ONE-LINE FOR MORE INFORMATION.
- 5 CONTRACTOR SHALL PROTECT ALL EXISTING SLAB RUN CONDUITS, EXISTING CEILING DROPS AND BRANCH CIRCUITS ARE PROTECTED DURING DEMOLITION FOR REUSE IS POSSIBLE.
- 6 EXISTING LIGHTING FIXTURES SHALL BE DISCONNECTED AND REMOVED. SAFE-OF BRANCH CIRCUITS, SWITCH LEGS AND CONTROLS FOR REUSE, WHERE REQUIRED.

NOTES:

1. REFER TO DWG. E0.1 FOR SYMBOL LIST, NOTES AND ABBREVIATIONS.
2. 'EX' DENOTES EXISTING TO REMAIN. 'ED' DENOTES EXISTING TO BE REMOVED.
3. EXISTING RTU HVAC SYSTEMS ARE TO REMAIN. EXISTING FEEDERS AND CIRCUIT BREAKERS SHALL REMAIN.

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT:

Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr,
Jarrettsville, MD, 21084
410-776-5868

PROJECT




7-ELEVEN 42655
CST

**1360 NC 24-87, CAMERON NC
28326**

DNC TITLE:

ELECTRICAL DEMOLITION
FLOOR PLAN

	ISSUE / REVISIONS					
0	06/06/25	ISSUE FOR BID AND PERMIT				
	(DATE)	(DESCRIPTION)				



DRAWN BY: JAL	CHECKED BY: JAL
SCALE: $1/4" = 1'-0"$	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:

E1.0

E1.1

F

E

D

C

B

A

PANELBOARD EXIST. A SCHEDULE																																																					
VOLTAGE: 208Y/120V PHASE: 3Ø WIRE: 4W AIC RATING: EXISTING				BUS RATING: 225A MAIN BREAKER: 200A MCB NEUTRAL SIZE: 100%				LOCATION: ON PLAN MOUNTING: SURFACE ISO. GROUND: N SPD: N																																													
NOTE	TYPE	LOAD	DESCRIPTION	BRANCH C/B P	CIRCUIT # Ø #	BRANCH C/B P	DESCRIPTION	LOAD	TYPE	NOTE																																											
	L	200	EXISTING DRINK COOLER LTG	20	1 1 A 2	30 3	EXISTING SURGE PROTECTOR																																														
	R	200	EXISTING COOLER EVAP	20	1 3 B 4	- -																																															
			EXISTING SPARE	20	1 5 C 6	- -																																															
	R	400	EXISTING DRINK COOLER HEAT	20	1 7 A 8	20 1	EXISTING SPARE																																														
	R	1000	EXISTING MENS WATER HEATER	20	1 9 B 10	20 1	EXISTING SPARE																																														
	L	300	EXISTING EXIT SIGNS	20	1 11 C 12	20 1	EXISTING NEON	540	L																																												
	L	200	EXISTING REST ROOM LTG	20	1 13 A 14	20 1	EXISTING TMS POWER	200	R																																												
	R	300	EXISTING HEAT TAPE RECEPT	20	1 15 B 16	20 1	EXISTING LOAD	400	R																																												
	R	180	EXISTING BEER COOLER RECEPT	20	1 17 C 18	50 3	EXISTING QUIZNOS TOASTER	360	R																																												
	L	200	EXISTING BEER COOLER LTG	20	1 19 A 20	- -	OVEN	4800	R																																												
	R	300	EXISTING BEER COOL DR HEAT	20	1 21 B 22	- -		4800	R																																												
	R	600	EXISTING AIR MACHINE	20	1 23 C 24	- -																																															
					25 A 26																																																
					27 B 28																																																
					29 C 30																																																
					31 A 32																																																
					33 B 34																																																
					35 C 36																																																
					37 A 38																																																
					39 B 40																																																
					41 C 42																																																
<table><tr><th>TYPE</th><th>CONNECTED LOAD (VA)</th><th>NEC DEMAND FACTOR</th><th>NEC DEMAND LOAD (VA)</th></tr><tr><td>R RECEPTACLES ≤ 10KVA</td><td>10000</td><td>1.00</td><td>10000</td></tr><tr><td>RECEPTACLES > 10KVA</td><td>7980</td><td>0.50</td><td>3990</td></tr><tr><td>L LIGHTING</td><td>1200</td><td>1.25</td><td>1500</td></tr><tr><td>M LARGEST MOTOR</td><td>-</td><td>1.25</td><td>-</td></tr><tr><td>REMAINING MOTORS</td><td>-</td><td>1.00</td><td>-</td></tr><tr><td>H HEATING (RESISTIVE)</td><td>-</td><td>1.25</td><td>-</td></tr><tr><td>E EQUIPMENT</td><td>-</td><td>1.00</td><td>-</td></tr><tr><td>K KITCHEN EQUIPMENT</td><td>-</td><td>1.00</td><td>-</td></tr><tr><td>TOTAL</td><td>19180</td><td></td><td>15490</td></tr></table> <div><div>PHASE A LOAD = 6000 VA PHASE B LOAD = 7000 VA PHASE C LOAD = 6180 VA</div><div>NEC DEMAND LOAD = 43 A SPARE CAPACITY = 157 A TOTAL AVAILABLE = 200 A</div></div>														TYPE	CONNECTED LOAD (VA)	NEC DEMAND FACTOR	NEC DEMAND LOAD (VA)	R RECEPTACLES ≤ 10KVA	10000	1.00	10000	RECEPTACLES > 10KVA	7980	0.50	3990	L LIGHTING	1200	1.25	1500	M LARGEST MOTOR	-	1.25	-	REMAINING MOTORS	-	1.00	-	H HEATING (RESISTIVE)	-	1.25	-	E EQUIPMENT	-	1.00	-	K KITCHEN EQUIPMENT	-	1.00	-	TOTAL	19180		15490
TYPE	CONNECTED LOAD (VA)	NEC DEMAND FACTOR	NEC DEMAND LOAD (VA)																																																		
R RECEPTACLES ≤ 10KVA	10000	1.00	10000																																																		
RECEPTACLES > 10KVA	7980	0.50	3990																																																		
L LIGHTING	1200	1.25	1500																																																		
M LARGEST MOTOR	-	1.25	-																																																		
REMAINING MOTORS	-	1.00	-																																																		
H HEATING (RESISTIVE)	-	1.25	-																																																		
E EQUIPMENT	-	1.00	-																																																		
K KITCHEN EQUIPMENT	-	1.00	-																																																		
TOTAL	19180		15490																																																		
NOTES: 1 NEW REQUIRED BRANCH CIRCUITS SHALL BE INSTALLED IN SPACES CREATED DURING DEMOLITION.																																																					

PANELBOARD EXIST. B SCHEDULE													
VOLTAGE: 208Y/120V PHASE: 3Ø WIRE: 4W AIC RATING: EXISTING				BUS RATING: 225A MAIN BREAKER: 200A MCB NEUTRAL SIZE: 100%				LOCATION: ON PLAN MOUNTING: SURFACE ISO. GROUND: N SPD: N					
NOTE	TYPE	LOAD	DESCRIPTION	BRANCH		CIRCUIT		BRANCH		DESCRIPTION	LOAD	TYPE	NOTE
	R	1600	EXISTING COFFEE RECEPT	C/B	P	#	Φ	#	C/B	P			
	R	1600		20	2	1	A	2	80	3	EXISTING HVAC #1	5700	E
	R	1600		.	-	3	B	4	.	-		5700	E
	R	1500	EXISTING DRINK RECEPT	20	2	5	C	6	.	-		5700	E
	R	1500		.	-	7	A	8	20	1	EXISTING HALLWAY RECEPT	180	R
	R	400	EXISTING DRINK RECEPT	20	1	9	B	10	20	1	EXISTING DSL RECEPT	200	R
	R	400	EXISTING DRINK RECEPT	20	1	11	C	12	20	1	EXISTING DSL RECEPT	540	R
	R	360	EXISTING LEFT FRONT GFI	20	1	13	A	14	20	1	EXISTING RECEPTACLE	180	R
	R	600	EXISTING ATM RECEPTACLE	20	1	15	B	16	20	1	EXISTING FLOOR BOX RECEPT.	400	R
	R	180	EXISTING LEFT FRONT GFI	20	1	17	C	18	20	1	EXISTING FLOOR BOX RECEPT.	360	R
	R	180	EXISTING LEFT FT WALL REC	20	1	19	A	20	20	2	EXISTING QUIZNOS COOLER	1500	R
	R	180	EXISTING COUNTER PLUG	20	1	21	B	22	.	-	CONDENSER	1500	R
	R	180	EXISTING COUNTER PLUG	20	1	23	C	24	30	2	EXISTING QUIZNOS FREEZER	1800	R
	R	360	EXISTING GONDOLA RECEPT	20	1	25	A	26	.	-	CONDENSER	1800	R
	R	360	EXISTING GONDOLA RECEPT	20	1	27	B	28	20	1	EXISTING CASH COUNTER	400	R
	R	360	EXISTING GONDOLA RECEPT	20	1	29	C	30	20	1	EXISTING LOTTERY	300	R
	R	360	EXISTING GONDOLA RECEPT	20	1	31	A	32	20	1	EXISTING COUNTER REC	400	R
	R	180	EXISTING SAFE	20	1	33	B	34	20	1	EXISTING COUNTER REC	400	R
	R	400	EXISTING CASH COUNTER	20	1	35	C	36					
						37	A	38					
						39	B	40					
						41	C	42					
						</							

PANELBOARD EXIST. C SCHEDULE																																																					
VOLTAGE: 208Y/120V PHASE: 3Φ WIRE: 4W AIC RATING: EXISTING				BUS RATING: 225A MAIN BREAKER: 200A MCB NEUTRAL SIZE: 100%				LOCATION: ON PLAN MOUNTING: SURFACE ISO. GROUND: N SPD: N																																													
NOTE	TYPE	LOAD	DESCRIPTION	BRANCH		CIRCUIT		BRANCH		DESCRIPTION		LOAD	TYPE																																								
	E	8600	EXISTING HVAC #2	90	3	1	A 2	50	2	EXISTING INSTAHOT	4100	E																																									
	E	8600		-	-	3	B 4	-	-	EXISTING DRINK RECEPT	4100	E																																									
	E	8600		-	-	5	C 6	20	1	EXISTING EXHAUST FAN	300	E																																									
	L	200	EXISTING WALK IN COOLER LTG	20	1	7	A 8	20	1	EXISTING DRINK RECEPT	400	R																																									
	R	200	EXISTING WALK IN COOL EVAP	20	1	9	B 10	20	1	EXISTING GENERAL RECEPT	360	R																																									
	R	300	EXISTING WALK IN COOL HEAT	20	1	11	C 12	20	1	EXISTING DRINK RECEPT	540	R																																									
	R	300	EXISTING WALK IN COOL FRAME	20	1	13	A 14	20	1	EXISTING ICE MACHINE	600	R																																									
	R	180	EXISTING CASH REGIST. RECEPT	20	1	15	B 16	20	1	EXISTING GENERAL RECEPT	400	R																																									
	R	180	EXISTING COUNTER RECEPT	20	1	17	C 18	20	1	EXISTING HALLWAY RECEPT	360	R																																									
	R	180	EXISTING CASH REGIST. RECEPT	20	1	19	A 20	-	-																																												
	R	180	EXISTING COUNTER RECEPT	20	1	21	B 22	20	1	EXISTING QUIZNOS COUNTER	360	R																																									
	R	400	EXISTING HOT BOX GFI	20	1	23	C 24	20	1	EXISTING QUIZNOS COUNTER	360	R																																									
						25	A 26	20	1	EXISTING QUIZNOS CASH	360	R																																									
						27	B 28	20	1	EXISTING QUIZNOS COUNTER	360	R																																									
						29	C 30																																														
						31	A 32	20	2	EXISTING SANDWICH BOX	1600	R																																									
						33	B 34	-	-		1600	R																																									
						35	C 36																																														
						37	A 38																																														
						39	B 40																																														
						41	C 42																																														
<table><tr><th>TYPE</th><th>CONNECTED LOAD (VA)</th><th>NEC DEMAND FACTOR</th><th>NEC DEMAND LOAD (VA)</th></tr><tr><td>R RECEPTACLES ≤ 10KVA</td><td>9040</td><td>1.00</td><td>9040</td></tr><tr><td>RECEPTACLES > 10KVA</td><td>-</td><td>0.50</td><td>-</td></tr><tr><td>L LIGHTING</td><td>200</td><td>1.25</td><td>250</td></tr><tr><td>M LARGEST MOTOR</td><td>-</td><td>1.25</td><td>-</td></tr><tr><td>REMAINING MOTORS</td><td>-</td><td>1.00</td><td>-</td></tr><tr><td>H HEATING (RESISTIVE)</td><td>-</td><td>1.25</td><td>-</td></tr><tr><td>E EQUIPMENT</td><td>34300</td><td>1.00</td><td>34300</td></tr><tr><td>K KITCHEN EQUIPMENT</td><td>-</td><td>1.00</td><td>-</td></tr><tr><td>TOTAL</td><td>43540</td><td></td><td>43590</td></tr></table> <div><div>PHASE A LOAD = 16340 VA</div><div>PHASE B LOAD = 16300 VA</div><div>PHASE C LOAD = 10900 VA</div><div>NEC DEMAND LOAD = 121 A</div><div>SPARE CAPACITY = 79 A</div><div>TOTAL AVAILABLE = 200 A</div></div>														TYPE	CONNECTED LOAD (VA)	NEC DEMAND FACTOR	NEC DEMAND LOAD (VA)	R RECEPTACLES ≤ 10KVA	9040	1.00	9040	RECEPTACLES > 10KVA	-	0.50	-	L LIGHTING	200	1.25	250	M LARGEST MOTOR	-	1.25	-	REMAINING MOTORS	-	1.00	-	H HEATING (RESISTIVE)	-	1.25	-	E EQUIPMENT	34300	1.00	34300	K KITCHEN EQUIPMENT	-	1.00	-	TOTAL	43540		43590
TYPE	CONNECTED LOAD (VA)	NEC DEMAND FACTOR	NEC DEMAND LOAD (VA)																																																		
R RECEPTACLES ≤ 10KVA	9040	1.00	9040																																																		
RECEPTACLES > 10KVA	-	0.50	-																																																		
L LIGHTING	200	1.25	250																																																		
M LARGEST MOTOR	-	1.25	-																																																		
REMAINING MOTORS	-	1.00	-																																																		
H HEATING (RESISTIVE)	-	1.25	-																																																		
E EQUIPMENT	34300	1.00	34300																																																		
K KITCHEN EQUIPMENT	-	1.00	-																																																		
TOTAL	43540		43590																																																		
NOTES: 1 NEW REQUIRED BRANCH CIRCUITS SHALL BE INSTALLED IN SPACES CREATED DURING DEMOLITION.																																																					

PANELBOARD EXIST. D SCHEDULE														
VOLTAGE: 208Y/120V PHASE: 3Ø WIRE: 4W AIC RATING: EXISTING				BUS RATING: 225A MAIN BREAKER: 200A MCB NEUTRAL SIZE: 100%				LOCATION: ON PLAN MOUNTING: SURFACE ISO. GROUND: N SPD: N						
NOTE	TYPE	LOAD	DESCRIPTION	BRANCH		CIRCUIT		BRANCH		DESCRIPTION		LOAD	TYPE	NOTE
	E	2800	EXISTING BEER CAVE CONDEN.	30	3	1	A	2	30	3	EXISTING DRINK CONDEN.	2800	E	
	E	2800		-	-	3	B	4	-	-		2800	E	
	E	2800		-	-	5	C	6	-	-		2800	E	
	L	300	EXISTING PANEL ROOM LTG	20	1	7	A	8	20	1	EXISTING STOR/OFFICE LTG	300	L	
	R	360	EXISTING REST./OUTSIDE GFI	20	1	9	B	10	20	1	EXISTING STOR/OFFICE REC	400	R	
	R	200	EXISTING WATER FOUNTAIN GFI	20	1	11	C	12	20	1	EXISTING WOMENS WH	540	R	
	R	800	EXISTING WATER HEATER	20	1	13	A	14	20	1	EXISTING WH	600	R	
	R	400	EXISTING DRINK COUNTER REC	20	1	15	B	16	20	1	EXISTING QUIZNOS REC	400	R	
	R	400	EXISTING DRINK COUNTER REC	20	1	17	C	18	20	1	EXISTING QUIZNOS REC	360	R	
	R	400	EXISTING DRINK COUNTER REC	20	1	19	A	20	20	1	EXISTING QUIZNOS REC	400	R	
	R	400	EXISTING DRINK COUNTER REC	20	1	21	B	22	20	1	EXISTING QUIZNOS REC	400	R	
	R	400	EXISTING DRINK COUNTER REC	20	1	23	C	24	30	2	EXISTING INSTAHOT	1600	E	
	R	400	EXISTING DRINK COUNTER REC	20	1	25	A	26	-	-		1600	E	
	R	400	EXISTING DRINK COUNTER REC	20	1	27	B	28	30	3	EXISTING REACH IN BEER	2800	E	
	R	400	EXISTING FLY FAN	20	1	29	C	30	-	-	COOLER CONDENSER	2800	E	
	E	1600	EXISTING COFFEE MACHINE	30	2	31	A	32	-	-		2800	E	
	E	1600		-	-	33	B	34						
						35	C	36						
						37	A	38						
						39	B	40						
						41	C	42						


TYPE		CONNECTED LOAD (VA)	NEC DEMAND FACTOR	NEC DEMAND LOAD (VA)
R	RECEPTACLES ≤ 10KVA	7760	1.00	7760
R	RECEPTACLES > 10KVA	-	0.50	-
L	LIGHTING	600	1.25	750
M	LARGEST MOTOR	-	1.25	-
	REMAINING MOTORS	-	1.00	-
H	HEATING (RESISTIVE)	-	1.25	-
E	EQUIPMENT	31600	1.00	31600
K	KITCHEN EQUIPMENT	-	1.00	-
TOTAL		39960		40110

PHASE A LOAD =	14800	VA
PHASE B LOAD =	12760	VA
PHASE C LOAD =	12400	VA

NEC DEMAND LOAD =	111	A
SPARE CAPACITY =	89	A
TOTAL AVAILABLE =	200	A

NOTES: 1 NEW REQUIRED BRANCH CIRCUITS SHALL BE INSTALLED IN SPACES CREATED DURING DEMOLITION.

F
E
D
C
B
A



1 PARTIAL EXISTING ELECTRICAL SINGLE LINE DIAGRAM
N.T.S.

2 INTERIOR ELEVATION - STOREFRONT
3/8" = 1'-0"

COMcheck Software Version COMcheckWeb
Interior Lighting Compliance Certificate

Project Information
Energy Code: 2018 IECC
Project Title: 25-008 7-11 Cameron, NC
Project Type: Alteration

Construction Site: 1360 NC 24-87 CAMERON 28326
Owner/Agent: Designer/Contractor:

A Area Category	B Floor Area (ft ²)	C Allowed Watts / ft ²	D Allowed Watts
1-Retail	4028	1.36	4270
Total Allowed Watts = 4270			

Proposed Interior Lighting Power

A Fixture ID : Description / Lamp / Wattage Per Lamp / Ballast	B Lamps/ Fixture	C # of Fixture	D Fixture Watt.	E (C X D)
Retail (4028 sq.ft.)				
LED RECESSED 2'x4': A3: Other:	1	3	36	108
LED RECESSED 1'x4': A4: Other:	1	40	32	1280
LED SURFACE 1'x4': D54: Other:	1	6	32	192
Total Proposed Watts = 1580				

Interior Lighting PASSES

Interior Lighting Compliance Statement
Compliance Statement: The proposed interior lighting alteration project represented in this document is consistent with the building plans, specifications, and other calculations submitted with this permit application. The proposed interior lighting systems have been designed to meet the 2018 IECC requirements in COMcheck Version COMcheckWeb and to comply with any applicable mandatory requirements listed in the Inspection Checklist.

Name - Title: Signature: Date:

Project Title: 25-008 7-11 Cameron, NC
Data filename: Report date: 05/31/25
Page 1 of 5

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT:
Joseph A. Loiero, Jr.
NC PE License #042310
2007 Twin Lakes Dr.
Jarrettsville, MD, 21084
410-776-5868

PROJECT:
7-ELEVEN
**7-ELEVEN 42655
CST**
**1360 NC 24-87, CAMERON NC
28326**

DRG. TITLE:
ELECTRICAL ONE-LINE AND DETAILS

DATE		DESCRIPTION

6/06/25
Designed by: 186720047ASAB
SEAL
042310
J. A. LOIERO, JR.
ENGINEER

DRAWN BY: JAL	CHECKED BY: JAL
SCALE: 1/4" = 1'-0"	PROJECT No: JAL#25-008
DATE: 6/06/25	FILE NAME:
SHEET No:	

E1.3



Scale: $1/4" = 1'$

- KEY:**
360 - 360 DEGREE CAMERA
180 - 180 DEGREE CAMERA
PVM - PERSONAL VIDEO MONITOR
WDR - WIDE DYNAMIC RANGE

E1.4


LOW VOLTAGE WIRING TABLE								
FROM	TO	DESCRIPTION	ID	CABLE	QTY	NOTE		
PHONE BOARD	SALES COUNTER	VOICE	T1	CAT6	1			
	SALES COUNTER	FAX	T2	CAT6	3			
	SALES (ATM)	ATM	T3	CAT6	1			
ISP DESK	SALES COUNTER	POS 1	D1	CAT6	4	2		
	SALES COUNTER	POS 2	D2	CAT6	4	2		
	SALES COUNTER	POS 3	D3	CAT6	4	2		
	SALES COUNTER	SAFE	D7	CAT6	1			
	SALES COUNTER	MONEY ORDER	D8	CAT6	2			
	SALES COUNTER	LOTTO	D9	CAT6	1			
	ELECTRICAL	EMS	D10	CAT6	1			
	SALES	AP-11A	D11.1	CAT6	1			
	SALES	AP-11B	D11.2	CAT6	1			
	VAULT COOLER	AP-11C	D11.3	CAT6	1			
	BEER CAVE	AP-11D	D11.4	CAT6	1			
	ELECTRICAL	FUELING	D12	CAT6	4	1		
	TELECOM	RIS / BROADBAND	D13	CAT6	4			
	SALES (ATM)	ATM	D14	CAT6	1			
	MANAGER	DVR	D15	CAT6	1			
	SALES	Q5IC SPEAKER	D20.1	CAT6	1			
	SALES	Q5IC SPEAKER	D20.2	CAT6	1			
	SALES	Q5IC SPEAKER	D20.3	CAT6	1			
	SALES COUNTER	DMB SALES	D21.1	CAT6	1			
	SALES COUNTER	DMB SALES	D21.2	CAT6	1			
	SALES COUNTER	DMB SALES	D21.3	CAT6	1			
	SALES	AUTO VOLUME ADJUSTMENT (Q5IC)	L4	24/3 SHLD	1	3		
	MANAGER OFFICE	SALES COUNTER	SALES COUNTER 360 CAMERA	V1	CAT6	1		
		SALES	SALES 360 CAMERA	V2	CAT6	1		
		SALES	FRONT 180 CAMERA	V3	CAT6	1		
		SALES	FRONT WDR BOX CAMERA	V4	CAT6	1		
		SALES	FRONT PUBLIC VIEW MONITOR	V5	CAT6	1		
		SALES	SALES 360 CAMERA	V6	CAT6	1		
		SALES	SALES 360 CAMERA	V7	CAT6	1		
		SALES	SALES 360 CAMERA	V8	CAT6	1		
EXTERIOR		EXTERIOR CAMERA (FACING REAR DOOR)	V9	CAT6	1			
EXTERIOR		EXTERIOR CAMERA (FACING AUTO CANOPY)	V10	CAT6	1			
EXTERIOR		EXTERIOR CAMERA (FACING AUTO CANOPY)	V11	CAT6	1			
BEER CAVE		SALES 360 CAMERA	V12	CAT6	1			
SALES		SALES 360 CAMERA	V13	CAT6	1			
MANAGER		MANAGER 360 CAMERA	V14	CAT6	1			
FOOD PREP		FOOD PREP 360 CAMERA	V15	CAT6	1			
MANAGER		KEYPAD OUTSIDE MANAGERS OFFICE	L1	22/4	1			
SALES	FRONT PVM POWER	L2	18/2	1				
ELECTRIC ROOM	SALES COUNTER	INTERCOM WIRING	L5		1	1		

NOTES:

[CONTRACTOR TO VERIFY ALL EXISTING LOW VOLTAGE EQUIPMENT AND FIELD COORDINATE QUANTITIES AND LOCATIONS OF EQUIPMENT PRIOR TO ORDERING]

1. EC TO PROVIDE AND INSTALL CONDUIT AND PULL STRING. WIRING AND TERMINATIONS PROVIDED BY FUELING CONTRACTOR.
2. ALL CABLING SHALL BE CAT6 WIRED TO TIA/EIA 568B EXCEPT FOR POS REGISTERS WHICH SHALL BE WIRED TO TIA/EIA 568A.
3. BELDEN 8406 OR EQUIVALENT.
4. INSTALL ONLY WHEN REQUIRED.

1 LOW VOLTAGE TABLE
N.T.S.



2 STANDARD 7-ELEVEN IP CCTV TOPOLOGY

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT:
Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr,
Jarrettsville, MD, 21084
410-776-5868

CONSULTANT:

PROJECT:



**7-ELEVEN 42655
CST**

**1360 NC 24-87, CAMERON NC
28326**


DNG. TITLE:

LOW VOLTAGE DETAILS

ISSUE REVISIONS		
0	06/06/25	ISSUE FOR BID AND PERMIT
DATE	DESCRIPTION	

6/06/25

Docusigned by:



DRAWN BY: JAL	CHECKED BY: JAL
SCALE: 1/4" = 1'-0"	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:

SHEET NO:

E1.5



LIGHTING PLAN

LIGHT FIXTURE SCHEDULE

KEYED NOTES

- 1) ALL NEW LIGHTING FIXTURES, EM LIGHTING AND EXIT SIGNALS IN THIS AREA SHALL BE CONNECT TO EXISTING BRANCH CIRCUITS/SWITCH LEGS. MAKE SAFE-OFF DURING DEMOLITION. ALL LIGHTING CONTROLS SHALL BE REUSED, WHEN REQUIRED.
- 2) NEW LIGHTING FIXTURES ARE TO BE INSTALLED IN THIS AREA AND CONNECTED TO LOCAL EXISTING LIGHTING BRANCH CIRCUITS/SWITCH LEGS. EXISTING LIGHTING CONTROLS ARE TO REMAIN, WHERE REQUIRED.
- 3) EXISTING ELECTRICAL PANELS TO REMAIN. REFER TO ONE-LINE FOR MORE INFORMATION.
- 4) EMERGENCY LIGHT FIXTURE. CONNECT TO EXISTING LIGHTING CIRCUIT IN AREA AHEAD OF ALL SWITCHES. COORDINATE SELECTION WITH ARCHITECT.
- 5) LIGHTING FIXTURES, CONTROLS AND LIGHTING BRANCH CIRCUITS IN THIS AREA ARE EXISTING TO REMAIN.

GENERAL NOTES

THE INTENT OF THE PROJECT IS AN ALTERATION TO REPLACE EXISTING LIGHTING FIXTURES, EQUIPMENT AND DEVICES IN A LIMITED AREA OF THE BUILDING AND TO REUSE EXISTING BRANCH CIRCUITS IN THE AREA WHERE POSSIBLE.

NO ADDITIONAL LIGHTING OR DEVICE ELECTRICAL LOAD IS EXPECTED. BE ADDED TO THE EXISTING BRANCH CIRCUITS.

LIGHTING FIXTURES ARE TO BE SELECTED BY OWNER/ARCHITECT.

GENERAL NOTES

THE INTENT OF THE PROJECT IS AN ALTERATION TO REPLACE EXISTING LIGHTING FIXTURES, EQUIPMENT AND DEVICES IN A LIMITED AREA OF THE BUILDING AND TO REUSE EXISTING BRANCH CIRCUITS IN THE AREA WHERE POSSIBLE.

NO ADDITIONAL LIGHTING OR DEVICE ELECTRICAL LOAD IS
EXPECTED BE ADDED TO THE EXISTING BRANCH CIRCUIT.

LIGHTING FIXTURES ARE TO BE SELECTED BY
OWNER/ARCHITECT.

NOTES

1. REFER TO DWG. E0.1 FOR SYMBOL LIST, NOTES AND ABBREVIATIONS.
2. LIGHTING FIXTURE SELECTIONS SHALL BE COORDINATED WITH THE ARCHITECT.



**7-ELEVEN 42655
CST**


1360 NC 24-87, CAMERON NC
28326

DNG. TITLE

LIGHTING PLAN


ISSUE REVISIONS		
0	06/06/25	ISSUE FOR BID AND PERMIT
	DATE	DESCRIPTION

6/06/25



DRAWN BY: JAL	CHECKED BY: JAL
SCALE: 1/4" = 1'-0"	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:


E2.0



1 HVAC DEMOLITION PLAN
Scale: 1/4"=1'

HVAC Drawing Notes: 1 2 3

- EXISTING THERMOSTAT TO REMAIN. (TYPICAL)
- EXISTING SA DIFFUSER TO REMAIN.
- EXISTING SA DIFFUSER TO REMAIN.
- RESTROOMS ARE OUTSIDE SCOPE OF WORK. EXISTING EXHAUST FANS TO REMAIN.



2 HVAC NEW WORK PLAN
Scale: 1/4"=1'

HVAC NOTES

- NOTES APPLY TO ALL MECHANICAL SHEETS.
- EACH CONTRACTOR IS RESPONSIBLE FOR HAVING THOROUGH KNOWLEDGE OF ALL DRAWINGS AND SPECIFICATIONS AS THEY RELATE TO THIS WORK. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED DUE TO LACK OF THIS KNOWLEDGE.
- PROVIDE ALL MATERIALS FOR A COMPLETE INSTALLATION IN ALL RESPECTS READY FOR INTENDED USE AND IN STRICT ACCORDANCE WITH STATE AND LOCAL CODES AND MANUFACTURER'S RECOMMENDATIONS.
- SPRINKLER HEAD AND LIGHTING FIXTURE LOCATIONS TAKE PRECEDENCE OVER DIFFUSER LOCATIONS. COORDINATE WITH ELECTRICAL CONTRACTOR AND FIRE PROTECTION CONTRACTOR.
- DUCTWORK IDENTIFICATION AND INSTALLATION TO ADHERE TO GOVERNING CODES.
- TYPICAL BRANCH DUCT FITTING DETAIL IS APPLICABLE THROUGHOUT. FLEXIBLE DUCTWORK IS ONLY PERMITTED FOR FINAL CONNECTION - MAX LENGTH OF 8'-0".
- FURNISH AND INSTALL VOLUME BALANCE DAMPERS AT ALL BRANCH DUCTS TO DIFFUSERS. LOCATE DAMPERS A MINIMUM 4'-0" AWAY FROM DIFFUSERS. PROVIDE ACCESS AS REQUIRED.
- ALL CEILING DIFFUSERS ARE 4-WAY PATTERN UNLESS SHOWN OTHERWISE.

MECHANICAL SYMBOLS

	RECTANGULAR DUCT 18" WIDE BY 12" DEEP (INSIDE CLEAR DIMENSIONS)
	12" DIAMETER ROUND DUCT (INSIDE CLEAR DIMENSIONS)
	SUPPLY DUCT IN SECTION
	RETURN OR EXHAUST DUCT IN SECTION
	ELBOW WITH TURNING VANES
	TEE WITH TURNING VANES
	ROUND (OR OVAL) ELBOW
	SUPPLY AIR DIFFUSER WITH ROUND SUPPLY DUCT
	RETURN OR EXHAUST AIR DIFFUSER WITH ROUND DUCT
	DIFFUSER OR GRILLE TYPE & CFM
	SPACE/HUMIDITY/CO2 COMBO SENSOR
	TEMPERATURE/HUMIDITY COMBO SENSOR
	SMOKE DETECTOR
	SMOKE DETECTOR TEST/RESET STATION
	HORN & STROBE ANNUNCIATOR
	PRESSURE TRANSDUCER
	BALANCE DAMPER

LAY-IN CEILING NOTE: SUPPLY AIR DEVICES SHALL BE INDICATED AS 3-WAY AIR DEVICES WHEN LOCATED WITHIN A 10'-0" RADIUS OF THE OPEN AIR SANDWICH CASE.

BRIAN D. LAUG, AIA NCARB ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT

Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr.
Jarrettsville, MD, 21084
410-776-5868

PROJECT



**7-ELEVEN 42655
CST**

**1360 NC 24-87, CAMERON NC
28326**


DATE

MECHANICAL PLANS

DATE

DATE	DESCRIPTION
06/06/25	ISSUE FOR BID AND PERMIT
06/06/25	REVISION

6/06/25



DRAWN BY	CHECKED BY
JAL	JAL
SCALE	PROJECT NO.
1/4" = 1'-0"	JAL#25-008
DATE	FILE NAME
6/06/25	

SHEET NO.

M1.0

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT:


Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr,
Jarrettsville, MD, 21084
410-776-5868

Mechanical Drawing Notes:

1	2	#
---	---	---

1. CONDENSING UNIT TO BE INSTALLED AND CONNECTED COMPLETE TO THE ASSOCIATED PIECE OF STORE EQUIPMENT. THIS INCLUDES ALL POWER, CONTROL WIRING, AND REFRIGERATION LINES. COORDINATE INSTALLATION WITH MANUFACTURER'S INSTALLATION REQUIREMENTS. LOCATE UNITS TO MINIMIZE REFRIGERANT RUNS AND MAINTAIN MAINTENANCE AND CODE REQUIRED CLEARANCES AND MAINTENANCE CLEARANCES OF EXISTING EQUIPMENT. (TYPICAL)
2. REFRIGERANT PIPE SET THRU WALL TO GRADE MOUNTED CONDENSER. INSTALL, SIZE AND TRAP PER MANUFACTURERS INSTRUCTIONS. (TYPICAL)
3. REFRIGERANT PIPE DOWN WITHIN WALL TO EQUIPMENT. INSTALL, SIZE AND TRAP PER MANUFACTURERS INSTRUCTIONS. (TYPICAL)



2 MECHANICAL FLOOR PLAN
Scale: 1/4" = 1'

MECHANICAL MANUFACTURER CONTACT INFORMATION			
MANUFACTURER	CONTACT	PHONE	EMAIL
HEATCRAFT WORLDWIDE REFRIGERATION / BOHN	RYAN KELLY	678-472-9885	RYAN.KELLY@HEATCRAFTRPD.COM

REFRIGERATION REMOTE CONDENSING UNIT SCHEDULE													
TAG	QTY	ORACLE	MFR	MODEL	SUPPLIER	SUPPLIER PART NUMBER	SERVICE	ELECTRICAL			WEIGHT (LBS)	FURNISH BY	INSTALL BY
								V/PH	MCA	MOCPP			
CU-2	1	03309785	FBD	FBD-DRC	FBD PARTNERSHIP LP	-	DUAL CIRCUIT SLURPEE	208/2	2.2	15	143	TURNKEY	GC
CU-3	1	03309784	FBD	FBD-SRC	FBD PARTNERSHIP LP	-	FROZEN LEMONADE	208/2	1.8	15	105	TURNKEY	GC
CU-4	1	03164149	HOSHIZAKI	URC-5F	HOSHIZAKI	-	ICE MAKER	120/1	--	--	60	TURNKEY	GC
CU-5	1	TBD	BOHN	TBD	HEATCRAFT	-	1-DOOR MERCHANDISER	208/2	20	20	169	TURNKEY	GC
CU-6	1	00130388	BOHN	BZT010M6BF	HEATCRAFT	-	4' DISPLAY CASE	208-230/1	38	40	209	TURNKEY	GC
CU-7	1	TBD	BOHN	TBD	HEATCRAFT	-	6' DISPLAY CASE	208-230/1	38	40	209	TURNKEY	GC

- NOTES:
1. CONTRACTOR TO VERIFY ALL EQUIPMENT SELECTIONS WITH LATEST 7-11 STANDARDS AND 7-11 EQUIPMENT REPRESENTATIVES PRIOR TO ORDERING. NOT ALL EQUIPMENT SELECTIONS WERE PROVIDED. VERIFY SCHEDULE INFORMATION
 2. FIELD COORDINATE LOCATIONS OF CONDENSERS TO MINIMIZE REFRIGERANT RUNS, SIZE, TRAP AND INSTALL PER MANUFACTURERS RECOMMENDATIONS. CONTRACTOR TO CONSULT FACTORY FOR ALL LONG LINE SET SIZING AND FIELD COORDINATE INSTALLATION.

PROJECT:



**7-ELEVEN 42655
CST**

**1360 NC 24-87, CAMERON NC
28326**


DNG. TITLE:

MECHANICAL ROOF PLAN

SUE/REVISIONS:

0	06/06/25	SCHE FOR BID AND PERMIT
	DATE	DESCRIPTION

06/25



DocuSigned by:

3E7250D67A54BA

DRAWN BY: JAL	CHECKED BY: JAL
SCALE: 1/4" = 1'-0"	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:

SHEET NO:

M1.1

F


E

D


C

B

A




SUPPLY AIR DIFFUSER KEY
NO SCALE



FLEXIBLE DUCT RUN-OUT SUPPORT DETAIL
NO SCALE


- NOTES:
1) FLEXIBLE DUCT SHOULD EXTEND STRAIGHT FOR SEVERAL INCHES FROM RECTANGULAR DUCT CONNECTION BEFORE BENDING.
2) USE RIGID DUCTWORK WHEN FLEXIBLE DUCT LENGTH EXCEEDS 6'-0" LENGTH.



AIR-TITE SIZE CHART			
DUCT SIZE	CONNECTION RING	DUCT SIZE	CONNECTION RING
5"	6"	9"	12"
6"	9"	10"	13"
7"	10"	11"	15"
8"	11"	12"	17"


NOTE:
WHERE CONNECTION RING SIZE IS LARGER THAN SUPPLY DUCT, THEN CONNECTION RING SHALL BE CRIMPED OVER DUCT AND CONNECTED, SCREWED & SEALED ON TOP AND BOTTOM OF SUPPLY DUCT.

AIR-TITE SPIN-IN FITTING DETAIL
NO SCALE




RETURN AIR GRILLE/EXHAUST REGISTER MOUNTING DETAIL
NO SCALE

- NOTES:
1) ALL EXHAUST REGISTERS LOCATED IN WET AREAS SHALL BE ALUMINUM.
2) ALL EXHAUST AIR DUCTWORK CONVEYING MOISTURE SHALL BE ALL ALUMINUM.




1 BRANCH DUCT DETAIL
1/4" = 1'-0"



2 REFRIGERANT LINE SUPPORT DETAIL
1/4" = 1'-0"



COORDINATE ALL REFRIGERANT PIPING AND EQUIPMENT INSTALLATION WITH EQUIPMENT VENDER. SIZE TRAP AND INSTALL PER MANUFACTURERS RECOMMENDATIONS



NOTE:
MECHANICAL CONTRACTOR SHALL LEVEL EQUIPMENT CURB PRIOR TO MOUNTING UNIT.

3 CONDENSING UNIT DETAIL
1/4" = 1'-0"

LEGEND	
A	SYRUP LINE BUNDLE WALL CHASE EVERBILT - 12"Wx17.75"L STAINLESS STEEL RECESSED WALL CHASE/DRYER VENT BOX - MODEL MDRBHD; FURNISHED AND INSTALLED BY MECHANICAL CONTRACTOR. https://www.homedepot.com/p/Everbilt-12-in-W-x-17-75-in-L-Metal-Recessed-Dryer-Vent-Box-MDRBHD/313366890
B	REFRIGERANT LINE WALL CHASE OATEY - CENTRO II 3/4" PVC WALL CHASE/WASHING MACHINE OUTLET BOX, MODEL 38120; FURNISHED AND INSTALLED BY MECHANICAL CONTRACTOR. https://www.homedepot.com/p/Oatey-3-1-2-in-Center-Drain-Washing-Machine-Outlet-Box-38120/205124568
C	REFRIGERANT LINE WALL CHASE OATEY - QUADRO II 1/2" WALL CHASE/WASHING MACHINE OUTLET BOX, MODEL 38550; FURNISHED AND INSTALLED BY MECHANICAL CONTRACTOR. https://www.oatey.com/products/oatey-quadro-single-lever-washing-machine-outlet-boxes-848912322?upc=038753385501



4 SYRUP & REFRIGERANT LINE WALL CHASE MOUNTING HEIGHTS
1/4" = 1'-0"

BRIAN D. LAUG, AIA NCARB ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT

Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr.
Jarrettsville, MD, 21084
410-776-5868

PROJECT



**7-ELEVEN 42655
CST**

**1360 NC 24-87, CAMERON NC
28326**

ORG. TITLE


MECHANICAL DETAILS

DATE REVISION

DATE	DESCRIPTION

DATE: 06/06/25 ISSUE FOR BID AND PERMIT
DATE:

6/06/25



DRAWN BY: JAL
SCALE: 1/4" = 1'-0"
DATE: 6/06/25
CHECKED BY: JAL
PROJECT No: JAL#25-008
FILE NAME:
PROJECT No:

M2.0

F

E

D

C

B

A

ABBREVIATIONS			
A	COMPRESSED AIR	HZ	HERTZ
AAV	AUTOMATIC ADMITTANCE VALVE	ICE	ICE MAKER
ABV	ABOVE	ID	INDIRECT DRAIN
ACU	AIR CONDITIONING UNIT	IE	INVERT ELEVATION
AD	AREA DRAIN	IN W. C.	INCHES WATER COLUMN
AE	ANESTHESIA EXHAUST	KW	KILOWATT
AF	ABOVE FINISHED FLOOR	LAV	LAVATORY
AHU	AIR HANDLING UNIT	LB	POUNDS
AS	AIR SEPARATOR	LBS/HR	POUNDS PER HOUR
AV	AUTOMATIC AIR VENT	LG	LENGTH
AW	ACID WASTE	LPR	LOW PRESSURE STEAM RETURN
@	AT	LPS	LOW PRESSURE STEAM SUPPLY
B	BOILER	LWT	LEAVING WATER TEMPERATURE
BAS	BUILDING AUTOMATION SYSTEM	MAU	MAKEUP AIR VENT
BCF	BACKFLOW PREVENTION DEVICE	MAV	MANUAL AIR UNIT
BHP	BRAKE HORSEPOWER	MAX	MAXIMUM
BLDG	BUILDING	MB	THOUSANDS OF BTU PER HOUR
BOP	BOTTOM OF PIPE	MC	MECHANICAL CONTRACTOR
BO	BOILER BLOW OFF	MCA	MINIMUM CURRENT AMPACITY
BTUH	BRITISH THERMAL UNITS PER HOUR	MIN	MINIMUM
CD	CEILING DIFFUSER /CONDENSATE DRAIN	MOPC	MAXIMUM OVERCURRENT PROTECTION
CH	CHILLER	MPR	MEDIUM PRESSURE RETURN
CHR	CHILLED WATER RETURN	MPS	MEDIUM PRESSURE STEAM
CHS	CHILLED WATER SUPPLY	N	NITROGEN
CLG	CEILING	N.C.	NORMALLY CLOSED
COND	CONDENSATE	NIC	NOT IN CONTACT
COP	COEFFICIENT OF PERFORMANCE	NO	NITROUS OXIDE
CT	COOLING TOWER	N.O.	NORMALLY OPEN
CU	CONDENSING UNIT	NTS	NOT TO SCALE
CV	CONTROL VALVE	O	OXYGEN
CW	DOMESTIC COLD WATER	OFD	OVERFLOW ROOF DRAIN
D	DRAIN	P	PUMP
DC	DRY COOLER	P-1	PLUMBING FIXTURE IDENTIFIER
'F	DEGREE FAHRENHEIT	PBD	PARALLEL BLADE DAMPER
DH	DEHUMIDIFIER	PC	PLUMBING CONTRACTOR
DI	DEIONIZED WATER	PD	PRESSURE DROP
DN	DOWN	PH	PHASE
DOAS	DEDICATED OUTDOOR AIR SYSTEM	PPM	PARTS PER MILLION
DS	DOWNSPOUT NOZZLE	PRV	PRESSURE RELIEF VALVE
DTR	DUAL TEMPERATURE RETURN	PS	PRESSURE SWITCH
DTs	DUAL TEMPERATURE SUPPLY	PSI	POUNDS PER SQUARE INCH
DW	DISHWASHER	PSIA	POUNDS PER SQUARE INCH ABSOLUTE
EACH	EACH	PSIG	POUNDS PER SQUARE INCH GAUGE
EC	ELECTRICAL CONTRACTOR	PTAC	PACKAGED TERMINAL AIR CONDITIONER
EFF	EFFICIENCY	R	ROOF DRAIN
EL	ELEVATION	RLA	RUNNING LOAD AMPS
ER	EXHAUST REGISTER	RL	RAIN LEADER
ET	EXPANSION TANK	RM	ROOM
EWC	ELECTRIC WATER COOLER	RO	REVERSE OSMOSIS SUPPLY
EWI	ELECTRIC WATER HEATER	RPM	REVOLUTIONS PER MINUTE
EWT	ENTERING WATER TEMPERATURE	RR	REVERSE OSMOSIS RETURN
EXT	EXISTING	RTU	ROOFTOP AIR HANDLING UNIT
EXT	EXTERNAL	RMV	REMOVE EXISTING
FCO	FLOOR CLEANOUT	SF	SQUARE FOOT
FCU	FAN COIL UNIT	SH	SHOWER
FD	FLOOR DRAIN	SPEC.	PROJECT SPECIFICATIONS
FDC	FIRE DEPARTMENT CONNECTION	SS	STAINLESS STEEL
FDV	FIRE DEPARTMENT VALVE	STRUCT	STRUCTURAL
FL	FLOOR	SW	STORM WATER
FLA	FULL LOAD AMPS	TEMP	TEMPERATURE
FOR	FUEL OIL RETURN	TMV	THERMOSTATIC MIXING VALVE
FOS	FUEL OIL SUPPLY	TOP	TOP OF PIPE
FOV	FUEL OIL VENT	TP	TRAP PRIMER
FPM	FEET PER MINUTE	TWH	TANKLESS WATER HEATER
FS	FLOOR SINK	Typ	TYPICAL
FSD	FIRE SMOKE DAMPER	UH	UNIT HEATER
FT	FEET	UN	UNLESS OTHERWISE NOTED
FT²	SQUARE FEET	UR	URINAL
FTR	FINNED TUBE RADIATOR	V	VOLT / VACUUM
FW	FEED WATER PUMPED DISCHARGE	VAC	VOLTS ALTERNATING CURRENT
GAL	GALLON	VB	VACUUM BREAKER
GC	GENERAL CONTRACTOR	VP	VELOCITY PRESSURE
GPM	GALLONS PER MINUTE	VRF	VARIABLE REFRIGERANT FLOW
GR	GLYCOL RETURN	VTR	VENT THRU ROOF
GR	GAS RADIANT HEATER	W	WATTS
GS	GLYCOL SUPPLY	W	WITH
GUH	GAS UNIT HEATER	W/O	WITHOUT
GV	GRAVITY VENTILATOR	WC	WATER CLOSET
GW	GREASE WASTE	WCO	WALL CLEANOUT
GW/H	GAS WATER HEATER	WF	WATER FILTER
H	HUMIDIFIER	WG	WATER GAUGE
HC	HOSE BIBB	WH	WALL HYDRANT
HC	HEATING COIL	WS	WATER SOFTENER
HCWR	DUAL TEMPERATURE RETURN	WSHP	WATER SOURCE HEAT PUMP
HCWS	DUAL TEMPERATURE SUPPLY		
HD	HUB DRAIN		
HP	HEAT PUMP / HORSEPOWER		
HPR	HIGH PRESSURE STEAM RETURN		
HPS	HIGH PRESSURE STEAM SUPPLY		
HR	HOUR		
HW	HOT WATER		
HWR	HW RECIRC/HEATING WATER RETURN		
HW	HEATING WATER SUPPLY		
HX	HEAT EXCHANGER		

GENERAL NOTES

GENERAL PLUMBING REQUIREMENTS

- The Materials, equipment, and systems shall meet all pertinent requirements of the Underwriters Laboratory (UL), the American Society for Testing Materials (ASTM), American Water Works Association (AWWA), American Gas Association (AGA), National Fire Protection Association (NFPA), and other nationally recognized agencies as well as the latest adopted edition of state and local code procedures, methods, and regulations, including the most stringent of health and safety standards as required and as interpreted by the authority having jurisdiction. Applicable codes include, but are not limited to the following: International Plumbing, Building, Energy, mechanical, and fuel gas codes; applicable local and municipal codes and ordinances.
- Bidders shall be licensed contractors in accordance with local and state laws.
- Bidders shall thoroughly acquaint themselves with the conditions under which the work is to be performed. They shall examine all services, equipment, surfaces, etc., with this work is in any way dependent upon, and bring any discrepancies determined or omissions found in the drawings to the owner's attention before submitting bid.
- All installed systems, devices and related items shall be tested in place on site. Replace any and all contractor supplied defective devices, items or systems at contractor's own expense before completion of the project.
- Contractor shall guarantee all work for which materials are furnished, fabricated or field erected, all factory assembled equipment for which no specific manufacturer's guarantee is furnished, and all work in connection with installing manufacturer's guaranteed equipment. This contractor's guarantee shall apply for a period of one (1) year from the date of final owner acceptance of the work and shall apply to defects in material and to defective workmanship of any kind.
- The systems shown on the drawings shall be provided to serve all fixtures, equipment, and areas within the Contract Limit Lines as set forth by the Architectural solution for the project. Systems must include all equipment, accessories, safety devices, and controls necessary for the intended service.
- All permits and fees required for the work shall be secured and paid for by the plumbing contractor and included in bid price.
- Anything drawn or specified on these plans shall not be construed to conflict with any local, municipal or state law, regulation or ordinance which governs the installation of any plumbing or related work. Where any portion of the systems are not installed as in accordance with applicable laws, ordinances, regulations and codes, this contractor shall make all changes required by the enforcing authorities in a manner approved by the owner and without additional cost to the owner.
- Where job conditions require changes from the contract documents that do not change the scope of installation or nature of work required, the contractor shall make such changes without additional cost to the owner. No other changes may be made without written permission of the owner.
- All equipment and fixtures shall be new and unused and installed in strict conformance to manufacturer's recommendations. Provide fixtures complete with all trim, stops, hangers, carriers, supports, etc. including protection for the handicapped, if required. Where fixtures are accessible to the handicapped, fixtures must comply with all federal ADA regulations.
- Arrange for chases, slots, and openings in other building components to allow for plumbing installations. Coordinate the cutting and patching of building components to accommodate installation of plumbing equipment and materials.
- Do not endanger or damage installed Work through procedures and processes of cutting and patching. Provide repairs required to restore other work, because of damage caused as a result of plumbing installations.
- Coordinate the installation of required supporting devices and sleeves to be set in poured in place concrete and other structural components, as they are constructed. Plumbing contractor shall be responsible for assuring all hangers and supports are anchored or attached to building elements adequate for intended plumbing system or equipment. Plumbing contractor to provide and install nail plates where piping passes through stud(s) within 2" of nailing surface to protect pipe from nails or drywall screws.
- Sealing, coordinate, and integrate installations of plumbing materials and equipment for efficient flow of the Work. Give particular attention to large equipment requiring positioning prior to closing-in the building.
- Where mounting heights are not detailed or dimensioned, install plumbing services and overhead equipment to provide the maximum headroom possible.
- Install plumbing equipment to facilitate maintenance and repair or replacement of equipment components. As much as practical, connect equipment for ease of disconnecting, with minimum of interference with other installations.
- Coordinate the installation of plumbing materials and equipment above ceilings with suspension system, light fixtures, ductwork, conduit, and other installations. Coordinate plumbing equipment and materials installation with other building components.
- All pipes shall be of the size given on the drawings. All piping shall be run true to line. Pipes may be moved, if necessary for installation, provided that the nature of the system is not changed. All pipes shall be concealed: located above ceiling, below floor or in walls, except where connection is made to fixture.
- Coordinate connection of plumbing systems with exterior underground and overhead utilities and services. Comply with requirements of governing regulations, franchised service companies, and controlling agencies. Provide required coordination for each service and coordinate all locations, sizes and invert elevations with civil engineer.
- Plumbing service rough-in shall be based on information, drawings, equipment cuts, etc. prepared by the equipment supplier. Final plumbing connections shall be made from rough-in equipment after equipment is set in place.
- Actual locations and mounting methods for fixtures and penetrations are subject to Architect's approval. All piping is shown schematically for clarity - coordinate with structure, ducts, lights, utilities, etc. Verify all dimensions by field measurements.
- The hot and cold water supply line branches for all lavatories and sinks shall have Jossam & Zurn water hammer arresters installed on the high point at the end of each branch line.
- All above-ground water supply piping shall be Type L rigid copper. All below-grade water supply piping shall be Type K soft copper with at least 50° between joints. All joints shall be soldered with "lead-free" solder (e.g., 95-5).
- Flush and sterilize water system after connections are made in accordance with local regulations.
- All sanitary waste piping below slab shall be cast-on-or sold-weld PVC. All grease waste piping shall be cast iron. 59 Other DWV piping may be solid wall-PVC or cast-iron or galvanized steel, except that PVC may NOT be used in demising walls and may NOT be used in return plenum ceilings.
- All condensate drain piping and indirect drains shall be DWV seamless copper tubing with soldered drainage fittings per schedule 40 plastic pipe with solvent welded plastic fittings, except that PVC may NOT be used in demising walls and may NOT be used in return plenum ceilings.
- All floor penetrations and all exterior penetrations shall be completely waterproofed, firesealed, and sealed. All pipe 62 penetrations of fire rated assemblies shall be sleeved and sealed as required to maintain the rating of the assembly. Sleeves shall be used for all masonry penetrations. Proper sealing of penetrations as described here is 63 the sole responsibility of the plumbing contractor.
- All domestic water piping, vent piping and gas piping shall run above ceiling, UON. All sanitary piping shall be run under the floor, UON.
- Existing piping shown on drawings is based on original drawings, and location, mounting heights and points of connection must be verified in field. All items that are indicated in bold print shall be considered new or relocated, unless otherwise noted.

NOTICE TO CONTRACTORS

ALL CONTRACTORS PRIOR TO BID SUBMISSION PROCESS SHALL VISIT PROPOSED WORK SITE AND FIELD VERIFY ALL EXISTING CONDITIONS. ANY CONDITIONS THAT DIFFER FROM THAT SHOWN ON THESE PLANS SHALL BE REPORTED TO ARCHITECT/ENGINEER SO THAT NEW AND REVISED BID DRAWINGS OR INFORMATION MAY BE ISSUED. MODIFICATIONS TO SCOPE OF WORK WHICH RESULT FROM CONTRACTORS NEGLECT TO VISIT THE SITE PRIOR TO SUBMITTING BID, SHALL BE THE CONTRACTORS SOLE RESPONSIBILITY.

DRAWING CONVENTIONS

- NEW WORK - HEAVY AND SOLID LINES
 ——— EXISTING TO REMAIN - LIGHT AND SOLID LINES
 - - - - REMOVE EXISTING - HEAVY AND DASHED LINES

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT

Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr,
Jarrettsville, MD, 21084
410-776-5868

PROJECT:



7-ELEVEN 42655
CST

**1360 NC 24-87, CAMERON NC
28326**


DWC. TITLE:

GENERAL NOTES

ISSUE/REVISION

0	06/06/25	ISSUE FOR BID AND PERMIT
	DATE	DESCRIPTION

6/06/25



DRAWN BY: JAL	CHECKED BY: JAL
SCALE: 1/4" = 1'-0"	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:

SHEET NO:

P0.0

F


E

D

C

B



























A




1 DRAIN PLAN - DEMOLITION
Scale: 1/4"=1'

PLUMBING NOTES

- A. NOTES APPLY TO ALL PLUMBING SHEETS.
- B. EACH CONTRACTOR IS RESPONSIBLE FOR HAVING THOROUGH KNOWLEDGE OF ALL DRAWINGS AND SPECIFICATIONS AS THEY RELATE TO THIS WORK. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED DUE TO LACK OF THIS KNOWLEDGE.
- C. PROVIDE ALL MATERIALS FOR A COMPLETE INSTALLATION IN ALL RESPECTS READY FOR INTENDED USE AND IN STRICT ACCORDANCE WITH STATE AND LOCAL CODES AND MANUFACTURER'S RECOMMENDATIONS.
- D. COORDINATE SEWER AND WATER CONNECTIONS WITH CIVIL AND A/HJ PROVIDE PRESSURE-TESTING VALVE AND BACKFLOW PREVENTER AS SHOWN OR REQUIRED BY A/HJ. VERIFY INVERT AND SLOPE OF INCOMING SANITARY SEWER BEFORE TRENCHING.
- E. REFER TO RISER DIAGRAMS AND PLUMBING FIXTURE SCHEDULE FOR ALL PIPING AND PIPE SIZES NOT SHOWN ON PLAN.
- F. SANITARY AND STORM SEWER PIPING SHOWN IS BASED ON 1/4" PER FOOT FALL FOR ALL PIPE. NOTIFY 7-11 CM IF THE SLOPE CANNOT BE ACHIEVED.
- G. ALL SEWER PIPING BELOW SLAB TO BE 2" DIAMETER MINIMUM.
- H. PROVIDE ACCESS DOORS TO ALL CONCEALED VALVES AND CLEAN-OUTS, AND NOT ABOVE AN ACCESSIBLE CEILING.
 - PROVIDE TRAP SEAL PRIMERS AND 1/2" COPPER TUBING CONNECTION TO ALL FLOOR DRAINS AS SHOWN OR AS REQUIRED BY A/HJ.
 - CONTRACTOR SHALL FERRY REQUIREMENTS.
- I. INSTALL VTR'S, EXHAUST FANS, AND FLUES A MINIMUM 5'-0" FROM PARAPET OR OUTSIDE WALL AND 10'-0" MINIMUM FROM EQUIPMENT WITH OUTSIDE AIR INTAKE.
- K. INSTALL WATER PIPE ON INSIDE OF EXTERIOR WALL INSULATION TO PREVENT FREEZING.
- L. WHEN DEEP ROOT LOCATIONS ARE ENCOUNTERED, ROUTE SANITARY LINES UNDER BUILDING AS FAR AS POSSIBLE.
- M. PROVIDE PVC SLEEVE FOR ALL COLD/HOT WATER FLOOR PIPE PENETRATIONS. MAKE SURE THERE IS A HIGH FLOOR INSULATION SEAL WITH GRAY MASTIC AND ENSURE OF NO WATER PENETRATIONS.
- N. PROVIDE AND INSTALL WATTS BA VACUUM BREAKER ON ANY THREADED EXTERIOR OR INTERIOR FAUCETS.
- O. ALL WATER SHUT-OFF VALVES SHALL BE "BALL LOCK" TYPE. PROVIDE SHUT-OFF VALVES AT EACH TERMINATION POINT OF ASSOCIATED EQUIPMENT.
- P. PROVIDE SEISMIC BRACING BASED ON APPROPRIATE SEISMIC ZONE REQUIREMENTS PER LOCAL AND NATIONAL CODES. CONTRACTOR'S RESPONSIBILITY INCLUDES STRUCTURAL ENGINEER'S CERTIFICATION ON DETAILS SUBMITTED FOR PERMITTING.

PLUMBING SYMBOLS			
	SANITARY SEWER		TEE - TURNED DOWN
	GREASE WASTE		TEE - TURNED UP
	GREASE INTERCEPTOR		BALL VALVE
	DOMESTIC COLD WATER		BACKFLOW PREVENTER
	DOMESTIC HOT WATER		FD FLOOR DRAIN
	DOMESTIC HOT WATER RETURN		FS FLOOR SINK
	FILTERED WATER		FCO FLOOR CLEANOUT
	NATURAL GAS		YCO YARD CLEANOUT
	CONDENSATE DRAIN		FPWH
	PLUMBING VENT		HB HOSE BIBB
	UNION		WCO WALL CLEANOUT
	ELBOW - TURNED DOWN		GAS PRESSURE REGULATOR
	ELBOW - TURNED UP		GAS COCK



2 DRAIN PLAN - NEW WORK

Drawing Notes: ① ② #


1. APPROXIMATE LOCATION OF EXISTING GREASE PIPING TO EXISTING OUTSIDE UNDERGROUND GREASE INTERCEPTOR TO REMAIN. CONTRACTOR TO VERIFY EXACT SIZE AND LOCATION OF GREASE INTERCEPTOR AND PIPING. PRIOR TO WORK BEING PERFORMED.
2. APPROXIMATE LOCATION OF EXISTING SANITARY PIPING. CONTRACTOR TO VERIFY EXACT SIZE AND LOCATION PRIOR TO WORK BEING PERFORMED.
3. EXISTING PLUMBING FIXTURE TO REMAIN.
4. EXISTING CLEANOUT TO REMAIN. (TYPICAL)
5. EXISTING HUB DRAIN TO REMAIN. (TYPICAL)
6. REMOVE EXISTING PLUMBING FIXTURE AND ALL ASSOCIATED PIPING BACK TO MAINS AND CAP. (TYPICAL)
7. REMOVE EXISTING FLOOR SINK/HUBDRAIN AND REWORK AS SHOWN IN NEW WORK PLAN.
8. REMOVE EXISTING PLUMBING IN CASEWORK AS REQUIRED TO ACCOMMODATE NEW WORK
9. NEW SAN PIPING UNDER SLAB. EXTEND TO NEAREST SAN MAIN. CONTRACTOR TO FIELD LOCATE EXISTING MAIN. (TYPICAL)
10. NEW GREASE WASTE PIPING UNDER SLAB. EXTEND TO NEAREST GREASE MAIN. CONTRACTOR TO FIELD LOCATE EXISTING MAIN. (TYPICAL)
11. NEW VENT PIPING ABOVE CEILING EXTEND TO NEAREST VENT MAIN. CONTRACTOR TO FIELD LOCATE EXISTING MAIN. (TYPICAL)
12. PLUMBING CONTRACTOR TO PROVIDE FULL SIZE DRAINS FROM BEVERAGE EQUIPMENT TO FS WITH AIR GAP (TYP) (TYPICAL)
13. ROUTE FULL SIZE DRAIN FROM DUMP SINK (S4) TO FS WITH AN APPROVED AIR GAP
14. ROUTE FULL SIZE SCH 80 PVC DRAINS FROM 3 COMPARTMENT SINK (S2) TO FS WITH AN APPROVED AIR GAP. SEE DETAIL 3/P2 FOR MORE INFORMATION.

BRIAN D. LAUG, AIA NCARB
ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT:
Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr,
Jarrettsville, MD, 21084
410-776-5868




7-ELEVEN 42655
CST

**1360 NC 24-87, CAMERON NC
28326**

DWG. TITLE:


DRAIN PIPING PLAN

ISSUE REVISIONS		
0	06/06/25	ISSUE FOR BID AND PERMIT
DATE	DESCRIPTION	




DRAWN BY: JAL	CHECKED BY:
SCALE: 1/4" = 1'-0"	PROJECT No. JAL#25-008
DATE: 6/06/25	FILE NAME:
SHEET NO.	

P1.0



1 DOMESTIC WATER PIPING PLAN - DEMOLITION
Scale: 1/4"=1'



2 DOMESTIC WATER PIPING PLAN - NEW WORK
Scale: 1/4"=1'

- PLUMBING NOTES**
- A. NOTES APPLY TO ALL PLUMBING SHEETS.
- B. EACH CONTRACTOR IS RESPONSIBLE FOR HAVING THOROUGH KNOWLEDGE OF ALL DRAWINGS AND SPECIFICATIONS AS THEY RELATE TO THIS WORK. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED DUE TO LACK OF THIS KNOWLEDGE.
- C. PROVIDE ALL MATERIALS FOR A COMPLETE INSTALLATION IN ALL RESPECTS READY FOR INTENDED USE AND IN STRICT ACCORDANCE WITH STATE AND LOCAL CODES AND MANUFACTURER'S RECOMMENDATIONS.
- D. COORDINATE SEWER AND WATER CONNECTIONS WITH CIVIL AND A/HJ. PROVIDE PRESSURE REDUCING VALVE AND BACKFLOW PREVENTER AS SHOWN OR REQUIRED BY A/HJ. VERIFY INVERT AND SLOPE OF INCOMING SANITARY SEWER BEFORE TRENCHING.
- E. REFER TO RISER DIAGRAMS AND PLUMBING FIXTURE SCHEDULE FOR ALL PIPING AND PIPE SIZES NOT SHOWN ON PLAN.
- F. SANITARY AND STORM SEWER PIPING SHOWN IS BASED ON 1/4" PER FOOT FALL FOR ALL PIPE. NOTIFY 7-11 CM IF THE SLOPE CANNOT BE ACHIEVED.
- G. ALL SEWER PIPING BELOW SLAB TO BE 2" DIAMETER MINIMUM.
- H. PROVIDE ACCESS DOORS TO ALL CONCEALED VALVES AND CLEAN-OUTS, AND NOT ABOVE AN ACCESSIBLE CEILING.
- I. PROVIDE TRAP SEAL PRIMERS AND 1/2" COPPER TUBING CONNECTION TO ALL FLOOR DRAINS AS SHOWN OR AS REQUIRED BY A/HJ. CONTRACTOR SHALL VERIFY REQUIREMENTS.
- J. INSTALL VTR'S, EXHAUST FANS, AND FLUES A MINIMUM 5'-0" FROM PARAPET OR OUTSIDE WALL AND 10'-0" MINIMUM FROM EQUIPMENT WITH OUTSIDE AIR INTAKE.
- K. INSTALL WATER PIPE ON INSIDE OF EXTERIOR WALL INSULATION TO PREVENT FREEZING.
- L. WHEN DEEP FROST LOCATIONS ARE ENCOUNTERED, ROUTE SANITARY LINES UNDER BUILDING AS MUCH AS POSSIBLE.
- M. PROVIDE PVC SLEEVE FOR ALL COLD/HOT WATER FLOOR PIPE PENETRATIONS. MAKE SLEEVE LARGE ENOUGH FOR INSULATION. SEAL WITH GRAY MASTIC AND ENSURE OF NO WATER PENETRATIONS.
- N. PROVIDE AND INSTALL WATTS 8A VACUUM BREAKER ON ANY THREADED EXTERIOR OR INTERIOR FAUCETS.
- O. ALL WATER SHUT-OFF VALVES SHALL BE "BALL LOCK" TYPE. PROVIDE SHUT-OFF VALVES AT EACH TERMINATION POINT OF ASSOCIATED EQUIPMENT.
- P. PROVIDE SEISMIC BRACING BASED ON APPROPRIATE SEISMIC ZONE REQUIREMENTS PER LOCAL AND NATIONAL CODES. CONTRACTOR'S RESPONSIBILITY INCLUDES STRUCTURAL ENGINEER'S CERTIFICATION ON DETAILS SUBMITTED FOR PERMITTING.

PLUMBING SYMBOLS			
SS	SANITARY SEWER	TEE - TURNED DOWN	
GW	GREASE WASTE	TEE - TURNED UP	
GI	GREASE INTERCEPTOR	BALL VALVE	
	DOMESTIC COLD WATER	BACKFLOW PREVENTER	
	DOMESTIC HOT WATER	FLOOR DRAIN	FD
	DOMESTIC HOT WATER RETURN	FLOOR SINK	FS
FW	FILTERED WATER	FLOOR CLEANOUT	FCO
G	NATURAL GAS	YARD CLEANOUT	YCO
CD	CONDENSATE DRAIN	HOSE BIBB	FPWH
	PLUMBING VENT	WALL CLEANOUT	HB
	UNION	GAS PRESSURE REGULATOR	WCO
	ELBOW - TURNED DOWN	GAS COCK	
	ELBOW - TURNED UP		

Drawing Notes: 1 2 3

- EXISTING 199MBH INSTANTANEOUS WATER HEATERS TO REMAIN. CONTRACTOR TO VERIFY IN WORKING ORDER. REPLACE IF NECESSARY.
- REMOVE EXISTING POINT OF USE WATER HEATER.
- REMOVE AND REPLACE EXISTING WATER FILTRATION SYSTEM.
- REMOVE EXISTING PLUMBING FIXTURE AND ASSOCIATED PIPING BACK TO MAIN.
- REMOVE EXISTING PLUMBING FIXTURE AND PREP EXISTING PIPING FOR NEW FIXTURE.
- REMOVE ALL BEVERAGE BAR PLUMBING BACK TO MAINS AND REWORK AS SHOWN IN NEW WORK.
- EXTEND TO EXISTING DOMESTIC WATER MAINS. CONTRACTOR TO FIELD LOCATE AND VERIFY SIZES OF MAINS PRIOR TO WORK BEING PERFORMED.
- ROUTE PIPING DOWN INSIDE WALL INTO CASEWORK AND EXTEND TO SYSTEMS AS SHOWN IN PLAN AND RISER DIAGRAM.
- ROUTE 1/2" FW TO ICE MAKER WITH SHUT OFF VALVE AND DCV (ASSE 1022)
- ROUTE 1/2" FW TO POST MIX WITH SHUT OFF VALVE AND DCV (ASSE 1022)
- ROUTE 3/4" FW TO SLURPEES/LEMONADE WITH SHUT OFF VALVE AND DCV (ASSE 1022)
- ROUTE 3/4" FW TO ICED TEA BREWER WITH SHUT OFF VALVE AND DCV (ASSE 1022)
- 1/2" CW ROUTED DOWN WALL INTO CASEWORK FOR AUTO-FLUSH SYSTEM. SEE DRV ON SPECIALTY PLUMBING FIXTURE SCHEDULE FOR MORE INFORMATION. INCLUDE WITH DCV (ASSE 1022) PRIOR TO CONNECTION. INSTALL PER MANUFACTURER REQUIREMENTS.
- NEW 3/4" CW TO NEW FILTER SYSTEM. REFER TO DETAIL 1/P2.0.
- 1/2" CW, 1/2" HW, 3/4" FW ROUTED DOWN TO UNDER SLAB AND EXTENDED TO COFFEE BAR.
- 1/2" CW AND 1/2" HW ROUTED TO NEW PLUMBING FIXTURE.

BRIAN D. LAUG, AIA NCARB ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT
Joseph A. Loiero, Jr.
NC PE License #042310
2007 Twin Lakes Dr.
Jarrettsville, MD, 21084
410-776-5868

PROJECT
7-ELEVEN 42655 CST
1360 NC 24-87, CAMERON NC 28326

DRG. TITLE
DOMESTIC WATER PIPING PLAN

DATE: 6/06/25
DESCRIPTION: ISSUE FOR BID AND PERMIT

6/06/25
Seal of Joseph A. Loiero, Jr., Professional Engineer, License #042310, State of North Carolina.

DRAWN BY: JAL
SCALE: 1/4" = 1'-0"
DATE: 6/06/25

CHECKED BY: JAL
PROJECT NO: JAL#25-008
FILE NAME:
SHEET NO:

P1.1

P1.2

F

E

D

C

B

A

PLUMBING FIXTURE SCHEDULE (NOT ALL DEVICES ARE USED ON THIS PROJECT)												
TAG	FIXTURE	ORACLE	MANUFACTURER	MODEL	FURNISH BY	INSTALL BY	SUPPLIER	CONNECTION				DESCRIPTION
								CW SEE PLAN	HW	WASTE	VENT	
DCV	DUAL CHECK VALVE	-	WATTS	SD-3	GC	GC	--	--	--	--	--	LEAD FREE STAINLESS STEEL BODY WITHS TRAINER AND VENT DISCHARGE PORT. (ASSE 1022)
DRV	DRAIN VALVE	-	GRANZGOW	E2B15-00V	GC	GC	--	1/4"	--	--	--	ELECTRONIC DRAIN VALVE, TIMER SET TO 15 SECONDS ON, 15 MINUTES OFF.
FCO	FLOOR CLEANOUT	-	SILOUX CHIEF	851	GC	GC	--	--	--	NOTE A	--	PVC BODY, ROUND HEAVY-DUTY CAST IRON TOP, POLYPROPYLENE OR ABS PLUG, ADJUSTABLE TO FINISH SURFACE
FD	FLOOR DRAIN	-	SILOUX CHIEF	832-36PNQ	GC	GC	--	--	--	3"	1-1/2"	3" LIGHT DUTY DRAIN WITH 7" SQUARE TOP, PVC BODY WITH NICKEL BRONZE RING AND STRAINER.
FS	FLOOR SINK	-	SILOUX CHIEF	861	GC	GC	--	--	--	3"	1-1/2"	WHITE PVC 12"x12" FLOOR SINK WITH 24" HEAVY-DUTY PVC HALF GRATE, SEDIMENT BUCKET, SEAMLESS MOLDED POLYETHYLENE TANK, 50 GPM FLOW RATE, 439.5 LB GREASE CAPACITY, 65 GALLON LIQUID CAPACITY, 1/2" BUILT-IN FLOW CONTROL, INTEGRAL AIR RELIEF/ANTI SYPHON, FIELD ADJUSTABLE RISER SYSTEM, 4" PLAIN INLET/OUTLET, WATER/GAS TIGHT SEAL COVER WITH MIN 16,000 LB LOAD CAPACITY, CERTIFIED TO ASME A112.14.3 AND CSA B481.1
GT	GREASE TRAP	-	SCHIER (GREAT BASIN)	GB-50	GC	GC	--	--	--	3"	--	FIXTURE AND HARDWARE PROVIDED AND INSTALLED BY PLUMBING CONTRACTOR, NO. 839AA FAUCET WITH INTEGRAL VACUUM BREAKER, NO. 832-AA HOSE AND BRACKET NO. 1453BB FLOOR STRAINER AND NO. 899-CC MOP HANGER.
MS	MOP SINK	-	FIAT	MSB-2424	GC	GC	--	1/2"	1/2"	3"	1-1/2"	LEAD FREE BRONZE BODY WITH SHUT-OFF VALVES, Y STRAINER, AND TEST COCKS. (ASSE 1013)
RPZ	REDUCED PRESSURE BACKFLOW PREVENTER	-	WATTS	LF909QTS	GC	GC	--	2"	--	--	--	FIXTURE AND HARDWARE OWNER FURNISHED, INSTALLED BY PLUMBING CONTRACTOR. ADA COMPLIANT, CUSTOM WALL MOUNT 10" FRONT TO BACK X 14" W X 6" D HAND SINK (PRODUCTION LINE), PROVIDED WITH BRASS FAUCET (REF SF-1 THIS SCHEDULE) & P-TRAP, INSTALL TRUEBRO LAV GUARD 2 PROTECTIVE PIPE COVERS ON EXPOSED HOT WATER AND DRAIN LINES, STOP VALVES, AND TEMPERATURE-ACTIVATING MIXING VALVE SET TO 105°F.
S1	HAND SINK	03291395	JOHN BOOS	PBHS-W0140-SSLR	TURNKEY	GC	--	1/2"	1/2"	1-1/2"	1-1/2"	BOWL SIZE 12"x19"x12", FIXTURE AND HARDWARE OWNER FURNISHED, INSTALLED BY PLUMBING CONTRACTOR, PROVIDED WITH FAUCET (REF SF-2 THIS SCHEDULE), P-TRAP AND STOP VALVES.
S2	3-COMP SINK	03119411	TURBO AIR	TSA-3-D1-711	TURNKEY	GC	--	1/2"	1/2"	2"(3)	--	FIXTURE AND HARDWARE PROVIDED FURNISHED, INSTALLED BY PLUMBING CONTRACTOR. STAINLESS STEEL FIXTURE, DECK MOUNTED BRASS FAUCET (REF SF-4 THIS SCHEDULE) WITH AERATOR & P-TRAP, PROVIDED WITH STOP VALVES, FLEXIBLE SUPPLY RISERS, TUEBRO LAV GUARD 2 PROTECTIVE PIPE COVERS.
S4	DUMP SINK	-	DAYTON	K1115152	TURNKEY	GC	ROYSTON	1/2"	1/2"	1-1/2"	1-1/2"	FIXTURE AND HARDWARE PROVIDED FURNISHED, INSTALLED BY PLUMBING CONTRACTOR. STAINLESS STEEL FIXTURE, DECK MOUNTED BRASS FAUCET (REF SF-4 THIS SCHEDULE) WITH AERATOR & P-TRAP, PROVIDED WITH STOP VALVES, FLEXIBLE SUPPLY RISERS, TUEBRO LAV GUARD 2 PROTECTIVE PIPE COVERS.
S5	DUMP SINK	-	ELKAY	PSR19181	TURNKEY	GC	ROYSTON	1/2"	1/2"	1-1/2"	1-1/2"	4" WALL MOUNT WORKBOARD FAUCET, QUARTER-TURN ETERNA CARTRIDGES WITH SPRING CHECKS, LEVER HANDLES, 5 3/4" SWIVEL GOOSENECK, 2.2 GPM AERATOR.
SF-1	SINK FAUCET	03136254	T&S BRASS AND BRONZE WORKS, INC.	B-1146	TURNKEY	GC	--	1/2"	1/2"	--	--	8" WALL MOUNT MIXING FAUCET, QUARTER-TURN CERAMA CARTRIDGES WITH CHECK VALVES, LEVER HANDLES, ADD-ON FAUCET WITH 8" SOING NOZZLE, COMPACT SPRING, 24" FLEXIBLE STAINLESS STEEL HOSE, 0.65 GPM LOW FLOW SPRAY VALVE, 6" WALL BRACKET
SF-2	SINK FAUCET	03164018	TURNKEY RESOURCES	MPY8WLN-08CR	TURNKEY	GC	--	1/2"	1/2"	--	--	FIXTURE AND HARDWARE OWNER FURNISHED, INSTALLED BY PLUMBING CONTRACTOR. ADA COMPLIANT, 1.5 GPM FLOW RATE STAINLESS STEEL FAUCET.
SF-4	SINK FAUCET	-	MOEN	5995	TURNKEY	GC	ROYSTON	1/2"	1/2"	--	--	
TMV	THERMOSTATIC MIXING VALVE	-	WATTS	LFUSG-B-M1	GC	GC	--	1/2"	1/2"	--	--	4"-3/8" UP TO 120" F WITH BUILT-IN CHECK VALVES, BRASS BODY, AND COPPER THERMOSTAT.
WF-3	FILTER CARTRIDGE	07883005	ECOLAB	92213690	TURNKEY	GC	--	--	--	--	--	TO20S SCALE FILTER CARTRIDGE
WF-4	FILTER CARTRIDGE	07883001	ECOLAB	92213686	TURNKEY	GC	--	--	--	--	--	TO14 FILTER CARTRIDGE
WF-8	WATER FILTER MANIFOLD	04300903	ECOLAB	9320-2357			ECO-LAB, INC.	1"	--	--	--	SPLIT TRIPLE HEAD MANIFOLD

NOTES:
A. CLEANOUT (FCO, YCO) SHALL BE SAME SIZE AS PIPE BEING SERVED.

MANUFACTURER CONTACT INFORMATION			
MANUFACTURER	CONTACT	PHONE	EMAIL
ECOLAB, INC.	JENNIFER GREENE	612-366-9836	JENNIFER.GREENE@ECOLAB.COM
FERGUSON ENTERPRISES, LLC	JASON WADDLES	757-234-8204	NA.PORJECTS@FERGUSON.COM
SCHIER PRODUCTS	SEAN MOLEN	8165063203	SEAN.MOLEN@SCHIERPRODUCTS.COM


RECIRCULATING PUMP SCHEDULE (IF REQUIRED)							
TAG	QTY	MANUFACTURER	MODEL	HEAD LOSS (FT)	ELECTRICAL	NOTES	INSTALL BY
P-1	1	BELL & GOSSETT	NBF-90ULW	11 @ 5 GPM	120/1	A-D	GC

NOTES:
A. LEAD FREE CONSTRUCTION.
B. PROVIDE WITH FLEXIBLE PLUG-IN CORD.
C. INSTALL PER MANUFACTURER'S RECOMMENDATIONS.
D. PROVIDE WITH FLOW AND TEMPERATURE SWITCH PER 2018 IECC C404.7, REF 2/P2.0.


WATER ROUGH-IN HEIGHTS (NOT ALL USED ON EVERY PROJECT)			
TAG	SERVICE	SIZE	HEIGHT (AFF)
WC	COLD WATER	1"	28"
LAV	HOT & COLD WATER	1/2"	22"
MS	HOT & COLD WATER	1/2"	36"
S1	HOT & COLD WATER	1/2"	18"
S2	HOT & COLD WATER	1/2"	24"
S3	HOT & COLD WATER	1/2"	18"
HB	COLD WATER	1/2"	24"
UR	COLD WATER	3/4"	46-34"

NOTES:
A. FIELD VERIFY ROUGH-IN REQUIREMENTS PER MANUFACTURER'S RECOMMENDATIONS.

BACKFLOW PREVENTION SCHEDULE (NOT ALL USED ON EVERY PROJECT)	
EQUIPMENT	BACKFLOW PREVENTION
HOSE BIBB	INTEGRAL VACUUM BREAKER
MOP SINK	INTEGRAL VACUUM BREAKER
3-COMPARTMENT SINK	AIR GAP
HAND SINK	AIR GAP
DUMP SINK	AIR GAP
ICE MAKER	DCV (ASSE 1022)
CARBONATED BEVERAGE DISPENSER	DCV (ASSE 1022)
SLURPEE/FROZEN LEMONADE MACHINE	DCV (ASSE 1022)
COFFEE/BEVERAGE DISPENSERS	DCV (ASSE 1022)
FOUNTAIN DRAINS	DCV (ASSE 1022)
REFRIGERATION CONDENSATE LINES	AIR GAP
TROUGH FOUNTAIN DRAINS	DRV



4 LAVATORY SHROUD
1" = 1'-0"



FILTER SYSTEM REQUIREMENTS:

1. WATER SUPPLY MUST BE 1" INCH.
2. WATER SHUT-OFF VALVE SHALL BE "BALL LOCK" TYPE POSITIVE ON-OFF.
3. DRAIN MUST BE PROVIDED TO PERMIT FLUSHING OF NEW FILTERS.
4. KAY HIGH CAPACITY KAY-T014 FILTER WILL BE REPLACED AS REQUIRED BASED ON GALLONAGE.
5. WATER FOR ICE MAKERS, COFFEE MAKERS, AND CAPPUCCINO MACHINES SHALL BE ROUTED THROUGH THE ECOLAB (2)KAY-T020S FILTER.
6. WATER FOR FSD AND FCB EQUIPMENT SHOULD NOT BE ROUTED THROUGH THE KAY-T020S FILTERS (WILL REDUCE CARBONATION).
7. KAY-T014 AND/OR T020S FILTERS MAY BE CHANGED INDIVIDUALLY AND/OR ADDITIONALLY AS NEEDED. KAT-T014 PROVIDES UP TO 75,000 GALLONS. (2) KAY-T020S FILTERS WILL PROVIDE UP TO 200,000 GALLONS OF SCALE CONTROL.
8. HONEYWELL PRESSURE REDUCING VALVE MODEL DS05C1030 (SET AT 65 PSI) INSTALLED BEFORE FIRST TEE TO BEVERAGE EQUIPMENT.
9. ECOLAB RECOMMENDS MINIMUM INLET PRESSURE TO BE 45 PSI AND WILL REPORT BACK / CALL OUT ANY UNITS WITH INLET FLOW BELOW 45 PSI FOR REVIEW. IN THIS CIRCUMSTANCE, GRUNFOS MQ3-35 BOOSTER PUMP ASSEMBLY IS RECOMMENDED.
10. KAY HSD 20 PREFILTER - ONLY REQUIRED IN EXTREME WATER CONDITION AREAS AND WILL REQUIRE EXTRA SINGLE MANIFOLD IN FRONT OF STANDARD SYSTEM.

COFFEE RELATED EQUIPMENT ON 3/4" FILTER LINE:

- REQUIREMENTS FOR COFFEE RELATED EQUIPMENT:
3/4" FILTERED WATER LINE TO COFFEE RELATED EQUIPMENT IS IN THE FOLLOWING ORDER OF CONNECTION:
1. BUNN ICED TEA BREWERS (2)
 2. CURTIS CAPPUCCINO
 3. BUNN NITRO
 4. BUNN COFFEE BREWERS (2)
 5. FOLLETT ICE MAKER
 6. FRANK BEAN TO CUP (2)
- ECOLAB KAY-T014S (SCALE CONTROL FILTER) WILL SUPPORT COFFEE FILTRATION APPLICATION.
ECOLAB HIGH CAPACITY FILTERS WILL BE REPLACED AS REQUIRED BASED ON GALLONAGE.
ECOLAB RECOMMENDS A SEPARATE KAY-T014S (SCALE CONTROL FILTER) INSTEAD OF THE SS-IMF SCALE STICKS FOR UNITS REQUIRING 15,000 GALLONS OR MORE OF SCALE CONTROL OR WHERE THE RAW WATER HARDNESS EXCEEDS 10 GPG HARDNESS TO PROTECT EQUIPMENT FROM EXCESS WATER HARDNESS SCALE BUILD-UP.
ECOLAB HIGH CAPACITY TO14 FILTERS TO PROVIDE 0.5 MICRON AND 75,000 GALLONS AT 5 GPM AND T020S FILTERS TO PROVIDE 0.5 MICRON AND 100,000 GALLONS AT 10 GPM.

1 ECOLAB WATER PURIFICATION SYSTEM
1/4" = 1'-0"

BRIAN D. LAUG, AIA NCARB ARCHITECT

16925 OLD SAWMILL ROAD
WOODBINE, MD 21797
443-250-6557

CONSULTANT
Joseph A. Loiero, Jr.
NC PE License #042310

2007 Twin Lakes Dr.
Jarrettsville, MD, 21084
410-778-5868

PROJECT

7-ELEVEN 42655
CST

1360 NC 24-87, CAMERON NC
28326

DATE: 6/06/25
PROJECT: PLUMBING DETAILS

DATE		DESCRIPTION	

6/06/25

Drawn by: JAL
Scale: 1/4" = 1'-0"
Date: 6/06/25

Checked by: JAL
Project No: JAL#25-008
File Name: P2.0