## 30332

## HTE# Basical Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Impro

A building perin	PROPERTY LOCATION: Should Grove Ad (50 2050)
ISSUED TO: Jimmy W. West	PROPERTY LOCATION: Shady Grove 1d. (Sn. 2050)  SUBDIVISION
NEW ☐ REPAIR ☐ EXPANSION ☐	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: 382 50WMH	
Proposed Wastewater System Type:	
Projected Daily Flow: 360 GPD	
Number of bedrooms:3	max
Basement Yes No	
Pump Required: ☐Yes ☐ No ☐ May be required based on	final location and elevations of facilities
	Distance from well feet Permit valid for:
Permit conditions:	—————————————————————————————————————
Authorized State Agent::	
The issuance of this permit by the Health Department in no way guarantees the issuance	of other permits. The permit holder is responsible for checking with appropriate governing hodies in meeting their requirement. This
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	everent Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
Cor	nstruction Authorization
	(Required for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956.	. 1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	systems shall be installed in accordance
ISSUED TO: Jimmy W. West	PROPERTY LOCATION: Shady Grove Rd (52 2050)
9	PROPERTY LOCATION: Shady Grove Rd. (52 2050) SUBDIVISION LOT # TR8
Facility Type: 381 DOMH	New   Expansion   Repair
Basement?  Yes  Basement Fixtures?  Yes	es 🗆 No
Type of Wastewater System** Conventiona	Gravel Sys. (Initial) Wastewater Flow: 360 GPD
(See note below, if applicable □)	
Conventional (	(Repair)
Installation Requirements/Conditions Number of	trenches 3
	h of each trench 90 feet Trench Spacing: 9 Feet on Center
	all be installed on contour at a Soil Cover:
•	rench Depth of: 28 inches (Maximum soil cover shall not exceed
in all direct	and the state of t
Pump Requirements:ft. TDH vs GPM	
rump requirementsit. IDH vs GPM	inches below pipe
Conditions	Aggregate Depth: inches above pipe
Conditions:	inches total
NATED LINES (INCLUDING IDDICATION) MUST BE 10FT FRO	AND DADT OF CERTIC CYCTEM OR REPAIR AREA
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FRO	M ANT PAKT OF SEPTIC SYSTEM OK KEPAIK AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD A	
**If applicable: I understand the system type specified is different fr	from the type specified on the application. I accept the specifications of this permit.
Owner/Legal Representative Signature:	Date:
his Construction Authorization is subject to revocation if the site plan, plat, or the intended	d use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
Construction Authorization is subject to compliance with the provisions of the Laws and Rule	es for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH
	- /
Authorized State Agent:	Carrinette Date: 01/15/2019
ANDREW WAND	Construction Authorization Expiration Date: 01/15/2024

## Harnett County Department of Public Health Site Sketch

