



# STRUCTURAL DESIGN

# **ENCLOSED BUILDING**

# MAXIMUM 30'- 0" WIDE X 14'- 0" HEIGHT-BOX EAVE FRAME AND BOW FRAME

5 November 2018 Revision 6 M&A Project No. 17062S/17174S/17254S/18033S/18113S/18246S

Prepared for:

Newmart Builders 1000 Cycle Lane South Hill, VA 23970

**Prepared by:** 

Moore and Associates Engineering and Consulting, Inc.

1009 East Avenue North Augusta, SC 29841

401 S. Main Street, Suite 200 Mount Airy, NC 27030



MOORE AND ASSOCIATES ENGINEERING AND CONSULTING






				SEAL 26784
				SEAL 26784 IV 1/16 WE S. MOONING
MOORE AND A ENGINEERING AND C	SSOCIATES	DRAWN BYILT	NEV	VMART BUILDERS, INC. 1000 CYCLE LANE DUTH HILL, VA 23970 '-0" ENCLOSED STRUCTURE
THIS DOCLMENT IS THE PROPERTY OF MODRE AND CONSULTING. THE UNAUTHORIZED REPREDUCTION, THIS DOCLMENT IS STRUCTLY PROHIBITED AND AN BE SUBJECT TO LEGAL ACTION.		CHECKED BY PDH		-0" ENCLOSED STRUCTURE JOB ND SCALE: NTS 180335/181135/182465
BE SUBJECT TO LEGAL ACTION	IT DAY KUNUCINCI THE RELIPON MAY	CLIENT: NEWMART BUILDERS	SHT. 1	DWG. NDI SK-3 REV. 6


# DRAWING INDEX


SHEET 1	PE SEAL COVER SHEET
	DRAWING INDEX
SHEET 3A	
SHEET 3B	TYPICAL SIDE AND END ELEVATIONS
SHEET 4	TYPICAL RAFTER/COLUMN END AND SIDE FRAMING SECTIONS
	(BOX EAVE RAFTER)
SHEET 5A	24'-0" < V ≤ 30'-0" MAXIMUM RAFTER SPAN CONNECTION DETAILS (BOX EAVE RAFTER)
SHEET 5B	W < 24'-0" MAXIMUM RAFTER SPAN CONNECTION DETAILS (BOX EAVE RAFTER)
SHEET 6	TYPICAL RAFTER/COLUMN END AND SIDE FRAMING SECTIONS (BOW RAFTER)
SHEET 7A	24'-0" < W < 30'-0" MAXIMUM RAFTER SPAN CONNECTION DETAILS (BOW RAFTER)
SHEET 7B	W < 24'-0" MAXIMUM RAFTER SPAN CONNECTION DETAILS (BOW RAFTER)
SHEET 8	BASE RAIL ANCHURAGE UPTIONS
SHEET 9	BOX EAVE RAFTER END WALL AND SIDE WALL OPENINGS
SHEET 10	BOW EAVE RAFTER END WALL AND SIDE WALL OPENINGS
SHEET 11	BOX AND BOW EAVE RAFTER WALL OPENING DETAILS
SHEET 12	BOX AND BOW EAVE RAFTER WALL OPENING DETAILS
SHEET 13	BOX EAVE RAFTER LEAN-TO OPTION
SHEET 14 SHEET 15	BOW RAFTER LEAN-TO OPTION
OUEET A	BOX EAVE RAFTER VERTICAL ROOF/SIDING OPTION
SHEET TO	ADDITIONAL BASE RAIL ANCHURAGE OPTION
	TH CAROLIN
	OFESSION AL
	1 Test / Cart -
	SEAL
	SEAL 26784
	11/9/1B
	SEAL 26784 VGINEER VGINEER S. MOUTIN
	ES. MOUTH
and the second	


MOORE AND ASSOCIATES ENGINEERING AND CONSULTING, INC.	DRAVN BYI LT	-	NEWMART BUILDERS, INC. 1000 CYCLE LANE SOUTH HILL, VA 23970 30'-0"x14'-0" ENCLOSED STRUCTURE		
THIS DOCUMENT IS THE PROPERTY OF MOORE AND ASSOCIATES EMEMBERING AND CONSULTING THE UNAUTHORIZED REPRODUCTION, COPYING, OR OTHERVISE USE OF THIS DOCUMENT IS STRUCTLY PROMODITED AND ANY INFRINGEMENT THEREUPON MAY RE SUBJECT TO LEGAL ACTION.	PROJECT MGRI VSM CLIENTI NEVMART BUILDERS	DATE: 11-5-18		JUB ND 180335/181135/182465	


INSTALLATION NOT 1 DESIGN IS FOR MAXIMUM 30'-0' VIDE x 14'-0' EAVE HEIGHT E 2 DESIGN WAS DONE IN ACCORDANCE WITH THE 2018 NORTH CAR 2009 IBC, 2012 IBC AND 2015 IBC 3 DESIGN LOADS ARE AS FOLLOWS: A) DEAD LOAD = 15 PSF B) LIVE LOAD = 12 PSF C) GROUND SNOW LOAD = 30 PSF (W $\leq 24'-0'$ ) = 35 PSF (18'-0' (W $\leq 30'-0'$ ), = 45 PSF @ 4'-0' DC MAX RAFTER @ 5'-0' DC MAX RAFTER @ SPECING = 50 FEET (UNLESS NOTED DTHERWISE). 5 END WALL COLUMNS (PDST) ARE SIMILAR TD SIDE WALL PDSTS 6 RISK CATEGORY I 7 WIND EXPOSURE CATEGORY B 8 SPECIFICATIONS APPLICABLE TD 29 GAUGE METAL PANELS FASS FRAMING MEMBERS FOP (24'-0' (W $\leq 30'-0'$ ) AND W 24'-0' STEEL (TS) FOR (W $\leq 24'-0'$ ) (UNLESS NOTED DTHERWISE). 9. AVERAGE FASTENER SPACING DN-CENTERS ADNO RAFTERS OR 10 FASTENERS CONSIST OF 1/4'X3/4' SEC-DRILLING FASTENER (O SPECIFICATIONS APPLICABLE DN-CENTERS ANDOF MEIGHT OF PEOLIDEMENTS EOD BLEED BLEED DIFE WICHS ANDOF MEIGHT OF PEOLIDEMENTS EOD BLEED BLEED BLEED DIFE WICHS ANDOF MEIGHT OF PEOLIDEMENTS EOD BLEED BLEED BLEED DIFE WICHS ANDOF MEIGHT OF PEOLIDEMENTS EOD BLEED BLEED BLEED DIFE WICHS ANDOF MEIGHT OF PEOLIDEMENTS EOD BLEED	INCLOSED STRUCTURES OLINA BUILDING CODE, 200 /COLUMN AND END COLUMN /COLUMN AND END COLUMN IND SPEED 81 TO 101 MPH3 S UNLESS NOTED OTHERWIS STENED DIRECTLY TO 2*×3* WITH EAVE HEIGHT 12*-0* HAT CHANNELS AND COLUM SDE3 USE CONTROL SEAL	SPACING (24'-0' SPACING (24'-0' SPACING (₩ ≤ 24 MAXIMUM RAFTER SE '-14 GAUGE TUBE < TO ≤ 14'-0') 2 MNS (INTERIOR OR WASHER WITH FY	<pre>&lt; W ≤ 30'-0") '-0") '-0") U/0" AND END ( STEEL (TS) L/4"x2 1/4"-14 ( END) = 10" DC ( STEEL (TS)</pre>	COLUMN AUGE TUBE MAX.3
REQUIREMENTS FOR OTHER ROOF HEIGHTS AND/OR SLOPES MAY 11 GROUND ANCHORS SHALL BE INSTALLED THROUCH BASE RAIL W 12 GROUND ANCHORS CONSIST OF #4 REDAR W/ WELDED NUT/FOR MAY BE USED IN SUITABLE SOLLS AND MUST BE USED IN UNSU 13 WIND FORCES GOVERN OVER SEISMIC FORCES SEISMIC PARAME SOLL SITE CLASS = D RISK CATEGORY I/II/III R = 3.25 Ie = 10 SDS = 20.39 V = CSW SDI = 1.258	VARY ITHIN 6° OF EACH RAFTER MED HEAD × 30° LONG IN ITABLE SOUS AS NOTED	COLUMN ALONG S	IDES	
		and the second second second	SEAL 26784	
MOORE AND ASSOCIATES ENGINEERING AND CONSULTING, INC.	DRAVN BY: LT CHECKED BY: PDH PRDJECT MGR: VSM	-	WMART BUILDI 1000 CYCLE LA SOUTH HILL, VA 4'-0" ENCLOSED	ANE 23970
THIS DOCUMENT IS STRUCTLY PROMIBITED AND ANY DIFRIMEMENT THEREUPON MAY DE SUBJECT TO LEGAL ACTION.	CLIENT: NEWMART BUILDERS	SHT. 3A	DWG. NDI SK-3	REV. 6



















### BASE RAIL ANCHORAGE OPTIONS FOR LOW WIND SPEEDS





#### **GENERAL NOTES**

3A

NOTE: CONCRETE MONDLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 PSF

#### CONCRETE

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH DF 3,000 PSI AT 28 DAYS.

#### COVER OVER REINFORCING STEEL

FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3' IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH OR WEATHER, AND 1 1/2' ELSEWHERE

#### REINFORCING STEEL

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM AGIS GRADE 60 THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT


#### REINFORCEMENT MAY BE BENT IN THE SHOP OR THE FIELD PROVIDED

REINFORCEMENT IS BENT COLD.

- 2 THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS 3 REINFORCEMENT PARTIALLY EMBEDIED IN CONCRETE SHALL NOT
- BE FIELD BENT


#### HELIX ANCHOR NOTESI

- 1 FOR VERY DENSE AND/OR CEMENTED SANDS, COARSE GRAVEL AND COBBLES, CALICHE, PRELOADED SILTS AND CLAYS, USE MINIMUM (2) 4" HELICES WITH MINIMUM 30" EMBEDMENT OR SINGLE 6" HELIX WITH MINIMUM SC" EMBEDMENT
- 2 FOR CORAL USE MINIMUM (2) 4' HELICES WITH MINIMUM 30' EMBEDMENT OR SINGLE 6' HELIX WITH MINIMUM SC' EMBEDMENT
- 3 FOR MEDIUM DENSE COARSE SANDS, SANDY GRAVELS, VERY STIFF SILTS, AND CLAYS USE MINIMUM (2) 4" HELICES WITH MINIMUM 30 INCH EMBEDMENT DR SINGLE 6" HELIX WITH MINIMUM 50" EMBEDMENT.
- 4 FOR LODSE TO MEDIUM TENSE SANDS, FIRM TO STIFF CLAYS AND SILTS ALLUVIAL FILL, USE MINIMUM (2) 6' HELICES WITH MINIMUM 5C' EMBEDMENT
- 5 FOR VERY LOSE TO MEDIUM DENSE SANDS, FIRM TO STIFFER CLAYS AND SILTS, ALLUVIAL FILL, USE MINIMUM (2) 8' HELICES WITH MINIMUM 6C' EMBEDMENT




MOORE AND ASSOCIATES ENGINEERING AND CONSULTING, INC.	DRAWN BY: LT CHECKED BY: PDH	-	NEWMART BUILDERS, INC. 1000 CYCLE LANE SOUTH HILL, VA 23970 30'-0"x14'-0" ENCLOSED STRUCTURE		
THIS DOCUMENT IS THE PROPERTY OF MODRE AND ASSOCIATES ENGINEERING AND CONSULTING THE UNAUTHORIZED REPRODUCTION, COPYING, OR DTHERVISE USE OF THIS DOCUMENT IS STRUCTLY PROMODICED AND ANY INFRINGEMENT THEREUPON MAY BE SUBJECT TO LEGAL ACTOON	PREJECT MGR: VSM CLIENT: NEVMART BUILDERS	DATE: 11-5-18 Sht. 8	SCALE NTS	JOB NO: 190335/181135/182465 REV. 6	







## **BOW EAVE RAFTER END WALL AND SIDE WALL OPENINGS**





## **BOX AND BOW EAVE RAFTER WALL OPENING DETAILS**














## **ADDITIONAL BASE RAIL ANCHORAGE OPTION**

