

Harnett County Department of Public Health

Improvement Permit

	A building permit cannot be issued with only an Improven	nent Permit
ISSUED TO: Thomas Allen	Denning PROPERTY LOCATION: 34 13	umpas Greek Access
NEW REPAIR EXPAI	NSION Site Improvements	required prior to Construction Authorization Issuance:
Type of Structure: SFD 84.5'	X 46	require prior to construction Authorization issuance.
	duction	
Projected Daily Flow: 360 GPD	,	
	ccupants:max	
Basement ☐Yes ☒ No ☐ May be ro		
	equired based on final location and elevations of facilities Well Distance from well 72 feet	171 -
Permit conditions:	The Distance from well 12 leer	Permit valid for: 🔀 Five years
2 /		
Authorized State Agent::	d REHS-I Date: 7-26-19	CCC ATTACHED CITY CHEEK
The issuance of this permit by the Health Department in ho Allow	12/20/00 the source of the source half in second half in second half	SEE ATTACHED SITE SKETCH checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the Site plan, plat, or the Intended us the Laws and Rules for Sewage Treatment and Disposal and to condi		checking with appropriate governing bodies in meeting their requirements. This whership of the site. This permit is subject to compliance with the provisions of
	tions of this permit.	
	Construction Authorization	
	Construction Authorization	
The construction and installation requirements of Rules 1950 1952	(Required for Building Permit)	
with the attached system layout.	1734, 1733, 1730, 1731, 1730. and 1739 are incorporated by reference	ses into this permit and shall be met. Systems shall be installed in accordance
WHEN TO Thomas Allen	Dannia.	P ()
more 10: Trottes Hiller	PROPERTY LOCATION: 34	Bumpas Creek Access
Facility Type: SFD 84.5' x41	SUBDIVISION	LOT #
	д пен с схранаюн с перан	r
Type of Wastewater System**		01.5
(See note below, if applicable)	eaucha i	(Initial) Wastewater Flow: 360 GPD
75%	Reduction (Renair)	
Installation Requirements/Conditions	Number of trenches 3	
Septic Tank Size 1000 gallons		Indian 9
Pump Tank Sizegallons	Trenches shall be installed on contour at a	Trench Spacing: Feet on Center
6.1013	Maximum Trench Depth of: 12 inches	Soil Cover:inches
	(Trench bottoms shall be level to +/-1/4"	The state of the s
	in all directions)	36" above the trench bottom)
Pump Requirements:ft. TDH vs	GPM	index before the
		Aggregate Depth: inches below pipe
Conditions:		inches total
		miches forai
VATER LINES (INCLUDING IRRIGATION) MUST	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR	REPAIR AREA
IO UTILITIES ALLOWED IN INITIAL OR REPAIR	DRAIN FIFID ARFA	REFAIR AREA.
wappincable. I understand the system type specifie	ed is different from the type specified on the application	n. I accept the specifications of this permit.
Owner/Legal Representative Signature:		
	plat, or the intended use changes. The Construction Authorization shall not	Date:
onstruction Authorization is subject to compliance with the provisions	of the Laws and Rules for Sewage Treatment and Disposal and to the condi	tions of this permit. SEE ATTACHED SITE SKETCH
	1 1 1 222	SEE MINCHED SHE SKEICH
uthorized State Agent:	Manhay to 12H3	7-7619
11/1/	Construction Authorization Expiration I	
Chat (C)		VAIE
	REHS-I	

HTE#	SFD1907.	-0008
------	----------	-------

Permit #

Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: 34 Bumpas Creek	(SIZ 1908)
DISTURBLE TO THE PROPERTY OF T	LOT #
Authorized State Agent: Date:	
This drawing is for illustrative Purposes only.	
system installation must meet all pertinent laws,	
rules, and regulations.	

