Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	. domento		viliton	vveich Rd, Camero		
ISSUED TO: Richard L		SUBDIVISION	SUBDIVISIONLOT #			
NEW X REPA		ISION Site Improv	rements re	quired prior to Construction Authori	ization Issuance:	
Proposed Wastewater System		uction				
Projected Daily Flow: 360		iction				
Number of bedrooms: 3		ccupants: 6 max		W		
Basement Yes X N		ccupantsmax				
	- CARETON	equired based on final location and elevations of facil	ities			
		Well Distance from well		Permit valid for:	★ Five years	
		d to design septic system			☐ No expiration	
	12-1	ELL REHS-T Date: 7/8/202	0	CCC ATT	ACUED CITE CHETCH	
Authorized State Agent::		parantees the issuance of other permits. The permit holder is respon			ACHED SITE SKETCH	
		ise changes. The Improvement Permit shall not be affected by a ch				
the Laws and Rules for Sewage Treat	ment and Disposal and to cond	litions of this permit.				
		Construction Authorizat	ion			
		(Required for Building Permit)				
militaria - malaban ema cambida sa Palabana a sa sa manda haranga a casa sa m	sirements of Rules .1950, .1952	1954, .1955, .1956, .1957, .1958, and .1959 are incorporated b	by references	into this permit and shall be met. Systems	shall be installed in accordance	
with the attached system layout.						
ISSUED TO:		PROPERTY LOCATION:				
		SUBDIVISION				
Facility Type:			Repair			
		Fixtures? Yes No				
Type of Wastewater System	- Parties Interpretation of the Control of the Cont	- N. C C C C C C C		(Initial) Wastewater Flow:	GPD	
(See note below, if applical				(minus) Wastewater Flows		
(see note below, if applical	//C 🗀 /	(Repair)				
Installation Requirements/Co	anditions	Number of trenches				
Septic Tank Size	9.00	Exact length of each trench	feet	Trench Spacing:	Feet on Center	
Pump Tank Size	o .	Trenches shall be installed on contour at a			nches	
rump rank size	ganons	Maximum Trench Depth of:	inches	(Maximum soil cover shall n		
		(Trench bottoms shall be level to +/-1/4"	inches	36" above the trench botto		
		The second of th		Jo above the trench botto	oiii)	
Duma Daminamanto	6 TDU	in all directions) GPM			inches below pine	
Pump Requirements:	1t. IUH VS	Grn		Aggregate Depth:	inches below pipe	
C divi				Aggregate Depth.	inches above pipe inches total	
Londitions:					Inches total	
WATER LIVES (INC. UR.)	0 10010 171011 1111	7 05 1057 50011 1111 D. D. O. SEDTIS SUST		DED. 10.51		
	•	T BE 10FT. FROM ANY PART OF SEPTIC SYST	EM OR	REPAIR AREA.		
NO UTILITIES ALLOWED I	N INITIAL OR REPAIR	R DRAIN FIELD AREA.				
**If applicable: / understand	the system type speci.	fied is different from the type specified on the a	polication	. I accept the specifications of t	this permit.	
wapineapie. 7	ine system type speem	are to emercial from the type specimes on the ap	ppmeanon	Letter the specimentons or .		
Owner/Legal Representative	Signature:			Date:	Mary Constitution Constitution (Constitution Constitution	
		an, plat, or the intended use changes. The Construction Authorization				
		ns of the Laws and Rules for Sewage Treatment and Disposal and t		****	ATTACHED SITE SKETCH	
		0 1				
Authorized State Agent.			Date:			
nutilionized state Agent						
		Construction Authorization Exp	iration L	Jale.		