

Job 20020021-J	Truss A01	Truss Type Common Supported Gable	Qty 15	Ply 1	quotes-Chuck Smith Job Reference (optional)
-------------------	--------------	--------------------------------------	-----------	----------	--

Carter Components, Sanford, NC, user

Run: 8.42 S Dec 30 2020 Print: 8.420 S Dec 30 2020 MiTek Industries, Inc. Fri Feb 12 12:31:21

Page: 1

ID:g_ZLYJsDNQV2OzqEl40Cp5zlv5S-9C4FK?OatW5m7A5N7QrHIGx2Yf8qGWuzBQSu1zIueM




Plate Offsets (X, Y): [8:0-5-0,0-4-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.82	Vert(LL)	-0.07	8-9	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.40	Vert(CT)	-0.12	8-9	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.28	Horz(CT)	0.03	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 138 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 2-2-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=1043/0-3-8, (min. 0-1-8), 6=1043/0-3-8, (min. 0-1-8)
 Max Horiz 2=-183 (LC 12)
 Max Uplift 2=-113 (LC 14), 6=-113 (LC 15)
 Max Grav 2=1171 (LC 24), 6=1171 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1646/162, 3-16=-1487/159, 16-17=-1402/174, 4-17=-1395/192, 4-18=-1395/192, 18-19=-1402/174, 5-19=-1487/159, 5-6=-1646/162
 BOT CHORD 2-9=-157/1476, 9-20=-1/970, 20-21=-1/970, 8-21=-1/970, 6-8=-40/1372
 WEBS 4-9=-95/688, 3-9=-422/208, 4-8=-95/688, 5-8=-422/208

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-2-8 to 1-9-8, Interior (1) 1-9-8 to 9-1-8, Exterior(2R) 9-1-8 to 15-1-8, Interior (1) 15-1-8 to 22-5-8, Exterior(2E) 22-5-8 to 25-5-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 20020021-J	Truss A02	Truss Type Common Supported Gable	Qty 1	Ply 1	quotes-Chuck Smith Job Reference (optional)
-------------------	--------------	--------------------------------------	----------	----------	--

Carter Components, Sanford, NC, user

Run: 8.42 S Dec 30 2020 Print: 8.420 S Dec 30 2020 MiTek Industries, Inc. Fri Feb 12 12:31:23

Page: 1

ID:5eMBRbjfERzPulyUorB3zlv4L-1zJmAMShxibHFkUscvZnRbQn1958m41UuoOf1ozluel



Scale = 1:48.1

Plate Offsets (X, Y): [2:0-3-8,Edge], [14:0-3-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	0.18	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.31	Horz(CT)	-0.01	16	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 148 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3
WEDGE Left: 2x4 SP No.3
Right: 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 10-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 24-3-0.
(lb) - Max Horiz 2=-183 (LC 12), 28=-183 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 14, 16, 17, 18, 19, 21, 23, 24, 25, 26, 27, 28, 34
Max Grav All reactions 250 (lb) or less at joint(s) 2, 17, 18, 19, 24, 25, 26, 27, 28 except 16=289 (LC 22), 21=262 (LC 22), 22=340 (LC 22), 23=258 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-35=-140/256, 3-35=-133/285, 3-4=-112/265, 4-5=-85/254
WEBS 8-22=-300/20

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner(3E) -1-2-8 to 1-9-8, Exterior(2N) 1-9-8 to 9-1-8, Corner(3R) 9-1-8 to 15-1-8, Exterior(2N) 15-1-8 to 22-5-8, Corner(3E) 22-5-8 to 25-5-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 2.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14, 14, 23, 24, 25, 26, 27, 21, 19, 18, 17, and 16. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job 20020021-J	Truss A02	Truss Type Common Supported Gable	Qty 1	Ply 1	quotes-Chuck Smith Job Reference (optional)
-------------------	--------------	--------------------------------------	----------	----------	--

Carter Components, Sanford, NC, user

Run: 8.42 S Dec 30 2020 Print: 8.420 S Dec 30 2020 MiTek Industries, Inc. Fri Feb 12 12:31:23

Page: 2

ID:5eMBRbjfERzPulyUorB3zlv4L-1zJmAMShxlbHFkUsczVnRbQn1958m41UuoOf1ozluel

LOAD CASE(S) Standard