## Harnett County Department of Public Health

## Improvement Permit A building permit cannot be issued with only an Improvement Permit

	PROPERTY LOCATION: 1378 Hicks Rd (SR 1266)
ISSUED TO: Ronald Hill	
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: workshop 48'x60'	
Proposed Wastewater System Type: 25% reduction	
Projected Daily Flow: 100 GPD  Number of bedrooms: O Number of Occupants: 1	max
Basement Tres No	III da
Pump Required: Wes No May be required based on final I	ocation and elevations of facilities
Type of Water Supply: Community Public Well Distar	
Permit conditions:	No expiration
Authorized State Agent:: Mal AET	Date: 09-30-22 SEE ATTACHED SITE SKETCH
Authorized State Agent::  The issuance of this permit by the Health Department in no way guarantees the issuance of other	er permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement	Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	
	2 1 2 2
Constr	ruction Authorization
	quired for Building Permit)
	, 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
ISSUED TO: Ronald Hill	PROPERTY LOCATION: 1378 Hicks Rd (SR 1266)
	SUBDIVISION LOT #
Facility Type: workshop 48'x60'	☐ Expansion ☐ Repair
Basement? Yes No Basement Fixtures? Yes	⊠ No
Type of Wastewater System** 25% reduction	(Initial) Wastewater Flow: 100 GPD
(See note below, if applicable )	
25% reduction	(Repair)
Installation Requirements/Conditions Number of trend	
Septic Tank Size 1000 gallons Exact length of	1 1 10 1 7 1 5 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	each trench 40feet Trench Spacing: 9 Feet on Center
- 0	e installed on contour at a Soil Cover: 6inches
Maximum Trench	ne installed on contour at a Soil Cover: 6inches h Depth of: 18-24inches (Maximum soil cover shall not exceed
Maximum Trench	e installed on contour at a Soil Cover: 6inches
Maximum Trench (Trench bottoms in all directions)	she installed on contour at a soil Cover: 6 inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)
Maximum Trench (Trench bottoms	she installed on contour at a soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"   Maximum soil cover shall not exceed 36" above the trench bottom)
Maximum Trench (Trench bottoms in all directions)	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Soil Cover: 6inches (Maximum soil cover shall not exceed 36" above the trench bottom)  inches below pipe Aggregate Depth:inches above pipe
Maximum Trench (Trench bottoms in all directions)	she installed on contour at a soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"   Maximum soil cover shall not exceed 36" above the trench bottom)
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  A.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	Soil Cover: 6inches h Depth of: 18-24inches shall be level to +/-1/4"  Aggregate Depth:inches above pipeinches total  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  A.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:ft. TDH vsGPM  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE  **If applicable: _I understand the system type specified is different from  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation if the site plan, plat, or the intended use	Soil Cover: 6inches h Depth of: 18-24inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)  Aggregate Depth:inches above pipeinches total  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  A.  the type specified on the application. I accept the specifications of this permit.  Date:  changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE  **If applicable: understand the system type specified is different from Owner/Legal Representative Signature:	Soil Cover: 6inches h Depth of: 18-24inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)  Aggregate Depth:inches above pipeinches total  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  A.  the type specified on the application. I accept the specifications of this permit.  Date:  changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:ft. TDH vsGPM  Conditions:ft. TDH vsGPM  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE  **If applicable:	Soil Cover: 6inches h Depth of: 18-24inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)  Aggregate Depth:inches above pipeinches total  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  A.  the type specified on the application. I accept the specifications of this permit.  Date:  changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Sewage Treatment and Disposal and to the conditions of this permit.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:ft. TDH vsGPM  Conditions:	Soil Cover: 6inches h Depth of: 18-24inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)  ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.  See Sewage Treatment and Disposal and to the conditions of this permit.  See ATTACHED SITE SKETCH

## Harnett County Department of Public Health Site Sketch

operty Location: 1378 Hicks Rd (SR sued To: Ronald Hill	Subdivision	Lot #
uthorized State Agent: Mal	La SEHS	Date: <u>09-30-22</u>
C		
		25%/1dvc1101
		futura 25% reduction
		1 40'
		1 9' 40'
		990
workshop =>[		<b>1</b> 30'
workshop		C. istic
		Existing Pole Born
	]	tole born
)	(1001)	
	Driveway TO His	he Rd ->