


Job Q-2302145-1	Truss T1	Truss Type Common	Qty 18	Ply 1	Lucas Shelter-Lucas Shelter Job Reference (optional)
--------------------	-------------	----------------------	-----------	----------	---

Peak Truss Builders LLC, New Hill, user

Run: 8.72 S Sep 21 2023 Print: 8.720 S Sep 21 2023 MiTek Industries, Inc. Thu Oct 12 11:47:37

Page: 1

ID:VcWXdaL1YmuR9BLeM\_z4EyUAwn-kQgenvGKQbWv1c8f1s0iULpxwcH6wNqlapsFfyUAva



Scale = 1:62.5

Plate Offsets (X, Y): [1:0-0-2,Edge], [9:0-0-2,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.57	Vert(LL)	-0.23	12-14	>999	240	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.77	Vert(CT)	-0.48	12-14	>945	180		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.14	9	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS								Weight: 181 lb FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.3

**BRACING**  
 TOP CHORD Structural wood sheathing directly applied or 2-9-5 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** (lb/size) 1=1507/0-5-8, (min. 0-2-6), 9=1507/0-5-8, (min. 0-2-6)  
 Max Horiz 1=-104 (LC 9)  
 Max Uplift 1=-186 (LC 11), 9=-186 (LC 11)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-21=-3281/440, 2-21=-3222/454, 2-3=-2973/382, 3-4=-2900/408, 4-22=-2057/325, 5-22=-1982/351, 5-23=-1982/351, 6-23=-2057/325, 6-7=-2900/408, 7-8=-2973/382, 8-24=-3222/454, 9-24=-3281/440  
 BOT CHORD 1-14=-356/2992, 13-14=-226/2403, 13-25=-226/2403, 25-26=-226/2403, 12-26=-226/2403, 11-12=-226/2403, 11-27=-226/2403, 27-28=-226/2403, 10-28=-226/2403, 9-10=-356/2992  
 WEBS 5-12=-141/1187, 6-12=-776/188, 6-10=-4/572, 8-10=-422/171, 4-12=-776/188, 4-14=-4/572, 2-14=-422/171

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; B=20ft; L=38ft; eave=5ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior (2) 0-0-0 to 3-9-3, Interior (1) 3-9-3 to 18-10-0, Exterior (2) 18-10-0 to 22-7-3, Interior (1) 22-7-3 to 37-8-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 186 lb uplift at joint 1 and 186 lb uplift at joint 9.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


Job Q-2302145-1	Truss T1GE	Truss Type Common Supported Gable	Qty 2	Ply 1	Lucas Shelter-Lucas Shelter Job Reference (optional)
--------------------	---------------	--------------------------------------	----------	----------	---

Peak Truss Builders LLC, New Hill, user

Run: 8.72 S Sep 21 2023 Print: 8.720 S Sep 21 2023 MiTek Industries, Inc. Thu Oct 12 11:47:37

Page: 1

ID:zo4vqwMfJ40InLpXC3VCdSyUAwm-kQgenvGKQQbWv1c8f1s0iULxzwoQ68oQlapsFfyUAva



Scale = 1:62.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.06	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0*	Rep Stress Incr	YES	WB	0.12	Horiz(TL)	0.00	21	n/a	n/a		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-MS								Weight: 221 lb FT = 20%

**LUMBER**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x4 SP No.1  
 OTHERS 2x4 SP No.3

**BRACING**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS** All bearings 37-8-0.  
 (lb) - Max Horiz 1=-104 (LC 9), 41=-104 (LC 9)  
 Max Uplift All uplift 100 (lb) or less at joint(s) 22, 23, 24, 25, 26, 27, 28, 30, 32, 33, 34, 35, 36, 37, 39, 40  
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 21, 22, 23, 24, 25, 26, 27, 28, 30, 31, 32, 33, 34, 35, 36, 37, 39, 40, 41, 44

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**FORCES** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCCL=6.0psf; h=30ft; B=20ft; L=38ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner (3) 0-0-0 to 3-9-3, Exterior (2) 3-9-3 to 18-10-0, Corner (3) 18-10-0 to 22-10-0, Exterior (2) 22-10-0 to 37-8-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 32, 33, 34, 35, 36, 37, 39, 40, 30, 28, 27, 26, 25, 24, 23, 22.
  - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 21, 44.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard