Bres 2306-0053

Harnett County Department of Public Health

Improvement Permit

	permit cannot be issued with only an Improvement Permit
	PROPERTY LOCATION: 415 Roberts rd (SR 2158)
ISSUED TO: Joseph Lugiano	SUBDIVISION LOT #
NEW REPAIR EXPANSION Type of Structure: 70'x64' SFD	Site Improvements required prior to Construction Authorization Issuance:
Proposed Wastewater System Type: 25% reduction	
Projected Daily Flow: 360 GPD	
Number of bedrooms: 3 Number of Occupants:	S max
	2 1101
Basement Yes No	and are final location and elevations of facilities
Pump Required: Yes No May be required bas	ed on final location and elevations of facilities Vell Distance from well feet Permit valid for: 🔀 Five years
Type of Water Supply: Community X Public V	Distance from well leet remit valid for.
Permit conditions:	The Expiration
1 . N	
#// // 05	HF Date: 07-14-23 SEE ATTACHED SITE SKETCH
Authorized State Agent:: / Yall Wife	
The issuance of this permit by the Health Department in no way guarantees the	issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This he Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this	ne improvement retinit shan not be anected by a change in ownership of the site. This period is society to comprise the first the province of
the Laws and holes for sewage freatment and proposal and to contamons of this	per min.
	Construction Authorization
	(Required for Building Permit)
The construction and installation requirements of Rules 1950-1952-1954-195	5, 1956, 1957, 1958 and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
ISSUED TO: Joseph Lugiano	PROPERTY LOCATION: 415 Roberts rd (SR 2158)
	SUBDIVISION LOT #
Facility Type: 70'x64' SFD	New Expansion Repair
7 77	
Type of Wastewater System** 25% reduction	(Initial) Wastewater Flow: 360 GPD
(See note below, if applicable)	
25% reduction	(Repair)
Installation Requirements/Conditions Num	ber of trenches 1
	t length of each trench 180feet
Films lank 1/79 gallong	char thall be installed on contour at a Soil Cover 6 inches
	ches shall be installed on contour at a Soil Cover: 6 inches
Max	mum Trench Depth of: 24 inches (Maximum soil cover shall not exceed
Max	cites still be instance on control at
Max (Tre	mum Trench Depth of: 24 inches (Maximum soil cover shall not exceed
Max (Tre in a	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) directions inches below pipe
Max (Tre in a	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) Il directions)inches below pipe
Max (Tre in a Pump Requirements:ft. TDH vsGPI	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed above the trench bottom) directions inches below pipe inches above pipe
Max (Tre in a	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed above the trench bottom) directions inches below pipe Aggregate Depth:inches above pipe
Max (Tre in a Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) inches below pipe Aggregate Depth:inches above pipe inches above pipe
Max (Tre in a Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) inches below pipe Aggregate Depth:inches above pipe inches above pipe
Pump Requirements:ft. TDH vsGPM Conditions: 36" curtain drain will be requi	mum Trench Depth of: 24inches
Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements ft. TDH vsGPN WATER LINES (INCLUDING IRRIGATION) MUST BE 100 NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN	mum Trench Depth of: 24inches
Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements ft. TDH vsGPN WATER LINES (INCLUDING IRRIGATION) MUST BE 100 NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN	mum Trench Depth of: 24inches (Maximum soil cover shall not exceed above the trench bottom) directions inches below pipe Aggregate Depth:inches above pipe inches total FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements ft. TDH vsGPN WATER LINES (INCLUDING IRRIGATION) MUST BE 100 NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN	mum Trench Depth of: 24inches
Pump Requirements:ft. TDH vsGPN Conditions: 36" curtain drain will be requirements:ft. TDH vsGPN WATER LINES (INCLUDING IRRIGATION) MUST BE 10: NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN **If applicable: 1 understand the system type specified is different type.	mum Trench Depth of: 24inches
Pump Requirements:ft. TDH vsGPI Conditions:ft. TDH vsGPI WATER LINES (INCLUDING IRRIGATION) MUST BE 10 NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN **If applicable: 1 understand the system type specified is did Owner/Legal Representative Signature:	mum Trench Depth of: 24 inches (Maximum soil cover shall not exceed above shall be level to +/-1/4" 36" above the trench bottom) directions inches below pipe inches above pipe inches above pipe inches total FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. FIELD AREA. FIELD AREA.
Pump Requirements:	mum Trench Depth of: 24 inches
Pump Requirements:	mum Trench Depth of: 24 inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) directions inches below pipe
Pump Requirements:	inches below pipe Aggregate Depth:
Pump Requirements:ft. TDH vsGPP Conditions:ft. TDH vsGPP Conditions:ft. TDH vsGPP WATER LINES (INCLUDING IRRIGATION) MUST BE 10: NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN **If applicable:	mum Trench Depth of: 24 inches (Maximum soil cover shall not exceed nch bottoms shall be level to +/-1/4" 36" above the trench bottom) directions inches below pipe inches above pipe inches above pipe inches above pipe inches total FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. FIELD AREA. General from the type specified on the application. I accept the specifications of this permit.

Harnett County Department of Public Health Site Sketch



This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.