



NC 1-919-787-8787 / 1-800-473-8787  
Fax 1-919-783-0617

VA 1-757-833-5300 / 1-800-868-8787  
Fax 1-757-833-5400

**THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.**

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the entire truss support structure including, but not limited to headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of wood trusses" available from the Truss Plate Institute, 583 D'Onifrio Drive, Madison, WI 53179

**TRUSS TO BEARING DESIGN RESPONSIBILITY.**

Truss to bearing connections if shown on this layout are suggested by Truswood based solely on the uplift reactions and considerations for the truss component. All truss to bearing connections must be specified or approved by the Building Designer to adequately transfer all loads to the building system and foundation. Consult hardware manufacturer's specifications for all installation requirements.

**GENERAL NOTES:**

- 1.) REFER TO INDIVIDUAL TRUSS DRAWINGS FOR ADDITIONAL .....INFO.
- 2.) DIMENSIONS SHOWN ARE FROM FACE OF STUD OF BEARING .....WALL U.N.O.
- 3.) DIMENSIONAL VERIFICATION IS THE RESPONSIBILITY OF THE .....SITE CONTRACTOR AND /OR ARCHITECT.
- 4.) ALL INTERIOR HEADERS TO BE DROPPED EXCEPT AS NOTED.
- 5.) ALL TRUSSES MUST BE SPACED AT A MAXIMUM OF 24" OC .....UNLESS OTHERWISE NOTED.
- 6.) \*DO NOT CUT, DRILL, OR ALTER ANY TRUSS WITHOUT THE .....\*WRITTEN CONSENT FROM A REGISTERED ENGINEER.

CUSTOMER NAME:	Cambell Garage
PROJECT:	Cambell Garage
DATE:	8/2/23
SCALE:	SCALE
REVISION:	
REVISION:	
REVISION:	
FILENAME:	R
LOT:	
DATE:	
BY:	
DATE:	
BY:	
DATE:	
BY:	

DESIGNED BY: psc CHECKED BY:

JOB NUMBER: 2300753