DEPARTMENT OF HEALTH AND HUMAN SERVICES DIVISION OF PUBLIC HEALTH, ENVIRONMENTAL HEALTH SECTION ON-SITE WATER PROTECTION BRANCH

	Page 1	of
PROPERTY ID #: _		
COUNTY:		

011 01	TE WATERTROTT	Serior Blant								100 Folds	
					TON for ON (Complete all	-SITE WASTE	WATER SY	STEM			
OWN	ER: _ Cherles RESS: _ POSED FACILITY ATION OF SITE: _	Wilson			(Complete an	neids in fuir)		DAT	E EVALU	ATED:	
ADD	RESS:	3964 Mr	Pisgal Ch	. Rel	D DESIGN	FLOW (.0400):	100500	PROP	FRTY SIZ	E.	
LOCA	ATION OF SITE:	Sar	1	KOI OSE	D DESIGN	1 LOW (.0400).	100 700	PROPE	ERTY REC	ORDED:	
WAT	ER SUPPLY:	Publie Sin	gle Family Well		red Well	Spring Oth	er	WATE	R SUPPLY	SETBACK:_	
EVAI	LUATION METH	OD: Auge	er Boring Pit	Cut	TY	PE OF WASTE	WATER:	Domest	ic High	Strength	IPWW
P R O F			SOIL MORPHOLOGY			OTHER PROFILE FACTORS					
I L E	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTURE TEXTURE	CON	.0503 SISTENCE/ ERALOGY	.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
		0-10	45			104R6/1 232	. "			5	
	/_	10-48	SCI			\$ 72"	>48"	_		-4	
1	2-5%	,				232					1 41/8
	2-5%					-					il de
						-					15 4
_											-
		0-12	15			10 ya 6/2 = 31"	~u8"	_	_	5	
	2-5%	12-48	sci			≥31	740			.4	
2	2-56							E			
1											
ļ						-					
2				-		-					
3											
4											
Ι'				+		-					
	3			-		-					
L					Marie University Control						
	DESCRIPTION	INITIAL SYS	STEM REPAIR	SYSTEM							
	able Space (.0508)	V	- V		SITE CLA	SSIFICATION (	.0509):				
	m Type(s)				EVALUAT	ΓΕD BY:		A	a - 11.		
Site L	TAR	. 4	-4		UTHER(S)	PRESENT:	m	1	RLID		

Maximum Trench Depth

Comments:

## **LEGEND**

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE
CC (Concave slope)		S (Sand)		0.6 - 0.8		MOIST	WET	SG (Single grain)
CV (Convex Slope)	ı	LS (Loamy sand)	0.8 - 1.2	0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)
D (Drainage way)	11	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)
FP (Flood plain)		L (Loam)		0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)
FS (Foot slope)		SiL (Silt loam)		0.1 - 0.3		FI (Firm)	VS (Very sticky)	ABK (Angular blocky)
H (Head slope)	Ш	SCL (Sandy clay Ioam)		0.05 - 0.15**	0.15 - 0.3	VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)
L (Linear Slope)		CL (Clay loam)	0.3 - 0.6			EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)
N (Nose slope)		SiCL (Silty clay loam)					P (Plastic)	
R (Ridge/summit)		Si (Silt)		None			VP (Very plastic)	
S (Shoulder slope)		SC (Sandy clay)				SEXP (Slightly	expansive)	
T (Terrace)	IV	SiC (Silty clay)	0.1 - 0.4		0.05 - 0.2 EXP (I	EXP (Expansive)		
TS (Toe Slope)		C (Clay)						•
		O (Organic)	None					

<sup>\*</sup> Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

HORIZON DEPTH

In inches below natural soil surface

DEPTH OF FILL

In inches from land surface

RESTRICTIVE HORIZON SAPROLITE Thickness and depth from land surface S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits.

SOIL WETNESS CLASSIFICATION Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation

S (Suitable) or U (Unsuitable)

Show profile locations and other site features (dimensions, reference or benchmark, and North).

Mr Pisgah Ch. Rd

<sup>\*\*</sup>Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200.