6029

Harnett County Department of Public Health

Improvement Permit

A politific bettill caulity of issued with	TION: 51/538 Mobry PLD	
ISSUED TO: STEPHENSON BUTICES FIX SUBDIVISION	LOT #	
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:	
Type of Structure: SD + Det 642		
Proposed Wastewater System Type: 25% 12600 CTCD		
Projected Daily Flow: 480 GPD		
Number of bedrooms: / M Number of Occupants: 8max		
Basement Yes No		
Pump Required: Yes No May be required based on final location and eleva	tions of facilities	
Type of Water Supply: Community Public Well Distance from well		
Permit conditions:	No expiration	
1 1 7011		
Markar For TRAS	10-2-23 SEE ATTACHED SITE SKETCH	
Authorized State Agent. The issuance of this permit by the yealth Department in no way guarantees the issuance of other permits. The permit		
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be		
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.		
Construction Authorization		
(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 at		
with the attached system layout.	4 22	
Facility Type: SPD + Det GALV New Expansion	LOCATION: SC MABRY 143	
SUBDIVISION SUBDIV	ON LOT #	
Facility Type: STORY New LExpans	ion LI Repair	
Basement? ☐ Yes ☑ No Basement Fixtures? ☐ Yes ☑ No	4445	
Type of Wastewater System** 25% TREBUCTOD 540+6	(Initial) Wastewater Flow: 488 GPD	
(See note below, if applicable)		
56% TRAVLETAN (PPBS	≥ J Repair)	
Installation Requirements/Conditions Number of trenches	P	
Septic Tank Size 1250 gallons Exact length of each trench	75feet Trench Spacing: Feet on Center ontour at a Soil Cover: inches	
Pump Tank Size 1250 gallons Trenches shall be installed on co	ontour at a Soil Cover:inches	
Maximum Trench Depth of:	18 minches (Maximum soil cover shall not exceed	
(Trench bottoms shall be level t	to +/-1/4" 36" above the trench bottom)	
in all directions)		
Pump Requirements:ft. TDH vsGPM	inches below pipe	
	Aggregate Depth: inches below pipe	
Conditions:	inches total	
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF S	EPTIC SYSTEM OR REPAIR AREA	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	ETTIC STSTEM ON RETAIN AREA.	
**If applicable: 1 understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.		
Owner/Legal Representative Signature:	Date:	
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This		
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.		
1 127643		
Authorized State Agence & Marshand Date: 10-2-23 Construction Authorization Expiration Date: 10-2-28		
Construction Author	ization Evolution Date: 10-7-79	
- I ODSTRUCTION AUTHOR	IZALIUII EXDITALIUII DALE,	

Harnett County Department of Public Health Site Sketch

Property Location: 50 Malong 140 Issued To: STEPHENSON BUELden Subdivision	
Issued To: STEPHENSON BUELDES Subdivision	Lot #
Authorized State Agent: ones & Marshand REHS	Date: <u>/0 -z - 23</u>
West of Property of the Proper	
De stri	
De stri	
- Sa Pari	
196.88	

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.