PROPERTY ID #: Bre \$ 240 3-000 COUNTY: Horaett

## SOIL/SITE EVALUATION for ON-SITE WASTEWATER SYSTEM

			. 1.	(Complete all	fields in full)					1 212
OWNE	R: Mar 1.1/	Jane	Langdon				DA	ΓΕ EVALU	ATED:/	0-21-2
PROP	ER: Mar 1: 1/2 ESS: 3149 OSED FACILITY	: DU	Ka	PROPOSED DESIGN	FLOW (.0400):	360	PROP	ERTY SIZ	E:	
LOCA	TION OF SITE:							ERTY REC		
WATE	ER SUPPLY:	Public Sir	ngle Family We	ell Shared Well	Spring Oth	ner	WATE	R SUPPLY	SETBACK	:
EVAL	UATION METH	OD: Aug	er Boring F	Pit Cut TY	PE OF WASTE	EWATER:	Domest	ic High	Strength	IPWW
P R O F	£ 1		SOIL MORPHOLOGY		OTHER PROFIL		LE FACTORS			
L E #	.0502 LANDSCAPE POSITION/ SLOPE %	HORIZON DEPTH (IN.)	.0503 STRUCTUR TEXTURE		.0504 SOIL WETNESS/ COLOR	.0505 SOIL DEPTH	.0506 SAPRO CLASS	.0507 RESTR HORIZ	.0509 PROFILE CLASS & LTAR*	.0503 SLOPE CORRE CTION
٤x.	2%	0-40	54,9"	VFF, NS, NP, SE		48"				
5/5/4 1	eck	40-48	Sel,58K	FYSS, NO, SE		48			.8	
H	2%	0-38	54,21			48"			,375	
2,3	15	38-48	SC, SIN	Fr,55, NP,5E	-				,3,2	
4	2%	0-31 31-48	56 g ( Sec, 58 K	Fryss, NYSE	-	48''			,375	
H					1					
4									3	
distribution of			MARKET STATE OF THE STATE OF TH		The state of the s		and the state of t			or Company of the Assessment
	ESCRIPTION	INITIAL SY	_	R SYSTEM		5				
	Type(s)	Ex. Sys	757	SITE CLA EVALUAT	SSIFICATION ( TED BY:	.0509):				
Jocenn	- ) Po(0)	CM VEntion	a1 42	LVALUA.	LUDI. NG					

OTHER(S) PRESENT:

,375

Maximum Trench Depth

Site LTAR

Comments:

## **LEGEND**

LANDSCAPE POSITION	SOIL GROUP	SOIL TEXTURE	CONVENTIONAL LTAR (gpd/ft²)	SAPROLITE LTAR (gpd/ft²)	LPP LTAR (gpd/ft²)	MINERALOGY/ CONSISTENCE		STRUCTURE	
CC (Concave slope)		S (Sand)		0.6 - 0.8		MOIST	WET	SG (Single grain)	
CV (Convex Slope)		LS (Loamy sand)	0.8 - 1.2	0.5 -0.7	0.4 -0.6	Lo (Loose)	NS (Non-sticky)	M (Massive)	
D (Drainage way)	п	SL (Sandy loam)	0.6 - 0.8	0.4 -0.6	0.3 - 0.4	VFR (Very friable)	SS (Slightly sticky)	GR (Granular)	
FP (Flood plain)		L (Loam)		0.2 - 0.4		FR (Friable)	S (Sticky)	SBK (Subangular blocky)	
FS (Foot slope)	111	SiL (Silt loam)	0.3 - 0.6	0.1 - 0.3		FI (Firm)	VS (Very sticky)	ABK (Angular blocky)	
H (Head slope)		SCL (Sandy clay loam)		0.05 - 0.15**	0.15 - 0.3	VFI (Very firm)	NP (Non-plastic)	PR (Prismatic)	
L (Linear Slope)		CL (Clay loam)		None		EFI (Extremely firm)	SP (Slightly plastic)	PL (Platy)	
N (Nose slope)  R (Ridge/summit)		SiCL (Silty clay loam)					P (Plastic) VP		
		Si (Silt)					(Very plastic)		
S (Shoulder slope)	IV	SC (Sandy clay)	0.1 - 0.4		0.05 - 0.2	SEXP (Slightly expansive)		1.0	
T (Terrace)		SiC (Silty clay)				EXP (Expansive)			
TS (Toe Slope)		C (Clay)						,	
		O (Organic)	None						

HORIZON DEPTH

In inches below natural soil surface In inches from land surface :

DEPTH OF FILL RESTRICTIVE HORIZON

Thickness and depth from land surface

**SAPROLITE** 

S(suitable) or U(unsuitable); Evaluation of saprolite shall be by pits.

SOIL WETNESS CLASSIFICATION Inches from land surface to free water or inches from land surface to soil colors with chroma 2 or less - record Munsell color chip designation

S (Suitable) or U (Unsuitable)

Show profile locations and other site features (dimensions, reference or benchmark, and North). 124' to contar of ful

<sup>\*</sup> Adjust LTAR due to depth, consistence, structure, soil wetness, landscape, position, wastewater flow and quality.

\*\*Sandy clay loam saprolite can only be used with advanced pretreatment in accordance with 15A NCAC 18E .1200.