

HAL OWEN & ASSOCIATES, INC.

SOIL & ENVIRONMENTAL SCIENTISTS

P.O. Box 400, Lillington, NC 27546-0400

Phone (910) 893-8743 / Fax (910) 893-3594

www.halowensoil.com

20 May 2024

Tom Ludke

Reference: Preliminary Soil Investigation
Gilchrist Road; PIN 9575-02-4533

Dear Mr. Ludke,

A site investigation has been conducted for the above referenced property, located on the northern side of Gilchrist Road in Harnett County, North Carolina. The purpose of this investigation was to determine the site's ability to support subsurface sewage waste disposal systems. This report and map are intended for planning purposes only and not for lot recordation.

All sewage disposal ratings and determinations were made in accordance with the Rules for "Wastewater Treatment and Dispersal Systems", 15A NCAC 18E. This report represents my professional opinion as a Licensed Soil Scientist but does not guarantee or represent permit approval for any lot by the Local Health Department. An application for an approved wastewater system shall be made to the Local Health Department that specifies the proposed building size and location and the design and location of the septic system to be installed.

The soils were evaluated under moist soil conditions through the advancing of auger borings. This evaluation included observations of topography and landscape position, soil morphology (texture, structure, clay mineralogy, organics), soil wetness, soil depth, and restrictive horizons. Soils units shown on the attached map represent dominant soil types with similar profiles but may include minor components of contrasting soil types.

The soils shown as suitable on the attached map are adequate to support subsurface sewage waste disposal systems. You should expect that approximately 50 feet of accepted status drainline would be required for the initial system per bedroom in any proposed residence.

The soils shown as suitable for low profile chamber systems are limited in soil depth to the extent that low profile chamber type drainlines installed at-grade will likely be required. Due to ultra shallow trench depths, the addition of approximately six inches of approved soil will be necessary to completely cover the system. You should expect that approximately 100 feet of low profile chamber drainline would be required for the initial system per bedroom in any proposed residence.

The unsuitable soil area is so rated due to a 50-foot setback from an existing well. In order to negate this setback, the well will need to be properly abandoned.

It appears that the soils underlying this property are adequate to support the septic disposal needs of a three- or four-bedroom residence. I appreciate the opportunity to provide this service and trust that you will feel free to call on me again in the future. If you have any questions or need additional information, please contact me at your convenience.



Sincerely,




A handwritten signature in cursive script that reads "Britt Wilson".

Britt Wilson
Licensed Soil Scientist

Preliminary Soil Investigation
Gilchrist Road; PIN 9575-02-4533
20 May 2024


SOIL MAP

Soil Map Legend

	Suitable
	Suitable for Low Profile Systems
	Unsuitable



Scale 1 in = 50 ft



*Map for reference only.
Distances are paced and
approximate. Not a survey.*

