


ENCLOSED GABLE END BUILDING

MIN. 31' TO MAX. 60' WIDE X 20' EAVE HEIGHT WITH BOX FRAME / (UP TO) 145 M.P.H. WIND ZONE - 35 P.S.F. SNOW LOAD

FOR:

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

ISSUE DATE: 12/12/2024




12/12/2024
THESE PLANS HAVE BEEN PROPERLY EXAMINED BY THE UNDERSIGNED. I DETERMINED THAT THEY COMPLY WITH EXISTING LOCAL NORTH CAROLINA CODES AND ARE APPROPRIATE FOR USE IN THIS AREA


NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDAR YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

SHEET INDEX

SHEET NUMBER	SHEET TITLE
S0	SEALED COVER SHEET
S2	DRAWING INDEX
S3	GENERAL NOTES AND SPECIFICATIONS
S4	END ELEVATION
S4A	SIDE ELEVATION
S5	TYPICAL RAFTER / COLUMN FRAME SECTIONS (<20'H / >31' TO <40'W)
S5A	TYPICAL RAFTER / COLUMN FRAME SECTIONS (<20'H / >41' TO <50'W)
S5B	TYPICAL RAFTER / COLUMN FRAME SECTIONS (<20'H / >51' TO <60'W)
S5C	TYPICAL FRAME SECTION
S5D	TYPICAL FRAME SECTION
S6	BOX EAVE / LACED COLUMN SECTION (<20'H / >31' TO <50')
S6A	BOX EAVE / LACED COLUMN SECTION (<20'H / >51' TO <60')
S7	BASE RAIL ANCHORGE / SINGLE COLUMN
S7A	BASE RAIL ANCHORGE / SINGLE COLUMN (NO SLAB)
S7B	BASE RAIL ANCHORGE / SINGLE COLUMN (NO SIDING SHELF)
S7C	BASE RAIL ANCHORGE / SINGLE COLUMN (NO SLAB / NO SIDING SHELF)
S7D	BASE RAIL ANCHORGE / SINGLE COLUMN (CLIP ANGLE ATTACHMENT OPTION)
S7E	BASE RAIL ANCHORGE / DOUBLE COLUMN
S7F	BASE RAIL ANCHORGE / DOUBLE COLUMN (NO SLAB)
S7G	BASE RAIL ANCHORGE / DOUBLE COLUMN (NO SIDING SHELF)
S7H	BASE RAIL ANCHORGE / DOUBLE COLUMN (NO SLAB / NO SIDING SHELF)
S7J	BASE RAIL ANCHORGE / LACED COLUMN (NO SLAB / NO SIDING SHELF)
S7K	BASE RAIL ANCHORGE / LACED COLUMN (NO SLAB / NO SIDING SHELF)
S7L	BASE RAIL ANCHORGE / LACED COLUMN (NO SLAB / NO SIDING SHELF)
S7M	BASE RAIL ANCHORGE / LACED COLUMN (NO SLAB / NO SIDING SHELF)


SHEET NUMBER	SHEET TITLE
S8	(SOIL) BASE RAIL ANCHORAGE
S9	TYPICAL BOX EAVE / END WALL FRAMING AND OPENINGS
S9A	TYPICAL BOX EAVE / END WALL FRAMING AND OPENINGS
S9B	TYPICAL BOX EAVE / SIDE WALL FRAMING AND OPENINGS
S10	CONNECTION DETAILS
S11	CONNECTION DETAILS
S12	CONNECTION DETAILS
S13	CONNECTION DETAILS
S14	BOX EAVE RAFTER / SINGLE & DOUBLE RAFTER LEAN-TO OPTIONS
S14A	BOX EAVE / LACED RAFTER LEAN-TO OPTIONS
S14B	LEAN-TO HIP OPTIONS
S15	LEAN-TO CONNECTION DETAILS / SINGLE COLUMN
S15A	LEAN-TO CONNECTION DETAILS / DOUBLE COLUMN
S15B	LEAN-TO CONNECTION DETAILS / SINGLE COLUMN / LACED RAFTER
S15C	LEAN-TO CONNECTION DETAILS / DOUBLE COLUMN / LACED RAFTER
S15D	LEAN-TO / MAIN FRAME CONNECTION DETAILS
S15E	LEAN-TO / MAIN FRAME / LACED RAFTER CONNECTION DETAIL
S15F	LEAN-TO / MAIN FRAME CONNECTION DETAILS
S15G	LEAN-TO / MAIN FRAME / LACED RAFTER CONNECTION DETAIL (FLUSH)
S15H	END WALL COLUMN / HIP RAFTER CONNECTION DETAIL
S16	VERTICAL ROOF / SIDING OPTION
S16A	VERTICAL ROOF / SIDING OPTION
S16B	VERTICAL ROOF / SIDING OPTION
S17	SIDE WALL HEADER OPTIONS
S17A	END WALL HEADER OPTIONS



 <p>TAYLOR & VIOLA STRUCTURAL ENGINEERS P.O.B. 2616 HICKORY NORTH CAROLINA TELE: 828-328-6331 FAX: 828-322-1801 WWW.TAYLORVIOLA.COM</p> <p>JCMT Associates, PLLC 211 Stone Drive, Pilot Mountain, NC 27041 Telephone: (336) 399-6277</p>	<p>Tyler Heishman 2603 Abattoir Rd Coats, NC 27521</p>	DRAWN BY: BKS	PROJECT NO: 0724-0122
		DATE: 12/12/24	SHEET NO: S2


NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

BOX EVE FRAME RAFTER STURCTURE



W >31'-0" TO <60'-0" MAXIMUM RAFTER SPAN

TYPICAL END ELEVATION



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122


DATE:
 12/12/24

SHEET NO:
S4

BOX EVE FRAME RAFTER STURCTURE



TYPICAL SIDE ELEVATION



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0


Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521

DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S4A



TYPICAL RAFTER / COLUMN FRAME SECTION

NORTH CAROLINA
 PROFESSIONAL SEAL
 27874
 JASON M. REEP
 ENGINEER
 12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S5

>41' TO <50'



TYPICAL RAFTER / COLUMN FRAME SECTION



12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
SSA

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.



TYPICAL RAFTER / COLUMN FRAME SECTION

NORTH CAROLINA
 PROFESSIONAL ENGINEER
 SEAL
 27874
 JASON M. REEP
 12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S5B

TYPICAL FRAME SECTIONS



TYPICAL RAFTER / COLUMN / END WALL FRAME SECTION

12/12/2024

TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521



DRAWN BY:
BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S5C

TYPICAL FRAME SECTIONS



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S5D


>31'-0" TO <50'-0"




**BOX EAVE / CORNER POST CONNECTION DETAIL
FOR HEIGHTS <20'-0"**

1
S6

SCALE: 3/4" = 1'-0"



18ga. U-CHANNEL BRACE FASTENED TO THE COLUMN AND BOTTOM CHORD WITH #12-14 x 3/4" S.D.F.'S AT EACH END AS SHOWN IN ELEVATION.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S6


NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.




**BOX EAVE / CORNER POST CONNECTION DETAIL
FOR HEIGHTS <math>< 20'-0''</math>**

1
S6A

SCALE: 3/4" = 1'-0"



18ga. U-CHANNEL BRACE FASTENED TO THE COLUMN AND BOTTOM CHORD WITH #12-14 x 3/4" S.D.F.'S AT EACH END AS SHOWN IN ELEVATION.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S6A

CONCRETE BASE RAIL ANCHORAGE (LEAN-TO'S ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**BASE RAIL ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"

1
S7 **BASE RAIL ANCHORAGE DETAIL**

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24


SHEET NO:
S7

CONCRETE BASE RAIL ANCHORAGE (NO SLAB / LEAN-TO'S ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



SCALE: 3/4" = 1'-0"



1 BASE RAIL ANCHORAGE DETAIL (NO SLAB)

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENTS SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7A

CONCRETE BASE RAIL ANCHORAGE (NO LEDGE / LEAN-TO'S ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**BASE RAIL ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"



1 BASE RAIL ANCHORAGE DETAIL

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENTS SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC

211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7B


CONCRETE BASE RAIL ANCHORAGE (NO LEDGE / NO SLAB / LEAN-TO'S ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**BASE RAIL ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"



1
S7C **BASE RAIL ANCHORAGE DETAIL (NO SLAB)**
SCALE: 3/4" = 1'-0"

GENERAL NOTES:


ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:
CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:
FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318:
3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:
THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

- REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:**
1. REINFORCEMENT IS BENT COLD.
 2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
 3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.




12/12/2024

 TAYLOR & VIOLA STRUCTURAL ENGINEERS P.O.B. 2616 HICKORY NORTH CAROLINA TELE: 828-328-6331 FAX: 828-322-1801 WWW.TAYLORVIOLA.COM JCMT Associates, PLLC 211 Stone Drive, Pilot Mountain, NC 27041 Telephone: (336) 399-6277	Tyler Heishman 2603 Abattoir Rd Coats, NC 27521	DRAWN BY: BKS	PROJECT NO: 0724-0122
		DATE: 12/12/24	SHEET NO: S7C

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

CONCRETE BASE RAIL ANCHORAGE (CLIP ANGLE ATTACHMENT OPTION)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR




SCALE: 3/4" = 1'-0"

BASE RAIL ANCHORAGE DETAIL (CLIP ANGLE ATTACHMENT OPTION)



SCALE: 3/4" = 1'-0"



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7D

CONCRETE BASE RAIL ANCHORAGE (LEAN-TO ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**BASE RAIL ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"

1
S7E **BASE RAIL ANCHORAGE DETAIL**
SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENTS SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S7E

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

CONCRETE BASE RAIL ANCHORAGE (NO SLAB - LEAN-TO ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**BASE RAIL ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"

1
S7F **BASE RAIL ANCHORAGE DETAIL (NO SLAB)**
SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318:
3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7F

CONCRETE BASE RAIL ANCHORAGE (NO LEDGE - LEAN-TO ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



1 BASE RAIL ANCHORAGE DETAIL
 S7G SCALE: 3/4" = 1'-0"

GENERAL NOTES:


ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:
 CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:
 FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318:
 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:
 THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

- REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:**
1. REINFORCEMENT IS BENT COLD.
 2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
 3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.





12/12/2024

<p>TAYLOR & VIOLA STRUCTURAL ENGINEERS P.O.B. 2616 HICKORY NORTH CAROLINA TELE: 828-328-6331 FAX: 828-322-1801 WWW.TAYLORVIOLA.COM</p> <p>JCMT Associates, PLLC 211 Stone Drive, Pilot Mountain, NC 27041 Telephone: (336) 399-6277</p> <p>VI.0</p>	<p align="center">Tyler Heishman 2603 Abattoir Rd Coats, NC 27521</p>	DRAWN BY: BKS	PROJECT NO: 0724-0122
		DATE: 12/12/24	SHEET NO: S7G

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

CONCRETE BASE RAIL ANCHORAGE (NO LEDGE / NO SLAB - LEAN-TO ONLY)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



1 BASE RAIL ANCHORAGE DETAIL
SCALE: 3/4" = 1'-0"

GENERAL NOTES:


ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:
CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:
FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318:
3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:
THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

- REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:**
1. REINFORCEMENT IS BENT COLD.
 2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
 3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024

TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277



Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY: BKS	PROJECT NO: 0724-0122
DATE: 12/12/24	SHEET NO: S7H

VI.0

CONCRETE BASE RAIL ANCHORAGE

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



ANCHORAGE DETAIL (PLAN VIEW)

SCALE: 3/4" = 1'-0"



BASE RAIL ANCHORAGE DETAIL

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC

211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S7J

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

CONCRETE BASE RAIL ANCHORAGE (NO SLAB)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



ANCHORAGE DETAIL (PLAN VIEW)

SCALE: 3/4" = 1'-0"



BASE RAIL ANCHORAGE DETAIL

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENT SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC

211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S7K

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


CONCRETE BASE RAIL ANCHORAGE (NO LEDGE)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



**ANCHORAGE
DETAIL (PLAN VIEW)**

SCALE: 3/4" = 1'-0"



BASE RAIL ANCHORAGE DETAIL

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENTS SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS



PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7L

CONCRETE BASE RAIL ANCHORAGE (NO LEDGE / NO SLAB)

ANCHORAGE BOLT SCHEDULE	
WIND SPEED	BOLT SIZE
UP TO 115 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 125 M.P.H.	1/2" x 6-1/2" EXPANSION ANCHOR
UP TO 135 M.P.H.	1/2" x 9" EXPANSION ANCHOR
UP TO 145 M.P.H.	1/2" x 9" EXPANSION ANCHOR



ANCHORAGE DETAIL (PLAN VIEW)

SCALE: 3/4" = 1'-0"



BASE RAIL ANCHORAGE DETAIL

SCALE: 3/4" = 1'-0"

GENERAL NOTES:

ALL CONCRETE MONOLITHIC SLAB DESIGN BASED ON MINIMUM SOIL BEARING CAPACITY OF 1,500 P.S.F.

CONCRETE:

CONCRETE SHALL HAVE A MINIMUM SPECIFIED COMPRESSIVE STRENGTH OF 3,000 P.S.I. AT 28 DAYS.

COVER OVER REINFORCING STEEL:


FOR FOUNDATIONS, MINIMUM CONCRETE COVER OVER REINFORCING BARS SHALL BE PER ACI-318: 3" IN FOUNDATIONS WHERE THE CONCRETE IS CAST AGAINST AND PERMANENTLY IN CONTACT WITH THE EARTH OR EXPOSED TO THE EARTH AND WEATHER AND 1-1/2" ELSEWHERE.

REINFORCING STEEL:

THE TURNDOWN REINFORCING STEEL SHALL BE ASTM A615 GRADE 60. THE SLAB REINFORCEMENTS SHALL BE WELDED WIRE FABRIC MEETING ASTM A185 OR FIBERGLASS FIBER REINFORCEMENT.

REINFORCEMENT MAT BE BENT IN THE SHOP OF THE FIELD PROVIDED:

1. REINFORCEMENT IS BENT COLD.
2. THE DIAMETER OF THE BEND, MEASURED ON THE INSIDE OF THE BAR, IS NOT LESS THAN SIX-BAR DIAMETERS.
3. REINFORCEMENT PARTIALLY EMBEDDED IN CONCRETE SHALL NOT BE FIELD BENT.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC

211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S7M

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

SOIL NAIL BASE RAIL ANCHORAGE



1
S8
BASE RAIL ANCHORAGE DETAIL
 SCALE: 3/4" = 1'-0"

HELIX EMBEDMENT INFORMATION:

FOR VERY DENSE OR CEMETED SANDS, COARSE GRAVEL, COBBLES, CALICHE, PRELOADED SILT.S. AND CLAYS, USE MIN. (2) 4" HELICES WITH MINIMUM 30" EMBEDMENT OR SINGLE 6" HELIX WITH 50" EMBEDMENT – ONE EACH END BASE RAIL AND 20'-0"oc MAX. WITH #4 REBAR AT 5'-0"oc BETWEEN.

FOR CORAL, USE MIN (2) 4" HELICES WITH MINIMUM 30" EMBEDMENT OR SINGLE 6" HELIX WITH 50" EMBEDMENT – ONE EACH END BASE RAIL AND 20'-0"oc MAX. WITH #4 REBAR AT 5'-0"oc BETWEEN.


FOR MED DENSE COARSE SANDS, SANDY GRAVEL, VERY STIFF SILT.S., AND CLAYS, USE MIN (2) 4" HELICES WITH MINIMUM 30" EMBEDMENT OR SINGLE 6" HELIX WITH 50" EMBEDMENT – ONE EACH END BASE RAIL AND 20'-0"oc MAX. WITH #4 REBAR AT 5'-0"oc BETWEEN.

FOR LOOSE TO MEDIUM DENSE SANDS, FIRM TO STIFF CLAYS AND SILT.S., USE MIN (2) 6" HELICES WITH MINIMUM 50" EMBEDMENT – ONE EACH END BASE RAIL AND 20'-0"oc MAX. WITH #4 REBAR AT 5'-0"oc BETWEEN.

FOR VERY LOOSE TO MEDIUM DENSE SANDS, FIRM TO STIFFER CLAYS AND SILT.S. AND ALLUVIAL FILL, USE MIN (2) 8" HELICES WITH MINIMUM 60" EMBEDMENT – ONE EACH END BASE RAIL AND 20'-0"oc MAX. WITH #4 REBAR AT 5'-0"oc BETWEEN.

NOTE:

IN ALL CASES, IF FROST DEPTH EXCEEDS STATED DEPTH, ANCHOR SHOULD EXTEND A MIN. OF 12" BELOW FROST LINES



12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122


DATE:
 12/12/24

SHEET NO:
S8

TYPICAL END WALL FRAMING SECTION



TYPICAL END WALL OPENING FRAMING



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521

DRAWN BY:
 BKS


PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S9

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

TYPICAL END WALL OPENING FRAMING SECTION



TYPICAL END WALL OPENING FRAMING

NORTH CAROLINA
 PROFESSIONAL ENGINEER
 SEAL
 27874
 JASON M. RELEP
 12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521

DRAWN BY:
 BKS

PROJECT NO:
 0724-0122


DATE:
 12/12/24

SHEET NO:
S9A

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


BOX EAVE RAFTER / SIDE WALL OPENINGS FRAMING

NOTE:
 ROLL UP DOORS SHALL HAVE ONE JAMB
 EACH SIDE + ONE FRAME COLUMN BETWEEN
 OR SITE SPECIFIC SHALL BE REQ'D.



TYPICAL SIDE WALL OPENING FRAMING SECTION

NOTE:
 ROLL UP DOORS SHALL HAVE ONE JAMB
 EACH SIDE + ONE FRAME COLUMN BETWEEN
 OR SITE SPECIFIC SHALL BE REQ'D.



TYPICAL SIDE WALL OPENING FRAMING SECTION

12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S9B


BASE RAIL CONNECTION DETAILS



**COLUMN / BASE RAIL
CONNECTION DETAIL**

1
S10


SCALE: 1/2" = 1'-0"



**COLUMN / BASE RAIL
CONNECTION DETAIL**

2
S10


SCALE: 1/2" = 1'-0"



**END COLUMN / BASE RAIL
CONNECTION DETAIL**


2A
S10

SCALE: 1/2" = 1'-0"



**COLUMN / BASE RAIL
CONNECTION DETAIL**

3
S10



**END COLUMN / BASE RAIL
CONNECTION DETAIL**

3A
S10

27874
2024
TAYLOR & VIOLA
STRUCTURAL ENGINEERS
SON M. REEP
12/12/2024

TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM


JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY: BKS	PROJECT NO: 0724-0122
DATE: 12/12/24	SHEET NO: S10

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


T.S. OPENING CONNECTION DETAILS



COLUMN / BASE RAIL CONNECTION DETAIL

1
S11


SCALE: 1/2" = 1'-0"



TRUSS / HEADER TO POST CONNECTION DETAIL

2
S11


SCALE: 1/2" = 1'-0"



HEADER / WINDOW OR DOOR RAIL TO POST CONNECTION DETAIL

3
S11


SCALE: 1/2" = 1'-0"



COLUMN / DOUBLE HEADER CONNECTION DETAIL

4
S11

SCALE: 1/2" = 1'-0"



DOUBLE HEADER TO COLUMN CONNECTION DETAIL

5
S11

SCALE: 1/2" = 1'-0"

27874
Professional Engineer
Taylor & Viola
12/12/2024

TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM


JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY: BKS	PROJECT NO: 0724-0122
DATE: 12/12/24	SHEET NO: S11

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


T.S. OPENING CONNECTION DETAILS



1
COLUMN / LACED HEADER
CONNECTION DETAIL

S12


SCALE: 1/2" = 1'-0"



2
LACED HEADER / COLUMN
CONNECTION DETAIL

S12

SCALE: 1/2" = 1'-0"



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0


Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24


SHEET NO:
S12




1 SPLICE CONNECTION DETAIL
S13 SCALE: 1/2" = 1'-0"



2 TRUSS TIE CONNECTION DETAIL
S13 SCALE: 1/2" = 1'-0"



3 CONNECTION DETAIL
S13 SCALE: 1/2" = 1'-0"



4 TRUSS TIE CONNECTION DETAIL
S13 SCALE: 1/2" = 1'-0"

Professional Engineer
 North Carolina
 License No. 27874
 Jason M. Reep
 12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S13


CONNECTION DETAILS



TRUSS TIE CONNECTION DETAIL

1
S13A


SCALE: 1/2" = 1'-0"



TRUSS TIE / TRUSS CONNECTION DETAIL

2
S13A

SCALE: 1/2" = 1'-0"



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24


SHEET NO:
S13A

BOX EVE RAFTER / SINGLE & DOUBLE RAFTER - LEAN-TO OPTIONS

NOTE:
SINGLE LEG LEAN-TO MAY
EXTEND TO 14'-0" HEIGHT IF
A HORIZONTAL GIRT IS
INSTALLED WITHIN 24" BELOW
THE TOP OF THE COLUMN.




**SINGLE RAFTER / SINGLE COLUMN
LEAN-TO FRAMING SECTION**




**SINGLE RAFTER / DOUBLE COLUMN
LEAN-TO FRAMING SECTION**


NOTE:
SINGLE LEG LEAN-TO MAY
EXTEND TO 14'-0" HEIGHT IF
A HORIZONTAL GIRT IS
INSTALLED WITHIN 24" BELOW
THE TOP OF THE COLUMN.



**DOUBLE RAFTER / SINGLE COLUMN
LEAN-TO FRAMING SECTION**



**DOUBLE RAFTER / DOUBLE COLUMN
LEAN-TO FRAMING SECTION**



12/12/2024



JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

V1.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24


SHEET NO:
S14

BOX EVE RAFTER / LACED RAFTER - LEAN-TO OPTIONS


NOTE:
SINGLE LEG LEAN-TO MAY
EXTEND TO 14'-0" HEIGHT IF
A HORIZONTAL GIRT IS
INSTALLED WITHIN 24" BELOW
THE TOP OF THE COLUMN.



LACED RAFTER / SINGLE COLUMN
LEAN-TO FRAMING SECTION



LACED RAFTER / DOUBLE COLUMN
LEAN-TO FRAMING SECTION



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS



PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S14A

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.

LEAN-TO 'HIP' OPTIONS



NOTE:
VERIFY IF SINGLE OR DOUBLE COLUMNS
 12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S14B


LEAN-TO CONNECTION DETAILS - SINGLE COLUMN



LEAN-TO SINGLE RAFTER / SINGLE COLUMN CONNECTION DETAIL

1
S15

SCALE: 3/4" = 1'-0"



LEAN-TO DOUBLE RAFTER / SINGLE COLUMN CONNECTION DETAIL

1A
S15

SCALE: 3/4" = 1'-0"

JASON M. REEP
 ENGINEER
 27874
 NORTH CAROLINA
 PROFESSIONAL ENGINEER

12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S15


LEAN-TO CONNECTION DETAILS - DOUBLE COLUMN



LEAN-TO SINGLE RAFTER / DOUBLE COLUMN CONNECTION DETAIL

1
S15A

SCALE: 3/4" = 1'-0"



LEAN-TO DOUBLE RAFTER / DOUBLE COLUMN CONNECTION DETAIL

1A
S15A

SCALE: 3/4" = 1'-0"

STATE OF NORTH CAROLINA
 PROFESSIONAL SEAL
 27874
 JASON M. REEP
 ENGINEER
 12/12/2024



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24

SHEET NO:
S15A

LEAN-TO CONNECTION DETAILS - LACED RAFTER / SINGLE COLUMN



LEAN-TO LACED RAFTER / SINGLE COLUMN CONNECTION DETAIL

1
S15B

SCALE: 3/4" = 1'-0"

NORTH CAROLINA
PROFESSIONAL ENGINEER
SEAL
27874
JASON M. REEP
12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S15B

LEAN-TO CONNECTION DETAILS - LACED RAFTER / DOUBLE COLUMN



LEAN-TO LACED RAFTER / DOUBLE COLUMN
CONNECTION DETAIL

1
S15C

SCALE: 3/4" = 1'-0"

12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S15C

LEAN-TO / MAIN FRAME CONNECTION DETAILS

2"x2"x2" 14ga. ANGLE CLIP
SECURE TO COLUMN AND RAFTER
WITH #12-14 x 3/4" S.D.F. (2)
ON TOP AND (2) ON BOTTOM

T.S. SINGLE RAFTER



LEAN-TO SINGLE RAFTER / BUILDING FRAME
CONNECTION DETAIL

1
S15D

SCALE: 3/4" = 1'-0"


2"x2"x2" 14ga. ANGLE CLIP
SECURE TO COLUMN AND RAFTER
WITH #12-14 x 3/4" S.D.F. (2)
ON TOP AND (2) ON BOTTOM

T.S. DOUBLE RAFTER

TYP. 3/12
3/12

3/16
3/16 CONNECTOR
SLEEVE TO
COLUMN


MIN. 6" LONG, 14ga. CONNECTOR
SLEEVE - SECURE COLUMN TO
SLEEVE WITH (4) #12-14 x 3/4"
S.D.F.'S



LEAN-TO DOUBLE RAFTER / BUILDING FRAME
CONNECTION DETAIL

1A
S15D

SCALE: 3/4" = 1'-0"



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S15D

LEAN-TO / MAIN FRAME CONNECTION DETAILS

MIN. 6" LONG, 14ga. CONNECTOR SLEEVE - SECURE COLUMN TO SLEEVE WITH (4) #12-14 x 3/4" S.D.F.'S

T.S. LADDER LEAN-TO TRUSS




2"x2"x2" 14ga. ANGLE CLIP SECURE TO COLUMN AND RAFTER WITH #12-14 x 3/4" S.D.F. (2) ON TOP AND (2) ON BOTTOM

LEAN-TO SINGLE RAFTER / BUILDING FRAME CONNECTION DETAIL

1
S15E

SCALE: 3/4" = 1'-0"



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S15E


LEAN-TO / MAIN FRAME CONNECTION DETAILS



LEAN-TO SINGLE RAFTER / BUILDING FRAME
(FLUSH) CONNECTION DETAIL

1
S15F

SCALE: 3/4" = 1'-0"



LEAN-TO DOUBLE RAFTER / BUILDING FRAME
(FLUSH) CONNECTION DETAIL

1A
S15F

SCALE: 3/4" = 1'-0"

NORTH CAROLINA
 PROFESSIONAL ENGINEER
 SEAL
 27874
 JASON M. REEP
 12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S15F

12" LONG 14ga. CONNECTOR SLEEVE SECURE TO TOP WITH (8) #12-14 x 3/4" S.D.F.'S

T.S. LACED LEAN-TO TRUSS



6" LONG 14ga. CONNECTOR SLEEVE SECURE TO TOP WITH (4) #12-14 x 3/4" S.D.F.'S

3/16
3/16
CONNECTOR SLEEVE TO COLUMN


2"x2"x2" 14ga. ANGLE CLIP SECURE TO COLUMN AND RAFTER WITH #12-14x3/4" S.D.F. (2) ON TOP AND (2) ON BOTTOM

T.S. MAIN FRAME COLUMN

LEAN-TO SINGLE RAFTER / BUILDING FRAME
(FLUSH) CONNECTION DETAIL

1
S15G

SCALE: 3/4" = 1'-0"



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S15G

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


END WALL COLUMN / HIP RAFTER CONNECTION DETAIL



END WALL COLUMN / HIP RAFTER CONNECTION DETAIL

1
S15H

SCALE: 3/4" = 1'-0"



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S15H

VERTICAL ROOF / SIDING OPTION ELEVATIONS



TYPICAL END ELEVATION



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521


DRAWN BY:
 BKS

PROJECT NO:
 0724-0122

DATE:
 12/12/24


SHEET NO:
S16

VERTICAL ROOF / SIDING OPTION ELEVATIONS



LENGTH VARIES DEPENDING ON NUMBER AND SPACING OF RAFTERS

TYPICAL SIDE ELEVATION



TAYLOR & VIOLA
 STRUCTURAL ENGINEERS
 P.O.B. 2616 HICKORY NORTH CAROLINA
 TELE: 828-328-6331 FAX: 828-322-1801
 WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
 211 Stone Drive, Pilot Mountain, NC 27041
 Telephone: (336) 399-6277

VI.0

Tyler Heishman
 2603 Abattoir Rd
 Coats, NC 27521

DRAWN BY:
 BKS

PROJECT NO:
 0724-0122


DATE:
 12/12/24

SHEET NO:
S16A

VERTICAL ROOF / SIDING OPTION


1.125"-18ga. HAT CHANNELS
FASTENED TO EACH RAFTER
WITH (2) #12-14 x 3/4"
S.D.F. SPACED AT 4'-0"oc MAX.

29ga. GALVANIZED METAL
ROOF AND WALL PANELS
FASTENED TO GIRTS OR
HAT CHANNELS AND POST



W >31'-0" TO <60'-0" MAXIMUM RAFTER SPAN

TYPICAL RAFTER / COLUMN FRAME SECTION



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S16B

SEE NOTES
(SHEET S3)
FOR MAXIMUM
SPACING

VERTICAL ROOF / SIDING OPTION


1.125"-18ga. HAT CHANNELS FASTENED TO
EACH RAFTER WITH (3) #12-14 x 3/4" S.D.F.
SPACED AT 4'-0"oc MAX.



LENGTH VARIES DEPENDING ON NUMBER AND SPACING OF RAFTERS

TYPICAL SIDE FRAMING SECTION VERTICAL ROOF / SIDING OPTION

NOTE:



1.125" - 18ga H,
12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS


PROJECT NO:
0724-0122

DATE:
12/12/24


SHEET NO:
S16C

NOTE: THESE DRAWINGS ARE VALID FOR (1) CALENDER YEAR AFTER THE ISSUE DATE LISTED ON THIS SHEET.


SIDE WALL HEADER OPTIONS




LACED HEADER DETAIL FOR
OPENINGS <4'-0"



LACED HEADER DETAIL FOR
OPENINGS >4'-0" TO <12'-0"




LACED HEADER DETAIL FOR
OPENINGS >12'-1" TO <15'-0"



LACED HEADER DETAIL FOR
OPENINGS >15'-1" TO <20'-0"

GENERAL NOTE:

PROVIDE DOUBLE WYTHE HEADER
ON DOUBLE COLUMNS.



12/12/2024



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521


DRAWN BY:
BKS

PROJECT NO:
0724-0122


DATE:
12/12/24

SHEET NO:
S17


END WALL HEADER OPTIONS



LACED HEADER DETAIL FOR
OPENINGS <7'-0"




LACED HEADER DETAIL FOR
OPENINGS >7'1" TO <16'-0"



LACED HEADER DETAIL FOR
OPENINGS >16'-1" TO <20'-0"

GENERAL NOTE:

PROVIDE DOUBLE WYTHE HEADER
ON DOUBLE COLUMNS



TAYLOR & VIOLA
STRUCTURAL ENGINEERS
P.O.B. 2616 HICKORY NORTH CAROLINA
TELE: 828-328-6331 FAX: 828-322-1801
WWW.TAYLORVIOLA.COM

JCMT Associates, PLLC
211 Stone Drive, Pilot Mountain, NC 27041
Telephone: (336) 399-6277

VI.0

Tyler Heishman
2603 Abattoir Rd
Coats, NC 27521

DRAWN BY:
BKS

PROJECT NO:
0724-0122

DATE:
12/12/24

SHEET NO:
S17A