



# Plan Review, Inspection, and Permit Fees

Application Number : 17-50042037

\$200.00	<input type="checkbox"/>	Explosive Material (90 Days)	\$	-
\$100.00	<input type="checkbox"/>	Explosive Materials (72 Hours)	\$	-
\$100.00	<input type="checkbox"/>	Fireworks Public Display	\$	-
\$50.00	<input checked="" type="checkbox"/>	Final Inspection	\$	-
\$35.00 + \$2.00 per device	<input type="checkbox"/>	Fire Alarm Testing	\$	50.00
\$35.00 + \$2.00 per nozzle	<input type="checkbox"/>	Fixed Fire Suppression	\$	-
\$75.00	<input type="checkbox"/>	Insecticide Fog/Fumigation	\$	-
\$100.00	<input type="checkbox"/>	Pipe Test/UST/AGST	\$	-
\$50.00	<input checked="" type="checkbox"/>	Plans up to 5000 sq ft	\$	-
\$100.00	<input type="checkbox"/>	Plans 5001 sq ft to 10,000 sq ft	\$	50.00
\$150.00	<input type="checkbox"/>	Plans 10,001 sq ft to 25,000 sq ft	\$	-
\$250.00	<input type="checkbox"/>	Plans 25,001 sq ft and over	\$	-
\$35.00 + 2.00 per head	<input type="checkbox"/>	Sprinkler Certification Test	\$	-
\$50.00	<input type="checkbox"/>	Standpipe Testing	\$	-
\$50.00	<input type="checkbox"/>	Special Assembly (ie. amusement buildings, carnivals, fairs)	\$	-
\$75.00	<input type="checkbox"/>	Tents/Canopies/Air Supported Structure	\$	-
\$100.00	<input type="checkbox"/>	Tank Installation (charge for each tank)	\$	-
\$100.00	<input type="checkbox"/>	Tank Removal (charge for each tank)	\$	-
		Total Devices/Heads	\$	-
		<b>Total Cost</b>	\$	<b>100.00</b>

Code Enforcement Official

Rodney Daniels


11/9/2017



- Emergency illumination is required to meet minimum foot candle illumination.
- **1011 Exit Signs**
  - Exit signs shall be installed at all required exits. Exit signs shall meet all provisions of chapter 10.
- **506.1 Knox Box**
  - A Knox box is required to be installed on the building.
  - An application /order form has been attached to the review comments.
    - <https://www.knoxbox.com/commercial-knox-boxes/>
- **1004.3 Posting of occupant load.**
  - Every room or space that is an assembly occupancy shall have the *occupant load* of the room or space posted in a conspicuous place, near the *main exit* or *exit access doorway* from the room or space. Posted signs shall be of an *approved* legible permanent design and shall be maintained by the owner or authorized agent.
    - An occupant load certificate will be provided by the Fire Marshal's Office.
- **1008.1.10 Panic and fire exit hardware.**
  - Doors serving a Group H occupancy and doors serving rooms or spaces with an *occupant load* of 50 or more in a Group A or E occupancy shall not be provided with a latch or lock unless it is panic hardware or *fire exit hardware*.
- **Notes**
  - Please contact the Fire marshal's office to schedule fire final inspection when work is complete, 910-893-0743

Please review the plans and adhere to any notes and alterations that were made in addition to the original designed plans. These remarks are for the plans that were submitted and its original intent. If you have any questions please do not hesitate to contact me. We look forward to working with you during the construction period.

Sincerely,



Rodney Daniels  
Chief Deputy Fire Marshal



November 9, 2017

RE: **Victory Baptist Church**  
**914 Lasater Road**  
**Bunnlevel, NC**

Re: Application Number – 17-50042037

Mr. Murray,

Thank you for submitting plans for the new Church. The plans have been reviewed by a qualified code enforcement official for compliance with the North Carolina Fire Prevention code and all other fire protection regulations. The following are items that will need to be addressed before a final inspection of this project can be completed. The items are listed and described below.

- **503 Fire Department Access**
  - The fire department access shall extend to within 150 feet of all portions of the facility.
  - The fire department access road shall be of an unobstructed width of not less than 20 feet and shall have an unobstructed vertical clearance of not less than 13 feet 6 inches.
  
- **505.1 Physical Address**
  - The physical address of the building shall be posted in a conspicuous place so that it can be seen on approach from the road, access road, and/or parking lot.
  - The numbers used to make up the physical address shall be at least 5 inches in height.
  
- **906.1 Fire Extinguishers**
  - Fire extinguishers shall be placed in approved locations and may be field verified on final inspection. The fire extinguishers provided shall have a minimum rating of 2A 10 B: C.
  - Fire extinguisher shall be installed not to exceed 75' distance of travel.
  
- **1006.1 / 1006.2 Emergency Illumination**