Harnett County Department of Public Health

26484

	m	p)	0	١V	'e	r	n	e	n	t	P	e	r	r	n	I	t

A building permit cannot be issued with only an Improvement Permit

01	1	
	PROPERTY LOCATION.	NCHWY27

ISSUED TO: KEVIN GREGORY SUBDIVISION	KENNETH M CAMERON	LOT # 2
NEW REPAIR 🗆 EXRANSION 🗆	Site Improvements required prior to Construction Author	rization Issuance:
Type of Structure: MOO (76'25')		
Proposed Wastewater System Type: CONVENTIONAL (PUMP)		·····
Projected Daily Flow: 480 GPD		
Number of bedrooms: Number of Occupants: max		· · · · · · · · · · · · · · · · · · ·
Basement 🔀 Yes 🗆 No		
Pump Required: Xes 🗆 No 🗙 May be required based on final location and e	levations of facilities	
Type of Water Supply: Community X Public Well Distance from well	<u>100</u> feet Permit valid for:	Five years
Permit conditions:		No expiration
1 41 - 44		•
Authorized State Agent:: White Information Date	: 3 14 1) SEE ATT	TACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The pe	ermit holder is responsible for checking with appropriate governing bodies ir	n meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not	be affected by a change in ownership of the site. This permit is subject to	compliance with the provisions of

the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.

HTE# 11-5-26264

Construction Authorization

(Required for Building Permit)

The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout.

ISSUED TO: KENIN GREGORY	PROPERTY LOCATION: NC	- Hwy 27
	SUBDIVISION KENNETH	M CAMERON LOT # 2
Facility Type: Mod (76'X28')	🔀 New 🗆 Expansion 🗆 Repair	
Basement? 🗹 Yes 🗆 No Basement Fix		
Type of Wastewater System** Pume To	CONVENTIONAL	(Initial) Wastewater Flow: <u>480</u> GPD
(See note below, if applicable X)		
Pump To	CONVENTIONAL (Repair)	
Installation Requirements/Conditions	Number of trenches <u>5</u>	\$
Septic Tank Size <u>1000</u> gallons	Exact length of each trench <u>80</u> feet	Trench Spacing: Feet on Center
Pump Tank Size <u>ヽつつ ♡</u> gallons	Trenches shall be installed on contour at a	Soil Cover:G inches
	Maximum Trench Depth of: <u>\8</u> inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)
	in all directions)	,
Pump Requirements:ft. TDH vs	GPM	inches below pipe
		Aggregate Depth: inches above pipe
Conditions:		IZ inches total

WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.

