HTE# 05-500 12 SYYR Harnett County Department of Public health 23679 Improvement Permit

A building permit cannot be issued with only an Improvement Permit

P	ROPERTY LOCATION: 1238
ISSUED TO: Some, Holder PREPAIR EXPANSION	SUBDIVISION CALLIC B Holder LOT # 7
NEW REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: $SFO - So \times G \Rightarrow 3BA$	
Proposed Wastewater System Type: GRAVET	
Projected Daily Flow: 365 GPD	
	ax
Basement □Yes No Pump Required: □Yes	
	don and elevations of facilities
Permit conditions: ST4B Out Plumbles Shallow	from well feet Permit valid for: \(\begin{array}{cccccccccccccccccccccccccccccccccccc
Type of Water Supply: Community Public Well Distance Permit conditions: ST4B Oct Plumbing Shallow Shown, Maintain All Set Backs	At Goond fevel on higher where I No expiration
Authorized State Agent: 0 - ARJ	2 32 25
The state of the s	Date: 227-27 SEE ATTACHED SITE SKETCH
their requirements. This site is subject to revocation if the site plan plat or the intended	of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting
permit is subject to compliance with the provisions of the Laws and Rules for Sewage Tre.	I use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This
Construc	ction Authorization
	red for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956	, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be
installed in accordance with the attached system layout.	
ISSUED TO: James Holder	PROPERTY LOCATION: 1236
	SUBDIVISION CAIL: B Holder LOT # 7
Facility Type: SFD-50x60-3BR X New	☐ Expansion ☐ Repair
Basement? Yes No Basement Fixtures? Yes 5	⊴ No
Type of Wastewater System** GRAVE! (In	itial) Wastewater Flow: GPD
(See note below, if applicable ☑)	,
480 LF of LPP	(Repair)
Installation Requirements/Conditions	· · /
	h trench 4 x 100 feet Trench Spacing: 9 Feet on Center
Pump Tank Size gallons Trenches shall be in	ostalled on contour at a Soil Cover inches
Maximum Trench De	epth of: 18 may inches (Maximum soil cover shall not exceed
(Trench bottoms sha	all be level to $\pm \frac{1}{4}$ 36" above the trench bottom)
in all directions)	1
Pump Requirements:ft. TDH vs GPM	Aggregate Depth: inches below pipe inches above pipe inches total
	Aggregate Denth: 2 inches above nine
Conditions:	12 inches total
**If applicable: / understand the system type specified is differen	nt from the type specified on the application. I accept the specifications of this permit.
7	- nom the type specified on the application. I accept the specifications of this perinte.
Owner/Legal Representative Signature:	Date:
This Construction Authorization is subject to revocation if the site plan, plat, or the intende	ed use changes. The Construction Authorization shall not be transferred when there is a change in ownership
of the site. This Construction Authorization is subject to compliance with the provisions of t	the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.
(CEE ATTACHER CITE CVETCH
Authorized State Agent: Vor W	1112000
Authorized State Agent.	Date: 02 27- 07

HTE# 05-500 12544R

Permit # 23679

Harnett County Department of Public Health Site Sketch

	UED TO: James Holden	PROPERTY LOCATON: 1238 SUBDIVISION CAI), B. Holder LOT # 7
Aut	thorized State Agent:	Date: _ ス・ み 7 - 5 フ
		469
5 Alvar	Daws.	B R B L D D D D D D D D D D D D D D D D D D
y ⁴ 5	150'	SOR CORD PEPAIR
	(43] lo · m·^
		424
10 10 NC	Stub out flum orhisher	bing shallow where shown, at ground level

95 No 10

orhisher
MAINTAIN All SctBArk,

Enstall 4x100 of gravel At 18" max Outeh Depth