HTE# 07-5-16954K

Har t County Department of Public ealth 28874

Improvement Permit

PROPERTY LOCATION: 82156 Silves House NO
ISSUED TO: STANCEL BUZILLES INC SUBDIVISION HUNTERS POINT LOT # Z1
NEW REPAIR EXPANSION Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: SFD
Proposed Wastewater System Type: 25 20 Reduction
Projected Daily Flow: 360 GPD
Number of bedrooms: 3 Number of Occupants: 6 max
Basement
Pump Required: Yes No May be required based on final location and elevations of facilities
Type of Water Supply: Community Public Well Distance from well feet Permit valid for: Five years
Permit conditions:
Authorized State Agent: Date: 6-6-16 SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.
Construction Authorization
(Required for Building Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.
ISSUED TO: STANCEL BUCKBERS FAC PROPERTY LOCATION: SUSTES Silas HAGES NO
ISSUED TO: STANCEL BUCKBERS FUC PROPERTY LOCATION: SUSTES Silve Hoges POSENT LOT # 21
Facility Type: New Expansion Repair
Basement? Yes No Basement Fixtures? Yes No
Type of Wastewater System** 252 NETOUCE System (Initial) Wastewater Flow: 360 GPD
(See note below, if applicable □)
252 Rod / LPA (Repair)
Installation Requirements/Conditions Number of trenches /
Septic Tank Size /oro gallons Exact length of each trench 300 feet Trench Spacing: Feet on Center
Pump Tank Size gallons Trenches shall be installed on contour at a Soil Cover: inches
Maximum Trench Depth of: inches (Maximum soil cover shall not exceed
(Trench bottoms shall be level to $\pm \frac{1}{4}$ " 36" above the trench bottom)
in all directions)
Pump Requirements:ft. TDH vs GPM inches below pipe
Aggregate Depth: 7 inches above pip
Conditions: inches tota
Conditions: inches tota
WATER LINES (INCLUDING IRRIGATION) WHIST RE LOTT FROM MAY RART OF SERVIC SYSTEM OR REPAIR AREA
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.
** f applicable: understand the system type specified is different from the type specified on the application. accept the specifications of this permit.
Owner/Legal Representative Signature: Date:
Owner/Legal Representative Signature: Date:
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.
S M 1 KD ROAS
Authorized State Agent: Date: L-Co-16

Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: 52/565 Silvas (tagges RD

ISSUED TO: STANCE! BUELDER FIC SUBDIVISION LOT # 24

Authorized State Agent: Date: 6-6-16

