## HTE# 07-500-18607 Harnett County Department of Public nealth 24374

## Improvement Permit

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: NC27 SUBDIVISION TINSEN Pointe Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SFO -Proposed Wastewater System Type: Punt to 25% leduction statem Projected Daily Flow: 360 Number of Occupants: 6 max Number of bedrooms: Basement Yes Pump Required: Yes □ No ☐ May be required based on final location and elevations of facilities Type of Water Supply: Community & Public Well Distance from well 50 feet Permit valid for: Permit conditions: Mect on site for Final Layout Mountain all set Backs No expiration STUB Dut Plumbing Shallow, At ground level where shown-Authorized State Agent:

Date: 10-19-37

SEE ATTACHED SITE SKETCH

The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. Construction Authorization (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout.

ISSUED TO: 

you

Const-PROPERTY LOCATION: \_\_\_\_\_\_ Facility Type: SFO- 44x30 3BR KNew Expansion Repair Basement? Tyes And Basement Fixtures? Yes No
Type of Wastewater System\*\* ASTAGASSYS. (Initial) Wastewater Flow: 365 GPD (See note below, if applicable ) Pump to 25% Red Sys. (Repair) Installation Requirements/Conditions Exact length of each trench 1 × 180 feet Trench Spacing: \_\_\_\_\_\_ Feet on Center Septic Tank Size Opp gallons Pump Tank Size 1000 gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 18-24 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_ft. TDH vs. \_\_\_\_ inches below pipe Aggregate Depth: inches above pipe inches total Conditions: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. \*\*If applicable: Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date: 10-19-2012

## Harnett County Department of Public Health Site Sketch

	ISSUED TO: Wyon Const.	PROPERTY LOCATON: 1100 27	LOT # 20
+	Authorized State Agent:	Date: _/ 0 - 19 - 0 7	-
156	12 12 0 12 12 12 12 12 12 12 12 12 12 12 12 12	38' 1 lisi  25'/. Red-ition  5757EM  Repair  39	

STUB OUT Plumbing Shallow, at ground level or his her Maintain All set Dacks Much ons. to for Final Layort Zostall | X 180 | 25% Reduction System At 18+024" Precp.