HTE# 08-500- 19565 Harrier County Department of Public nealth 24661

Improvement Permit

A building permit cannot be issued with only an Improvement Permit Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SFD - 57x 39- 302
Proposed Wastewater System Type: 25% Red-fin System Projected Daily Flow: 365 Number of Occupants: 6 max Number of bedrooms: Basement Yes V No May be required based on final location and elevations of facilities Pump Required: ☐Yes ☐ No Type of Water Supply:
Community Public Well Distance from well 50 feet Permit valid for: Five years Permit conditions: 5 TuB and Plumbing Shallow At grand level or higher 10 No expiration where shown maintain All set Dacks Date: 07-80 11-0 V SEE ATTACHED SITE SKETCH Authorized State Agent:: (The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958 and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: Kenneth Commings PROPERTY LOCATION: 125
SUBDIVISION WOOdshire LOT # 216 Facility Type: SFD - 57 x 39 - 3BC New Expansion Repair

Basement? Yes No Basement fixtures? Yes No Wastewater Flow: 36.3 GPD Type of Wastewater System** 25% (Initial) (See note below, if applicable) 25% (Repair) Installation Requirements/Conditions Exact length of each trench 1×180 feet Septic Tank Size Do gallons Pump Tank Size Trenches shall be installed on contour at a Maximum Trench Depth of: 18-24 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: ft. TDH vs. inches below pipe Aggregate Depth: inches above pipe inches total ** If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: ___ This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership

of the site. This Construction Authorization, is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. Authorized State Agent:

Construction Authorization Expiration Date: 03-11-2013

Harnett County Department of Public Health Site Sketch

Daive 31. JBR STX 39 Level or high Maintain Al Markon Mapar 10 251. Malaction Mapar 251. Malaction Mapar 80.	Shallow, At 80 level or higher Minhain All 1 Mainhain All 1 Mary 25% Reduction At 18to 24" 10	1 105'	new state agent.
Daive 31. JBR STX 39 Level or high Maintain Al Adator Apper 10 251. Reduction At 186. 24	Shallow, At 80 level or higher maintain All 1 maintain 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Dave 31. JBR STX39 257. Maintain Al Martin At 18to 24	reduction At 18to 24" John John Mills At 18to 24"		
Jan Jan Jan Al Stratal Ixis. STX 39 Level or high Maintain Al Lost all Ixis. 25% Reduction At 18t. 24 Lost and Lost At 18t. 24 Lost Lo	reduction At 18to 24" John John Mills At 18to 24"		^
STX39 STX39 MAINTAIN AL ANTAIN IXIS. AL 18t. 24 10 257. Reduction Alphir Repair 800	Maintain All s Maintain All s	1 004	
10 10 10 10 10 10 10 10 10 10 10 10 10 1	At 18to 24"	JUK	30,
10 10 10 10 10 10 10 10 10 10 10 10 10 1	1 D S At 18to 24"	57×39	
10 10 10 10 10 10 10 10 10 10 10 10 10 1	1 D S At 18to 24"		
10 10 10 10 10 10 10 10 10 10 10 10 10 1	J 13 8 At 18to 24"	1	
10 25% Reduction Repair 80°			
10 25% Reduction Repair 80°	13		
25% Reduction Repair 80°			
25% Reduction Repair 80°			-
25% Reduction Repair 80°	^		
25% Reduction Repair 80°	^		
	^		10
		201 Pe	
	I	2 MOA	
		10.1.	
7,			
SONDRA DRUE			