HTE# 08-500-21029

Harmet County Department of Public ...alth

25083

Improvement Permit

A bu	ilding permit cannot be issued with only an Improvement	Permit			
	PROPERTY LOCATION: 1) C 27	0 1			
ISSUED TO: Wynn Const.	SUBDIVISION (IWSCA)	Pointe LOT # 47			
NEW REPAIR ☐ EXPANSION		quired prior to Construction Authorization Issuance:			
Type of Structure: SFD- 40x40- 33					
Proposed Wastewater System Type: Pum to 25	its Reduction 575-				
Projected Daily Flow: 360 GPD	3"				
Number of bedrooms:3 Number of Occupan	ts: 6 max				
Basement □Yes ☑ No					
	d based on final location and elevations of facilities				
	□ Well Distance from well 100 feet	Permit valid for: 🔀 Five years			
STUB Out Olimbia Shall	Ly at Occupal lovel and	11 Sct BACKS No expiration			
STAS EAT THANNING STAN	Isw at ground level or h	inghir where shown			
Authorized State Agent:	n 10-11 24	CEE ATTACHED CITE CHETCH			
	Date: 10-16-08	SEE ATTACHED SITE SKETCH			
site is subject to revocation if the site plan plat or the intended use char	s the issuance of other permits. The permit holder is responsible for the	ecking with appropriate governing bodies in meeting their requirements. This ership of the site. This permit is subject to compliance with the provisions of			
the Laws and Rules for Sewage Treatment and Disposal and to conditions of		ersnip of the site. This permit is subject to compliance with the provisions of			
the cars and roles for senage freathers and ossposal and to conditions to	i uno permita.				
	Construction Authorization				
	(Required for Building Permit)				
The construction and installation requirements of Rules .1950, .1952, .1954 with the attached system layout.		into this permit and shall be met. Systems shall be installed in accordance			
11 0	ν.	27			
ISSUED TO: Wynn Const.	PROPERTY LOCATION:	d I			
	SUBDIVISION TINGER	Pointe LOT # 47			
Facility Type: SFD - 40x40- 3BR	New 🗆 Expansion 🗆 Repair	2008 030			
Basement? Yes No Basement Fixtur					
	25% Reduction Sys.	(Licin W			
	2) 10 langish sys.	(Initial) Wastewater Flow: 360 GPD			
(See note below, if applicable Dury 1- 2	5% Reduction Sys. (Repair)				
Installation Requirements/Conditions	Number of trenches				
10	Exact length of each trench 150 feet	Trench Spacing: Feet on Center			
	Trenches shall be installed on contour at a				
		Soil Cover: inches			
	Maximum Trench Depth of: 18.24 inches	(Maximum soil cover shall not exceed			
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)			
	in all directions)	,			
Pump Requirements:ft. TDH vs	GPM	inches below pipe			
	3111				
Conditions		Aggregate Depth: inches above pipe			
Conditions:		inches total			
**If applicable: I understand the system type specified in	s different from the type specified on the application	n. I accept the specifications of this permit.			
Owner/Legal Representative Signature:		Date:			
Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, pla	or the intended use changes. The Construction Authorization shall not	ha transferred when there is a change is a smarthin of the size This			
Construction Authorization is subject to compliance with the providence of	, or one antenueu use changes. The construction Authorization shall not	be transferred when there is a change in ownership of the site. This			
Construction Authorization is subject to compliance with the provisions of t	re cams and noises for sewage freatment and Disposal and to the condit	ions of this permit. SEE ATTACHED SITE SKETCH			
() [Ao:		12 11 24			
Authorized State Agent: Date: 16.08					
1	Construction Authorization Expiration Date: 10-16-08				

Harnett County Department of Public Health Site Sketch

	ISSUED TO:	lynn Cont.	PROPERTY L	OCATON: NO	27 cn Pointe 10T # 47
	Authorized State				Date: 10-16-08
		25% Reduction System Lypain	R	70	Meet onsite Maintain Allset Backs Zostall 150° of 25% Reduction System StuB out Plumbing Shallow At & Round level
		4x4.		2 .	orhigher where shown
	0			30'	
50'	AZ JE		to.		120.
		120,		1	