HTE# 09-5-22044

# Har..... County Department of Public mealth

25654


**Improvement Permit** 

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: HWY27 E ISSUED TO: KENDAWSON HOMES INC SUBDIVISION WC CARDNER Site Improvements required prior to Construction Authorization Issuance: REPAIR Type of Structure: SED (54243 Proposed Wastewater System Type: 25% REDUCTION SYSTEM Projected Daily Flow: 360 GPD 3 Number of Occupants: 6 max Number of bedrooms: Basement Yes No Pump Required: ☐Yes ☐ No May be required based on final location and elevations of facilities Type of Water Supply: 

Community Public 

Well Distance from well 100 feet Permit valid for: Five years ■ No expiration SEE ATTACHED SITE SKETCH Date: Authorized State Agent:: The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: KEN DANSON HOMES INC PROPERTY LOCATION: HWY2TE SUBDIVISION W.C. GRODNER Facility Type: SGD(54'x43') New 🗆 Expansion 🗆 Repair Basement Fixtures? 

Yes 
No Basement? \( \subseteq \text{Yes} \text{ No} \) 25% REDUCTIONAL (Initial) Wastewater Flow: 360 Type of Wastewater System\*\* (See note below, if applicable LPP Number of trenches 1 Installation Requirements/Conditions Exact length of each trench 180 feet Trench Spacing: 9 Feet on Center Septic Tank Size 1000 gallons Soil Cover: Trenches shall be installed on contour at a Pump Tank Size Maximum Trench Depth of: 18 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_ft. TDH vs. \_\_\_ inches below pipe Aggregate Depth: \_\_\_\_\_\_ inches above pipe Conditions: This PERMIT BASED ON A PROPOSAL FROM APPLICANTS SOIL inches total CONSULTANT. SEE ATTACHED SHEET FOR SEPTIC EASENERT LOCATION AND DRAINFIELD LANGUT WATER LINE MUST BE AT LEAST 10' FROM ANY PART OF THE SEPTIC SYSTEM \*\*|f applicable: | understand the system type specified is different from the type specified on the application. | accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provides of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date:



Scale: 1"= 100"

争。

Scale: 12:100

# Foisy, Amy - True: 1 (4.14 Acres) On-Site Wastewater Design Specifications

House Footprint:41-ft x 56-ft Foundation Drain Possible Bedrooms: 3 (Daily Flow 360 gallons)

	LEGEN	D
女	EIP	□ Septic Tank
	Supply Line	■ Pump Tank
$\bigcirc$	Proposed Well	♦ D-Box
$\otimes$	Existing Well	manifold Pressure Manifold

60.00 feet XXXXXXXXXX Lines flagged at site on 5-ft and 9-ft centers. Line Color Elevation **Field Line** Drainline Initial/ Length (ft) Repair (ft) Length(ft) 21 W N/A 1 51 N/A 2 Y 100 60 70 3 R 99.81 Repair 70 101 В 99.61 4 Repair 80 W 99.33 70 Repair 5 70 86 Y 99.02 6 Repair 80 93 В 98.74\* 7 Repair 82 W 98.49\* 70 Repair 8 63 Repair 9 Y 98.53\* 60 98.54\* 45 56 R 10 Initial 58 W 98.4 45 Initial 11 68 55 Initial 12 97.84 97.52 35 37 R Initial 13 310 111.2 Pump Tank: \* Elevation measured and recorded at terminal end of drainline. 100.00 feet S 84° 38' 6"W 80.00 feet N 84° 38' 6"E 230.24 feet 100 00 feet S 84° 38' 6"W N 84° 38' 6"E 230.24 feet

# **Onsite Wastewater Design Specifications**

House Footpr	int:	41' x 56'	Foundation Drain: Yes
# Bedrooms:	3	_	Daily Flow (gpd): 360

### **Initial System**

Gravity distribution to 180-ft of accepted system drainline with lines 11-13 installed on contour at 18 inches. Line 10 is to be installed at 18 inches and deepen to 22 inches below the natural surface. LTAR 0.5 gal/day/sqft

#### Repair System

Pressure distribution to 480-ft of LPP drainline with lines 3-6 installed on contour at 12 inches. Lines 7-9 are to be installed at 18 inches and shallow to 12 inches below the natural surface. LTAR 0.15 gal/day/sqft

Lines flagged at site on 5-ft and 9-ft centers.

Initial/ Repair	Line #	Color	Elevation (ft)	Drainline Length(ft)	Field Line Length (ft)
N/A	1	W	-	-	21
N/A	2	Υ	100	-	51
Repair	3	R	99.81	60	70
Repair	4	В	99.61	70	101
Repair	5	W	99.33	70	80
Repair	6	Y	99.02	70	86
Repair	7	В	98.74*	80	93
Repair	8	W	98.49*	70	82
Repair	9	Υ	98.53*	60	63
Initial	10	R	98.54*	45	56
Initial	11	W	98.4	45	58
Initial	12	Υ	97.84	55	68
Initial	13	R	97.52	35	37
Pump Ta	ank:		111.2		310

<sup>\*</sup> Elevation measured and recorded at terminal end of drainline.

### Repair System

# Low Pressure Pipe Distribution Flow Sheet

Subfields	Line #	Line Color	Line Length	Relative Elev(ft)	Elevation Change	Pressure Head(ft)	Hole Size	Flow/ Hole	Flow/ Lateral	gpm/ft	# Holes	Hole Spacing	First/Last Holes
1	3	R	60	99.8	0.0	4.0	5/32	0.5757	6.33	0.1055	11	5	5.00
1	4	В	70	99.6	0.2	4.2	5/32	0.5899	7.08	0.1011	12	5	7.50
1	5	W	70	99.3	0.5	4.5	5/32	0.6092	6.70	0.0957	11	5.75	6.25
1	6	. Y	70	99.0	0.8	4.8	5/32	0.6306	6.31	0.0901	10	6	8.00
2	7	В	80	98.7	0.0	4.0	5/32	0.5757	6.91	0.0864	12	6	7.00
2	8	W	70	98.5	0.2	4.2	5/32	0.5899	5.90	0.0843	10	7	3.50
2	9	Y	60	98.5	0.0	4.0	5/32	0.5757	4.61	0.0768	8	7	5.50
	Total lin	e length=	480				Т	otal Flow=	43.83				
		Pur	np Tank =	111.2		% Decrease of	gpm/ft fro	om top to bo		27.20379			

#### Calculations:

gpm/ft = (flow /hole) x # Holes / Line Length

Supply Ln Volume = Supply Line Length /100 x Pipe Size & Volume Table

Lateral Ln Vol (1&1/4) =Total linear footage /100 x Pipe Size & Volume Table

Manifold Vol. = Manifold Length x Pipe Volume /100

Dose Vol = Supply Line Vol. + Manifold Vol. + (5 to 10)(Lateral Line Vol.)

Run Time = Dose Volume /Total Flow

Draw Down = Dose Vol /Pump Tank Vol x liquid depth of tank(inches)

Elev Head = Manifold Elevation - (Pump Tank Elevation - 5ft)

## **Design Specifications**

Supply Line		
Volume=	53.9	
Lateral Line		1
Volume=	74.9	
Manifold		1
Volume=	0.0	
Dose Vol	428.34-	
Range=	802.7	
Dose Vol=	428.3	0

Total	
Flow =	43.83
	-5310/
LTAR=	0.15
Run	
Time =	9.77
Draw	
Down=	20.40

Pressure	
Head (ft)=	4.00
Elevation	
Head (ft)=	0.00
Friction	
Head (ft)=	2.51
TDH (ft)=	6.51

Friction Head = [0.00113 x (Supply Line Length(ft) + 70ft for fittings in pump tank) x Flow(gpm)^1.85] / Pipe Inside Diameter(in)^4.87 Computed by the Hazen Williams Formula

TDH = Pressure Head + Elevation Head + Friction Head

### HAL! VEN & ASSOCIATES

#### SOIL & ENVIRONMENTAL SCIENTISTS

P.O. Box 400, 266 Old Coats Road Lillington, NC 27546-0400 Phone (910) 893-8743 / Fax (910) 893-3594

E-mail: service@halowensoil.com

17 August, 2009

Mr. Oliver Tolksdorf Harnett County Department of Environmental Health 307 Cornelius Harnett Blvd. Lillington, NC 27546

Reference: Jean-Paul and Amy Foisy - Septic Easement Design

4.14 Total Acres PIN: 0690-34-3607

Dear Mr. Tolksdorf.

A site investigation was conducted for the above referenced property located on the southern side of N.C. Highway 27, Grove Township, Harnett County, North Carolina. The purpose of the investigation was to determine the ability of a septic easement area for this lot to support a subsurface sewage waste disposal system and 100 % repair area for a typical threebedroom home.

A foundation drain will be possible for this lot. Gravity distribution to 180 feet of accepted system drainline is the proposed design for the initial septic system. topographical differences were observed in the upper reaches of the initial system and therefore line 10 of the initial system will need to be installed at 22 inches below the soil surface and shallow to 18 inches below the soil surface at the terminal end. The repair system includes pressure distribution to 480 feet of low pressure pipe drainline. Due to complex topography observed within the repair area, lines 7, 8 and 9 will need trench bottoms installed at 18 inches below the soil surface and shallow to 12 inches at the terminal end. All other septic drainlines at the site are demonstrated on contour.

Attached is the septic system layout and supporting information for this lot. I trust that this report provides all the information that you require at this time. If you have any questions or need additional information, please contact me at your convenience.

Sincerely,

John C. Roberts

Licensed Soil Scientist

Soil Science Investigations • Wetland Delineations, Permitting, and Consulting

