25858

HTE# 09-5-23513R

## Harnett County Department of Public nealth

## Improvement Permit

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: LASATER RO ISSUED TO: STERHENSON BUILDERS INC SUBDIVISION WALNUT GROVE LOT # 30 REPAIR 🗆 EXPANSION Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SEO (69'x22) Proposed Wastewater System Type: 25% REDUCTION STEEM 480 GPD Projected Daily Flow: Number of Occupants: 8 Number of bedrooms: Basement Yes No Pump Required: ☐Yes ☐ May be required based on final location and elevations of facilities Five years Type of Water Supply: 
Community Public Well Distance from well 100 feet Permit valid for: Permit conditions: ■ No expiration Authorized State Agent:: SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: STERIFEMSON BUILDERS INC PROPERTY LOCATION: LASATER RD SUBDIVISION WALNUT GROVE Facility Type: SFO (69'22) New ☐ Expansion ☐ Repair Basement? Yes No Basement Fixtures? Yes 25% REDUCTION STSTEM (Initial) Wastewater Flow: 480 GPD Type of Wastewater System\*\* (See note below, if applicable 

) 25% REDUCTION SYSTEM (Repair) Number of trenches Installation Requirements/Conditions Exact length of each trench 246 feet Trench Spacing: Feet on Center Septic Tank Size 1000 gallons Trenches shall be installed on contour at a Soil Cover: 12 Pump Tank Size gallons Maximum Trench Depth of: 24 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_\_ft. TDH vs. \_\_\_\_\_ inches below pipe Aggregate Depth: \_\_\_\_\_\_ inches above pipe Conditions: WKGOZZING MUST BE 10' FOOD SEPTIC SUCTEM inches total \*\*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subfect to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provisions of the Taws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date: 19

## Harnett County Department of Public Health Site Sketch

