25872

HTE# 10-5-33557

Harnett County Department of Public Health

Improvement Permit

	PROPERTY LOCATION: PUTTOLOG LAKE RD		
ISSUED TO: WYNN CONSTRUCT	PROPERTY LOCATION: BUTFOLOG LAKE KD		
NEW □ REPAIR □ EXPANSI	101 # <u></u>		
Type of Structure: SEO (38452)	ON Site Improvements required prior to Construction Aut	iorization Issuance:	
Proposed Wastewater System Type: Pume To	25% REDUCTION		
Projected Daily Flow: 360 GPD			
Number of bedrooms: 3 Number of Occu	pants: G max		
Basement 🗆 Yes 🔀 No			
Pump Required:	uired based on final location and elevations of facilities		
Type of Water Supply: Community Public Permit conditions:	☐ Well Distance from well 100 feet Permit valid for:	Five years No expiration	
	000		
Authorized State Agent:	QEHS Date: 1 29 10 SEE A	TTACHED SITE SKETCH	
site is subject to revocation if the site plan, plat, or the intended use the Laws and Rules for Sewage Treatment and Disposal and to condition	untees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject ns of this permit.	in meeting their requirements. This to compliance with the provisions of	
	Construction Authorization		
	(Required for Building Permit)		
with the attached system layout.	954, 1955, 1956, 1957, 1958, and 1959 are incorporated by references into this permit and shall be met. Syste	ms shall be installed in accordance	
ISSUED TO: WYMN CONSTRUC	FION PROPERTY LOCATION: BUFFFELOE LAKERS	,	
Facility Type: SED (38/45)	SUBDIVISION UNGSON TINGS	LOT # \ \\	
	New Expansion Repair		
Basement? Yes No Basement Fix	tyres? 口 Yes X No 100 25% RESUCTION (Initial) Wastewater Flow		
Type of Wastewater System**	(Initial) Wastewater Flow	:_360 GPD	
(See note below, if applicable \square) $Pv r r$	25% REDUCTION (Repair)		
Installation Requirements/Conditions	Number of trenches 2		
Septic Tank Size \ \ \coc gallons		Feet on Center	
Pump Tank Size \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Trenches shall be installed on contour at a Soil Cover:	inches	
	Maximum Trench Depth of: $\frac{\partial^2 Y}{\partial x^2}$ inches (Maximum soil cover shall		
	(Trench bottoms shall be level to +/-1/4" 36" above the trench bottoms		
	in all directions)	ttom)	
Pump Requirements:ft. TDH vs		inahan kalaur mina	
	Aggregate Death:	inches below pipe	
Conditions WATER LINE MUST	DE 10 Francis Statica System This forms	inches above pipe	
BOSED ON POROSOL FOR	Aggregate Depth: DE 10 From SECTIC SYSTEM. THIS FOUNT IN APPLICANTS SOIL CONSULTANT	inches total	
	THE COUNTY SOIL CONSULTANT		
applicable: I understand the system type specified	is different from the type specified on the application. I accept the specifications of	this permit.	
Owner/Legal Representative Signature:	Date:		
This Construction Authorization is subject to revocation if the site plan,	olat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in	ownership of the site. This	
Construction Authorization is subject to compliance with the provisions o	the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.	ATTACHED SITE SKETCH	
		The state of the s	
Authorized State Agent:	REMS Date: 1 29 10		
	Construction Authorization Expiration Date: 12915		

HTE#	10	5-23557	
------	----	---------	--

Permit # _ 35872

Harnett County Department of Public Health Site Sketch

	PROPERTY LOCATON: BUFFALOE LAKE RD	
ISSUED TO: WYMM CONSTRUCTION	SUBDIVISION CAMERON PINES	LOT # \H
Authorized State Agent:	RENS (OLIVER TOLYSDORF) Date: 1 29/10	

