26142

HTE# 10-5-24597

Harnett county Department of Public Hearin

Improvement Permit

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: 27 WEST WYNN CONSTRUCTION SUBDIVISION TINGEN POINTE Type of Structure: SFO 60 GO EXPANSION -Site Improvements required prior to Construction Authorization Issuance: Proposed Wastewater System Type: Pump To 25% REDUCTION Projected Daily Flow: 360 Number of Occupants: _ 6 max Number of bedrooms: Basement Yes No ☐ No Pump Required: Kes ☐ May be required based on final location and elevations of facilities Type of Water Supply:

Community Public Well Distance from well 160 feet Permit valid for: Five years ■ No expiration Permit conditions: RENS Authorized State Agent:: SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. Construction Authorization (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: WYNN CONSTRUCTION PROPERTY LOCATION: 27 WEST TINGEN POINTE SUBDIVISION Facility Type: 5FD(60'x60") New ☐ Expansion ☐ Repair Basement?
Yes No Basement Fixtures? Yes No RUMP TO 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 360 Type of Wastewater System** (See note below, if applicable

) PUMP TO 25% REDUCTION SYSTEM (Renair) Number of trenches 1 Installation Requirements/Conditions Trench Spacing: 9 Feet on Center Exact length of each trench 225 Septic Tank Size LOOO gallons Pump Tank Size 1000 gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 12 (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: ft. TDH vs. inches below pipe Conditions: Do NOT REMOVE ANY SOIL DURING CLEARING-HAND CLEARING inches above pipe inches total RECOMMENDED. SOIL DEPTH TOBE VERIFIED BY PRELICANTS SOIL SCIENTIST OR HOHO PRICE TO INSTALLATION. MINIMUM OF G"OF COVER NEEDED OVER DRAINFIELD. MAINTAIN ALL SETBACKS! **If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This SEE ATTACHED SITE SKETCH Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. Authorized State Agent: Construction Authorization Expiration Date:

Harnett County Department of Public Health Site Sketch

