Harnett county Department of Public Hearm

Improvement Permit

A	building permit cannot be issued with only an Improvement PROPERTY LOCATION: 5 R ///5	Permit FC In I a Rd
ISSUED TO: WYAN CONSTRUC	FROPERTY LOCATION: SR /// S SUBDIVISION COMERON	Pines LOT # 13
NEW REPAIR - EXPANSIO		ired prior to Construction Authorization Issuance:
Type of Structure: SFD 37×42'	20 PCCTO DOMESTICS TO BE	
Proposed Wastewater System Type: 25 % Red	ction System	
Projected Daily Flow: 360 GPD	,	
Number of bedrooms: Number of Occup	pants:max	
Basement Yes No	ired based on final location and elevations of facilities	
	Well Distance from well feet	Permit valid for: Five years
Permit conditions:	The Distance from wen feet	□ No expiration
- A Note	2-115 122 122	
Authorized State Agent: 1 243	-REHS Date: 6/22/201	
The issuance of this permit by the Health Department in no way guara site is subject to revocation if the site plan, plat, or the intended use	ntees the issuance of other permits. The permit holder is responsible for chec changes. The Improvement Permit shall not be affected by a change in owner	ship of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to condition		
	Construction Authorization	
	(Required for Building Permit)	
	954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references i	nto this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	0	-61 1 1 0
ISSUED TO: WYAA (onstrue	tion PROPERTY LOCATION: 50+	tele hake Kel.
	Froperty Location: But subdivision Camero.	n Pines LOT # 13
Facility Type: SFD	New Expansion Repair	
Decement Civ	tures? Ves No	2/ 6
Type of Wastewater System** 25% Ke	duction System	(Initial) Wastewater Flow: 360 GPD
(See note below, if applicable ()	(. C.)	
25 % /edus	troa lyster (Repair)	
installation kequirements/conditions	Number of frenches	Br. S
Septic Tank Size/OOO gallons	Exact length of each trench 75 feet	Trench Spacing: 6 9 Feet on Center
Pump Tank Size gallons	Trenches shall be installed on contour at a	Soil Cover: 6-12 inches
	Maximum Trench Depth of: 18-24 inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)
	in all directions)	index follows also
Pump Requirements:ft. TDH vs		inches below pipe
If fall on ant be	achied from took to lives	Aggregate Depth: inches above pipe
ditch death (Maintaine	de au l'ail les recived	Aggregate Depth:inches above pipe inches total
anoctepts mariane	6 6 6 10 51 6	- I f salis siche
of referrores, All water	lines must be 10 H. from any d is different from the type specified on the application.	account the energifications of this permit
applicable: I understand the system type specifie	а із атегент тот те туре зрестей он те аррисатон.	Taccept the specifications of this perint.
Owner/Legal Representative Signature:		Date:
	plat, or the intended use changes. The Construction Authorization shall not	
Construction Authorization is subject to compliance with the provisions		CEE ATTACHED CITE CVETCH
	of the Laws and holes for sewage freatment and bisposar and to the contain	
	of the cars and times to service reactions and disposal and to the control	
Authorized State Agenty Luga MC	Date:	6/22/2010

Harnett County Department of Public Health Site Sketch

Authorized State Agent: June Mc Supplied State Agent: June Agent A

