HTE#10-5-24942

## Harnett County Department of Public Health

## **Improvement Permit**

26238

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: Marches 120 ISSUED TO: WYMY CONSTRUCTION INC SUBDIVISION COOPER FARMS LOT # 39 Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SFD (49 X44 Proposed Wastewater System Type: CONVENTION RL Projected Daily Flow: 360 GPD Number of Occupants: Number of bedrooms: Basement □Yes ≥ No Pump Required: □Yes ≺ No ☐ May be required based on final location and elevations of facilities Type of Water Supply: 
Community Public Well Distance from well 100 feet Permit valid for: Five years Permit conditions: ☐ No expiration REHS\_ Date: \_ The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: WYNN CONSTRUCTION INC PROPERTY LOCATION: MARKS RD SUBDIVISION COOPER FARMS LOT # 39 Facility Type: SFD (49×48) SUBDIVISION SUBDIVISION Repair Basement? ☐ Yes ⋈ No Basement Fixtures? ☐ Yes ⋈ No Conservous (Initial) Wastewater Flow: 360 GPD Type of Wastewater System\*\* (See note below, if applicable  $\square$ ) ConversionAL Number of trenches \ **Installation Requirements/Conditions** Trench Spacing: \_\_\_\_\_\_ Feet on Center Exact length of each trench 150 Septic Tank Size 1000 gallons Pump Tank Size \_\_\_\_\_ gallons Trenches shall be installed on contour at a Soil Cover: 12-18 inches Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_ft. TDH vs. GPM WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. \*\*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the providing of the laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Date: Construction Authorization Expiration Date:

## Harnett County Department of Public Health Site Sketch

