HTE# 10-5-25144

Harnett County Department of Public nealth

Improvement Permit


26267

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: MARKS RD ISSUED TO: EALY DEVELOPMENTS LLC SUBDIVISION ASHEROED Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SED (52×6 Proposed Wastewater System Type: Pump Projected Daily Flow: _ 360 Number of bedrooms: _ 3 Number of Occupants: 6 max Basement Yes Pump Required: Xes ☐ No ☐ May be required based on final location and elevations of facilities Type of Water Supply:

Community Public Well Distance from well 100 feet Permit valid for: Five years Permit conditions: No expiration RENS Date: The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: Early DEVELOPMENTS LLC PROPERTY LOCATION: MARKER PO SUBDIVISION ASHEFORD Facility Type: SFD (52×62) 🗏 New 🗆 Expansion 🗆 Repair Basement? ☐ Yes 🗀 No Basement Fixtures? ☐ Yes 🙀 No Pume Te 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 360 GPD Type of Wastewater System** (See note below, if applicable ume TO 25% REDUCKION (Repair) Installation Requirements/Conditions Number of trenches Exact length of each trench 180 feet Trench Spacing: _____ Feet on Center Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons Trenches shall be installed on contour at a Soil Cover: 6 inches Maximum Trench Depth of: 14 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: ft. TDH vs. GPM inches below pipe Aggregate Depth: ______ inches above pipe inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. **If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date: 973

Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: MARKES RD		
ISSUED TO: EALY DEVELOPMENTS LLC SUBDIVISION ASHEFORD	LOT #	138
sololo becare and alaboration		
Authorized State Agent: RCHS (PLIVER TOLKS DORF) Date: 9 13 10		



LOCKWOUD DR