HTE# 12-5-20-06

## Harnett County Department of Public Health

Improvement Permit

26495

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: DOCS RD HOME BUILDERS SUBDIVISION TROTTERS RIOGE ISSUED TO: SIGNER VOLG NEW 🕱 REPAIR 🗆 EXRANSION 🗆 Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SFD (DANTAS') (45 XM7') Proposed Wastewater System Type: Pume To 25% REDUCTION Projected Daily Flow: 600 Number of bedrooms: 5 Number of Occupants: 10 Basement Yes ☐ May be required based on final location and elevations of facilities Pump Required: \(\infty\)es ☐ No Type of Water Supply: 
Community & Public Well Distance from well 100 feet Permit valid for:

Permit conditions: Do Not Grade DRAINFIELD AREA OR REMOVE SOIL. ANY SITE Five years ☐ No expiration ALTERPRIORS MAY REQUIRE AN ALTERNATIVE BERTIC SYSTEM REMS Date: 3 | 23 | 11 Authorized State Agent:: The issuance of this permit by the Health Department in no way guarantees the squance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: SIGNATURE HOME BUILDERS PROPERTY LOCATION: Does & SUBDIVISION TROTTERS RIDGE Facility Type: 550 (47-x43) Mew Expansion X No Basement? Yes No Basement Fixtures? Yes Type of Wastewater System\*\* Pump To 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 600 GPD (See note below, if applicable X) ume to 25% REOUTION (Repair) Installation Requirements/Conditions Number of trenches \ Trench Spacing: Feet on Center Septic Tank Size 1200 Exact length of each trench \_ 270 gallons Soil Cover: <u>6-18</u> Pump Tank Size 1200 Trenches shall be installed on contour at a gallons Maximum Trench Depth of: 18-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_ft. TDH vs. \_\_\_\_ GPM \_\_\_ inches below pipe Aggregate Depth: inches above pipe WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. \*\*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This SEE ATTACHED SITE SKETCH Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. Authorized State Agent: \_

Construction Authorization Expiration Date:

HTF#	11-5-26206	
NIE#	1 0 0	

Permit # <u>26495</u>

## Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: Occ Ro	
ISSUED TO: SIGNATURE HOME BUILDERS SUBDIVISION TROTTERS RIDGE	LOT # <u>106</u>
Authorized State Agent: Date: 3 23 1)	

