HTE# 11-5-262-71

Harnett County Department of Public Health

26498

Improvement Permit

A	building	permit	cannot	be	issued	with	only	an	Improvement	Permi	t
	v	•					•			-	٦

A building permit cannot be issued with	only an improvement Permit ON: Lasas62 Q
	WALNUT GOOVE LOT # 1)
	Site Improvements required prior to Construction Authorization Issuance:
Tuns of Structures SEC (60'x EE)	site improvements required prior to construction Authorization issuance.
Proposed Wastewater System Type: Pump To 25% REDUCTION Projected Daily Flow: 360 GPD	
Projected Daily Flow: 360 GPD	
Number of bedrooms: <u>3</u> Number of Occupants: <u>6</u> max	
Basement 🗆 Yes 🔏 No	
Pump Required: IVes INO X May be required based on final location and elevation	ons of facilities
Type of Water Supply: Community Rublic Well Distance from well 10	
Permit conditions:	□ No expiration
	<u> </u>
Authorized State Agent:: Authorized State Agent:: Date:	B 258 (2.0)) SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit he	older is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affe	ected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit 🔪	
Construction Aut	norization
(Required for Building	g Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are i	
with the attached system layout.	
ISSUED TO: STERNENSON BUILDERS INC PROPERTY L	OCATION. LACATED RD
	WALNUT GROVE LOT # Y)
	on 🗆 Repair
Basement? I Yes X No Basement Fixtures? I Yes X No	
	System (Initial) Wastewater Flow: <u>360</u> GPD
(See note below, if applicable \Box)	
	(Repair)
Installation Requirements/Conditions Number of trenches	_
Septic Tank Size \underline{vooo} gallons Exact length of each trench <u>3</u>	<u>60</u> feet Trench Spacing: <u>9</u> Feet on Center
Pump Tank Size <u>NOOO</u> gallons Trenches shall be installed on con	ntour at a Soil Cover: <u>G</u> inches
(IFNEEDED) Maximum Trench Depth of: 13	L inches (Maximum soil cover shall not exceed
(Trench bottoms shall be level to	l l
in all directions)	· · · · · · · · · · · · · · · · · · ·
Pump Requirements:ft. TDH vs GPM	inches below pipe
· · · · · · · · · · · · · · · · · · ·	Aggregate Depth: inches above pipe
Conditions: FLAID LATONT & TREAK DEPTH TO B	DETERMINED inches total
Conditions: FINAL LATOVT & TRENCH DEPTH TO B AFFER DRAINFIELD AREA IS CLEARED.	
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEP	PTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
** If applicables I understand the system type specified is different from the type specified	I an the application I account the appeiling of this appril
<u>**If applicable: I understand the system type specified is different from the type specified</u>	on the application. Taccept the specifications of this permit.
	_
Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Constructio	Date:
Construction Authorization is subject to compliance with the providence of the laws and Rules for Sewage Treatment and D	Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH
IANI III	, I
Authorized State Agent.	Date: 3/28/201)

Construction Authorization Expiration Date: 327 2016

