HTE#11-5-26476

Authorized State Agent:

Harnett county Department of Public Hearm

26562

Improvement Permit A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: DOCK DO WYNN CONSTRUCTION SUBDIVISION TROTTERS RIGGE Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SEO (60'260' Proposed Wastewater System Type: 25% REOVERON Projected Daily Flow: _ 480 Number of Occupants: 8 Number of bedrooms: Basement Yes ☐ No May be required based on final location and elevations of facilities Pump Required: ☐Yes Type of Water Supply:

Community Public

Well Distance from well

Feet Five years Permit valid for: No expiration SEE ATTACHED SITE SKETCH Authorized State Agent:: The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.. Construction Authorization (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: WYMM COMSTONES ON PROPERTY LOCATION: DOCE RO Facility Type: SFD(60×60) X New Expansion Repair Basement? ☐ Yes ➤ No Basement Fixtures? ☐ Yes 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 480 Type of Wastewater System** (See note below, if applicable \square) 25% REDUCTION SYSTEM (Repair) Number of trenches Installation Requirements/Conditions Exact length of each trench 200 feet Trench Spacing: Septic Tank Size NOG o gallons Feet on Center Soil Cover: 12-24 Pump Tank Size gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: _____ft. TDH vs. ____ GPM inches below pipe Aggregate Depth: ______ inches above pipe inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. **If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is replaced to compliance with the provision of the laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH

Construction Authorization Expiration Date:

Harnett County Department of Public Health Site Sketch



