## HTE# 11-5-27180R Harnett County Department of Public nealth

Improvement Permit

26749

WESTAU CONSTRUCT	A building permit cannot be issued with only an Improvement Pe	
ISSUED TO: Comberrano Home	SUBDIVISION TINGEN PLACE	
NEW ⋈ REPAIR □ ĘXPANSI		red prior to Construction Authorization Issuance:
, , , , , , , , , , , , , , , , , , , ,	38 XHO	24 prior to construction Authorization Issuance.
Proposed Wastewater System Type: CONVENTY	LANC	
Projected Daily Flow: 360 GPD		
Number of bedrooms: 3 Number of Occu	pants: <u>6</u> max	
Basement □Yes ⋈ No	<u></u>	
Pump Required: ☐Yes ☐ No ☐ May be requ	uired based on final location and elevations of facilities	6.
Type of Water Supply:  Community Public Permit conditions:	☐ Well Distance from well 100 feet	Permit valid for: Five years   No expiration
Last 10		
Authorized State Agent::	2675 Date: 12811	SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guara site is subject to revocation if the site plan, plat, or the intended use the Laws and Rules for Sewage Treatment and Disposal and to condition	antees the issuance of other permits. The permit holder is responsible for checkin changes. The Improvement Permit shall not be affected by a change in ownershi us of this permit.	ng with appropriate governing bodies in meeting their requirements. This p of the site. This permit is subject to compliance with the provisions of
•	Construction Authorization	
	(Required for Building Permit)	
with the attached system layout	1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into	this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: CUMBERLAND HOMES	DRODERTY LOCATION: M.C.	32 Tay 53 Ro
BOLD TO. CONFIGURACIONES	PROPERTY LOCATION: MIC SUBDIVISION TINGEN PL	-ULE FOLKER
Facility Type: SFO(55×45) 38 X L	ဃ 🔀 New 🔲 Expansion 🔲 Repair	101 # _0.0
	ctures? 🗆 Yes 🔍 No	
	•	2 4 -
Type of Wastewater System** Concent	IONAL	_ (Initial) Wastewater Flow: <u>360</u> GPD
(See note below, if applicable □)		_ (Initial) Wastewater Flow: <u>360</u> GPD
	10NRL (Repair)	_ (Initial) Wastewater Flow: <u>360</u> GPD
(See note below, if applicable □)	Number of trenches 3 (Repair)	
(See note below, if applicable □)	Number of trenches 3 (Repair)	
(See note below, if applicable □)	Number of trenches 3 Exact length of each trench 50 feet T	rench Spacing: Feet on Center
(See note below, if applicable □)    Convert   Installation Requirements/Conditions   Septic Tank Size 1008 gallons	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a S	rench Spacing: 9 Feet on Center oil Cover: 12-24 inches
(See note below, if applicable □)    Convert   Installation Requirements/Conditions   Septic Tank Size 1008 gallons	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches	rench Spacing: Feet on Center oil Cover:\
(See note below, if applicable □)    Convert   Installation Requirements/Conditions   Septic Tank Size 1008 gallons	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches  (Trench bottoms shall be level to +/-1/4"	rench Spacing: 9 Feet on Center oil Cover: 12-24 inches
(See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)	rench Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)
(See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM	rench Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)
(See note below, if applicable   Installation Requirements/Conditions Septic Tank Size 100 gallons Pump Tank Size gallons  Pump Requirements:ft. TDH vs	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM	French Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe
(See note below, if applicable □)    Convert   Installation Requirements/Conditions   Septic Tank Size 1008 gallons	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM	rench Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)
(See note below, if applicable     Convert   Installation Requirements/Conditions	Number of trenches 3  Exact length of each trench 50 feet T  Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM	French Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total
(See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REP	French Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total
(See note below, if applicable     Convert   Installation Requirements/Conditions	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REP	French Spacing: Feet on Center oil Cover: inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total
(See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REP	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches above pipe inches above pipe inches total  PAIR AREA.
(See note below, if applicable   )	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPORAIN FIELD AREA.	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches above pipe inches above pipe inches total  PAIR AREA.  Accept the specifications of this permit.
See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPORAIN FIELD AREA.  It is different from the type specified on the application. It	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches above pipe inches above pipe inches total  PAIR AREA.  Date:
See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPORAIN FIELD AREA.	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total  PAIR AREA.  Paccept the specifications of this permit.  Date:
See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPORAIN FIELD AREA.  It is different from the type specified on the application. It plat, or the intended use changes. The Construction Authorization shall not be treated.	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total  PAIR AREA.  Paccept the specifications of this permit.  Date:
See note below, if applicable	Number of trenches 3  Exact length of each trench 50 feet T Trenches shall be installed on contour at a Maximum Trench Depth of: 24-36 inches (Trench bottoms shall be level to +/-1/4" in all directions)  GPM  BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPORAIN FIELD AREA.  It is different from the type specified on the application. It plat, or the intended use changes. The Construction Authorization shall not be treated.	Feet on Center oil Cover: 12-24 inches (Maximum soil cover shall not exceed 36" above the trench bottom)  Aggregate Depth: inches below pipe inches above pipe inches total  PAIR AREA.  Date:

HTE#	_//	-5-	9_	71	80	R

Permit # <u>26749</u>

## Harnett County Department of Public Health Site Sketch

WESTAN CONSTRUCTION PROPERTY LOCATON: MICROTOWER RO	
ISSUED TO: CHARGERIAND ARES THE SUBDIVISION TINGEN PLACE	<u> →6</u> # 101
Authorized State Agent: 12/8/11	
REVISED 10/24/12	

