HTE# 12-5-2873912 R Harnett County Department of Public Health

Improvement Permit

26994

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: CHOCESS CHURCH &				
ISSUED TO: DR HORTON IN	C SUBDIVISION CYPRESS POINTE	4.4 # 10J		
NEW REPAIR REPAIR STRANSION Type of Structure: SFO (38×5)				
Proposed Wastewater System Type: Punp To 25 Projected Daily Flow: 35 GPD	% REDUCTION	1, 1446 William and Albandon y		
Number of bedrooms: 3 Number of Occupa	ants: S max			
Basement Yes No				
	ed based on final location and elevations of facilities			
Type of Water Supply: Community Public Permit conditions:	□ Well Distance from well <u>▶○ ○</u> feet Permit valid for:	Five years No expiration		
fall 11				
	REW Date: 51812 (0 8-12) SEE AT			
Authorized State Agent:: The issuance of this permit by the Health Department in no way guarant site is subject to revocation if the site plan, plat, or the intended use che Laws and Rules for Sewage Treatment and Disposal and to conditions	ees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies i anges. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to	TACHED SITE SKETCH in meeting their requirements. This o compliance with the provisions of		
	Construction Authorization (Required for Building Permit) 54, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. System	is shall be installed in accordance		
ISSUED TO: DR HOWON INC	PROPERTY LOCATION: COPRESS CALLOCAT	₹0		
	PROPERTY LOCATION: CHRESS CHURCH SUBDIVISION CHRRESS POINTE	LOT # 24		
Facility Type: SFO (38×51)	≥ New □ Expansion □ Repair			
Basement? Yes Mo Basement Fixtures? Yes Mo Type of Wastewater System** Pung To 25% REDUCTION - ULTORSHALLON (Initial) Wastewater Flow: 360 GPD				
·- · · · · · · · · · · · · · · · · · ·		010		
Pump To 20	CO/o RED ULTRESHALLOW (Repair)			
Installation Requirements/Conditions	Number of trenches 3			
Septic Tank Size 1000 gallons	Exact length of each trench 100 feet Trench Spacing:	Feet on Center		
Pump Tank Size \\ \rightarrow \ightarrow \ig	Trenches shall be installed on contour at a Soil Cover:	inches		
Sunons	Maximum Trench Depth of: 12 inches (Maximum soil cover shall			
	(Trench bottoms shall be level to +/-1/4" 36" above the trench bot			
	in all directions)	.tom)		
Pump Requirements:ft. TDH vs	,	imakan kalau mima		
rump requirementsit. IDN 45		inches below pipe		
Conditions: MINIMUM OF C'OF	COVER NEEDED OVER DRAWFIELD			
conditions.	WYCE NEWW OVER EVAM ILED	inches total		
NATER LINES (INCLUDING IRRIGATION) MUST B NO UTILITIES ALLOWED IN INITIAL OR REPAIR DI	E 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	, , , , , , , , , , , , , , , , , , ,		
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.				
Owner/Legal Representative Signature:	Date:			
	at, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in the bays and Rules for Sewage Treatment and Disposal and to the conditions of this permit.	ownership of the site. This ATTACHED SITE SKETCH		
Authorized State Agent:	Date: 53 12 6-8-	12		
	Construction Authorization Expiration Date: 5 9 12 6-	8-17		

Harnett County Department of Public Health Site Sketch

		RESS CHURCH RO	
ISSUED TO: DEC HORZON INC	SUBDIVISION C-79R	ess Pointe	FOI # ラゲ
Authorized State Agent:	26 HS	Date: <u> </u>	
		1 1	

