## HTE# 12-5-29244 Harnett County Department of Public Health

Improvement Permit

27109

A building permit cannot be issued with only an Improvement Permit		
	CATION: Marks Rd.	
ISSUED TO: SUBDIVISION DEW REPAIR : EXPANSION D	Site Improvements required prior to Construction Authorization Issuance:	
Type of Structure: SFD 44 x 50	site improvements required prior to construction authorization issuance:	
Proposed Wastewater System Type: 25% ledut: on System		
Projected Daily Flow: 360 GPD		
Number of bedrooms: Number of Occupants: max		
Basement Ves No		
Pump Required:   Yes   No   May be required based on final location and elements of the second of th	evations of facilities	
Type of Water Supply:   Community Public   Well Distance from well	feet Permit valid for: 🗗 Five years	
Permit conditions:	☐ No expiration	
<u> </u>	<del></del>	
Australia Sans Annes / M. Sci. 1846 Dec.	7/12/2012 SEE ATTACHED SITE SKETCH	
Authorized State Agent: Department in no way guarantees the issuance of other permits. The per		
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not		
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	, , , , , , , , , , , , , , , , , , , ,	
Construction A	uthorization	
(Required for Bu		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959		
with the attached system layout.		
ISSUED TO:PROPER	RTY LOCATION: Marks Rd.	
	SION Asheford LOT # 34	
Facility Type: New Expansion		
Basement?  Yes No Basement Fixtures? Yes No,	Illainii 🗀 vehaii	
	(Initial) Wastewater Flow: 360 GPD	
··· /	(Initial) Wastewater Flow: SOO GPD	
(See note below, if applicable )	(Repair)	
Installation Requirements/Conditions  Number of trenches 4	(nepair)	
	feet Trench Spacing: Feet on Center	
	• •	
Pump Tank Size gallons Trenches shall be installed on	,	
Maximum Trench Depth of: _		
(Trench bottoms shall be leve	1 to +/-1/4" 36" above the trench bottom)	
in all directions)		
Pump Requirements:ft. TDH vs GPM	inches below pipe	
	Aggregate Depth: inches above pipe	
Conditions:	inches total	
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF	SEPTIC SYSTEM OR REPAIR AREA.	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.		
**If applicable: / understand the system type specified is different from the type spec	rified on the application I account the engineerings of this parmit	
<u>n applicable. I understand the system type specified is unferent from the type spec</u>	пей он тне аррисаціон. Т ассерт те зреспісаціонз от тіні регіпіт.	
Owner/Lagel Representative Signatures	Doto	
Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Cons	Date:	
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH		
STEE ATTACHED SHE SALICH		
Authorized State Agent	Authorized State Arent / My Green REHS	
Authorized State Agent Super Main 16th Date: 7/12/2012		
Construction Authorization Expiration Date: 7/12/2017		

## Harnett County Department of Public Health Site Sketch

