Harnett	County	Department	of	Public	inealth
---------	--------	------------	----	--------	---------

HTE# 13-5-30515R

0	7	Λ	7	\cap
7		4	C	U

Improvement Permit

A	building permit cannot be issued with only an Improvement PROPERTY LOCATION: DOCS	
ISSUED TO: WYMM CONSTRUCT		RIDGE LOT # 69
NEW 🛛 REPAIR 🗆 EXPANSIQ	N 🔲 Site Improvements rea	uired prior to Construction Authorization Issuance:
Type of Structure: SFO (434 × 352)	56'466'	•
Proposed Wastewater System Type: Pume TO 29 Projected Daily Flow: 360 480 GPD	5°LA REDUCTION	
Projected Daily Flow: 560 480 GPD Number of bedrooms: 94 Number of Occup		
Basement \Box Yes No	pants: <u> </u>	
	red based on final location and elevations of facilities	
Type of Water Supply: Community Public Permit conditions:		Permit valid for: Five years
119		······································
Authorized State Agent::	<u>2EHS</u> Date: 47313	SEE ATTACHED SITE SKETCH
site is subject to revocation if the site plan, plat, or the intended use a the Laws and Rules for Sewage Treatment and Disposal and to condition	names. The Improvement Permit shall not be affected by a change in owne s of this permit	cking with appropriate governing bodies in meeting their requirements. This rship of the site. This permit is subject to compliance with the provisions of
REVISED 6/18/13	Construction Authorization	
	<u>Construction</u> Authorization	
The construction and installation requirements of Rules .1950, .1952, .19 with the attached system layout.	(<u>Required for Building Permit</u>) 254, .1955, .1956, .1957, .1958. and .1959 are incorporated by references	into this permit and shall be met. Systems shall be installed in accordance
ISSUED TO: WYMM CONSTRUCTIO		
Facility Type: SCD CARX 300 56 766) SUBDIVISION TROTTERS	R106E LOT # 69
Basement? Yes No Basement Fixt		
Type of Wastewater System** Pume To		(Initial) Wastewater Flow: <u>360</u> GPD
(See note below, if applicable □)	25% REDUCTION (Repair)	
Installation Requirements/Conditions	Number of trenches \times \rightarrow	
Septic Tank Size <u>+000</u> gallons	Exact length of each trench Dec 120 feet	Trench Spacing: Feet on Center
Pump Tank Size 1000 gallons	Trenches shall be installed on contour at a	Soil Cover: $6 - 18$ inches
	Maximum Trench Depth of: <u>18-30</u> inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)
	in all directions)	,
Pump Requirements:ft. TDH vs	GPM	inches below pipe
		Aggregate Depth: inches above pipe
Conditions:		inches total
WATER LINES (INCLUDING IRRIGATION) MUST B NO UTILITIES ALLOWED IN INITIAL OR REPAIR D	E 10FT. FROM ANY PART OF SEPTIC SYSTEM OR R RAIN FIELD AREA.	EPAIR AREA.
**If applicable: / understand the system type specified	is different from the type specified on the application.	I accept the specifications of this permit.
Owner/Legal Representative Signature:		Date:
	lat, or the intended use changes. The Construction Authorization shall not b	
construction warnorization is subject to complishe with the provisions of	the Laws and Rules for Sewage Treatment and Disposal and to the condition	ons of this permit. SEE ATTACHED SITE SKETCH
Authorized State Agent:	Date:	4)23,13
	Ens Construction Authorization Expiration D	ate: 4123 18
	<u> </u>	

