Harnett County Department of Public Health

HTE# 13-5-30594

27268

Im	p	ro	Ve	n	ne	nt	; P	'e	r	m	t

A	building	permit	cannot	be	issued	with	only	an	Improvement	Permit

A building permit cannot be issued with only	
ISSUED TO: Make Homes SUBDIVISION OF	DOCSKD AKMONT LOT # 16
	Improvements required prior to Construction Authorization Issuance:
Type of Structure: $5FQ(4c' \times 61')$	improvements required prior to construction Authorization issuance.
Proposed Wastewater System Type: 25% REDUCTION	
Projected Daily Flow: 480 GPD	
Number of bedrooms: <u>4</u> Number of Occupants: <u>8</u> max	
Basement \Box Yes \overleftarrow{X} No	
Pump Required: 🛛 Yes 🗡 No 🛛 May be required based on final location and elevations of	of facilities
Type of Water Supply: Community Public Well Distance from well 100	
Permit conditions:	
	1
Authorized State Agent:: Date: 2	19/13 SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder	is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected	by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit	
	• •
<u>Construction</u> Author	rization
(Required for Building Pe	rmit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorp with the attached system layout.	
m V = 11 = =	\circ \circ
	TION: Docs KD
SUBDIVISION C	DAKMONT LOT # 16
Facility Type: $SFO(4c' \times 6i')$ New \Box Expansion	🗆 Repair
Basement? 🗆 Yes 🛛 No 🛛 Basement Fixtures? 🗆 Yes 💢 No	
Type of Wastewater System** 25% REDUCTION SYSTEM	(Initial) Wastewater Flow: 480 GPD
(See note below, if applicable \Box)	
25% REDUCTION (Repu	air)
Installation Requirements/Conditions Number of trenches 1	air)
	Defect Transfer 1 9 For Car
Pump Tank Size gallons Trenches shall be installed on contour	
Maximum Trench Depth of: 18-24	
(Trench bottoms shall be level to +/-	1/4" 36" above the trench bottom)
in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
,	Aggregate Depth: inches above pipe
Conditions: KEEP TOP LINE 5 FROM HOUSE	inches total
WALER THER THE THERE BUDG ATTAIL MILE UL THET EDITAL AND DADT ME CLUTTE	CVATELL ON DEDLIN INC.
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	SYSTEM OR REPAIR AREA.

**If applicable: I understand the system type specified is different from the type specified on	the application. I accept the specifications of this permit.
Owner/Legal Representative Signature:	Date:
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Aut	uthorization shall not be transferred when there is a change in ownership of the site. This
Construction Authorization is subject to compliance with the provision of the Laws and Rules for Sewage Treatment and Dispos	
Authorized State Agent: Construction Authorization	Date: <u>2)19)3</u> Date: 2)19)8

