HTE# 13-5-31043

Har...t County Department of Public ...alth

Improvement Permit

27448

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: DOGS RO ISSUED TO: H+H CONSTRUCTORS SUBDIVISION OAKMONT Type of Structure: SEO (61 × 54) Site Improvements required prior to Construction Authorization Issuance: Proposed Wastewater System Type: 25% REDUCTION Projected Daily Flow: 600 GPD Number of Occupants: 10 Number of bedrooms: 5 Basement Yes Pump Required: ☐Yes ➤ No May be required based on final location and elevations of facilities Type of Water Supply:
Community Public Well Distance from well 100 feet Five years Permit valid for: ☐ No expiration Permit conditions: Authorized State Agent:: SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the squance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950. .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: H+H CONSTRUCTORS PROPERTY LOCATION: DOGS & SUBDIVISION OAKMONT Facility Type: 560 (61'x64') New Expansion Repair Basement Fixtures? | Yes | XNo 25% REDUCTION SYSTEM (Initial) Wastewater Flow: 600 Basement? ☐ Yes ☒ No Basement Fixtures? ☐ Yes Type of Wastewater System** (See note below, if applicable

) Installation Requirements/Conditions Exact length of each trench 125 feet Trench Spacing: Septic Tank Size 1 250 gallons Feet on Center Pump Tank Size gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 24-18 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: _____ft. TDH vs. inches below pipe Aggregate Depth: ______ inches above pipe Conditions: inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. **If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit. Owner/Legal Representative Signature: This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Construction Authorization is subject to compliance with the province of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent: Construction Authorization Expiration Date:


Harnett County Department of Public Health Site Sketch

Authorized State Agent:

PROPERTY LOCATON: Docs Ro

SUBDIVISION DALMONT

LOT # 145



CHERRY HILL DRIVE