HTE#13-5-31690

Harnett County Department of Public Health

27537

Imp	r٥١	/er	<u>nent</u>	Per	<u>mit</u>	

A	building	permit	cannot	be	issued	with	only	an	Improvement	Permit
	0						~·· '	Ý	w'.	\mathcal{O}

PRUPERIT	ULATION: I HALLA	, Lo	
ISSUED TO: TEACE HOMES INC SUBDIVISIO	N COOPER FAR	uns	LOT # <u>30</u>
NEW X REPAIR C EXPANSION C Type of Structure: SEO (ムムズステン)	Site Improvements re	quired prior to Construction Author	rization Issuance:
Type of Structure: SEO (44×52)			
Proposed Wastewater System Type: 25% REDUCTION SYSTEM			
Projected Daily Flow: 4780 GPD	····		
Number of bedrooms: Number of Occupants: max			
Basement 🗆 Yes 📈 No			
Pump Required: I Yes X No I May be required based on final location and			. 1
Type of Water Supply: 🗆 Community 💢 Public 🗀 Well Distance from wel	<u>100</u> feet	Permit valid for:	K Five years
Permit conditions:			No expiration
			•
	·····		
Authorized State Agent: Dat	130 13	SEE ATT	ACHED SITE SKETCH

The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.

Construction Authorization

(Required for Building Permit)

The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout.

ISSUED TO: TRACE HOMES IN	C PROPERTY LOCATION: MAK	oksRo	
2		FARMS	lot # <u>30</u>
Facility Type: SFD(44 ×52)	🖂 New 🗆 Expansion 🗆 Repair		
Basement? □ Yes ▷ No Basement Fixe Type of Wastewater System**	tures? 🗆 Yes 🛛 🕱 No		
Type of Wastewater System**	KEDUGIUN SYSTEM	(Initial) Wastewater Flow:	<u>480 </u>
(See note below, if applicable [])			
25% RE	DUCTION STEM (Repair)		
Installation Requirements/Conditions	Number of trenches	C	
Septic Tank Size <u>1000</u> gallons	Exact length of each trench 200 feet	Trench Spacing: Fo	eet on Center
Pump Tank Size gallons	Trenches shall be installed on contour at a	Soil Cover: <u>) 2</u> incl	hes
	Maximum Trench Depth of: <u>24</u> inches	(Maximum soil cover shall not	exceed
	(Trench bottoms shall be level to $+/-1/4$ "	36" above the trench bottom	ı)
	in all directions)		
Pump Requirements:ft. TDH vs	GPM		inches below pipe
		Aggregate Depth:	inches above pipe
Conditions:			inches total

WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.



