HTE# 14-5-32719

## Harnett County Department of Public Health

27777

**Improvement Permit** 

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: IINGEN RD ISSUED TO: BILL CLARK HOMES SUBDIVISION PATTONS POINT NEWX REPAIR □ , Site Improvements required prior to Construction Authorization Issuance: Type of Structure: SFO (38 XL)9 Proposed Wastewater System Type: 25% REDUCTION Projected Daily Flow: \_\_\_ Number of bedrooms: Number of Occupants: 8 Basement TYes Pump Required: □Yes ☐ May be required based on final location and elevations of facilities Type of Water Supply: 
Community Public 
Well Distance from well feet Permit valid for: Five years Permit conditions: ☐ No expiration REHS Date: SEE ATTACHED SITE SKETCH The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit. **Construction Authorization** (Required for Building Permit) The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958, and .1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance with the attached system layout. ISSUED TO: BILL CLARK HOMES PROPERTY LOCATION: TINGEN RD
SUBDIVISION PATIONS POINT Facility Type: 550 (38048) New 🗆 Expansion 🗆 Repair Basement? Yes No No Basement Fixtures? 

Yes Story

(Initial) Wastewater Flow: 480 GPD Type of Wastewater System\*\* (See note below, if applicable □) Pume To 25% REDUCTION (Repair) Installation Requirements/Conditions Number of trenches Septic Tank Size >000 gallons Exact length of each trench 200 Soil Cover: 6-18 Pump Tank Size \_\_\_\_\_ gallons Trenches shall be installed on contour at a Maximum Trench Depth of: 18-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom) in all directions) Pump Requirements: \_\_\_\_\_\_ft. TDH vs. \_\_\_\_\_ GPM \_\_\_\_\_ inches below pipe Aggregate Depth: \_\_\_\_\_\_ inches above pipe \_\_\_\_ inches total WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA. \*\*If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit, Owner/Legal Representative Signature: Construction Authorization is subject to exampliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH Authorized State Agent:

Construction Authorization Expiration Date:

## Harnett County Department of Public Health Site Sketch



