HTE# 14-5-32727

## Harnett County Department of Public Health

27783

**Improvement Permit** 

A building permit cannot be issued with only an Improvement Permit	
PROPERTY LOC	ATION: Docs RD
ISSUED TO: HYMN COMSTRUCTION INC SUBDIVISION D	
NEW X REPAIR COXOC EXPANSION CO	Site Improvements required prior to Construction Authorization Issuance:
Proposed Wastewater System Type: 25% REDUCTION SYSTEM	
Projected Daily Flow: 460 GPD	
Number of Dedrooms: Number of Occupants: 8 max	
Basement Yes No	
Pump Required: □Yes ⋈ No □ May be required based on final location and elev	vations of facilities
Type of Water Supply:  Community Public  Well Distance from well Permit conditions:	
	2121
Authorized State Agent:: Date:	SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the Issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Harpeyement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	
Construction Au	uthorization
(Required for Build	ding Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 with the attached system layout.	are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
4115 1116	Y LOCATION: Docs Ro
Facility Type: SFD (60'>60')  New Expan	ION TROTTERS ROGE LOT #50
Basement? ☐ Yes ✓ No Basement Fixtures? ☐ Yes ✓ No	·
Type of Wastewater System** 25% REDUCTION SYSTE	.m (Initial) Wastewater Flow: 480 GPD
(See note below, if applicable [7])	
25% RADUCTION SYSTEM	(Repair)
Installation Requirements/Conditions Number of trenches \( \)	
Septic Tank Size 1000 gallons Exact length of each trench	feet Trench Spacing: 9 Feet on Center
Pump Tank Size gallons Trenches shall be installed on	1 0
Maximum Trench Depth of: 3	
(Trench bottoms shall be level	1
in all directions)	above the trench bottom)
Pump Requirements:ft. TDH vs GPM	inakan kalam sisa
rump nequirementsit. IDM 43 UT	inches below pipe
Conditions:	Aggregate Depth: inches above pipe
Conditions.	inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE JOIT FROM ANY PART OF	SERVICE CUCTUL OR SERVICE CO.
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF S	SEPTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable:   understand the system type specified is different from the type specified	Field on the application I accept the specifications of this permit
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.	
Owner/Legal Representative Signature:	Date:
Owner/Legal Representative Signature:	
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.  SEE ATTACHED SITE SKETCH	
Authorized State Agent: Date: Date:	
Construction Authorization Expiration Date: 2519	

## Harnett County Department of Public Health Site Sketch

PROPERTY LOCATON: Docs RD

ISSUED TO: WYTH CONSTRUCTION INC SUBDIVISION TROTTEDS RIGGE LOT # 50

Authorized State Agent: Date: 2514

