HTE# 14-5-3415] R.R. Hari. .t County Department of Public ealth

28330

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

PROPERTY LOCATION: KENTUCKY DERBY LN	
SUBDIVISION SUBDIVISION	TROTIERS RIDGE LOT # 40
TEL AIT	Site Improvements required prior to Construction Authorization Issuance:
Type of Structure: SFO (60×60)	
Proposed Wastewater System Type: Pump To 25% REDUCTION	
Projected Daily Flow: GPD GPD GPD 480	
Number of bedrooms: Number of Occupants: 8 10 max 8	
Basement ☐ Yes ☐ No ☐ May be required based on final location and elev	
	ations of facilities
Type of Water Supply: Community Public Well Distance from well Permit conditions:	
Total Conditions.	—————————————————————————————————————
Authorized State Agent:: Date:	6 2 15
The issuance of this permit by the Health Department in no way guarantees the issuance of this permit. The permits	t holder is responsible for checking with appropriate governing hodies in meeting their requirements. This
are is subject to revocation if the site plan, plat, or the intended use changes. The improvement Permit shall not be	affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	5 St. A. M.
1 set a set	
Construction Au	thorization
(Required for Build	ing Permit)
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 at	re incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	
ISSUED TO: WYNN CONSTRUCTION PROPERTY	LOCATION: KENTUCKY DERBY LN
Facility Type: 550 (60' × 60') New Expans	
	ion Repair
Type of Wastewater System** Puno To 25% RED	
(See note below, if applicable \square)	GPD (Initial) Wastewater Flow: GPD
0 750	
	_(Repair)
Installation Requirements/Conditions Number of trenches	<u> </u>
Septic Tank Size Too Too gallons Exact length of each trench Trenches shall be installed on co	
	- 3 -
Maximum Trench Depth of: 22	
(Trench bottoms shall be level to	36" above the trench bottom)
in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
C I'-i'	Aggregate Depth: inches above pipe
Conditions:	inches total
NATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SE	PTIC SYSTEM OR REPAIR AREA.
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.	
Dumay/Legal Bassassian Company	
Owner/Legal Representative Signature:	Date:
his Construction Authorization is subject to revocation if the site plate plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This	
construction Authorization is source compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH	
Authorized State Agent: Date: 6215	
Recused 1 26/2 Construction Authorization Expiration Date: 6 2 20	

Harnett County Department of Public Health Site Sketch



