## Harnett County Department of Public Health

HTE# 15-537370

Improvement Permit

improvement remit			
A b	uilding permit cannot be issued with only an Improvement	Permit	
M Q Q	PROPERTY LOCATION: DLUG	Chip Gr	
ISSUED TO: MARKER PLACE BUT		PLACE LOT # 102	
NEW REPAIR C EXPANSION	□ Site Improvements re	uired prior to Construction Authorization Issuance:	
Type of Structure: SPO(HO×46)			
Proposed Wastewater System Type: 25% REDI	ICTION SYSTEM		
Projected Daily Flow: <u>360</u> GPD			
Number of bedrooms: Number of Occupation	nts: <u>6</u> max		
Basement 🗆 Yes 🔀 No		· · · · · · · · · · · · · · · · · · ·	
	ed based on final location and elevations of facilities	Χ.	
Type of Water Supply:  Community  Public	$\Box$ Well Distance from well <u>100</u> feet	Permit valid for: Five years	
Permit conditions:		No expiration	
		2 	
	>		
Authorized State Agent::	RGHS Date: 11 24 15	SEE ATTACHED SITE SKETCH	
		cking with appropriate governing bodies in meeting their requirements. This	
		ership of the site. This permit is subject to compliance with the provisions of	
the Laws and Rules for Sewage Treatment and Disposal and to conditions	of this permit		
· · · · · · · · · · · · · · · · · · ·			
	Construction Authorization		
	(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .195		into this permit and shall be met. Systems shall be installed in accordance	
with the attached system layout.		, ,	
ISSUED TO: MARKET PLACE BUILDERS PROPERTY LOCATION: BLUE CAIP G SUBDIVISION MARKET PLACE LOT # 102			
$\sim$	SUBDIVISION MARKE	FRACE LOT # 102	
Facility Type: 500 (40×46)	SUBDIVISION MAQKE		
Basement? Ves No Basement Fixty	res? 🗆 Yes 🖉 No		
Type of Wastewater System**	LEOUCTION SYSTEM	(Initial) Wastewater Flow: $360$ GPD	
(See note below, if applicable [])			
(see note below, it applicable ()	RED. Sys, (Repair)		
Installation Requirements/Conditions	Number of trenches	9	
Septic Tank Size <u>1000</u> gallons	Exact length of each trench 150 feet	Trench Spacing: Feet on Center	
Pump Tank Size gallons	Trenches shall be installed on contour at a	Soil Cover: <u>6 7</u> inches	
	Maximum Trench Depth of: 18-30 inches	(Maximum soil cover shall not exceed	
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)	
	(Treffell Doctoris shall be level to 17-174	Ju abuve the trench button)	
	in all directions)		
	in all directions)	,	
Pump Requirements:ft. TDH vs	in all directions)	inches below pipe	
Pump Requirements:ft. TDH vs	in all directions) GPM	Aggregate Depth: inches above pipe	
	in all directions) GPM	Aggregate Depth: inches above pipe	
Pump Requirements:ft. TDH vs Conditions:	in all directions) GPM	Aggregate Depth: inches below pipe inches above pipe inches total	
Pump Requirements:ft. TDH vs Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE	in all directions) GPM TOFT. FROM ANY PART OF SEPTIC SYSTEM OR	Aggregate Depth: inches below pipe inches above pipe inches total	
Pump Requirements:ft. TDH vs Conditions:	in all directions) GPM TOFT. FROM ANY PART OF SEPTIC SYSTEM OR	Aggregate Depth: inches below pipe inches above pipe inches total	

<u>and applicable</u> . I understand the system type specified is different from the type specified on t	he application. Taccept the specifications of this permit.
Owner/Legal Representative Signature:	Date:
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes.	orization shall not be transferred when there is a change in ownership of the site. This
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal	I and to the conditions of this permit. SEE ATTACHED SITE SKETCH
Authorized State Agent:	Date: M)222 JS

