HTE# 16-5-37869

## Harne County Department of Public I Ith 29020

Improvement Permit

A building permit cannot be issued with only an Improvement Permit  PROPERTY LOCATION: Baller Hongs RD	
ISSUED TO: DENEMY 120MRS RD SUBDIVISION SUBDIVISION	LOT #
NEW REPAIR   EXPANSION   Site Improvements required prior to Construction Author	
Type of Structure: SEO (75234)	
Proposed Wastewater System Type: 25% REDUCTION 575-En	
Projected Daily Flow: 360 GPD	
Number of bedrooms: Number of Occupants: max	
Basement 🗆 Yes 🔀 No	
Pump Required:   Yes No May be required based on final location and elevations of facilities	¥
Type of Water Supply:  Community Public Distance from well 100 feet Permit valid for:	Five years
Permit conditions:	☐ No expiration
Authorized State Agent:: 7 14 16 SEE AT	TACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the Issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies	
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to	o compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	
Construction Authorization	
Construction Authorization	
(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references into this permit and shall be met. System with the attached system layout.	ns shall be installed in accordance
ISSUED TO: JESTEMY THOMAS PROPERTY LOCATION: BAILEY THOMAS R	-0
SUBDIVISION	LOT #
Facility Type: 560 (75734) New Expansion Repair	
Basement? ☐ Yes  No Basement Fixtures? ☐ Yes  No	3()
Type of Wastewater System** 25% REDUCTION SYSTEM (Initial) Wastewater Flow	: _360 GPD
(See note below, if applicable $\square$ )	
(See Hote below, II applicable ) 25% REOUTION SIS (Repair)	
Installation Requirements/Conditions  Number of trenches3	
	_ Feet on Center
Pump Tank Size gallons Trenches shall be installed on contour at a Soil Cover: 22-6	inches
Maximum Trench Depth of: $36-38$ inches (Maximum soil cover shall	
(Trench bottoms shall be level to $\pm -1/4$ " 36" above the trench bottoms	ottom)
in all directions)	
Pump Requirements:ft. TDH vs GPM	inches below pipe
Aggregate Depth:	inches above pipe
Conditions: START @ 36". NEW PERMIT REQUESTED BY APPLICANT	inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.	
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.	
**If applicable: I understand the system type specified is different from the type specified on the application. I accept the specifications of	f this permit.
Owner/Legal Representative Signature: Date:	
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in	ownership of the site. This
Construction Authorization is abject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit.	
Authorized State Agent: Date: 9 14 14	
Construction Authorization Expiration Date:	

Permit # 29020

## Harnett County Department of Public Health Site Sketch

ISSUED TO: DECEMPTIZATION BOLLEY THOMBS RD

Authorized State Agent: Date: 9/14/16

260

REPAIR
AREN

TO BAILEY THUMAS RA